



Cisco

Exam Questions 300-735

Automating and Programming Cisco Security Solutions (SAUTO)

About ExamBible

Your Partner of IT Exam

Found in 1998

ExamBible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, ExamBible has its unique advantages that other companies could not achieve.

Our Advances

* 99.9% Uptime

All examinations will be up to date.

* 24/7 Quality Support

We will provide service round the clock.

* 100% Pass Rate

Our guarantee that you will pass the exam.

* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

NEW QUESTION 1

Which description of synchronous calls to an API is true?

- A. They can be used only within single-threaded processes.
- B. They pause execution and wait for the response.
- C. They always successfully return within a fixed time.
- D. They can be used only for small requests.

Answer: B

NEW QUESTION 2

DRAG DROP

Drag and drop the code to complete the script to search Cisco ThreatGRID and return all public submission records associated with cisco.com. Not all options are used.

Select and Place:

```
import requests
API_KEY = 'asdf1234asdf1234asdf1234'
QUERY = ' ',
URL = 'https://panacea.threatgrid.com/api/v2/ / ',
PARAMS={"q":QUERY,"api_key":API_KEY}
request = requests.get(url=URL, params=PARAMS)
print(request.json)
```

- | | | |
|-------------|--------|-----------|
| submissions | public | query |
| cisco | search | cisco.com |

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
import requests
API_KEY = 'asdf1234asdf1234asdf1234'
QUERY = ' cisco.com ',
URL = 'https://panacea.threatgrid.com/api/v2/ search / submissions ',
PARAMS={"q":QUERY,"api_key":API_KEY}
request = requests.get(url=URL, params=PARAMS)
print(request.json)
```

- | | | |
|-------------|--------|-----------|
| submissions | public | query |
| cisco | search | cisco.com |

NEW QUESTION 3

Refer to the exhibit.

Which expression prints the text "802.1x"?

- A. print(quiz[0]['choices']['b'])
- B. print(quiz['choices']['b'])
- C. print(quiz[0]['choices']['b']['802.1x'])
- D. print(quiz[0]['question']['choices']['b'])

Answer: A

NEW QUESTION 4

DRAG DROP

Drag and drop the code to complete the curl query to the Umbrella Reporting API that provides a detailed report of blocked security activity events from the organization with an organizationId of "12345678" for the last 24 hours. Not all options are used.

Select and Place:

```
curl --include --header "Authorization: Basic %base64string%"
https://reports.api.umbrella.com/v1/ [ ] /
[ ] / [ ]
```

- | | |
|--------------------------|-------------------|
| 12345678 | security-activity |
| security-activity-events | organizations |
| organizationId | security-events |

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

```
curl --include --header "Authorization: Basic %base64string%"
https://reports.api.umbrella.com/v1/ [ organizations ] /
[ organizationId ] / [ security-activity ]
```

- | | |
|--------------------------|-------------------|
| 12345678 | security-activity |
| security-activity-events | organizations |
| organizationId | security-events |

NEW QUESTION 5

Which two URI parameters are needed for the Cisco Stealthwatch Top Alarm Host v1 API? (Choose two.)

- A. startAbsolute
- B. externalGeos
- C. tenantId
- D. intervalLength
- E. tagID

Answer: CE

NEW QUESTION 6

DRAG DROP

```
def query(config, secret, url, payload):
    print('query url=' + url)
    print(' request=' + payload)
    handler = urllib.request.HTTPSHandler(context=config.get_ssl_context())
    opener = urllib.request.build_opener(handler)
    rest_request = urllib.request.Request(url=url, data=str.encode(payload))
    rest_request.add_header('Content-Type', 'application/json')
    rest_request.add_header('Accept', 'application/json')
    b64 = base64.b64encode((config.get_node_name() + ':' + secret).encode()).decode()
    rest_request.add_header('Authorization', 'Basic ' + b64)
    rest_response = opener.open(rest_request)
    print(' response status=' + str(rest_response.getcode()))
    print(' response content=' + rest_response.read().decode())
```

Refer to the exhibit. A Python function named "query" has been developed, and will be used to query the service "com.cisco.ise.session" via Cisco pxGrid 2.0 APIs. Drag and drop the code to construct a Python call to the "query" function to identify the user groups that are associated with the user "fred". Not all options are used. Select and Place:

```
query( [ ] , [ ] ,
[ ] , [ ] )
```

- | | |
|----------------------------------|--------|
| "getUserGroupByUserName", "fred" | url |
| '{ "userName": "fred" }' | secret |

- A. Mastered

B. Not Mastered

Answer: A

Explanation:

```
query( "getUserGroupByUserName", "fred" , secret ,
url , '{ "userName": "fred" }' )
```

Options:

"getUserGroupByUserName", "fred"	url
'{ "userName": "fred" }'	secret

NEW QUESTION 7

Refer to the exhibit. A network operator wants to add a certain IP to a DMZ tag. Which code segment completes the script and achieves the goal?

- A.

```
tag_data = json.dumps(tag_session) ['data']
tag_data ['ranges'].append(DMZ_IP)
session.put(TAG_URL, json=tag_data, headers=HEADERS, verify=False)
```
- B.

```
tag_data = json.loads(tag_session) ['data']
tag_data ['ranges'].append(DMZ_IP)
session.put(TAG_URL, data=tag_data, headers=HEADERS, verify=False)
```
- C.

```
tag_data = json.dumps(tag_session) ['data']
tag_data ['ranges'].append(DMZ_IP)
session.put(TAG_URL, data=json.loads(tag_data), headers=HEADERS, verify=False)
```
- D.

```
tag_data = json.loads(tag_session) ['data']
tag_data ['ranges'].append(DMZ_IP)
session.put(TAG_URL, json=tag_data, headers=HEADERS, verify=False)
```

Answer: A

NEW QUESTION 8

A security network engineer must implement intrusion policies using the Cisco Firepower Management Center API. Which action does the engineer take to achieve the goal?

- A. Make a PATCH request to the URI /api/fmc_config/v1/domain/{DOMAIN_UUID}/policy/intrusionpolicies.
- B. Make a POST request to the URI /api/fmc_config/v1/domain/{DOMAIN_UUID}/policy/intrusionpolicies.
- C. Intrusion policies can be read but not configured using the Cisco Firepower Management Center API.
- D. Make a PUT request to the URI /api/fmc_config/v1/domain/{DOMAIN_UUID}/policy/intrusionpolicies.

Answer: C

NEW QUESTION 9

Which two destinations are supported by the Cisco Security Management Appliance reporting APIs? (Choose two.)

- A. email
- B. Microsoft Word file
- C. FTP
- D. web
- E. csv file

Answer: AD

NEW QUESTION 10

```
import json
import requests

BASE_URL = "https://investigate.api.umbrella.com"
HEADERS = {"Authorization": "Bearer %YourToken%"}

---MISSING CODE---

request= requests.get(URL, parmas= PARAMS,
verify=False)
```

Refer to the exhibit. A network operator must create a Python script that makes an API request to Cisco Umbrella to do a pattern search and return all matched URLs with category information.

Which code completes the script?

- A. URL = BASE_URL + "/find/exa[a-z]ple.com" PARAMS = { "categoryinclude" : "true"}
- B. URL = BASE_URL + "/find/exa[a-z]ple.com" PARAMS = { "returncategory" : "true"}
- C. URL = BASE_URL + "/find/exa[a-z]ple.com" PARAMS = { "includeCategory" : "true"}
- D. URL = BASE_URL + "/find/exa[a-z]ple.com" PARAMS = { "returnCategory" : "true"}

Answer: D

NEW QUESTION 10

The Cisco Security Management Appliance API is used to make a GET call using the URI /sma/api/v2.0/reporting/mail_incoming_traffic_summary/detected_amp?startDate=2016-09-10T19:00:00.000Z&endDate=2018-0924T23:00:00.000Z&device_type=esa&device_name=esa01.

What does this GET call return?

- A. values of all counters of a counter group, with the device group name and device type for web
- B. value of a specific counter from a counter group, with the device name and type for email
- C. value of a specific counter from a counter group, with the device name and type for web
- D. values of all counters of a counter group, with the device group name and device type for email

Answer: D

NEW QUESTION 14

Which two APIs are available from Cisco ThreatGRID? (Choose two.)

- A. Access
- B. User Scope
- C. Data
- D. Domains
- E. Curated Feeds

Answer: CE

NEW QUESTION 19

Which two commands create a new local source code branch? (Choose two.)

- A. git checkout -b new_branch
- B. git branch -b new_branch
- C. git checkout -f new_branch
- D. git branch new_branch
- E. git branch -m new_branch

Answer: AD

NEW QUESTION 23

Which API is used to query if the domain "example.com" has been flagged as malicious by the Cisco Security Labs team?

- A. https://s-platform.api.opendns.com/1.0/events?example.com
- B. https://investigate.api.umbrella.com/domains/categorization/example.com
- C. https://investigate.api.umbrella.com/domains/volume/example.com
- D. https://s-platform.api.opendns.com/1.0/domains?example.com

Answer: B

NEW QUESTION 25

.....

Relate Links

100% Pass Your 300-735 Exam with ExamBible Prep Materials

<https://www.exambible.com/300-735-exam/>

Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>