

## 201-450 Dumps

### LPIC-2 Exam 201 Part 1 of 2 version 4.5

<https://www.certleader.com/201-450-dumps.html>



**NEW QUESTION 1**

In the following output, what percentage of time was the CPU waiting for pending I/O?

```
# vmstat 1 100
procs -----memory----- ---swap-- -----io---- --system-- ----cpu----
r b swpd free buff cache si so bi bo in cs us sy id wa
0 0 0 282120 134108 5797012 0 0 0 2 0 0 0 0 100 0
0 0 0 282120 134108 5797012 0 0 0 0 1007 359 0 0 100 0
0 0 0 282120 134108 5797012 0 0 0 0 1117 577 0 0 100 0
0 0 0 282120 134108 5797012 0 0 0 0 1007 366 0 0 100 0
```

- A. 100
- B. 35.9
- C. 57.7
- D. 36.6

**Answer:** A

**NEW QUESTION 2**

In this example output, which descriptions match the purpose of the free, buff and cache columns? (Choose THREE correct answers.)

```
# vmstat 1 100
procs -----memory----- ---swap-- -----io---- --system-- ----cpu----
r b swpd free buff cache si so bi bo in cs us sy id wa
0 0 0 282120 134108 5797012 0 0 0 2 0 0 0 0 100 0
0 0 0 282120 134108 5797012 0 0 0 0 1007 359 0 0 100 0
0 0 0 282120 134108 5797012 0 0 0 0 1117 577 0 0 100 0
0 0 0 282120 134108 5797012 0 0 0 0 1007 366 0 0 100 0
```

- A. Used swap space
- B. RAM available for filesystem buffers
- C. Available free RAM
- D. RAM used for buffers
- E. RAM used for filesystem cache

**Answer:** CDE

**NEW QUESTION 3**

In the below example output, which columns detail the percent of time the CPU spent running non-kernel code and the percent of time the CPU spent running kernel code? (Choose TWO correct answers.)

```
# vmstat 1 100
procs -----memory----- ---swap-- -----io---- --system-- ----cpu----
r b swpd free buff cache si so bi bo in cs us sy id wa
0 0 0 282120 134108 5797012 0 0 0 2 0 0 0 0 100 0
0 0 0 282120 134108 5797012 0 0 0 0 1007 359 0 0 100 0
0 0 0 282120 134108 5797012 0 0 0 0 1117 577 0 0 100 0
0 0 0 282120 134108 5797012 0 0 0 0 1007 366 0 0 100 0
```

- A. id
- B. us
- C. wa
- D. sy

**Answer:** BD

**NEW QUESTION 4**

What option in the collectd configuration file is required in order to define what to start monitoring?

- A. LoadModule
- B. Module
- C. Plugin
- D. LoadPlugin

**Answer:** D

**NEW QUESTION 5**

In capacity planning exercises, which tools assist in listing and identifying processes of interest? (Choose TWO correct answers.)

- A. acpid
- B. lsof
- C. pstree
- D. telinit

**Answer:** BC

**NEW QUESTION 6**

In the following output, the load averages represent the system load averages for what time frames? 12:10:05 up 18 days, 19:00, 2 users, load average: 0.47, 24.71, 35.31

- A. 1, 5 and 15 minutes
- B. 1, 15 and 30 minutes
- C. 1, 15, and 30 seconds
- D. 15, 30 and 60 minutes
- E. 15, 30 and 60 seconds

**Answer:** A

#### NEW QUESTION 7

What is the purpose of the command udevadm monitor?

- A. It listens to kernel events produced by a udev rule and print information to the console.
- B. It monitors the /dev directory for new devices.
- C. It monitors the udev process and prints performance statistics to the console.
- D. It communicates with D-Bus to setup new devices.

**Answer:** A

#### NEW QUESTION 8

After installing a compiled kernel, it can not find any modules that are needed to be loaded. What make target was likely missed while installing the kernel?

- A. Mastered
- B. Not Mastered

**Answer:** A

#### Explanation:

make modules\_install, modules\_install

#### NEW QUESTION 9

Which of the following terms are used to describe 3.x kernel releases? (Choose TWO correct answers.)

- A. beta
- B. final
- C. longterm
- D. prerelease
- E. stable

**Answer:** CE

#### NEW QUESTION 10

A Linux server is running in single user mode for regular maintenance. Which commands are used to restore the server to its usual runlevel? (Choose TWO correct answers.)

- A. telinit 0
- B. shutdown -r now
- C. sync
- D. shutdown -h now
- E. reboot

**Answer:** BE

#### NEW QUESTION 10

After changing the default runlevel in the SysV-init configuration file, the system boots in a different than intended runlevel. Where else could this different runlevel be defined?

- A. In the /etc/sysctl.conf
- B. In the boot loader configuration file
- C. In the /etc/runlevel file
- D. In the /boot/initramfs file
- E. In the /etc/rc.d/rc.local file

**Answer:** B

#### NEW QUESTION 12

A system with SysV-init has a service installed called apache2. Which file controls the start and stop of this service and is referenced by the various runlevel directories?

- A. /etc/init.d/apache2
- B. /etc/rc2.d/70apache2
- C. /etc/rc2.d/apache2
- D. /etc/rc2.d/apache2.start

**Answer:** A

**NEW QUESTION 14**

Why is the root file system mounted read-only during boot and remounted with write permission later on?

- A. Because if problems with the root file system are detected during the boot, fsck can be run, without risk of damage.
- B. Because this way crackers cannot collect information about root with boot sniffers.
- C. To avoid writing to the disk, unless the root password is known.
- D. To avoid other operating systems overwriting the Linux root partition.
- E. Because the disk has its own write protection that cannot be changed by the operating system.

**Answer:** A

**NEW QUESTION 16**

What is the main template file used by autofs?

- A. default.maps
- B. auto.conf
- C. auto.master
- D. autofs.master

**Answer:** C

**NEW QUESTION 20**

Which directory in /dev/disk/ can be used to determine the UUID of a connected hard disk?

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

/dev/disk/by-uuid, by-uuid, /dev/disk/by-uuid/

**NEW QUESTION 25**

A system has one hard disk and one CD writer which are both connected to SATA controllers. Which device represents the CD writer?

- A. /dev/hdb
- B. /dev/sdd
- C. /dev/scd1
- D. /dev/sr0
- E. /dev/sr1

**Answer:** D

**NEW QUESTION 29**

What mount option must be used in /etc/fstab when mounting an iSCSI target?

- A. \_\_santarget
- B. iscsi
- C. waitiscsi
- D. \_\_netdev

**Answer:** D

**NEW QUESTION 34**

What command will remove a physical volume from a volume group? (Specify ONLY the command without any path or parameters.)

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

vgreduce, /sbin/vgreduce

**NEW QUESTION 36**

Which single command will simulate a failed device within a RAID 5 array?

- A. mdadm --remove /dev/md0 /dev/sdd1
- B. mdadm --zero-superblock /dev/sdf3
- C. mdadm --force-fault /dev/md2 /dev/sde2
- D. mdadm --fail /dev/md0 /dev/sdc1
- E. mdadm /dev/md0 --offline /dev/sdc1

**Answer:** D

**NEW QUESTION 38**

Which RAID level value must be used with Linux software RAID in order to create an array of mirrored devices?

- A. 1
- B. 5
- C. 6
- D. container
- E. mirrorstripe

**Answer:** A

**NEW QUESTION 41**

Which two LVM commands are missing from the following sequence which is used to create a logical volume and make use of it on a Linux system?

pvcreate, \_\_\_\_\_, \_\_\_\_\_, mkfs, mount

- A. lvcreate, mdadm
- B. lvcreate, vgcreate
- C. lvmcreate, vgcreate
- D. vgcreate, lvcreate
- E. vgcreate, mdadm

**Answer:** D

**NEW QUESTION 45**

What action should be performed after increasing the size of a logical volume?

- A. Run vgresize.
- B. Increase the size of the filesystem used for the logical volume.
- C. Run lvresize.
- D. Remount the logical volume.

**Answer:** B

**NEW QUESTION 47**

Which of the following commands can be used to script interactions with various TCP or UDP services?

- A. ftp
- B. nc
- C. tcpdump
- D. strings
- E. wget

**Answer:** B

**NEW QUESTION 49**

Which command can be used to scan a specified network looking for IP addresses that appear to be in use?

- A. nmap
- B. tcpdump
- C. ip
- D. netscan
- E. hostdiscover

**Answer:** A

**NEW QUESTION 54**

Which of the following commands can be used to list IPv4 addresses and MAC addresses for IP devices that the system has seen on the local network?

- A. arp
- B. ifconfig
- C. ipadm
- D. iwlist

**Answer:** A

**NEW QUESTION 59**

Running tcpdump -nli eth1 'tcp' shows the following output:

14:41:53.694538 IP 10.1.52.145.51738 > 24.215.7.162.143: Flags [.), ack 33051, win 1002, options [nop,nop,TS val 36789130 ecr 1746004159], length 0

What is the source IP address of this packet? (Please specify the answer in digits and dots ONLY.)

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

10.1.52.145

**NEW QUESTION 62**

The following is an excerpt from the output of tcpdump -nli eth1 'udp': 13:03:17.277327 IP 192.168.123.5.1065 > 192.168.5.112.53: 43653+ A? lpi.org. (25)  
13:03:17.598624 IP 192.168.5.112.53 > 192.168.123.5.1065: 43653 1/0/0 A 198.51.100.42 (41)

Which network service or protocol was used?

- A. FTP
- B. HTTP
- C. SSH
- D. DNS
- E. DHCP

**Answer:** D

**NEW QUESTION 66**

Which of the following commands will erase the contents of the /dev/sdb3 partition?

- A. rm /dev/sdb3
- B. dd if=/dev/zero of=/dev/sdb3
- C. dd of=/dev/zero if=/dev/sdb3
- D. umount /dev/sdb3

**Answer:** B

**NEW QUESTION 67**

Which of the following commands will securely copy the directory ./fyf/ to /var/tmp/ on the remote host deltaur using the remote user account kevin?

- A. rsync -a -e ssh kevin@deltaur:/var/tmp/ fyf/
- B. rsync -a -u kevin -e ssh fyf/ deltaur:/var/tmp/
- C. rsync -a -u kevin -e ssh deltaur:/var/tmp/ fyf/
- D. rsync -a -e ssh fyf/ kevin@deltaur:/var/tmp/

**Answer:** D

**NEW QUESTION 72**

A regular user, joe, has just run:

./configure && make && make install

to build and install a program. However, the installation fails. What could be done to install the program? (Choose TWO correct answers.)

- A. Install the binaries manually with suinstall.
- B. Run make install with root privileges.
- C. Do not run ./configure in order to maintain the default configuration for correct installation.
- D. Rerun ./configure with a --prefix option where the user has permissions to write.
- E. Run make install\_local to install into /usr/local/.

**Answer:** BD

**NEW QUESTION 77**

Which file contains the message that is displayed above the login prompt of the system console? (Specify the full name of the file, including path.)

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

/etc/issue

**NEW QUESTION 81**

What is the purpose of a system mount unit?

- A. It is used by the command systemd-mount and allows users to mount partitions to mount points of their choice
- B. It is used only to mount network file systems to local mount point
- C. It cannot be used for local media
- D. It is created by the command systemd-fstab-generator to integrate entries from /etc/fstab into the system boot process
- E. It is used by the command mount when using system to mount and unmount file systems

**Answer:** A

**NEW QUESTION 84**

What is the purpose of an initramfs during the Linux system start?

- A. It loads required modules and starts sub systems like LVM to make the root file system accessible to the kernel

- B. It moves the kernel from normal system memory to initram memory to speed up kernel access
- C. It copies the root file system's content to RAM to speed up the system and reduce writes to disk
- D. It creates a ram disk to store volatile data for directories like /tmp to reduce writes to disk

**Answer:** A

**NEW QUESTION 85**

.....

## Thank You for Trying Our Product

\* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

\* One year free update

You can enjoy free update one year. 24x7 online support.

\* Trusted by Millions

We currently serve more than 30,000,000 customers.

\* Shop Securely

All transactions are protected by VeriSign!

**100% Pass Your 201-450 Exam with Our Prep Materials Via below:**

<https://www.certleader.com/201-450-dumps.html>