



CompTIA

Exam Questions CS0-002

CompTIA Cybersecurity Analyst (CySA+) Certification Exam

NEW QUESTION 1

A cybersecurity analyst is supposing an incident response effort via threat intelligence. Which of the following is the analyst MOST likely executing?

- A. Requirements analysis and collection planning
- B. Containment and eradication
- C. Recovery and post-incident review
- D. Indicator enrichment and research pivoting

Answer: D

NEW QUESTION 2

An analyst is participating in the solution analysis process for a cloud-hosted SIEM platform to centralize log monitoring and alerting capabilities in the SOC. Which of the following is the BEST approach for supply chain assessment when selecting a vendor?

- A. Gather information from providers, including datacenter specifications and copies of audit reports.
- B. Identify SLA requirements for monitoring and logging.
- C. Consult with senior management for recommendations.
- D. Perform a proof of concept to identify possible solutions.

Answer: B

NEW QUESTION 3

A cybersecurity analyst is reading a daily intelligence digest of new vulnerabilities. The type of vulnerability that should be disseminated FIRST is one that:

- A. enables remote code execution that is being exploited in the wild.
- B. enables data leakage but is not known to be in the environment
- C. enables lateral movement and was reported as a proof of concept
- D. affected the organization in the past but was probably contained and eradicated

Answer: C

NEW QUESTION 4

A security analyst needs to reduce the overall attack surface. Which of the following infrastructure changes should the analyst recommend?

- A. Implement a honeypot.
- B. Air gap sensitive systems.
- C. Increase the network segmentation.
- D. Implement a cloud-based architecture.

Answer: C

NEW QUESTION 5

A security analyst conducted a risk assessment on an organization's wireless network and identified a high-risk element in the implementation of data confidentiality protection. Which of the following is the BEST technical security control to mitigate this risk?

- A. Switch to RADIUS technology
- B. Switch to TACACS+ technology.
- C. Switch to 802.1X technology
- D. Switch to the WPA2 protocol.

Answer: B

NEW QUESTION 6

Which of the following should be found within an organization's acceptable use policy?

- A. Passwords must be eight characters in length and contain at least one special character.
- B. Customer data must be handled properly, stored on company servers, and encrypted when possible.
- C. Administrator accounts must be audited monthly, and inactive accounts should be removed.
- D. Consequences of violating the policy could include discipline up to and including termination.

Answer: D

NEW QUESTION 7

Which of the following is the MOST important objective of a post-incident review?

- A. Capture lessons learned and improve incident response processes
- B. Develop a process for containment and continue improvement efforts
- C. Identify new technologies and strategies to remediate
- D. Identify a new management strategy

Answer: A

NEW QUESTION 8

An organization is moving its infrastructure to the cloud in an effort to meet the budget and reduce staffing requirements. The organization has three environments: development, testing, and production. These environments have interdependencies but must remain relatively segmented. Which of the following methods would BEST secure the company's infrastructure and be the simplest to manage and maintain?

- A. Create three separate cloud accounts for each environmen
- B. Configure account peering and security rules to allow access to and from each environment.
- C. Create one cloud account with one VPC for all environment
- D. Purchase a virtual firewall and create granular security rules.
- E. Create one cloud account and three separate VPCs for each environmen
- F. Create security rules to allow access to and from each environment.
- G. Create three separate cloud accounts for each environment and a single core account for network service
- H. Route all traffic through the core account.

Answer: C

NEW QUESTION 9

During routine monitoring, a security analyst discovers several suspicious websites that are communicating with a local host. The analyst queries for IP 192.168.50.2 for a 24-hour period:

Time	SRC	DST	Domain	Bytes
6/26/19 10:01	192.168.50.2	138.10.2.5	www.wioapsfeje.co	50
6/26/19 11:05	192.168.50.2	138.10.2.5	www.wioapsfeje.co	1000
6/26/19 13:09	192.168.50.2	138.10.25.5	www.wfaojsjfjoe.co	1000
6/26/19 15:13	192.168.50.2	172.10.25.5	www.wfalksdjflse.co	1000
6/26/19 17:17	192.168.50.2	172.10.45.5	www.wsahlfdsjlfse.co	1000
6/26/19 23:45	192.168.50.2	172.10.3.5	ftp.walksdjgfl.co	50000
6/27/19 10:21	192.168.50.2	175.35.20.5	www.whatsmyip.com	25
6/27/19 11:25	192.168.50.2	175.35.20.5	www.whatsmyip.com	25

To further investigate, the analyst should request PCAP for SRC 192.168.50.2 and.

- A. DST 138.10.2.5.
- B. DST 138.10.25.5.
- C. DST 172.10.3.5.
- D. DST 172.10.45.5.
- E. DST 175.35.20.5.

Answer: A

NEW QUESTION 10

Which of the following BEST describes the process by which code is developed, tested, and deployed in small batches?

- A. Agile
- B. Waterfall
- C. SDLC
- D. Dynamic code analysis

Answer: A

NEW QUESTION 10

The inability to do remote updates of certificates, keys software and firmware is a security issue commonly associated with:

- A. web servers on private networks.
- B. HVAC control systems
- C. smartphones
- D. firewalls and UTM devices

Answer: B

NEW QUESTION 11

A security analyst has discovered suspicious traffic and determined a host is connecting to a known malicious website. The MOST appropriate action for the analyst to take would be to implement a change request to:

- A. update the antivirus software
- B. configure the firewall to block traffic to the domain
- C. add the domain to the blacklist
- D. create an IPS signature for the domain

Answer: B

NEW QUESTION 12

An analyst is reviewing a list of vulnerabilities, which were reported from a recent vulnerability scan of a Linux server. Which of the following is MOST likely to be a false positive?

- A. OpenSSH/OpenSSL Package Random Number Generator Weakness
- B. Apache HTTP Server Byte Range DoS
- C. GDI+ Remote Code Execution Vulnerability (MS08-052)
- D. HTTP TRACE / TRACK Methods Allowed (002-1208)
- E. SSL Certificate Expiry

Answer: E

NEW QUESTION 14

A security analyst discovered a specific series of IP addresses that are targeting an organization. None of the attacks have been successful. Which of the following should the security analyst perform NEXT?

- A. Begin blocking all IP addresses within that subnet.
- B. Determine the attack vector and total attack surface.
- C. Begin a kill chain analysis to determine the impact.
- D. Conduct threat research on the IP addresses

Answer: D

NEW QUESTION 17

The security team at a large corporation is helping the payment-processing team to prepare for a regulatory compliance audit and meet the following objectives:

- Reduce the number of potential findings by the auditors.
- Limit the scope of the audit to only devices used by the payment-processing team for activities directly impacted by the regulations.
- Prevent the external-facing web infrastructure used by other teams from coming into scope.
- Limit the amount of exposure the company will face if the systems used by the payment-processing team are compromised.

Which of the following would be the MOST effective way for the security team to meet these objectives?

- A. Limit the permissions to prevent other employees from accessing data owned by the business unit.
- B. Segment the servers and systems used by the business unit from the rest of the network.
- C. Deploy patches to all servers and workstations across the entire organization.
- D. Implement full-disk encryption on the laptops used by employees of the payment-processing team.

Answer: B

NEW QUESTION 21

A security analyst is investigating malicious traffic from an internal system that attempted to download proxy avoidance software as identified from the firewall logs but the destination IP is blocked and not captured. Which of the following should the analyst do?

- A. Shut down the computer
- B. Capture live data using Wireshark
- C. Take a snapshot
- D. Determine if DNS logging is enabled.
- E. Review the network logs.

Answer: A

NEW QUESTION 24

An organization developed a comprehensive incident response policy. Executive management approved the policy and its associated procedures. Which of the following activities would be MOST beneficial to evaluate personnel's familiarity with incident response procedures?

- A. A simulated breach scenario involving the incident response team
- B. Completion of annual information security awareness training by all employees
- C. Tabletop activities involving business continuity team members
- D. Completion of lessons-learned documentation by the computer security incident response team
- E. External and internal penetration testing by a third party

Answer: A

NEW QUESTION 25

A company was recently awarded several large government contracts and wants to determine its current risk from one specific APT. Which of the following threat modeling methodologies would be the MOST appropriate to use during this analysis?

- A. Attack vectors
- B. Adversary capability
- C. Diamond Model of Intrusion Analysis
- D. Kill chain
- E. Total attack surface

Answer: B

NEW QUESTION 27

A security analyst suspects a malware infection was caused by a user who downloaded malware after clicking `http://<malwaresource>/a.php` in a phishing email. To prevent other computers from being infected by the same malware variation, the analyst should create a rule on the.

- A. email server that automatically deletes attached executables.
- B. IDS to match the malware sample.
- C. proxy to block all connections to `<malwaresource>`.
- D. firewall to block connection attempts to dynamic DNS hosts.

Answer: C

NEW QUESTION 31

You are a cybersecurity analyst tasked with interpreting scan data from Company A's servers. You must verify the requirements are being met for all of the servers and recommend changes if you find they are not.

The company's hardening guidelines indicate the following:

- TLS 1.2 is the only version of TLS running.
- Apache 2.4.18 or greater should be used.
- Only default ports should be used. INSTRUCTIONS

Using the supplied data, record the status of compliance with the company's guidelines for each server.

The question contains two parts: make sure you complete Part 1 and Part 2. Make recommendations for issues based ONLY on the hardening guidelines provided.

Part 1

Scan Data	Compliance Report
<div>AppServ1AppServ2AppServ3AppServ4</div> <pre>root@INFOSEC:~# curl --head appsrv1.fictionalorg.com:443 HTTP/1.1 200 OK Date: Wed, 26 Jun 2019 21:15:15 GMT Server: Apache/2.4.48 (CentOS) Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT ETag: "13520-58c407930177d" Accept-Ranges: bytes Content-Length: 79136 Vary: Accept-Encoding Cache-Control: max-age=3600 Expires: Wed, 26 Jun 2019 22:15:15 GMT Content-Type: text/html root@INFOSEC:~# nmap --script ssl-enum-ciphers appsrv1.fictionalorg.com -p 443 Starting Nmap 6.40 (http://nmap.org) at 2019-06-26 16:07 CDT Nmap scan report for AppSrv1.fictionalorg.com (10.21.4.68) Host is up (0.042s latency). rDNS record for 10.21.4.68: inaddrArpa.fictionalorg.com PORT STATE SERVICE 443/tcp open https ssl-enum-ciphers: TLSv1.2: ciphers: TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong TLS_RSA_WITH_AES_128_CBC_SHA - strong TLS_RSA_WITH_AES_128_GCM_SHA256 - strong TLS_RSA_WITH_AES_256_CBC_SHA - strong TLS_RSA_WITH_AES_256_GCM_SHA384 - strong compressors: NULL _ least strength: strong Nmap done: 1 IP address (1 host up) scanned in 8.63 seconds root@INFOSEC:~# nmap --top-ports 10 appsrv1.fictionalorg.com Starting Nmap 6.40 (http://nmap.org) at 2019-06-27 10:13 CDT Nmap scan report for appsrv1.fictionalorg.com (10.21.4.68) Host is up (0.15s latency). rDNS record for 10.21.4.68: appsrv1.fictionalorg.com PORT STATE SERVICE 80/tcp open http 443/tcp open https Nmap done: 1 IP address (1 host up) scanned in 0.42 seconds</pre>	<div>Fill out the following report based on your analysis of the scan data.</div> <div><div><input type="checkbox"/> AppServ1 is only using TLS 1.2</div><div><input type="checkbox"/> AppServ2 is only using TLS 1.2</div><div><input type="checkbox"/> AppServ3 is only using TLS 1.2</div><div><input type="checkbox"/> AppServ4 is only using TLS 1.2</div><div><input type="checkbox"/> AppServ1 is using Apache 2.4.18 or greater</div><div><input type="checkbox"/> AppServ2 is using Apache 2.4.18 or greater</div><div><input type="checkbox"/> AppServ3 is using Apache 2.4.18 or greater</div><div><input type="checkbox"/> AppServ4 is using Apache 2.4.18 or greater</div></div>

Part 1

Scan Data

AppServ1 AppServ2 AppServ3 AppServ4

Compliance Report

Fill out the following report based on your analysis of the scan data.

```
root@INFOSEC:~# curl --head appsrv2.fictionalorg.com:443

HTTP/1.1 200 OK
Date: Wed, 26 Jun 2019 21:15:15 GMT
Server: Apache/2.3.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c407930177d"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html

root@INFOSEC:~# nmap --script ssl-enum-ciphers
appsrv2.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv2.fictionalorg.com (10.21.4.69)
Host is up (0.042s latency).
rDNS record for 10.21.4.69: inaddrArpa.fictionalorg.com
Not shown: 998 filtered ports
PORT      STATE SERVICE
80/tcp    open  http
443/tcp   open  https
| ssl-enum-ciphers:
|   TLSv1.0:
|   ciphers:
|     TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|     TLS_RSA_WITH_AES_128_CBC_SHA - strong
|     TLS_RSA_WITH_AES_256_CBC_SHA - strong
|   compressors:
|     NULL
|   TLSv1.1:
|   ciphers:
|     TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|     TLS_RSA_WITH_AES_128_CBC_SHA - strong
|     TLS_RSA_WITH_AES_256_CBC_SHA - strong
|   compressors:
|     NULL
|   TLSv1.2:
|   ciphers:
|     TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|     TLS_RSA_WITH_AES_128_CBC_SHA - strong
|     TLS_RSA_WITH_AES_128_GCM_SHA256 - strong
|     TLS_RSA_WITH_AES_256_CBC_SHA - strong
|     TLS_RSA_WITH_AES_256_GCM_SHA384 - strong
|   compressors:
|     NULL
|_ least strength: strong

Nmap done: 1 IP address (1 host up) scanned in 8.63 seconds

root@INFOSEC:~# nmap --top-ports 10 appsrv2.fictionalorg.com

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-27 10:13 CDT

Nmap scan report for appsrv2.fictionalorg.com (10.21.4.69)
Host is up (0.15s latency).
rDNS record for 10.21.4.69: appsrv2.fictionalorg.com
PORT      STATE SERVICE
80/tcp    open  http
443/tcp   open  https

Nmap done: 1 IP address (1 host up) scanned in 0.42 seconds
```

- ☐ AppServ1 is only using TLS 1.2
- ☐ AppServ2 is only using TLS 1.2
- ☐ AppServ3 is only using TLS 1.2
- ☐ AppServ4 is only using TLS 1.2
- ☐ AppServ1 is using Apache 2.4.18 or greater
- ☐ AppServ2 is using Apache 2.4.18 or greater
- ☐ AppServ3 is using Apache 2.4.18 or greater
- ☐ AppServ4 is using Apache 2.4.18 or greater

Part 1

Scan Data

AppServ1 AppServ2 AppServ3 AppServ4

```
root@INFOSEC:~# curl --head appsrv3.fictionalorg.com:443

HTTP/1.1 200 OK
Date: Wed, 26 Jun 2019 21:15:15 GMT
Server: Apache/2.4.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c406780177e"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html

root@INFOSEC:~# nmap --script ssl-enum-ciphers
appsrv3.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv3.fictionalorg.com (10.21.4.70)
Host is up (0.042s latency).
rDNS record for 10.21.4.70: inaddrArpa.fictionalorg.com
PORT      STATE SERVICE
80/tcp    open  http
443/tcp    open  https
| ssl-enum-ciphers:
|   TLSv1.0:
|   | ciphers:
|   | | TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_128_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_256_CBC_SHA - strong
|   | compressors:
|   | | NULL
|   TLSv1.1:
|   | ciphers:
|   | | TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_128_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_256_CBC_SHA - strong
|   | compressors:
|   | | NULL
|   TLSv1.2:
|   | ciphers:
|   | | TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_128_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_128_GCM_SHA256 - strong
|   | | TLS_RSA_WITH_AES_256_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_256_GCM_SHA384 - strong
|   | compressors:
|   | | NULL
|_ least strength: strong

Nmap done: 1 IP address (1 host up) scanned in 8.63 seconds

root@INFOSEC:~# nmap --top-ports 10 appsrv3.fictionalorg.com

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-27 10:13 CDT

Nmap scan report for appsrv3.fictionalorg.com (10.21.4.70)
Host is up (0.15s latency).
rDNS record for 10.21.4.70: appsrv3.fictionalorg.com
PORT      STATE SERVICE
80/tcp    open  http
443/tcp    open  https

Nmap done: 1 IP address (1 host up) scanned in 0.42 seconds
```

Compliance Report

Fill out the following report based on your analysis of the scan data.

- ☐ AppServ1 is only using TLS 1.2
- ☐ AppServ2 is only using TLS 1.2
- ☐ AppServ3 is only using TLS 1.2
- ☐ AppServ4 is only using TLS 1.2
- ☐ AppServ1 is using Apache 2.4.18 or greater
- ☐ AppServ2 is using Apache 2.4.18 or greater
- ☐ AppServ3 is using Apache 2.4.18 or greater
- ☐ AppServ4 is using Apache 2.4.18 or greater

Part 1

Scan Data

AppServ1 AppServ2 AppServ3 AppServ4

```
root@INFOSEC:~# curl --head appsrv4.fictionalorg.com:443

HTTP/1.1 200 OK
Date: Wed, 26 Jun 2019 21:15:15 GMT
Server: Apache/2.4.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c406780177e"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html

root@INFOSEC:~# nmap --script ssl-enum-ciphers
appsrv4.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv4.fictionalorg.com (10.21.4.71)
Host is up (0.042s latency).
rDNS record for 10.21.4.71: inaddrArpa.fictionalorg.com
PORT      STATE SERVICE
443/tcp   open  https
| TLSv1.2:
|   ciphers:
|     TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|     TLS_RSA_WITH_AES_128_CBC_SHA - strong
|     TLS_RSA_WITH_AES_128_GCM_SHA256 - strong
|     TLS_RSA_WITH_AES_256_CBC_SHA - strong
|     TLS_RSA_WITH_AES_256_GCM_SHA384 - strong
|   compressors:
|     NULL
|_  least strength: strong

Nmap done: 1 IP address (1 host up) scanned in 8.63 seconds

root@INFOSEC:~# nmap --top-ports 10 appsrv4.fictionalorg.com

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-27 10:13 CDT
Nmap scan report for appsrv4.fictionalorg.com (10.21.4.71)
Host is up (0.15s latency).
rDNS record for 10.21.4.71: appsrv4.fictionalorg.com
PORT      STATE SERVICE
80/tcp    open  http
443/tcp   open  https
8675/tcp  open  ssh

Nmap done: 1 IP address (1 host up) scanned in 0.42 seconds
```

Compliance Report

Fill out the following report based on your analysis of the scan data.

- ☐ AppServ1 is only using TLS 1.2
- ☐ AppServ2 is only using TLS 1.2
- ☐ AppServ3 is only using TLS 1.2
- ☐ AppServ4 is only using TLS 1.2
- ☐ AppServ1 is using Apache 2.4.18 or greater
- ☐ AppServ2 is using Apache 2.4.18 or greater
- ☐ AppServ3 is using Apache 2.4.18 or greater
- ☐ AppServ4 is using Apache 2.4.18 or greater

Part 2

Scan Data

AppServ1 AppServ2 AppServ3 AppServ4

Configuration Change Recommendations



Add recommendation for

AppSrv1
AppSrv2
AppSrv3
AppSrv4

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Part 1 Answer

Check on the following:

- AppServ1 is only using TLS.1.2
- AppServ4 is only using TLS.1.2
- AppServ1 is using Apache 2.4.18 or greater
- AppServ3 is using Apache 2.4.18 or greater
- AppServ4 is using Apache 2.4.18 or greater

Recommendation:

Scan Data		Configuration Change Recommendations																			
AppSrv1	AppSrv2	AppSrv3	AppSrv4																		
<pre>root@INFOSEC:~# curl --head appsrv2.fictionalorg.com:443 HTTP/1.1 200 OK Date: Wed, 26 Jun 2019 21:15:15 GMT Server: Apache/2.3.48 (CentOS) Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT ETag: "13520-58c407950177d" Accept-Ranges: bytes Content-Length: 79136 Vary: Accept-Encoding Cache-Control: max-age=3600 Expires: Wed, 26 Jun 2019 22:15:15 GMT Content-Type: text/html root@INFOSEC:~# nmap --script ssl-enum-ciphers appsrv2.fictionalorg.com -p 443 Starting Nmap 6.40 (http://nmap.org) at 2019-06-26 16:07 CDT Nmap scan report for AppSrv2.fictionalorg.com (10.21.4.69) Host is up (0.042s latency). rDNS record for 10.21.4.69: inaddrArpa.fictionalorg.com Not shown: 998 filtered ports PORT STATE SERVICE 80/tcp open http 443/tcp open https ssl-enum-ciphers:</pre>		<p>+ Add Recommendation for AppSrv2 ▼</p> <table border="1"> <tr> <td>Server</td> <td>AppSrv2 ▼</td> </tr> <tr> <td>Service</td> <td>Apache Version ▼</td> </tr> <tr> <td>Config Change</td> <td>Upgrade Version ▼</td> </tr> </table> <table border="1"> <tr> <td>Server</td> <td>AppSrv3 ▼</td> </tr> <tr> <td>Service</td> <td>HTTPD Security ▼</td> </tr> <tr> <td>Config Change</td> <td>Restrict To TLS 1.2 ▼</td> </tr> </table> <table border="1"> <tr> <td>Server</td> <td>AppSrv4 ▼</td> </tr> <tr> <td>Service</td> <td>SSH ▼</td> </tr> <tr> <td>Config Change</td> <td>Remove or Disable ▼</td> </tr> </table>		Server	AppSrv2 ▼	Service	Apache Version ▼	Config Change	Upgrade Version ▼	Server	AppSrv3 ▼	Service	HTTPD Security ▼	Config Change	Restrict To TLS 1.2 ▼	Server	AppSrv4 ▼	Service	SSH ▼	Config Change	Remove or Disable ▼
Server	AppSrv2 ▼																				
Service	Apache Version ▼																				
Config Change	Upgrade Version ▼																				
Server	AppSrv3 ▼																				
Service	HTTPD Security ▼																				
Config Change	Restrict To TLS 1.2 ▼																				
Server	AppSrv4 ▼																				
Service	SSH ▼																				
Config Change	Remove or Disable ▼																				

NEW QUESTION 34

A development team uses open-source software and follows an Agile methodology with two-week sprints. Last month, the security team filed a bug for an insecure version of a common library. The DevOps team updated the library on the server, and then the security team rescanned the server to verify it was no longer vulnerable. This month, the security team found the same vulnerability on the server.

Which of the following should be done to correct the cause of the vulnerability?

- A. Deploy a WAF in front of the application.
- B. Implement a software repository management tool.
- C. Install a HIPS on the server.
- D. Instruct the developers to use input validation in the code.

Answer: B

NEW QUESTION 39

A compliance officer of a large organization has reviewed the firm's vendor management program but has discovered there are no controls defined to evaluate third-party risk or hardware source authenticity. The compliance officer wants to gain some level of assurance on a recurring basis regarding the implementation of controls by third parties.

Which of the following would BEST satisfy the objectives defined by the compliance officer? (Choose two.)

- A. Executing vendor compliance assessments against the organization's security controls
- B. Executing NDAs prior to sharing critical data with third parties
- C. Soliciting third-party audit reports on an annual basis
- D. Maintaining and reviewing the organizational risk assessment on a quarterly basis
- E. Completing a business impact assessment for all critical service providers
- F. Utilizing DLP capabilities at both the endpoint and perimeter levels

Answer: AC

NEW QUESTION 40

A Chief Information Security Officer (CISO) wants to upgrade an organization's security posture by improving proactive activities associated with attacks from internal and external threats.

Which of the following is the MOST proactive tool or technique that feeds incident response capabilities?

- A. Development of a hypothesis as part of threat hunting
- B. Log correlation, monitoring, and automated reporting through a SIEM platform
- C. Continuous compliance monitoring using SCAP dashboards
- D. Quarterly vulnerability scanning using credentialed scans

Answer: A

NEW QUESTION 43

A Chief Information Security Officer (CISO) is concerned the development team, which consists of contractors, has too much access to customer data. Developers use personal workstations, giving the company little to no visibility into the development activities.

Which of the following would be BEST to implement to alleviate the CISO's concern?

- A. DLP
- B. Encryption
- C. Test data

D. NDA

Answer: D

NEW QUESTION 48

A security team wants to make SaaS solutions accessible from only the corporate campus. Which of the following would BEST accomplish this goal?

- A. Geofencing
- B. IP restrictions
- C. Reverse proxy
- D. Single sign-on

Answer: A

NEW QUESTION 49

A monthly job to install approved vendor software updates and hot fixes recently stopped working. The security team performed a vulnerability scan, which identified several hosts as having some critical OS vulnerabilities, as referenced in the common vulnerabilities and exposures (CVE) database. Which of the following should the security team do NEXT to resolve the critical findings in the most effective manner? (Choose two.)

- A. Patch the required hosts with the correct updates and hot fixes, and rescan them for vulnerabilities.
- B. Remove the servers reported to have high and medium vulnerabilities.
- C. Tag the computers with critical findings as a business risk acceptance.
- D. Manually patch the computers on the network, as recommended on the CVE website.
- E. Harden the hosts on the network, as recommended by the NIST framework.
- F. Resolve the monthly job issues and test them before applying them to the production network.

Answer: CE

NEW QUESTION 53

A security analyst is reviewing the following log entries to identify anomalous activity:

```
GET https://comptia.org/admin/login.html&user&password\ HTTP/1.1
GET http://comptia.org/index.php\ HTTP/1.1
GET http://comptia.org/scripts/..%5c../Windows/System32/cmd.exe?/C+dir+c:\ HTTP/1.1
GET http://comptia.org/media/contactus.html\ HTTP/1.1
```

Which of the following attack types is occurring?

- A. Directory traversal
- B. SQL injection
- C. Buffer overflow
- D. Cross-site scripting

Answer: A

NEW QUESTION 56

As a proactive threat-hunting technique, hunters must develop situational cases based on likely attack scenarios derived from the available threat intelligence information. After forming the basis of the scenario, which of the following may the threat hunter construct to establish a framework for threat assessment?

- A. Critical asset list
- B. Threat vector
- C. Attack profile
- D. Hypothesis

Answer: A

NEW QUESTION 59

Which of the following sets of attributes BEST illustrates the characteristics of an insider threat from a security perspective?

- A. Unauthorized, unintentional, benign
- B. Unauthorized, intentional, malicious
- C. Authorized, intentional, malicious
- D. Authorized, unintentional, benign

Answer: C

NEW QUESTION 64

An analyst has been asked to provide feedback regarding the control required by a revised regulatory framework. At this time, the analyst only needs to focus on the technical controls. Which of the following should the analyst provide an assessment of?

- A. Tokenization of sensitive data
- B. Establishment of data classifications
- C. Reporting on data retention and purging activities
- D. Formal identification of data ownership
- E. Execution of NDAs

Answer: A

NEW QUESTION 66

The inability to do remote updates of certificates, keys, software, and firmware is a security issue commonly associated with:

- A. web servers on private networks
- B. HVAC control systems
- C. smartphones
- D. firewalls and UTM devices

Answer: D

NEW QUESTION 69

The computer incident response team at a multinational company has determined that a breach of sensitive data has occurred in which a threat actor has compromised the organization's email system. Per the incident response procedures, this breach requires notifying the board immediately. Which of the following would be the BEST method of communication?

- A. Post of the company blog
- B. Corporate-hosted encrypted email
- C. VoIP phone call
- D. Summary sent by certified mail
- E. Externally hosted instant message

Answer: C

NEW QUESTION 70

An information security analyst is working with a data owner to identify the appropriate controls to preserve the confidentiality of data within an enterprise environment. One of the primary concerns is exfiltration of data by malicious insiders. Which of the following controls is the MOST appropriate to mitigate risks?

- A. Data deduplication
- B. OS fingerprinting
- C. Digital watermarking
- D. Data loss prevention

Answer: D

NEW QUESTION 72

A company wants to establish a threat-hunting team. Which of the following BEST describes the rationale for integration intelligence into hunt operations?

- A. It enables the team to prioritize the focus area and tactics within the company's environment.
- B. It provide critically analyses for key enterprise servers and services.
- C. It allow analysis to receive updates on newly discovered software vulnerabilities.
- D. It supports rapid response and recovery during and followed an incident.

Answer: A

NEW QUESTION 73

A security analyst is reviewing the logs from an internal chat server. The chat.log file is too large to review manually, so the analyst wants to create a shorter log file that only includes lines associated with a user demonstrating anomalous activity. Below is a snippet of the log:

Line	User	Time	Command	Result
36570	DEV12	02.01.13.151219	KICK DEV27	OK
36571	JAVASHARK	02.01.13.151255	JOIN #CHATOPS e32kk10	OK
36572	DEV12	02.01.13.151325	PART #CHATOPS	OK
36573	CHATTER14	02.01.13.151327	JOIN';CAT ../etc/config'	OK
36574	PYTHONFUN	02.01.13.151330	PRIVMSG DEV99 "?"	OK
36575	DEV99	02.01.13.151358	PRIVMSG PYTHONFUN "OK"	OK

Which of the following commands would work BEST to achieve the desired result?

- A. `grep -v chatter14 chat.log`
- B. `grep -i pythonfun chat.log`
- C. `grep -i javashark chat.log`
- D. `grep -v javashark chat.log`
- E. `grep -v pythonfun chat.log`
- F. `grep -i chatter14 chat.log`

Answer: D

NEW QUESTION 78

A security analyst has received information from a third-party intelligence-sharing resource that indicates employee accounts were breached. Which of the following is the NEXT step the analyst should take to address the issue?

- A. Audit access permissions for all employees to ensure least privilege.
- B. Force a password reset for the impacted employees and revoke any tokens.
- C. Configure SSO to prevent passwords from going outside the local network.

D. Set up privileged access management to ensure auditing is enabled.

Answer: B

NEW QUESTION 81

A security analyst wants to identify which vulnerabilities a potential attacker might initially exploit if the network is compromised Which of the following would provide the BEST results?

- A. Baseline configuration assessment
- B. Uncredentialed scan
- C. Network ping sweep
- D. External penetration test

Answer: D

NEW QUESTION 86

A small organization has proprietary software that is used internally. The system has not been well maintained and cannot be updated with the rest of the environment Which of the following is the BEST solution?

- A. Virtualize the system and decommission the physical machine.
- B. Remove it from the network and require air gapping.
- C. Only allow access to the system via a jumpbox
- D. Implement MFA on the specific system.

Answer: A

NEW QUESTION 89

An organization has not had an incident for several month. The Chief information Security Officer (CISO) wants to move to proactive stance for security investigations. Which of the following would BEST meet that goal?

- A. Root-cause analysis
- B. Active response
- C. Advanced antivirus
- D. Information-sharing community
- E. Threat hunting

Answer: E

NEW QUESTION 91

Which of me following BEST articulates the benefit of leveraging SCAP in an organization's cybersecurity analysis toolset?

- A. It automatically performs remedial configuration changes lo enterprise security services
- B. It enables standard checklist and vulnerability analysis expressions for automaton
- C. It establishes a continuous integration environment for software development operations
- D. It provides validation of suspected system vulnerabilities through workflow orchestration

Answer: B

NEW QUESTION 92

A system is experiencing noticeably slow response times, and users are being locked out frequently. An analyst asked for the system security plan and found the system comprises two servers: an application server in the DMZ and a database server inside the trusted domain. Which of the following should be performed NEXT to investigate the availability issue?

- A. Review the firewall logs.
- B. Review syslogs from critical servers.
- C. Perform fuzzing.
- D. Install a WAF in front of the application server.

Answer: C

NEW QUESTION 97

A developer wrote a script to make names and other PII data unidentifiable before loading a database export into the testing system Which of the following describes the type of control that is being used?

- A. Data encoding
- B. Data masking
- C. Data loss prevention
- D. Data classification

Answer: C

NEW QUESTION 98

A malicious hacker wants to gather guest credentials on a hotel 802.11 network. Which of the following tools is the malicious hacker going to use to gain access to information found on the hotel network?

- A. Nikto
- B. Aircrack-ng
- C. Nessus
- D. tcpdump

Answer: A

NEW QUESTION 102

Which of the following roles is ultimately responsible for determining the classification levels assigned to specific data sets?

- A. Data custodian
- B. Data owner
- C. Data processor
- D. Senior management

Answer: B

NEW QUESTION 105

A security analyst is supporting an embedded software team. Which of the following is the BEST recommendation to ensure proper error handling at runtime?

- A. Perform static code analysis.
- B. Require application fuzzing.
- C. Enforce input validation
- D. Perform a code review

Answer: B

NEW QUESTION 107

A security analyst is investigating a malware infection that occurred on a Windows system. The system was not connected to a network and had no wireless capability. Company policy prohibits using portable media or mobile storage. The security analyst is trying to determine which user caused the malware to get onto the system. Which of the following registry keys would MOST likely have this information?

- A)
`HKEY_USERS\<user SID>\Software\Microsoft\Windows\CurrentVersion\Run`
- B)
`HKEY_LOCAL_MACHINE\Software\Microsoft\Windows\CurrentVersion\Run`
- C)
`HKEY_USERS\<user SID>\Software\Microsoft\Windows\explorer\MountPoints2`
- D)
`HKEY_LOCAL_MACHINE\SYSTEM\ControlSet001\services\eventlog\System\iusb3hub`

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: C

NEW QUESTION 109

Which of the following policies would state an employee should not disable security safeguards, such as host firewalls and antivirus on company systems?

- A. Code of conduct policy
- B. Account management policy
- C. Password policy
- D. Acceptable use policy

Answer: D

NEW QUESTION 111

The help desk provided a security analyst with a screenshot of a user's desktop:

```
$ aircrack-ng -e AHT4 -w dictionary.txt wpa2.pcapdump
Opening wpa2.pcapdump
Read 6396 packets.
Opening wpa2.pcapdump
Reading packets, please wait...
```

For which of the following is aircrack-ng being used?

- A. Wireless access point discovery
- B. Rainbow attack
- C. Brute-force attack
- D. PCAP data collection

Answer: B

NEW QUESTION 116

A cybersecurity analyst is supporting an incident response effort via threat intelligence. Which of the following is the analyst MOST likely executing?

- A. Requirements analysis and collection planning
- B. Containment and eradication
- C. Recovery and post-incident review
- D. Indicator enrichment and research pivoting

Answer: A

NEW QUESTION 118

A team of security analysts has been alerted to potential malware activity. The initial examination indicates one of the affected workstations is beaconing on TCP port 80 to five IP addresses and attempting to spread across the network over port 445. Which of the following should be the team's NEXT step during the detection phase of this response process?

- A. Escalate the incident to management, who will then engage the network infrastructure team to keep them informed.
- B. Depending on system criticality, remove each affected device from the network by disabling wired and wireless connections.
- C. Engage the engineering team to block SMB traffic internally and outbound HTTP traffic to the five IP addresses.
- D. Identify potentially affected systems by creating a correlation search in the SIEM based on the network traffic.

Answer: D

NEW QUESTION 123

Which of the following technologies can be used to house the entropy keys for task encryption on desktops and laptops?

- A. Self-encrypting drive
- B. Bus encryption
- C. TPM
- D. HSM

Answer: A

NEW QUESTION 127

Bootloader malware was recently discovered on several company workstations. All the workstations run Windows and are current models with UEFI capability. Which of the following UEFI settings is the MOST likely cause of the infections?

- A. Compatibility mode
- B. Secure boot mode
- C. Native mode
- D. Fast boot mode

Answer: A

NEW QUESTION 132

As part of an exercise set up by the information security officer, the IT staff must move some of the network systems to an off-site facility and redeploy them for testing. All staff members must ensure their respective systems can power back up and match their gold image. If they find any inconsistencies, they must formally document the information.

Which of the following BEST describes this test?

- A. Walk through
- B. Full interruption
- C. Simulation
- D. Parallel

Answer: C

NEW QUESTION 137

Which of the following software security best practices would prevent an attacker from being able to run arbitrary SQL commands within a web application? (Choose two.)

- A. Parameterized queries
- B. Session management
- C. Input validation
- D. Output encoding
- E. Data protection
- F. Authentication

Answer: AC

NEW QUESTION 138

When attempting to do a stealth scan against a system that does not respond to ping, which of the following Nmap commands BEST accomplishes that goal?

- A. `nmap -sA -O <system> -noping`
- B. `nmap -sT -O <system> -P0`
- C. `nmap -sS -O <system> -P0`
- D. `nmap -sQ -O <system> -P0`

Answer: C

NEW QUESTION 140

A cybersecurity analyst is currently checking a newly deployed server that has an access control list applied. When conducting the scan, the analyst received the following code snippet of results:

```
Mail Server1
Trying 192.168.2.2
Connected
Get / HTTP/ 1.0

HTTP:1.0 200 Document follows
Server: server/0.10
Connection: close
Set-Cookie: testing=1; path=/
```

Which of the following describes the output of this scan?

- A. The analyst has discovered a False Positive, and the status code is incorrect providing an OK message.
- B. The analyst has discovered a True Positive, and the status code is correct providing a file not found error message.
- C. The analyst has discovered a True Positive, and the status code is incorrect providing a forbidden message.
- D. The analyst has discovered a False Positive, and the status code is incorrect providing a server error message.

Answer: B

NEW QUESTION 141

During a cyber incident, which of the following is the BEST course of action?

- A. Switch to using a pre-approved, secure, third-party communication system.
- B. Keep the entire company informed to ensure transparency and integrity during the incident.
- C. Restrict customer communication until the severity of the breach is confirmed.
- D. Limit communications to pre-authorized parties to ensure response efforts remain confidential.

Answer: D

NEW QUESTION 145

A security analyst has received reports of very slow, intermittent access to a public-facing corporate server. Suspecting the system may be compromised, the analyst runs the following commands:

```
[root@www18 /tmp]# uptime
19:23:35 up 2:33, 1 user, load average: 87.22, 79.69, 72.17
[root@www18 /tmp]# crontab -l
* * * * * /tmp/.t/t
[root@www18 /tmp]# ps ax | grep tmp
1325 ? Ss 0:00 /tmp/.t/t
[root@www18 /tmp]# netstat -anlp
tcp 0 0 0.0.0.0:22 172.168.0.0:* ESTABLISHED 1204/sshd
tcp 0 0 127.0.0.1:631 0.0.0.0:* LISTEN 1214/cupsd
tcp 0 0 0.0.0.0:443 0.0.0.0:* LISTEN 1267/httpd
```

Based on the output from the above commands, which of the following should the analyst do NEXT to further the investigation?

- A. Run `crontab -r; rm -rf /tmp/.t` to remove and disable the malware on the system.
- B. Examine the server logs for further indicators of compromise of a web application.
- C. Run `kill -9 1325` to bring the load average down so the server is usable again.
- D. Perform a binary analysis on the `/tmp/.t/t` file, as it is likely to be a rogue SSHD server.

Answer: B

NEW QUESTION 149

As part of a merger with another organization, a Chief Information Security Officer (CISO) is working with an assessor to perform a risk assessment focused on data privacy compliance. The CISO is primarily concerned with the potential legal liability and fines associated with data privacy. Based on the CISO's concerns, the assessor will MOST likely focus on:

- A. qualitative probabilities.
- B. quantitative probabilities.
- C. qualitative magnitude.
- D. quantitative magnitude.

Answer: D

NEW QUESTION 153

A user's computer has been running slowly when the user tries to access web pages. A security analyst runs the command `netstat -aon` from the command line and receives the following output:

LINE	PROTOCOL	LOCAL ADDRESS	FOREIGN ADDRESS	STATE
1	TCP	127.0.0.1:15453	127.0.0.1:16374	ESTABLISHED
2	TCP	127.0.0.1:8193	127.0.0.1:8192	ESTABLISHED
3	TCP	192.168.0.23:443	185.23.17.119:17207	ESTABLISHED
4	TCP	192.168.0.23:13985	172.217.0.14:443	ESTABLISHED
5	TCP	192.168.0.23:6023	185.23.17.120:443	ESTABLISHED
6	TCP	192.168.0.23:7264	10.23.63.217:445	ESTABLISHED

Which of the following lines indicates the computer may be compromised?

- A. Line 1
- B. Line 2
- C. Line 3
- D. Line 4
- E. Line 5
- F. Line 6

Answer: D

NEW QUESTION 155

An analyst performs a routine scan of a host using Nmap and receives the following output:

```
$ nmap -sS 10.0.3.1
Starting Nmap 8.9 (http://nmap.org) at 2019-01-19 12:03 PST
Nmap scan report for 10.0.3.1
Host is up (0.00098s latency).
Not shown: 979 closed ports

PORT      STATE      SERVICE
20/tcp    filtered   ftp-data
21/tcp    filtered   ftp
22/tcp    open       ssh
23/tcp    open       telnet
80/tcp    open       http

Nmap done: 1 IP address (1 host up) scanned in 0.840 seconds
```

Which of the following should the analyst investigate FIRST?

- A. Port 21
- B. Port 22
- C. Port 23
- D. Port 80

Answer: C

NEW QUESTION 157

A security analyst received a SIEM alert regarding high levels of memory consumption for a critical system. After several attempts to remediate the issue, the system went down. A root cause analysis revealed a bad actor forced the application to not reclaim memory. This caused the system to be depleted of resources. Which of the following BEST describes this attack?

- A. Injection attack
- B. Memory corruption
- C. Denial of service
- D. Array attack

Answer: B

NEW QUESTION 158

A SIEM solution alerts a security analyst of a high number of login attempts against the company's webmail portal. The analyst determines the login attempts used credentials from a past data breach. Which of the following is the BEST mitigation to prevent unauthorized access?

- A. Single sign-on
- B. Mandatory access control
- C. Multifactor authentication
- D. Federation
- E. Privileged access management

Answer: E

NEW QUESTION 162

A security analyst received an alert from the SIEM indicating numerous login attempts from users outside their usual geographic zones, all of which were initiated through the web-based mail server. The logs indicate all domain accounts experienced two login attempts during the same time frame.

Which of the following is the MOST likely cause of this issue?

- A. A password-spraying attack was performed against the organization.
- B. A DDoS attack was performed against the organization.
- C. This was normal shift work activity; the SIEM's AI is learning.
- D. A credentialed external vulnerability scan was performed.

Answer: A

NEW QUESTION 163

While planning segmentation for an ICS environment, a security engineer determines IT resources will need access to devices within the ICS environment without compromising security.

To provide the MOST secure access model in this scenario, the jumpbox should be.

- A. placed in an isolated network segment, authenticated on the IT side, and forwarded into the ICS network.
- B. placed on the ICS network with a static firewall rule that allows IT network resources to authenticate.
- C. bridged between the IT and operational technology networks to allow authenticated access.
- D. placed on the IT side of the network, authenticated, and tunneled into the ICS environment.

Answer: D

NEW QUESTION 165

An organization has several system that require specific logons Over the past few months, the security analyst has noticed numerous failed logon attempts followed by password resets. Which of the following should the analyst do to reduce the occurrence of legitimate failed logons and password resets?

- A. Use SSO across all applications
- B. Perform a manual privilege review
- C. Adjust the current monitoring and logging rules
- D. Implement multifactor authentication

Answer: B

NEW QUESTION 167

.....

About Exambible

[Your Partner of IT Exam](#)

Found in 1998

Exambible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, Exambible has its unique advantages that other companies could not achieve.

Our Advances

* 99.9% Uptime

All examinations will be up to date.

* 24/7 Quality Support

We will provide service round the clock.

* 100% Pass Rate

Our guarantee that you will pass the exam.

* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

NEW QUESTION 1

A cybersecurity analyst is supposing an incident response effort via threat intelligence. Which of the following is the analyst MOST likely executing?

- A. Requirements analysis and collection planning
- B. Containment and eradication
- C. Recovery and post-incident review
- D. Indicator enrichment and research pivoting

Answer: D

NEW QUESTION 2

An analyst is participating in the solution analysis process for a cloud-hosted SIEM platform to centralize log monitoring and alerting capabilities in the SOC. Which of the following is the BEST approach for supply chain assessment when selecting a vendor?

- A. Gather information from providers, including datacenter specifications and copies of audit reports.
- B. Identify SLA requirements for monitoring and logging.
- C. Consult with senior management for recommendations.
- D. Perform a proof of concept to identify possible solutions.

Answer: B

NEW QUESTION 3

A cybersecurity analyst is reading a daily intelligence digest of new vulnerabilities. The type of vulnerability that should be disseminated FIRST is one that:

- A. enables remote code execution that is being exploited in the wild.
- B. enables data leakage but is not known to be in the environment
- C. enables lateral movement and was reported as a proof of concept
- D. affected the organization in the past but was probably contained and eradicated

Answer: C

NEW QUESTION 4

A security analyst needs to reduce the overall attack surface. Which of the following infrastructure changes should the analyst recommend?

- A. Implement a honeypot.
- B. Air gap sensitive systems.
- C. Increase the network segmentation.
- D. Implement a cloud-based architecture.

Answer: C

NEW QUESTION 5

A security analyst conducted a risk assessment on an organization's wireless network and identified a high-risk element in the implementation of data confidentiality protection. Which of the following is the BEST technical security control to mitigate this risk?

- A. Switch to RADIUS technology
- B. Switch to TACACS+ technology.
- C. Switch to 802.1X technology
- D. Switch to the WPA2 protocol.

Answer: B

NEW QUESTION 6

Which of the following should be found within an organization's acceptable use policy?

- A. Passwords must be eight characters in length and contain at least one special character.
- B. Customer data must be handled properly, stored on company servers, and encrypted when possible.
- C. Administrator accounts must be audited monthly, and inactive accounts should be removed.
- D. Consequences of violating the policy could include discipline up to and including termination.

Answer: D

NEW QUESTION 7

Which of the following is the MOST important objective of a post-incident review?

- A. Capture lessons learned and improve incident response processes
- B. Develop a process for containment and continue improvement efforts
- C. Identify new technologies and strategies to remediate
- D. Identify a new management strategy

Answer: A

NEW QUESTION 8

An organization is moving its infrastructure to the cloud in an effort to meet the budget and reduce staffing requirements. The organization has three environments: development, testing, and production. These environments have interdependencies but must remain relatively segmented. Which of the following methods would BEST secure the company's infrastructure and be the simplest to manage and maintain?

- A. Create three separate cloud accounts for each environmen
- B. Configure account peering and security rules to allow access to and from each environment.
- C. Create one cloud account with one VPC for all environment
- D. Purchase a virtual firewall and create granular security rules.
- E. Create one cloud account and three separate VPCs for each environmen
- F. Create security rules to allow access to and from each environment.
- G. Create three separate cloud accounts for each environment and a single core account for network service
- H. Route all traffic through the core account.

Answer: C

NEW QUESTION 9

During routine monitoring, a security analyst discovers several suspicious websites that are communicating with a local host. The analyst queries for IP 192.168.50.2 for a 24-hour period:

Time	SRC	DST	Domain	Bytes
6/26/19 10:01	192.168.50.2	138.10.2.5	www.wioapsfeje.co	50
6/26/19 11:05	192.168.50.2	138.10.2.5	www.wioapsfeje.co	1000
6/26/19 13:09	192.168.50.2	138.10.25.5	www.wfaojsjfjoe.co	1000
6/26/19 15:13	192.168.50.2	172.10.25.5	www.wfalksdjflse.co	1000
6/26/19 17:17	192.168.50.2	172.10.45.5	www.wsahlfdsjlfse.co	1000
6/26/19 23:45	192.168.50.2	172.10.3.5	ftp.walksdjgfl.co	50000
6/27/19 10:21	192.168.50.2	175.35.20.5	www.whatsmyip.com	25
6/27/19 11:25	192.168.50.2	175.35.20.5	www.whatsmyip.com	25

To further investigate, the analyst should request PCAP for SRC 192.168.50.2 and.

- A. DST 138.10.2.5.
- B. DST 138.10.25.5.
- C. DST 172.10.3.5.
- D. DST 172.10.45.5.
- E. DST 175.35.20.5.

Answer: A

NEW QUESTION 10

Which of the following BEST describes the process by which code is developed, tested, and deployed in small batches?

- A. Agile
- B. Waterfall
- C. SDLC
- D. Dynamic code analysis

Answer: A

NEW QUESTION 10

The inability to do remote updates of certificates, keys software and firmware is a security issue commonly associated with:

- A. web servers on private networks.
- B. HVAC control systems
- C. smartphones
- D. firewalls and UTM devices

Answer: B

NEW QUESTION 11

A security analyst has discovered suspicious traffic and determined a host is connecting to a known malicious website. The MOST appropriate action for the analyst to take would be to implement a change request to:

- A. update the antivirus software
- B. configure the firewall to block traffic to the domain
- C. add the domain to the blacklist
- D. create an IPS signature for the domain

Answer: B

NEW QUESTION 12

An analyst is reviewing a list of vulnerabilities, which were reported from a recent vulnerability scan of a Linux server. Which of the following is MOST likely to be a false positive?

- A. OpenSSH/OpenSSL Package Random Number Generator Weakness
- B. Apache HTTP Server Byte Range DoS
- C. GDI+ Remote Code Execution Vulnerability (MS08-052)
- D. HTTP TRACE / TRACK Methods Allowed (002-1208)
- E. SSL Certificate Expiry

Answer: E

NEW QUESTION 14

A security analyst discovered a specific series of IP addresses that are targeting an organization. None of the attacks have been successful. Which of the following should the security analyst perform NEXT?

- A. Begin blocking all IP addresses within that subnet.
- B. Determine the attack vector and total attack surface.
- C. Begin a kill chain analysis to determine the impact.
- D. Conduct threat research on the IP addresses

Answer: D

NEW QUESTION 17

The security team at a large corporation is helping the payment-processing team to prepare for a regulatory compliance audit and meet the following objectives:

- Reduce the number of potential findings by the auditors.
- Limit the scope of the audit to only devices used by the payment-processing team for activities directly impacted by the regulations.
- Prevent the external-facing web infrastructure used by other teams from coming into scope.
- Limit the amount of exposure the company will face if the systems used by the payment-processing team are compromised.

Which of the following would be the MOST effective way for the security team to meet these objectives?

- A. Limit the permissions to prevent other employees from accessing data owned by the business unit.
- B. Segment the servers and systems used by the business unit from the rest of the network.
- C. Deploy patches to all servers and workstations across the entire organization.
- D. Implement full-disk encryption on the laptops used by employees of the payment-processing team.

Answer: B

NEW QUESTION 21

A security analyst is investigating malicious traffic from an internal system that attempted to download proxy avoidance software as identified from the firewall logs but the destination IP is blocked and not captured. Which of the following should the analyst do?

- A. Shut down the computer
- B. Capture live data using Wireshark
- C. Take a snapshot
- D. Determine if DNS logging is enabled.
- E. Review the network logs.

Answer: A

NEW QUESTION 24

An organization developed a comprehensive incident response policy. Executive management approved the policy and its associated procedures. Which of the following activities would be MOST beneficial to evaluate personnel's familiarity with incident response procedures?

- A. A simulated breach scenario involving the incident response team
- B. Completion of annual information security awareness training by all employees
- C. Tabletop activities involving business continuity team members
- D. Completion of lessons-learned documentation by the computer security incident response team
- E. External and internal penetration testing by a third party

Answer: A

NEW QUESTION 25

A company was recently awarded several large government contracts and wants to determine its current risk from one specific APT. Which of the following threat modeling methodologies would be the MOST appropriate to use during this analysis?

- A. Attack vectors
- B. Adversary capability
- C. Diamond Model of Intrusion Analysis
- D. Kill chain
- E. Total attack surface

Answer: B

NEW QUESTION 27

A security analyst suspects a malware infection was caused by a user who downloaded malware after clicking `http://<malwaresource>/a.php` in a phishing email. To prevent other computers from being infected by the same malware variation, the analyst should create a rule on the.

- A. email server that automatically deletes attached executables.
- B. IDS to match the malware sample.
- C. proxy to block all connections to `<malwaresource>`.
- D. firewall to block connection attempts to dynamic DNS hosts.

Answer: C

NEW QUESTION 31

You are a cybersecurity analyst tasked with interpreting scan data from Company A's servers. You must verify the requirements are being met for all of the servers and recommend changes if you find they are not.

The company's hardening guidelines indicate the following:

- TLS 1.2 is the only version of TLS running.
- Apache 2.4.18 or greater should be used.
- Only default ports should be used. INSTRUCTIONS

Using the supplied data, record the status of compliance with the company's guidelines for each server.

The question contains two parts: make sure you complete Part 1 and Part 2. Make recommendations for issues based ONLY on the hardening guidelines provided.

Part 1

Scan Data	Compliance Report
<div>AppServ1AppServ2AppServ3AppServ4</div> <pre>root@INFOSEC:~# curl --head appsrv1.fictionalorg.com:443 HTTP/1.1 200 OK Date: Wed, 26 Jun 2019 21:15:15 GMT Server: Apache/2.4.48 (CentOS) Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT ETag: "13520-58c407930177d" Accept-Ranges: bytes Content-Length: 79136 Vary: Accept-Encoding Cache-Control: max-age=3600 Expires: Wed, 26 Jun 2019 22:15:15 GMT Content-Type: text/html root@INFOSEC:~# nmap --script ssl-enum-ciphers appsrv1.fictionalorg.com -p 443 Starting Nmap 6.40 (http://nmap.org) at 2019-06-26 16:07 CDT Nmap scan report for AppSrv1.fictionalorg.com (10.21.4.68) Host is up (0.042s latency). rDNS record for 10.21.4.68: inaddrArpa.fictionalorg.com PORT STATE SERVICE 443/tcp open https ssl-enum-ciphers: TLSv1.2: ciphers: TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong TLS_RSA_WITH_AES_128_CBC_SHA - strong TLS_RSA_WITH_AES_128_GCM_SHA256 - strong TLS_RSA_WITH_AES_256_CBC_SHA - strong TLS_RSA_WITH_AES_256_GCM_SHA384 - strong compressors: NULL _ least strength: strong Nmap done: 1 IP address (1 host up) scanned in 8.63 seconds root@INFOSEC:~# nmap --top-ports 10 appsrv1.fictionalorg.com Starting Nmap 6.40 (http://nmap.org) at 2019-06-27 10:13 CDT Nmap scan report for appsrv1.fictionalorg.com (10.21.4.68) Host is up (0.15s latency). rDNS record for 10.21.4.68: appsrv1.fictionalorg.com PORT STATE SERVICE 80/tcp open http 443/tcp open https Nmap done: 1 IP address (1 host up) scanned in 0.42 seconds</pre>	<div>Fill out the following report based on your analysis of the scan data.</div> <div><div><input type="checkbox"/> AppServ1 is only using TLS 1.2</div><div><input type="checkbox"/> AppServ2 is only using TLS 1.2</div><div><input type="checkbox"/> AppServ3 is only using TLS 1.2</div><div><input type="checkbox"/> AppServ4 is only using TLS 1.2</div><div><input type="checkbox"/> AppServ1 is using Apache 2.4.18 or greater</div><div><input type="checkbox"/> AppServ2 is using Apache 2.4.18 or greater</div><div><input type="checkbox"/> AppServ3 is using Apache 2.4.18 or greater</div><div><input type="checkbox"/> AppServ4 is using Apache 2.4.18 or greater</div></div>

Part 1

Scan Data

AppServ1 AppServ2 AppServ3 AppServ4

Compliance Report

Fill out the following report based on your analysis of the scan data.

```
root@INFOSEC:~# curl --head appsrv2.fictionalorg.com:443

HTTP/1.1 200 OK
Date: Wed, 26 Jun 2019 21:15:15 GMT
Server: Apache/2.3.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c407930177d"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html

root@INFOSEC:~# nmap --script ssl-enum-ciphers
appsrv2.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv2.fictionalorg.com (10.21.4.69)
Host is up (0.042s latency).
rDNS record for 10.21.4.69: inaddrArpa.fictionalorg.com
Not shown: 998 filtered ports
PORT      STATE SERVICE
80/tcp    open  http
443/tcp   open  https
| ssl-enum-ciphers:
|   TLSv1.0:
|     ciphers:
|       TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|       TLS_RSA_WITH_AES_128_CBC_SHA - strong
|       TLS_RSA_WITH_AES_256_CBC_SHA - strong
|     compressors:
|       NULL
|   TLSv1.1:
|     ciphers:
|       TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|       TLS_RSA_WITH_AES_128_CBC_SHA - strong
|       TLS_RSA_WITH_AES_256_CBC_SHA - strong
|     compressors:
|       NULL
|   TLSv1.2:
|     ciphers:
|       TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|       TLS_RSA_WITH_AES_128_CBC_SHA - strong
|       TLS_RSA_WITH_AES_128_GCM_SHA256 - strong
|       TLS_RSA_WITH_AES_256_CBC_SHA - strong
|       TLS_RSA_WITH_AES_256_GCM_SHA384 - strong
|     compressors:
|       NULL
|_  least strength: strong

Nmap done: 1 IP address (1 host up) scanned in 8.63 seconds

root@INFOSEC:~# nmap --top-ports 10 appsrv2.fictionalorg.com

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-27 10:13 CDT

Nmap scan report for appsrv2.fictionalorg.com (10.21.4.69)
Host is up (0.15s latency).
rDNS record for 10.21.4.69: appsrv2.fictionalorg.com
PORT      STATE SERVICE
80/tcp    open  http
443/tcp   open  https

Nmap done: 1 IP address (1 host up) scanned in 0.42 seconds
```

- ☐ AppServ1 is only using TLS 1.2
- ☐ AppServ2 is only using TLS 1.2
- ☐ AppServ3 is only using TLS 1.2
- ☐ AppServ4 is only using TLS 1.2
- ☐ AppServ1 is using Apache 2.4.18 or greater
- ☐ AppServ2 is using Apache 2.4.18 or greater
- ☐ AppServ3 is using Apache 2.4.18 or greater
- ☐ AppServ4 is using Apache 2.4.18 or greater

Part 1

Scan Data

AppServ1 AppServ2 AppServ3 AppServ4

```
root@INFOSEC:~# curl --head appsrv3.fictionalorg.com:443

HTTP/1.1 200 OK
Date: Wed, 26 Jun 2019 21:15:15 GMT
Server: Apache/2.4.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c406780177e"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html

root@INFOSEC:~# nmap --script ssl-enum-ciphers
appsrv3.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv3.fictionalorg.com (10.21.4.70)
Host is up (0.042s latency).
rDNS record for 10.21.4.70: inaddrArpa.fictionalorg.com
PORT      STATE SERVICE
80/tcp    open  http
443/tcp   open  https
| ssl-enum-ciphers:
|   TLSv1.0:
|   | ciphers:
|   | | TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_128_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_256_CBC_SHA - strong
|   | compressors:
|   | | NULL
|   TLSv1.1:
|   | ciphers:
|   | | TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_128_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_256_CBC_SHA - strong
|   | compressors:
|   | | NULL
|   TLSv1.2:
|   | ciphers:
|   | | TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_128_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_128_GCM_SHA256 - strong
|   | | TLS_RSA_WITH_AES_256_CBC_SHA - strong
|   | | TLS_RSA_WITH_AES_256_GCM_SHA384 - strong
|   | compressors:
|   | | NULL
|_ least strength: strong

Nmap done: 1 IP address (1 host up) scanned in 8.63 seconds

root@INFOSEC:~# nmap --top-ports 10 appsrv3.fictionalorg.com

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-27 10:13 CDT

Nmap scan report for appsrv3.fictionalorg.com (10.21.4.70)
Host is up (0.15s latency).
rDNS record for 10.21.4.70: appsrv3.fictionalorg.com
PORT      STATE SERVICE
80/tcp    open  http
443/tcp   open  https

Nmap done: 1 IP address (1 host up) scanned in 0.42 seconds
```

Compliance Report

Fill out the following report based on your analysis of the scan data.

- ☐ AppServ1 is only using TLS 1.2
- ☐ AppServ2 is only using TLS 1.2
- ☐ AppServ3 is only using TLS 1.2
- ☐ AppServ4 is only using TLS 1.2
- ☐ AppServ1 is using Apache 2.4.18 or greater
- ☐ AppServ2 is using Apache 2.4.18 or greater
- ☐ AppServ3 is using Apache 2.4.18 or greater
- ☐ AppServ4 is using Apache 2.4.18 or greater

Part 1

Scan Data

AppServ1 AppServ2 AppServ3 AppServ4

```
root@INFOSEC:~# curl --head appsrv4.fictionalorg.com:443

HTTP/1.1 200 OK
Date: Wed, 26 Jun 2019 21:15:15 GMT
Server: Apache/2.4.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c406780177e"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html

root@INFOSEC:~# nmap --script ssl-enum-ciphers
appsrv4.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv4.fictionalorg.com (10.21.4.71)
Host is up (0.042s latency).
rDNS record for 10.21.4.71: inaddrArpa.fictionalorg.com
PORT      STATE SERVICE
443/tcp   open  https
| TLSv1.2:
|   ciphers:
|     TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|     TLS_RSA_WITH_AES_128_CBC_SHA - strong
|     TLS_RSA_WITH_AES_128_GCM_SHA256 - strong
|     TLS_RSA_WITH_AES_256_CBC_SHA - strong
|     TLS_RSA_WITH_AES_256_GCM_SHA384 - strong
|   compressors:
|     NULL
|_  least strength: strong

Nmap done: 1 IP address (1 host up) scanned in 8.63 seconds

root@INFOSEC:~# nmap --top-ports 10 appsrv4.fictionalorg.com

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-27 10:13 CDT
Nmap scan report for appsrv4.fictionalorg.com (10.21.4.71)
Host is up (0.15s latency).
rDNS record for 10.21.4.71: appsrv4.fictionalorg.com
PORT      STATE SERVICE
80/tcp    open  http
443/tcp   open  https
8675/tcp  open  ssh

Nmap done: 1 IP address (1 host up) scanned in 0.42 seconds
```

Compliance Report

Fill out the following report based on your analysis of the scan data.

- ☐ AppServ1 is only using TLS 1.2
- ☐ AppServ2 is only using TLS 1.2
- ☐ AppServ3 is only using TLS 1.2
- ☐ AppServ4 is only using TLS 1.2
- ☐ AppServ1 is using Apache 2.4.18 or greater
- ☐ AppServ2 is using Apache 2.4.18 or greater
- ☐ AppServ3 is using Apache 2.4.18 or greater
- ☐ AppServ4 is using Apache 2.4.18 or greater

Part 2

Scan Data

AppServ1 AppServ2 AppServ3 AppServ4

Configuration Change Recommendations



Add recommendation for

AppSrv1
AppSrv2
AppSrv3
AppSrv4

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Part 1 Answer

Check on the following:

- AppServ1 is only using TLS.1.2
- AppServ4 is only using TLS.1.2
- AppServ1 is using Apache 2.4.18 or greater
- AppServ3 is using Apache 2.4.18 or greater
- AppServ4 is using Apache 2.4.18 or greater

Recommendation is to disable TLS v1.1 on AppServ2 and AppServ3. Also upgrade AppServ2 Apache to version 2.4.48 from its current version of 2.3.48

Scan Data		Configuration Change Recommendations																			
AppSrv1	AppSrv2	AppSrv3	AppSrv4																		
<pre>root@INF0SEC:~# curl --head appsrv2.fictionalorg.com:443 HTTP/1.1 200 OK Date: Wed, 26 Jun 2019 21:15:15 GMT Server: Apache/2.3.48 (CentOS) Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT ETag: "13528-58c407930177d" Accept-Ranges: bytes Content-Length: 79136 Vary: Accept-Encoding Cache-Control: max-age=3600 Expires: Wed, 26 Jun 2019 22:15:15 GMT Content-Type: text/html root@INF0SEC:~# nmap --script ssl-enum-ciphers appsrv2.fictionalorg.com -p 443 Starting Nmap 6.40 (http://nmap.org) at 2019-06-26 16:07 CDT Nmap scan report for AppSrv2.fictionalorg.com (10.21.4.69) Host is up (0.042s latency). rDNS record for 10.21.4.69: inaddrArpa.fictionalorg.com Not shown: 998 filtered ports PORT STATE SERVICE 80/tcp open http 443/tcp open https ssl-enum-ciphers: _ TLSv1.0: _ TLSv1.1: _ TLSv1.2: _ TLSv1.3:</pre>		<p> Add Recommendation for AppSrv2 ▼</p> <table border="1"> <tr> <td>Server</td> <td>AppSrv2 ▼</td> </tr> <tr> <td>Service</td> <td>Apache Version ▼</td> </tr> <tr> <td>Config Change</td> <td>Upgrade Version ▼</td> </tr> </table> <p></p> <table border="1"> <tr> <td>Server</td> <td>AppSrv3 ▼</td> </tr> <tr> <td>Service</td> <td>HTTPD Security ▼</td> </tr> <tr> <td>Config Change</td> <td>Restrict To TLS 1.2 ▼</td> </tr> </table> <p></p> <table border="1"> <tr> <td>Server</td> <td>AppSrv4 ▼</td> </tr> <tr> <td>Service</td> <td>SSH ▼</td> </tr> <tr> <td>Config Change</td> <td>Remove or Disable ▼</td> </tr> </table>		Server	AppSrv2 ▼	Service	Apache Version ▼	Config Change	Upgrade Version ▼	Server	AppSrv3 ▼	Service	HTTPD Security ▼	Config Change	Restrict To TLS 1.2 ▼	Server	AppSrv4 ▼	Service	SSH ▼	Config Change	Remove or Disable ▼
Server	AppSrv2 ▼																				
Service	Apache Version ▼																				
Config Change	Upgrade Version ▼																				
Server	AppSrv3 ▼																				
Service	HTTPD Security ▼																				
Config Change	Restrict To TLS 1.2 ▼																				
Server	AppSrv4 ▼																				
Service	SSH ▼																				
Config Change	Remove or Disable ▼																				

A development team uses open-source software and follows an Agile methodology with two-week sprints. Last month, the security team filed a bug for an insecure version of a common library. The DevOps team updated the library on the server, and then the security team rescanned the server to verify it was no longer vulnerable. This month, the security team found the same vulnerability on the server. Which of the following should be done to correct the cause of the vulnerability?

- A. Deploy a WAF in front of the application.
- B. Implement a software repository management tool.
- C. Install a HIPS on the server.
- D. Instruct the developers to use input validation in the code.

NEW QUESTION 39

Which of the following would BEST satisfy the objectives defined by the compliance officer? (Choose two.)

- A. Executing vendor compliance assessments against the organization's security controls
- B. Executing NDAs prior to sharing critical data with third parties
- C. Soliciting third-party audit reports on an annual basis
- D. Maintaining and reviewing the organizational risk assessment on a quarterly basis
- E. Completing a business impact assessment for all critical service providers
- F. Utilizing DLP capabilities at both the endpoint and perimeter levels

NEW QUESTION 40

Which of the following is the MOST proactive tool or technique that feeds incident response capabilities?

- A. Development of a hypothesis as part of threat hunting
- B. Log correlation, monitoring, and automated reporting through a SIEM platform
- C. Continuous compliance monitoring using SCAP dashboards
- D. Quarterly vulnerability scanning using credentialed scans

NEW QUESTION 43

- A. DLP
- B. Encryption
- C. Test data

D. NDA

Answer: D

NEW QUESTION 48

A security team wants to make SaaS solutions accessible from only the corporate campus. Which of the following would BEST accomplish this goal?

- A. Geofencing
- B. IP restrictions
- C. Reverse proxy
- D. Single sign-on

Answer: A

NEW QUESTION 49

A monthly job to install approved vendor software updates and hot fixes recently stopped working. The security team performed a vulnerability scan, which identified several hosts as having some critical OS vulnerabilities, as referenced in the common vulnerabilities and exposures (CVE) database. Which of the following should the security team do NEXT to resolve the critical findings in the most effective manner? (Choose two.)

- A. Patch the required hosts with the correct updates and hot fixes, and rescan them for vulnerabilities.
- B. Remove the servers reported to have high and medium vulnerabilities.
- C. Tag the computers with critical findings as a business risk acceptance.
- D. Manually patch the computers on the network, as recommended on the CVE website.
- E. Harden the hosts on the network, as recommended by the NIST framework.
- F. Resolve the monthly job issues and test them before applying them to the production network.

Answer: CE

NEW QUESTION 53

A security analyst is reviewing the following log entries to identify anomalous activity:

```
GET https://comptia.org/admin/login.html&user&password\ HTTP/1.1
GET http://comptia.org/index.php\ HTTP/1.1
GET http://comptia.org/scripts/..%5c../Windows/System32/cmd.exe?/C+dir+c:\ HTTP/1.1
GET http://comptia.org/media/contactus.html\ HTTP/1.1
```

Which of the following attack types is occurring?

- A. Directory traversal
- B. SQL injection
- C. Buffer overflow
- D. Cross-site scripting

Answer: A

NEW QUESTION 56

As a proactive threat-hunting technique, hunters must develop situational cases based on likely attack scenarios derived from the available threat intelligence information. After forming the basis of the scenario, which of the following may the threat hunter construct to establish a framework for threat assessment?

- A. Critical asset list
- B. Threat vector
- C. Attack profile
- D. Hypothesis

Answer: A

NEW QUESTION 59

Which of the following sets of attributes BEST illustrates the characteristics of an insider threat from a security perspective?

- A. Unauthorized, unintentional, benign
- B. Unauthorized, intentional, malicious
- C. Authorized, intentional, malicious
- D. Authorized, unintentional, benign

Answer: C

NEW QUESTION 64

An analyst has been asked to provide feedback regarding the control required by a revised regulatory framework. At this time, the analyst only needs to focus on the technical controls. Which of the following should the analyst provide an assessment of?

- A. Tokenization of sensitive data
- B. Establishment of data classifications
- C. Reporting on data retention and purging activities
- D. Formal identification of data ownership
- E. Execution of NDAs

Answer: A

NEW QUESTION 66

The inability to do remote updates of certificates, keys, software, and firmware is a security issue commonly associated with:

- A. web servers on private networks
- B. HVAC control systems
- C. smartphones
- D. firewalls and UTM devices

Answer: D

NEW QUESTION 69

The computer incident response team at a multinational company has determined that a breach of sensitive data has occurred in which a threat actor has compromised the organization's email system. Per the incident response procedures, this breach requires notifying the board immediately. Which of the following would be the BEST method of communication?

- A. Post of the company blog
- B. Corporate-hosted encrypted email
- C. VoIP phone call
- D. Summary sent by certified mail
- E. Externally hosted instant message

Answer: C

NEW QUESTION 70

An information security analyst is working with a data owner to identify the appropriate controls to preserve the confidentiality of data within an enterprise environment. One of the primary concerns is exfiltration of data by malicious insiders. Which of the following controls is the MOST appropriate to mitigate risks?

- A. Data deduplication
- B. OS fingerprinting
- C. Digital watermarking
- D. Data loss prevention

Answer: D

NEW QUESTION 72

A company wants to establish a threat-hunting team. Which of the following BEST describes the rationale for integration intelligence into hunt operations?

- A. It enables the team to prioritize the focus area and tactics within the company's environment.
- B. It provide critically analyses for key enterprise servers and services.
- C. It allow analysis to receive updates on newly discovered software vulnerabilities.
- D. It supports rapid response and recovery during and followed an incident.

Answer: A

NEW QUESTION 73

A security analyst is reviewing the logs from an internal chat server. The chat.log file is too large to review manually, so the analyst wants to create a shorter log file that only includes lines associated with a user demonstrating anomalous activity. Below is a snippet of the log:

Line	User	Time	Command	Result
36570	DEV12	02.01.13.151219	KICK DEV27	OK
36571	JAVASHARK	02.01.13.151255	JOIN #CHATOPS e32kk10	OK
36572	DEV12	02.01.13.151325	PART #CHATOPS	OK
36573	CHATTER14	02.01.13.151327	JOIN';CAT ../etc/config'	OK
36574	PYTHONFUN	02.01.13.151330	PRIVMSG DEV99 "?"	OK
36575	DEV99	02.01.13.151358	PRIVMSG PYTHONFUN "OK"	OK

Which of the following commands would work BEST to achieve the desired result?

- A. `grep -v chatter14 chat.log`
- B. `grep -i pythonfun chat.log`
- C. `grep -i javashark chat.log`
- D. `grep -v javashark chat.log`
- E. `grep -v pythonfun chat.log`
- F. `grep -i chatter14 chat.log`

Answer: D

NEW QUESTION 78

A security analyst has received information from a third-party intelligence-sharing resource that indicates employee accounts were breached. Which of the following is the NEXT step the analyst should take to address the issue?

- A. Audit access permissions for all employees to ensure least privilege.
- B. Force a password reset for the impacted employees and revoke any tokens.
- C. Configure SSO to prevent passwords from going outside the local network.

D. Set up privileged access management to ensure auditing is enabled.

Answer: B

NEW QUESTION 81

A security analyst wants to identify which vulnerabilities a potential attacker might initially exploit if the network is compromised. Which of the following would provide the BEST results?

- A. Baseline configuration assessment
- B. Uncredentialed scan
- C. Network ping sweep
- D. External penetration test

Answer: D

NEW QUESTION 86

A small organization has proprietary software that is used internally. The system has not been well maintained and cannot be updated with the rest of the environment. Which of the following is the BEST solution?

- A. Virtualize the system and decommission the physical machine.
- B. Remove it from the network and require air gapping.
- C. Only allow access to the system via a jumpbox.
- D. Implement MFA on the specific system.

Answer: A

NEW QUESTION 89

An organization has not had an incident for several months. The Chief Information Security Officer (CISO) wants to move to a proactive stance for security investigations. Which of the following would BEST meet that goal?

- A. Root-cause analysis
- B. Active response
- C. Advanced antivirus
- D. Information-sharing community
- E. Threat hunting

Answer: E

NEW QUESTION 91

Which of the following BEST articulates the benefit of leveraging SCAP in an organization's cybersecurity analysis toolset?

- A. It automatically performs remedial configuration changes to enterprise security services.
- B. It enables standard checklist and vulnerability analysis expressions for automation.
- C. It establishes a continuous integration environment for software development operations.
- D. It provides validation of suspected system vulnerabilities through workflow orchestration.

Answer: B

NEW QUESTION 92

A system is experiencing noticeably slow response times, and users are being locked out frequently. An analyst asked for the system security plan and found the system comprises two servers: an application server in the DMZ and a database server inside the trusted domain. Which of the following should be performed NEXT to investigate the availability issue?

- A. Review the firewall logs.
- B. Review syslogs from critical servers.
- C. Perform fuzzing.
- D. Install a WAF in front of the application server.

Answer: C

NEW QUESTION 97

A developer wrote a script to make names and other PII data unidentifiable before loading a database export into the testing system. Which of the following describes the type of control that is being used?

- A. Data encoding
- B. Data masking
- C. Data loss prevention
- D. Data classification

Answer: C

NEW QUESTION 98

A malicious hacker wants to gather guest credentials on a hotel 802.11 network. Which of the following tools is the malicious hacker going to use to gain access to information found on the hotel network?

- A. Nikto
- B. Aircrack-ng
- C. Nessus
- D. tcpdump

Answer: A

NEW QUESTION 102

Which of the following roles is ultimately responsible for determining the classification levels assigned to specific data sets?

- A. Data custodian
- B. Data owner
- C. Data processor
- D. Senior management

Answer: B

NEW QUESTION 105

A security analyst is supporting an embedded software team. Which of the following is the BEST recommendation to ensure proper error handling at runtime?

- A. Perform static code analysis.
- B. Require application fuzzing.
- C. Enforce input validation
- D. Perform a code review

Answer: B

NEW QUESTION 107

A security analyst is investigating a malware infection that occurred on a Windows system. The system was not connected to a network and had no wireless capability. Company policy prohibits using portable media or mobile storage. The security analyst is trying to determine which user caused the malware to get onto the system. Which of the following registry keys would MOST likely have this information?

- A)
`HKEY_USERS\<user SID>\Software\Microsoft\Windows\CurrentVersion\Run`
- B)
`HKEY_LOCAL_MACHINE\Software\Microsoft\Windows\CurrentVersion\Run`
- C)
`HKEY_USERS\<user SID>\Software\Microsoft\Windows\explorer\MountPoints2`
- D)
`HKEY_LOCAL_MACHINE\SYSTEM\ControlSet001\services\eventlog\System\iusb3hub`

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: C

NEW QUESTION 109

Which of the following policies would state an employee should not disable security safeguards, such as host firewalls and antivirus on company systems?

- A. Code of conduct policy
- B. Account management policy
- C. Password policy
- D. Acceptable use policy

Answer: D

NEW QUESTION 111

The help desk provided a security analyst with a screenshot of a user's desktop:

```
$ aircrack-ng -e AHT4 -w dictionary.txt wpa2.pcapdump
Opening wpa2.pcapdump
Read 6396 packets.
Opening wpa2.pcapdump
Reading packets, please wait...
```

For which of the following is aircrack-ng being used?

- A. Wireless access point discovery
- B. Rainbow attack
- C. Brute-force attack
- D. PCAP data collection

Answer: B

NEW QUESTION 116

A cybersecurity analyst is supporting an incident response effort via threat intelligence. Which of the following is the analyst MOST likely executing?

- A. Requirements analysis and collection planning
- B. Containment and eradication
- C. Recovery and post-incident review
- D. Indicator enrichment and research pivoting

Answer: A

NEW QUESTION 118

A team of security analysts has been alerted to potential malware activity. The initial examination indicates one of the affected workstations is beaconing on TCP port 80 to five IP addresses and attempting to spread across the network over port 445. Which of the following should be the team's NEXT step during the detection phase of this response process?

- A. Escalate the incident to management, who will then engage the network infrastructure team to keep them informed.
- B. Depending on system criticality, remove each affected device from the network by disabling wired and wireless connections.
- C. Engage the engineering team to block SMB traffic internally and outbound HTTP traffic to the five IP addresses.
- D. Identify potentially affected systems by creating a correlation search in the SIEM based on the network traffic.

Answer: D

NEW QUESTION 123

Which of the following technologies can be used to house the entropy keys for task encryption on desktops and laptops?

- A. Self-encrypting drive
- B. Bus encryption
- C. TPM
- D. HSM

Answer: A

NEW QUESTION 127

Bootloader malware was recently discovered on several company workstations. All the workstations run Windows and are current models with UEFI capability. Which of the following UEFI settings is the MOST likely cause of the infections?

- A. Compatibility mode
- B. Secure boot mode
- C. Native mode
- D. Fast boot mode

Answer: A

NEW QUESTION 132

As part of an exercise set up by the information security officer, the IT staff must move some of the network systems to an off-site facility and redeploy them for testing. All staff members must ensure their respective systems can power back up and match their gold image. If they find any inconsistencies, they must formally document the information.

Which of the following BEST describes this test?

- A. Walk through
- B. Full interruption
- C. Simulation
- D. Parallel

Answer: C

NEW QUESTION 137

Which of the following software security best practices would prevent an attacker from being able to run arbitrary SQL commands within a web application? (Choose two.)

- A. Parameterized queries
- B. Session management
- C. Input validation
- D. Output encoding
- E. Data protection
- F. Authentication

Answer: AC

NEW QUESTION 138

When attempting to do a stealth scan against a system that does not respond to ping, which of the following Nmap commands BEST accomplishes that goal?

- A. `nmap -sA -O <system> -noping`
- B. `nmap -sT -O <system> -P0`
- C. `nmap -sS -O <system> -P0`
- D. `nmap -sQ -O <system> -P0`

Answer: C

NEW QUESTION 140

A cybersecurity analyst is currently checking a newly deployed server that has an access control list applied. When conducting the scan, the analyst received the following code snippet of results:

```
Mail Server1
Trying 192.168.2.2
Connected
Get / HTTP/ 1.0

HTTP:1.0 200 Document follows
Server: server/0.10
Connection: close
Set-Cookie: testing=1; path=/
```

Which of the following describes the output of this scan?

- A. The analyst has discovered a False Positive, and the status code is incorrect providing an OK message.
- B. The analyst has discovered a True Positive, and the status code is correct providing a file not found error message.
- C. The analyst has discovered a True Positive, and the status code is incorrect providing a forbidden message.
- D. The analyst has discovered a False Positive, and the status code is incorrect providing a server error message.

Answer: B

NEW QUESTION 141

During a cyber incident, which of the following is the BEST course of action?

- A. Switch to using a pre-approved, secure, third-party communication system.
- B. Keep the entire company informed to ensure transparency and integrity during the incident.
- C. Restrict customer communication until the severity of the breach is confirmed.
- D. Limit communications to pre-authorized parties to ensure response efforts remain confidential.

Answer: D

NEW QUESTION 145

A security analyst has received reports of very slow, intermittent access to a public-facing corporate server. Suspecting the system may be compromised, the analyst runs the following commands:

```
[root@www18 /tmp]# uptime
19:23:35 up 2:33, 1 user, load average: 87.22, 79.69, 72.17
[root@www18 /tmp]# crontab -l
* * * * * /tmp/.t/t
[root@www18 /tmp]# ps ax | grep tmp
1325 ? Ss 0:00 /tmp/.t/t
[root@www18 /tmp]# netstat -anlp
tcp 0 0 0.0.0.0:22 172.168.0.0:* ESTABLISHED 1204/sshd
tcp 0 0 127.0.0.1:631 0.0.0.0:* LISTEN 1214/cupsd
tcp 0 0 0.0.0.0:443 0.0.0.0:* LISTEN 1267/httpd
```

Based on the output from the above commands, which of the following should the analyst do NEXT to further the investigation?

- A. Run `crontab -r; rm -rf /tmp/.t` to remove and disable the malware on the system.
- B. Examine the server logs for further indicators of compromise of a web application.
- C. Run `kill -9 1325` to bring the load average down so the server is usable again.
- D. Perform a binary analysis on the `/tmp/.t/t` file, as it is likely to be a rogue SSHD server.

Answer: B

NEW QUESTION 149

As part of a merger with another organization, a Chief Information Security Officer (CISO) is working with an assessor to perform a risk assessment focused on data privacy compliance. The CISO is primarily concerned with the potential legal liability and fines associated with data privacy. Based on the CISO's concerns, the assessor will MOST likely focus on:

- A. qualitative probabilities.
- B. quantitative probabilities.
- C. qualitative magnitude.
- D. quantitative magnitude.

Answer: D

NEW QUESTION 153

A user's computer has been running slowly when the user tries to access web pages. A security analyst runs the command `netstat -aon` from the command line and receives the following output:

LINE	PROTOCOL	LOCAL ADDRESS	FOREIGN ADDRESS	STATE
1	TCP	127.0.0.1:15453	127.0.0.1:16374	ESTABLISHED
2	TCP	127.0.0.1:8193	127.0.0.1:8192	ESTABLISHED
3	TCP	192.168.0.23:443	185.23.17.119:17207	ESTABLISHED
4	TCP	192.168.0.23:13985	172.217.0.14:443	ESTABLISHED
5	TCP	192.168.0.23:6023	185.23.17.120:443	ESTABLISHED
6	TCP	192.168.0.23:7264	10.23.63.217:445	ESTABLISHED

Which of the following lines indicates the computer may be compromised?

- A. Line 1
- B. Line 2
- C. Line 3
- D. Line 4
- E. Line 5
- F. Line 6

Answer: D

NEW QUESTION 155

An analyst performs a routine scan of a host using Nmap and receives the following output:

```
$ nmap -sS 10.0.3.1
Starting Nmap 8.9 (http://nmap.org) at 2019-01-19 12:03 PST
Nmap scan report for 10.0.3.1
Host is up (0.00098s latency).
Not shown: 979 closed ports

PORT      STATE      SERVICE
20/tcp    filtered   ftp-data
21/tcp    filtered   ftp
22/tcp    open       ssh
23/tcp    open       telnet
80/tcp    open       http

Nmap done: 1 IP address (1 host up) scanned in 0.840 seconds
```

Which of the following should the analyst investigate FIRST?

- A. Port 21
- B. Port 22
- C. Port 23
- D. Port 80

Answer: C

NEW QUESTION 157

A security analyst received a SIEM alert regarding high levels of memory consumption for a critical system. After several attempts to remediate the issue, the system went down. A root cause analysis revealed a bad actor forced the application to not reclaim memory. This caused the system to be depleted of resources. Which of the following BEST describes this attack?

- A. Injection attack
- B. Memory corruption
- C. Denial of service
- D. Array attack

Answer: B

NEW QUESTION 158

A SIEM solution alerts a security analyst of a high number of login attempts against the company's webmail portal. The analyst determines the login attempts used credentials from a past data breach. Which of the following is the BEST mitigation to prevent unauthorized access?

- A. Single sign-on
- B. Mandatory access control
- C. Multifactor authentication
- D. Federation
- E. Privileged access management

Answer: E

NEW QUESTION 162

A security analyst received an alert from the SIEM indicating numerous login attempts from users outside their usual geographic zones, all of which were initiated through the web-based mail server. The logs indicate all domain accounts experienced two login attempts during the same time frame.

Which of the following is the MOST likely cause of this issue?

- A. A password-spraying attack was performed against the organization.
- B. A DDoS attack was performed against the organization.
- C. This was normal shift work activity; the SIEM's AI is learning.
- D. A credentialed external vulnerability scan was performed.

Answer: A

NEW QUESTION 163

While planning segmentation for an ICS environment, a security engineer determines IT resources will need access to devices within the ICS environment without compromising security.

To provide the MOST secure access model in this scenario, the jumpbox should be.

- A. placed in an isolated network segment, authenticated on the IT side, and forwarded into the ICS network.
- B. placed on the ICS network with a static firewall rule that allows IT network resources to authenticate.
- C. bridged between the IT and operational technology networks to allow authenticated access.
- D. placed on the IT side of the network, authenticated, and tunneled into the ICS environment.

Answer: D

NEW QUESTION 165

An organization has several system that require specific logons Over the past few months, the security analyst has noticed numerous failed logon attempts followed by password resets. Which of the following should the analyst do to reduce the occurrence of legitimate failed logons and password resets?

- A. Use SSO across all applications
- B. Perform a manual privilege review
- C. Adjust the current monitoring and logging rules
- D. Implement multifactor authentication

Answer: B

NEW QUESTION 167

.....

Relate Links

100% Pass Your CS0-002 Exam with ExamBible Prep Materials

<https://www.exambible.com/CS0-002-exam/>

Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>