

Exam Questions 200-901

Developing Applications and Automating Workflows using Cisco Core Platforms (DEVASC)

<https://www.2passeasy.com/dumps/200-901/>



NEW QUESTION 1

Refer to the exhibit.

```
<books>
  <science>
    <biology>10.00</biology>
    <geology>9.00</geology>
    <chemistry>8.00</chemistry>
  </science>
  <math>
    <calculus>20.00</calculus>
    <algebra>12.00</algebra>
  </math>
</books>
```

Which JSON is equivalent to the XML –encoded data?

```
{
  "books": {
    "science": {
      "biology": "10.00",
      "geology": "9.00",
      "chemistry": "8.00"
    },
    "math": {
      "calculus": "20.00",
      "algebra": "12.00"
    }
  }
}
```

```
[ {
  "books": {
    "science": {
      "biology": "10.00",
      "geology": "9.00",
      "chemistry": "8.00"
    },
    "math": {
```

```

"science": {
  "biology": "10.00",
  "geology": "9.00",
  "chemistry": "8.00"
},
"math": {
  "calculus": "20.00",
  "algebra": "12.00"
}
}
]
    
```

```

{
  "books": [
    "science": {
      "biology": "10.00",
      "geology": "9.00",
      "chemistry": "8.00"
    },
    "math": {
      "calculus": "20.00",
      "algebra": "12.00"
    }
  ]
}
    
```

```

{
  "books": [
    "science", {
      "biology": "10.00",
      "geology": "9.00",
      "chemistry": "8.00"
    },
    "math", {
      "calculus": "20.00",
      "algebra": "12.00"
    }
  ]
}
    
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: A

NEW QUESTION 2

What are two advantages of version control software? (Choose two.)

- A. It supports tracking and comparison of changes in binary format files.
- B. It allows old versions of packaged applications to be hosted on the Internet
- C. It provides wiki collaboration software for documentation.
- D. It supports comparisons between revisions of source code files.
- E. It allows new team members to access the current code and history.

Answer: DE

NEW QUESTION 3


Which REST architectural constraint indicates that no client context should be stored on the server between requests?

- A. stateless
- B. uniform interface
- C. cacheable
- D. client-server

Answer: A

NEW QUESTION 4

Drag and drop the network automation interfaces from the left onto the transport protocols that they support on the right. (Not all Options are used)



- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Grpc == http/2 , netconfig == ssh , restconfig == https

NEW QUESTION 5

Fill in the blanks to complete the python script to request a service ticket using the APIC-EM rest API for the user "devnetuser".

```
import requests
import json
controller = 'devnetapi.cisco.com/sandbox/apic_em'
url = "https://" + controller + "/api/va/ticket"
payload = { 'username': '_____', 'password': '371274739' }
header = { 'Content-type': 'application/json' }
response = _____ post(url, data=json.dumps(payload), \
headers=_____, verify=False)
r_json = response.json()
print(r_json)
ticket = r_json["response"]["serviceTicket"]
print(ticket)
```

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Solution as below

```
import requests
import json
controller = 'devnetapi.cisco.com/sandbox/apic_em'
url = "https://" + controller + "/api/va/ticket"
payload = { 'username': 'devnetuser', 'password': '371387657' }
header = { 'Content-type': 'application/json' }
response = requests post(url, data=json.dumps(payload), \
headers=header, verify=False)
r_json = response.json()
print(r_json)
ticket = r_json["response"]["serviceTicket"]
print(ticket)
```

NEW QUESTION 6

Which statement about authentication a RESTCONF API session with a router that runs Cisco IOS XE software is true?

- A. OAuth must be used.
- B. A token must be retrieved and the associated string must be embedded in the X-Auth-Token header.
- C. Basic authentication must be used.
- D. No authentication is required.

Answer: C

NEW QUESTION 7

What are two benefit of managing network configuration via APIs? (Choose two.)

- A. configuration on devices becomes less complex

- B. more security due to locking out manual device configuration
- C. increased scalability and consistency of network changes
- D. eliminates the need of legacy management protocols like SNMP
- E. reduction in network changes performed manually

Answer: CE

NEW QUESTION 8

What is the outcome of executing this command?
 git clone ssh://john@exmaple.com/path/to/my-project_git

- A. Creates a local copy of a repository called "my project"
- B. Creates a copy of a branch called "my project"
- C. Initiates a new Git repository called "my project"
- D. Creates a new branch called "my project"

Answer: A

NEW QUESTION 9

When a Cisco IOS XE networking device is configured using RESTCONF, what is the default data-encoding method?

- A. XML
- B. x-form-encoding
- C. YANG
- D. YAML

Answer: A

NEW QUESTION 10

Refer to the exhibit.

```
#!/bin/bash
read ndir
while [ -d "$ndir" ]
do
cd $ndir
done
mkdir $ndir
```

What is the action of the Bash script that is shown?

- A. The script waits until input is entered
- B. If the directory exists, the script goes into it until there is no directory with the same name, then it creates a new directory.
- C. The script goes into the directory called "\$ndir" and makes a new directory called "\$ndir"
- D. The script waits until input is entered, then it goes into the directory entered and creates a new directory with the same name.
- E. For all directories in the current folder
- F. The script goes into directory and makes a new directory.

Answer: A

NEW QUESTION 10

Drag and drop the network automation interfaces from the left onto the transport protocols that they support on the right.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

gRPC = C, NETCONF = A, RESTCONF = B, D

NEW QUESTION 11

Refer to the exhibit.

```
json_string = """
{
  "researcher": {
    "name": "Ford Perfect",
    "species": "Betelgeusian",
    "relatives": [
      {
        "name": "Zaphod Beeblebrox",
        "species": "Betelgeusian"
      }
    ]
  }
}
"""

my_json = json.loads(json_string)
```

Which python data structure does my_json contain?

- A. List
- B. Json
- C. Map
- D. Dict

Answer: D

NEW QUESTION 16

Which two NETCONF operations cover the RESTCONF GET operation? (Choose two.)

- A. <get>
- B. <edit>
- C. <get-update>
- D. <modify-config>
- E. <get-config>

Answer: AE

NEW QUESTION 19

Which platform has an API that be used to obtain a list of vulnerable software on user devices?

- A. Cisco Umbrella
- B. Cisco Firepower
- C. Cisco Identity Services Engine
- D. Cisco Advanced Malware Protection

Answer: D

NEW QUESTION 24

When using the Bash shell, how is the output of the devnet command saved to a file named "output.txt"?

- A. devnet & output.txt
- B. devnet > output.txt
- C. devnet < output.txt
- D. devnet | output.txt

Answer: B

NEW QUESTION 27

Refer to the exhibit.

```

1  ---
2  - hosts: ([ router ])
3  gather_facts: true
4  connection: local
5
6  tasks:
7  - ios_command
8    commands:
9    - show run
10   provider: "{{ router_credentials }}"
11   register: config
12
13 - copy:
14   content: "{{ config.stdout[0] }}"
15   dest: "etc/ansible/configs/command_{{ router_hostname }}.txt
16   ...

```

What is the effect of this Ansible playbook on an IOS router?

- A. A new running configuration is pushed to the IOS router.
- B. The current running configuration of the IOS router is backed up.
- C. The start-up configuration of the IOS router is copied to a local folder.
- D. A new start-up configuration is copied to the IOS router.

Answer: B

NEW QUESTION 28

Which CI/CD tool is an automation tool used to build, test, and deploy software?

- A. Nagios
- B. Gradle
- C. Jenkins
- D. Git

Answer: C

NEW QUESTION 29

A function my_func() returns True when it executes normally. Which python snippet tests my_func()?

- ```
def test_func(self):
 self.assertTrue(my_func())
```
- ```
def test_func(self):
    self.assertRaises(my_func())
```
- ```
def test_func(self):
 self.assertEqual(my_func(), '{true}')
```
- ```
def test_func(self):
    self.assertFalse(my_func())
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: B

NEW QUESTION 32

An automation script fails to connect to an internal server exactly 1 out of 2 times it is executed. This behavior is seen from different clients. Which networking device must be at fault?

- A. Laptop on which the script is running
- B. Router
- C. Switch
- D. Load balancer

Answer: D

NEW QUESTION 33

Which status code is used by a REST API to indicate that the submitted payload is incorrect?

A. A.-400B.403C.405D.429

Answer: A

NEW QUESTION 38

What is an example of a network interface hardware address?

- A. domain name
- B. IP address
- C. workstation name
- D. MAC address

Answer: D

NEW QUESTION 39

Refer to the exhibit.

URL: https://<ASA_IP>/api/access/global/rules
Method: POST
Payload:

```
{
  "destinationAddress": {
    "kind": "IPv4Address",
    "value": "10.1.1.1"
  },
  "remarks": [ ],
  "active": true
  "permit": true,
  "sourceAddress": {
    "kind": "IPv4Address",
    "value": "192.168.1.1"
  }
}
```

Response Status Code: 400 Bad Request

```
["messages":[{"level":"Error","code":"JSON-PARSE-ERROR","details":"
Unexpected character ('\'' (code 34)):
```

What caused the error in this API request?

- A. The API resource does not support the POST operation.
- B. The API resource does not support JSON format payloads.
- C. The submitted JSON payload includes a field that is not supported by the API resources.
- D. The submitted JSON payload has a formatting issue.

Answer: D

NEW QUESTION 42

Which PAI is used to obtain data voicemail ports?

- A. Finesse gadgets
- B. Cisco Unified Communications manager
- C. Webex devices
- D. Webex teams

Answer: B

NEW QUESTION 47

Refer to the exhibit.

```
class ucsm sdk . ucshandle . UcsHandle ( ip , username , password , port = None ,  
secure = None , proxy = None ) [ source ]  
Bases : ucsm sdk . ucsession . UcsSession  
UcsHandle class is the user interface point for any Ucs related communication .  
Parameters :  
• ip ( str ) – The IP or Hostname of the UCS Server  
• username ( str ) – The username as configured on the UCS Server  
• password ( str ) – The password as configured on the UCS Server  
• port ( int or None ) – The port number to be used during connection  
• secure ( bool or None ) – True for secure connection , otherwise False  
• proxy ( str ) – The proxy object to be used to connect
```

Given the API documentation for the UCS SDK python class, UcsHandle, which code snippet creates a handle instance?

```
#!/usr/bin/env python3  
from ucsm sdk . ucshandle import UcsHandle  
handle = UcsHandle ( " 10 . 1 . 2 . 254 " , " admin " , " password " ,  
port = " 443 " , secure = True )  
#!/usr/bin/env python3  
import ucsm sdk . ucshandle . UcsHandle  
handle = UcsHandle ( " 10 . 1 . 2 . 254 " , " admin " , " password " ,  
port = 443 , secure = 1 )  
#!/usr/bin/env python3  
from ucsm sdk . ucshandle import UcsHandle  
handle = UcsHandle ( ip = " 10 . 1 . 2 . 254 " , username = " admin " ,  
password = " password " , port = 443 , secure = True )  
#!/usr/bin/env python3  
from ucsm sdk . ucshandle import UcsHandle  
handle = UcsHandle ( " 10 . 1 . 2 . 254 " , " admin " , " password " ,  
port = " 443 " , secure = 1 )
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: B

NEW QUESTION 49

Which two statements describe the role of an artifact repository in a CI/CD pipeline? (Choose two.)

- A. An artifact repository allows to compare and merge changes in the source code of files involved in a build process.
- B. An artifact repository is needed only for CI/CD pipeline executed on a public cloud infrastructure.
- C. An artifact repository provides traceability, search, and management of binary files.
- D. An artifact repository is needed only for managing open source software.
- E. An artifact repository stores files needed and generated during the build process.

Answer: CE

NEW QUESTION 54

On which port does NETCONF operate by default?

- A. 23
- B. 443
- C. 822

D. 830

Answer: D

NEW QUESTION 57

What are two characteristics of Bare Metal environments that are related to application deployment? (Choose two.)

- A. Provide the hypervisor to host virtual servers
- B. Specifically designed for container-based workloads.
- C. Provides workloads with access to hardware features
- D. Suitable for legacy application that do not support virtualization
- E. Not compatible with other cloud services such as PaaS or SaaS offerings.

Answer: CD

NEW QUESTION 62

Refer to the exhibit.

The screenshot shows an API documentation page for the endpoint `/v1/messages`. The documentation includes the following query parameters:

- roomId** (string, required): List messages in a room, by ID.
- mentionedPeople** (array): List messages with these people mentioned, by ID. Use `me` as a shorthand for the current API user.
- before** (string): List messages sent before a date and time.
- beforeMessage** (string): List messages sent before a message, by ID.
- max** (number): Limit the maximum number of messages in the response. Default: 50.

The terminal window shows the following command and output:

```
bash-3.2$ curl -H "Content-Type: application/json" -H "Authorization: Fj2zzykEa091ic9GK2jBLtE1HkLH6oRHPQdw1pAT60I7NDThhWZL2BSpqMg14Kk_b9e159ISACly7-NarA-2n9H-tGgt-SxQ39IDejgcs" -i -X POST -d '{"roomId":"Y2geK53sjELknosrC75wQ5ZGL99pHgIuScB7DfNvUsr8Xx4wOKL1PORcEkryArPK3QmK9LQZsPOG4","text":"test2"}' https://api.ciscospark.com/v1/messages
```

```
HTTP/1.1 401 Unauthorized
Via: 1.1 linkerd
TrackingID: ROUTER_5E0FDC8C-EB6F-01BB-00EF-806BF1B000EF
Date: Sat, 04 Jan 2020 00:30:04 GMT
Server: Redacted
Content-Length: 267
Content-Type: application/json
Strict-Transport-Security: max-age=63072000; includeSubDomains; preload

{"message": "The request requires a valid access token set in the Authorization request header.", "errors": [{"description": "The request requires a valid access token set in the Authorization request header."}], "trackingId": "ROUTER_5E0FDC8C-EB6F-01BB-00EF-806BF1B000EF"}
```

A developer is troubleshooting an API with the given API with the given API documentation and cURL command. What is the cause of this problem?

- A. The user is not allowed to post messages from their account
- B. The request body is missing or incomplete
- C. The API token specified is expired
- D. The authorization header is missing or incomplete

Answer: C

NEW QUESTION 67

Drag and drop the functionalities from the left onto correct networking devices on the right.

ports are different broadcast domain by default	Firewall
ports can be in the same broadcast domain	Load Balancer
uses traffic inspection to make routing decisions	Router
blocks networks traffic by default	Switch

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

1 – D, 2 – C, 3 – A, 4 – B

NEW QUESTION 70

Which two statements describe the advantages of using a version control system? (Choose two.)

- A. It allows for branching and merging so that different tasks are worked on in isolation before they are merged into a feature or master branch.
- B. It allows multiple engineers to work against the same code and configuration files and manage differences and conflicts.
- C. It provides tooling to automate application builds and infrastructure provisioning.
- D. It allows developers to write effective unit tests.
- E. It provides a system to track User Stories and allocate to backlogs.

Answer: AB

NEW QUESTION 75


An application calls a REST API and expects a result set of more than 550 records, but each time the call is made, only 25 are returned. Which feature limits the amount of data that is returned by the API?

- A. pagination
- B. payload limit
- C. rate limiting
- D. service timeouts

Answer: A

NEW QUESTION 80

Refer to the exhibit.



An administrator attempts to perform a GET using the Cisco IOS XE RESTCONF API to return the hostname of a device. The sequence diagram illustrated the HTTP message observed. Which change to the API request resolves the issue?

- A. Add Content-Type HTTP header with 'application/yang-data+json' using -H 'Content-Type: application/yang-data+json'.
- B. Use -u cisco: cisco instead of -u 'cisco: cisco'.
- C. Change the request method from -X "GET" to- X' POST".
- D. Remove the -H 'Accept: application/yang-data^/son' HTTP header because it is not required.

Answer: B

NEW QUESTION 83

In DNS, which record specifies an alias that refers to another name that ultimately resolves to an IP address?

- A. AAA
- B. SOA
- C. NS
- D. CNAME

Answer: D

NEW QUESTION 84

Which device is a system that monitors and controls incoming and outgoing network traffic based on predetermined security rules?

- A. Switch
- B. Router
- C. Firewall
- D. Load balancer

Answer: C

NEW QUESTION 85

Which principle is a value from the manifesto for Agile software development?

- A. adhering to a plan over responding to requirements
- B. detailed documentation over working software
- C. processes and tools over teams and inter actions
- D. customer collaboration over contract negotiation

Answer: D

NEW QUESTION 87

Which action does the Git command git merge allow the development to perform?

- A. Combine multiple sequence of commits into one unified history.
- B. Push changes to the remote repository
- C. Switch between branches
- D. Create, list, rename, and delete branches

Answer: A

NEW QUESTION 91

Drag and drop the descriptions from the left onto correct application deployment models on the right.

provides a low-latency compute capability close to the data source	<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">Public Cloud</div> <div style="border: 1px solid black; height: 20px; margin-bottom: 5px;"></div> <div style="border: 1px solid black; height: 20px; margin-bottom: 5px;"></div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">Private Cloud</div> <div style="border: 1px solid black; height: 20px; margin-bottom: 5px;"></div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">Hybrid Cloud</div> <div style="border: 1px solid black; height: 20px; margin-bottom: 5px;"></div> <div style="border: 1px solid black; padding: 5px;">Edge Computing</div> <div style="border: 1px solid black; height: 20px;"></div>
environment where you pay only for the resources that you consume	
offers a self-service, elastic compute environment from a dedicated set of physical resources	
provides an approach for overflow traffic to burst out to meet peak demands	
shared compute platform that is offered over the Internet	

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

1 – B, 2 – E, 3 – C, 4 – D, 5 – A

NEW QUESTION 93

Drag and drop the HTTP status codes from the left onto the correct descriptions on the right.



- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

1 – B, 2 – D, 3 – A, 4 – C

NEW QUESTION 97

Fill in the blanks to complete the Python script to update the Webex Teams membership of a room using the Python requests library import requests

```
import requests
url = "https://api.ciscospark.com/v1/memberships/Y2lzY29zcGf_yazov371508156INISVAvOTJm2RkOWEINjc1ZC00YTQxLThjNDEtMmFiZGY4OWY0NGY0OjExNzJkNmYwLTJiYzMtMTFfIOS1iOWI3LWNmMjg3MTJhYTgzNw"

payload = [{"isModerator": true}]
headers = {
    'Authorization': 'Bearer ',
    'Content-Type': 'application/json'
}

response = requests. [ ] ("PATCH" url, headers= [ ], data = [ ])
print(response.text.encode('utf8'))
```

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

request, headers , payload

NEW QUESTION 98

What is the benefit of edge computing?

- A. It reduces network latency by moving processing closer to the data source.
- B. It simplifies security as devices and processing are brought closer together
- C. It removes the need for centralized data processing.
- D. It reduces data velocity from devices or other data sources.

Answer: A

NEW QUESTION 100

Which two statements about JSON and XML are true? (Choose two.)

- A. JSON objects are collection of key value pairs.
- B. The syntax of JSON contains tags, elements, and attributes.
- C. JSON arrays are an unordered set of key value pairs.
- D. The syntax of XML contains tags, elements, and attributes.
- E. XML objects are collections of key-value pairs.

Answer: AD

NEW QUESTION 105

What are two advantages of the Model-view-controller software design pattern? (Choose two.)

- A. simplifies network automation
- B. allows for multiple views of the same model
- C. makes code easier to deploy using CI/CD pipelines
- D. reduces need for error handling
- E. separates responsibilities of the code, which makes future modifications easier

Answer: BE

NEW QUESTION 108

Which two statements describe the traits of an asynchronous API call? (Choose two.)

- A. The order in which API calls return can be guaranteed
- B. A call to an API does not block the code, but rather it allows application processing to continue
- C. The end user can experience latency or performance lag while waiting for the API call to return
- D. Code execution blocks or waits for the call to an API to return.
- E. A callback function typically is used to process the response from an API call

Answer: BE

NEW QUESTION 112

Drag and Drop the Bash commands from the left onto the correct actions on the right.

cd~	list files in directory sorted by edited date descending
cd/	create directory
is -l	copy file
is -t	change directory to user \$HOME
cp	create environment variable
cp -r	change directory to file system root
mv	move file
touch	create file
mkdir	copy directory
export	list files in directory with details

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

1 - d, 2 - i, 3 - e, 4 - a, 5 - j, 6 - b, 7 - g, 8 - h, 9 - c, 10 - f

NEW QUESTION 115

Which type of threat occur when an attacker can send hostile data to an interpreter within an application?

- A. Cross-site scripting
- B. Sensitive data exposure
- C. Broken authentication
- D. Injection

Answer: D

NEW QUESTION 117

A company has written a script that creates a log bundle from the Cisco DNA Center every day. The script runs without error and the bundles are produced. However, when the script is run during business hours, report poor voice quality of phones calls. What explains this behavior?

- A. The application is running in the Voice VLAN and causes delays and jitter in the subnet.
- B. The speed and duplex settings in Cisco DNA Center are sot incorrectly, which causes the transfer to be too slow.
- C. 9 The script is written in a low-level programming language where there is no memory safet
- D. This causes a buffer overflow and disruption on the network.
- E. Generating the logs causes the CPU on the network controller to spike, which causes delays m forwarding the voice IP packets.

Answer: D

NEW QUESTION 119

Which two concepts describe test-driven development? (Choose two.)

- A. It enables code refactoring.

- B. Write a test before writing code.
- C. Implementation is driven by incremental testing of release candidates.
- D. User acceptance testers development the test requirements.
- E. Tests are created when code is ready for release.

Answer: BC

NEW QUESTION 122

What is the Git command to delete a local branch named "experiment" without a warning?

- A. git branch -n experiment
- B. git branch -rm experiment
- C. git branch -f experiment
- D. git branch -D experiment

Answer: D

NEW QUESTION 125

Refer to the exhibit.

```
$ diff -u5 fish.py cat.py
--- fish.py      2020-01-02 09:41:02.840000000 +0100
+++ cat.py      2020-01-02 09:41:06.885999800 +0100
@@ -160,11 +160,12 @@
 
     @single_request_timeout.setter
     def single_request_timeout(self, value):
         """The timeout (seconds) for a single HTTP REST API request."""
         check_type(value, int, optional=True)
-         assert value is None or value > 0
+         if value is not None and value <= 0:
+             raise ValueError("single_request_timeout must be positive integer")
         self._single_request_timeout = value
     """
 
     @property
     def wait_on_rate_limit(self):
         """Automatic rate limit handling.
```

The output of a unified diff when comparing two versions of a python script is shown. Which two "single_request_timeout ()"

The exhibit shows four code snippets:

- Option A (fish.py):** Original code with `assert value is None or value > 0`.
- Option B (cat.py):** Modified code with `if value is not None and value <= 0: raise ValueError("single_request_timeout must be positive integer")`.
- Option C (fish.py):** Original code with `assert value is None or value > 0`.
- Option D (cat.py):** Modified code with `if value is not None and value <= 0: raise ValueError("single_request_timeout must be positive integer")`.

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: BC

NEW QUESTION 127

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual 200-901 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the 200-901 Product From:

<https://www.2passeasy.com/dumps/200-901/>

Money Back Guarantee

200-901 Practice Exam Features:

- * 200-901 Questions and Answers Updated Frequently
- * 200-901 Practice Questions Verified by Expert Senior Certified Staff
- * 200-901 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * 200-901 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year