

Exam Questions AWS-Certified-Developer-Associate

Amazon AWS Certified Developer - Associate

<https://www.2passeasy.com/dumps/AWS-Certified-Developer-Associate/>



NEW QUESTION 1

In DynamoDB, if you create a table and request 10 units of write capacity and 200 units of read capacity of provisioned throughput, how much would you be charged in US East (Northern Virginia) Region?

- A. \$0.05 per hour
- B. \$0.10 per hour
- C. \$0.03 per hour
- D. \$0.15 per hour

Answer: A

Explanation:

To understand pricing in DynamoDB, consider the following example. If you create a table and request 10 units of write capacity and 200 units of read capacity of provisioned throughput, you would be charged:

$\$0.01 + (4 \times \$0.01) = \$0.05$ per hour

Reference: <http://aws.amazon.com/dynamodb/pricing/>

NEW QUESTION 2

You have been doing a lot of testing of your VPC Network by deliberately failing EC2 instances to test whether instances are failing over properly. Your customer who will be paying the AWS bill for all this asks you if he being charged for all these instances. You try to explain to him how the billing works on EC2 instances to the best of your knowledge. What would be an appropriate response to give to the customer in regards to this?

- A. Billing commences when Amazon EC2 AMI instance is completely up and billing ends as soon as the instance starts to shutdown.
- B. Billing commences when Amazon EC2 initiates the boot sequence of an AMI instance and billing ends when the instance shuts down.
- C. Billing only commences only after 1 hour of uptime and billing ends when the instance terminates.
- D. Billing commences when Amazon EC2 initiates the boot sequence of an AMI instance and billing ends as soon as the instance starts to shutdown.

Answer: B

Explanation:

Billing commences when Amazon EC2 initiates the boot sequence of an AMI instance. Billing ends when the instance shuts down, which could occur through a web services command, by running "shutdown -h", or through instance failure.

Reference: <http://aws.amazon.com/ec2/faqs/#Billing>

NEW QUESTION 3

AWS Elastic Load Balancer supports SSL termination.

- A. True
- B. For specific availability zones only.
- C. False
- D. True
- E. For specific regions only
- F. True
- G. For all regions

Answer: D

Explanation:

You can configure your load balancer in ELB (Elastic Load Balancing) to use a SSL certificate in order to improve your system security. The load balancer uses the certificate to terminate and then decrypt requests before sending them to the back-end instances. Elastic Load Balancing uses AWS Identity and Access Management (IAM) to upload your certificate to your load balancer.

Reference: http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/US_SettingUpLoadBalancerHTTPS.html

NEW QUESTION 4

How long can you keep your Amazon SQS messages in Amazon SQS queues?

- A. From 120 secs up to 4 weeks
- B. From 10 secs up to 7 days
- C. From 60 secs up to 2 weeks
- D. From 30 secs up to 1 week

Answer: C

Explanation:

The SQS message retention period is configurable and can be set anywhere from 1 minute to 2 weeks. The default is 4 days and once the message retention limit is reached your messages will be automatically deleted. The option for longer message retention provides greater flexibility to allow for longer intervals between message production and consumption.

Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 5

Which one of the following statements is NOT an advantage of DynamoDB being built on Solid State Drives:

- A. serve high-scale request workloads
- B. low request pricing
- C. high I/O performance of WebApp on EC2 instance
- D. low-latency response times

Answer: C

Explanation:

In DynamoDB, SSDs help achieve design goals of predictable low-latency response times for storing and accessing data at any scale. The high I/O performance of SSDs also enables to serve high-scale request workloads cost efficiently, and to pass this efficiency along in low request pricing.

Reference: <http://aws.amazon.com/dynamodb/faqs/>

NEW QUESTION 6

An orgAMzation has hosted an application on the EC2 instances. There will be multiple users connecting to the instance for setup and configuration of application. The orgAMzation is planning to implement certain security best practices. Which of the below mentioned pointers will not help the orgAMzation achieve better security arrangement?

- A. Apply the latest patch of OS and always keep it updated.
- B. Allow only IAM users to connect with the EC2 instances with their own secret access key.
- C. Disable the password based login for all the user
- D. All the users should use their own keys to connect with the instance securely.
- E. Create a procedure to revoke the access rights of the indMdual user when they are not required to connect to EC2 instance anymore for the purpose of application configuration.

Answer: B

Explanation:

Since AWS is a public cloud any application hosted on EC2 is prone to hacker attacks. It becomes extremely important for a user to setup a proper security mechAMsm on the EC2 instances. A few of the security measures are listed below:

Always keep the OS updated with the latest patch

Always create separate users with in OS if they need to connect with the EC2 instances, create their keys and disable their password

Create a procedure using which the admin can revoke the access of the user when the business work on the EC2 instance is completed

Lock down unnecessary ports

Audit any proprietary applications that the user may be running on the EC2 instance

Provide temporary escalated prMleges, such as sudo for users who need to perform occasional prMleged tasks

The IAM is useful when users are required to work with AWS resources and actions, such as launching an instance. It is not useful to connect (RDP / SSH) with an instance.

Reference: <http://aws.amazon.com/articles/1233/>

NEW QUESTION 7

A user is planning to make a mobile game which can be played online or offline and will be hosted on EC2.

The user wants to ensure that if someone breaks the highest score or they achieve some milestone they can inform all their colleagues through email. Which of the below mentioned AWS services helps achieve this goal?

- A. AWS Simple Workflow Service.
- B. AWS Simple Queue Service.
- C. Amazon Cognito
- D. AWS Simple Email Servic

Answer: D

Explanation:

Amazon Simple Email Service (Amazon SES) is a highly scalable and cost-effective email-sending service for businesses and developers. It integrates with other AWS services, making it easy to send emails from applications that are hosted on AWS.

Reference: <http://aws.amazon.com/ses/faqs/>

NEW QUESTION 8

True or False: In DynamoDB, Scan operations are always eventually consistent.

- A. No, scan is like Query operation
- B. Yes
- C. No, scan is strongly consistent by default
- D. No, you can optionally request strongly consistent sca

Answer: B

Explanation:

In DynamoDB, Scan operations are always eventually consistent.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/APISummary.html>

NEW QUESTION 9

In DynamoDB, to get a detailed listing of secondary indexes on a table, you can use the action.

- A. DescribeTable
- B. BatchGetItem
- C. GetItem
- D. TableName

Answer: A

Explanation:

In DynamoDB, DescribeTable returns information about the table, including the current status of the table, when it was created, the primary key schema, and any indexes on the table.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/SecondaryIndexes.html>

NEW QUESTION 10

is a task coordination and state management service for cloud applications.

- A. Amazon SES
- B. Amazon SWF
- C. Amazon FPS
- D. Amazon SNS

Answer: B

Explanation:

Amazon Simple Workflow (Amazon SWF) is a task coordination and state management service for cloud applications. With Amazon SWF, you can stop writing complex glue-code and state machinery and invest more in the business logic that makes your applications unique.

Reference: <http://aws.amazon.com/swf/>

NEW QUESTION 10

When a user is detaching an EBS volume from a running instance and attaching it to a new instance, which of the below mentioned options should be followed to avoid file system damage?

- A. Unmount the volume first
- B. Stop all the I/O of the volume before processing
- C. Take a snapshot of the volume before detaching
- D. Force Detach the volume to ensure that all the data stays intact

Answer: A

Explanation:

When a user is trying to detach an EBS volume, the user can either terminate the instance or explicitly remove the volume. It is a recommended practice to unmount the volume first to avoid any file system damage.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-detaching-volume.html>

NEW QUESTION 14

A user is planning to host a scalable dynamic web application on AWS. Which of the services may not be required by the user to achieve automated scalability?

- A. CloudWatch
- B. S3
- C. AutoScaling
- D. AWS EC2 instances

Answer: B

Explanation:

The user can achieve automated scaling by launching different EC2 instances and making them a part of an ELB. Cloudwatch will be used to monitor the resources and based on the scaling need it will trigger policies. AutoScaling is then used to scale up or down the instances.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/NhatlsAutoScaling.html>

NEW QUESTION 17

Regarding Amazon SNS, you can send notification messages to mobile devices through any of the following supported push notification services, EXCEPT:

- A. Google Cloud Messaging for Android (GCM)
- B. Apple Push Notification Service (APNS)
- C. Amazon Device Messaging (ADM)
- D. Microsoft Windows Mobile Messaging (MWMM)

Answer: D

Explanation:

In Amazon SNS, you have the ability to send notification messages directly to apps on mobile devices. Notification messages sent to a mobile endpoint can appear in the mobile app as message alerts, badge updates, or even sound alerts. Microsoft Windows Mobile Messaging (MWMM) doesn't exist and is not supported by Amazon SNS.

Reference: <http://docs.aws.amazon.com/sns/latest/dg/SNSMobilePush.html>

NEW QUESTION 20

What happens if your application performs more reads or writes than your provisioned capacity?

- A. Nothing
- B. requests above your provisioned capacity will be performed but you will receive 400 error codes.
- C. requests above your provisioned capacity will be performed but you will receive 200 error codes.
- D. requests above your provisioned capacity will be throttled and you will receive 400 error code

Answer: D

Explanation:

Speaking about DynamoDB, if your application performs more reads/second or writes/second than your table's provisioned throughput capacity allows, requests above your provisioned capacity will be throttled and you will receive 400 error codes.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ProvisionedThroughputIntro.html>

NEW QUESTION 23

What kind of service is provided by AWS DynamoDB?

- A. Relational Database
- B. NoSQL Database
- C. Dynamic Database
- D. Document Database

Answer: B

Explanation:

DynamoDB is a fast, fully managed NoSQL database service. Reference: <http://aws.amazon.com/dynamodb/>

NEW QUESTION 27

Doug has created a VPC with CIDR 10.201.0.0/16 in his AWS account. In this VPC he has created a public subnet with CIDR block 10.201.31.0/24. While launching a new EC2 from the console, he is not able to assign the private IP address 10.201.31.6 to this instance. Which is the most likely reason for this issue?

- A. Private IP address 10.201.31.6 is not part of the associated subnet's IP address range.
- B. Private IP address 10.201.31.6 is blocked via ACLs in Amazon infrastructure as a part of platform security.
- C. Private address IP 10.201.31.6 is currently assigned to another interface.
- D. Private IP address 10.201.31.6 is reserved by Amazon for IP networking purpose

Answer: C

Explanation:

In Amazon VPC, you can assign any Private IP address to your instance as long as it is: Part of the associated subnet's IP address range
Not reserved by Amazon for IP networking purposes Not currently assigned to another interface Reference: <http://aws.amazon.com/vpc/faqs/>

NEW QUESTION 31

In Amazon SNS, to send push notifications to mobile devices using Amazon SNS and ADM, you need to obtain the following, except:

- A. Client secret
- B. Client ID
- C. Device token
- D. Registration ID

Answer: C

Explanation:

To send push notifications to mobile devices using Amazon SNS and ADM, you need to obtain the following: Registration ID and Client secret.
Reference: <http://docs.aws.amazon.com/sns/latest/dg/SNSMobilePushPrereq.html>

NEW QUESTION 34

Regarding Amazon SNS, to begin using Amazon SNS mobile push notifications, you first need that uses one of the supported push notification services: APNS, GCM, or ADM.

- A. an access policy for the mobile endpoints
- B. to active push notification service of Amazon SNS
- C. to know the type of mobile device operating system
- D. an app for the mobile endpoints

Answer: D

Explanation:

In Amazon SNS, to begin using Amazon SNS mobile push notifications, you first need an app for the mobile endpoints that uses one of the supported push notification services: APNS, GCM, or ADM. After you've registered and configured the app to use one of these services, you configure Amazon SNS to send push notifications to the mobile endpoints.

Reference: <http://docs.aws.amazon.com/sns/latest/dg/SNSMobilePush.html>

NEW QUESTION 39

Can you SSH to your private machines that reside in a VPC from outside without elastic IP?

- A. Yes, but only if you have direct connect or vpn
- B. Only if you are using a non-US region
- C. Only if you are using a US region
- D. No

Answer: A

Explanation:

The instances that reside in the private subnets of your VPC are not reachable from the Internet, meaning that it is not possible to ssh into them. To interact with them you can use a bastion server, located in a public subnet, that will act as a proxy for them.

You can also connect if you have direct connect or vpn.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Scenario2.html

NEW QUESTION 41

A user has enabled the automated backup, but not specified the backup window. What will RDS do in this case?

- A. Will throw an error on instance launch
- B. RDS will take 3 AM — 3:30 AM as the default window
- C. RDS assigns a random time period based on the region
- D. Will not allow to launch a DB instance

Answer: C

Explanation:

If the user does not specify a preferred backup window while enabling an automated backup, Amazon RDS assigns a default 30-minute backup window which is selected at random from an 8-hour block of time per region. Reference:

<http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 43

A user has attached one RDS security group with 5 RDS instances. The user has changed the ingress rule for the security group. What will be the initial status of the ingress rule?

- A. Approving
- B. Implementing
- C. Authorizing
- D. It is not possible to assign a single group to multiple DB instances

Answer: C

Explanation:

When the user makes any changes to the RDS security group the rule status will be authorizing for some time until the changes are applied to all instances that the group is connected with. Once the changes are propagated the rule status will change to authorized.

Reference: http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_WorkingWithSecurityGroups.html

NEW QUESTION 45

When should a user try to Force Detach an EBS volume?

- A. If the volume is stuck in a detaching state
- B. If the volume is not accessible from the instance
- C. If the volume is not unmounted and the user still wants to detach
- D. If the volume is a root volume

Answer: A

Explanation:

If an EBS volume stays in the detaching state, the user can force the detachment by clicking Force Detach. Forcing the detachment can lead to either data loss or a corrupted file system. The user should use this option only as a last resort to detach a volume from a failed instance or if he is detaching a volume with the intention of deleting it.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-detaching-volume.html>

NEW QUESTION 47

How can a user configure three termination policies for the AutoScaling group?

- A. Define multiple policies in random order
- B. Define multiple policies in the ordered list
- C. Keep updating the AutoScaling group with each policy
- D. The user cannot specify more than two policies for AutoScaling

Answer: B

Explanation:

To configure the Auto Scaling termination policy, the user can either specify any one of the policies as a standalone policy or list multiple policies in an ordered list. The policies are executed in the order that they are listed.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/us-termination-policy.html>

NEW QUESTION 50

A user wants to configure AutoScaling which scales up when the CPU utilization is above 70% and scales down when the CPU utilization is below 30%. How can the user configure AutoScaling for the above mentioned condition?

- A. Use AutoScaling with a schedule
- B. Configure ELB to notify AutoScaling on load increase or decrease
- C. Use dynamic AutoScaling with a policy
- D. Use AutoScaling by manually modifying the desired capacity during a condition

Answer: C

Explanation:

The user can configure the AutoScaling group to automatically scale up and then scale down based on the specified conditions. To configure this, the user must setup policies which will get triggered by the CloudWatch alarms.

Reference:

<http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/as-scale-based-on-demand.html>

NEW QUESTION 52

A user has created an application which sends data to a log file. The server hosting the log files can be unavailable due to any reason. The user wants to make it so that whenever the log server is up it should be receive the messages. Which of the below mentioned AWS services helps achieve this functionality?

- A. AWS Simple Workflow
- B. AWS Simple Task Service
- C. AWS Simple Notification Service
- D. AWS Simple Queue Service

Answer: D

Explanation:

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. The user can use SQS to transmit any volume of data without losing messages or requiring other services to always be available. Using SQS, the application has to just send the data to SQS and SQS transmits it to the log file whenever it is available.

Reference: <http://aws.amazon.com/sqs/>

NEW QUESTION 55

Is there a limit to how much throughput you can get out of a single table in DynamoDB?

- A. Yes, not more than 1,000 writes/second or 1,000 reads/second
- B. No
- C. Yes, not more than 10,000 writes/second or 10,000 reads/second
- D. No, but If you wish to exceed throughput rates of 10,000 writes/second or 10,000 reads/second, you must first contact AWS.

Answer: D

Explanation:

In DynamoDB, you can increase the throughput you have provisioned for your table using UpdateTable API or in the AWS Management Console. If you wish to exceed throughput rates of 10,000 writes/second or 10,000 reads/second, you must first contact AWS.

Reference: <http://aws.amazon.com/dynamodb/>

NEW QUESTION 59

You have a number of image files to encode. In an Amazon SQS worker queue, you create an Amazon SQS message for each file specifying the command (jpeg-encode) and the location of the file in Amazon S3. Which of the following statements best describes the functionality of Amazon SQS?

- A. Amazon SQS is for single-threaded sending or receive speeds.
- B. Amazon SQS is a non-distributed queuing system.
- C. Amazon SQS is a distributed queuing system that is optimized for horizontal scalability, not for single-threaded sending or receive speeds.
- D. Amazon SQS is a distributed queuing system that is optimized for vertical scalability and for single-threaded sending or receive speeds.

Answer: C

Explanation:

Amazon SQS is a distributed queuing system that is optimized for horizontal scalability, not for single-threaded sending or receive speeds. A single client can send or receive Amazon SQS messages at a rate of about 5 to 50 messages per second. Higher receive performance can be achieved by requesting multiple messages (up to 10) in a single call. It may take several seconds before a message that has been to a queue is available to be received.

Reference: http://media.amazonwebservices.com/AWS_Storage_Options.pdf

NEW QUESTION 60

Can you configure an RDS Read Replica using CloudFormation templates?

- A. Yes, provided that you have root access.
- B. Yes, when you create a new CloudFormation template
- C. Yes, but not for all Regions.
- D. No, you can add the ReadReplica only when the resource is made available by CloudFormation

Answer: B

Explanation:

AWS CloudFormation gives developers and systems administrators an easy way to create and manage collections of AWS resources. You can now set Read Replicas for your databases with RDS when you create a new CloudFormation template. You can start using it with the sample template of CloudFormation.

Reference:

https://s3.amazonaws.com/cloudformation-templates-us-east-1/RDS_MySQL_With_Read_Replica.template

NEW QUESTION 64

What is the maximum time messages can be stored in SQS?

- A. 14 days
- B. one month
- C. 4 days
- D. 7 days

Answer: A

Explanation:

A message can be stored in the Simple Queue Service (SQS) from 1 minute up to a maximum of 14 days. Reference:
http://aws.amazon.com/sqs/faqs/#How_long_can_I_keep_my_messages_in_Amazon_SQS_queues

NEW QUESTION 68

In DynamoDB, the default table size is:

- A. 5 GB
- B. 1 GB
- C. 10 GB
- D. There is no table size

Answer: D

Explanation:

DynamoDB has seamless scalability with no table size limits and unlimited storage, so you shouldn't be worried about managing storage on the host or to provisioning more drive, as your data requirement changes.
Reference: <http://aws.amazon.com/dynamodb/>

NEW QUESTION 73

You want to have multiple versions of your application running at the same time, with all versions launched via AWS Elastic Beanstalk. Is this possible?

- A. N
- B. However if you have 2 AWS accounts this can be done
- C. N
- D. AWS Elastic Beanstalk is not designed to support multiple running environments
- E. Ye
- F. AWS Elastic Beanstalk is designed to support a number of multiple running environments
- G. Ye
- H. However AWS Elastic Beanstalk is designed to support only 2 multiple running environments

Answer: C

Explanation:

AWS Elastic Beanstalk is designed to support multiple running environments. As an example you could have one for integration testing, one for pre-production, and one for production, with each environment independently configured and running on its own separate AWS resources.
Reference: <https://aws.amazon.com/elasticbeanstalk/faqs/>

NEW QUESTION 75

In regard to AWS CloudFormation, what is a stack?

- A. The set of AWS templates that are created and managed as a template
- B. The set of AWS resources that are created and managed as a template
- C. The set of AWS resources that are created and managed as a single unit
- D. The set of AWS templates that are created and managed as a single unit

Answer: C

Explanation:

A stack is the set of AWS resources that are created and managed as a single unit when AWS CloudFormation initiates a template.
Reference: <http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/concept-stack.html>

NEW QUESTION 80

Which of the below mentioned options is not a best practice to securely manage the AWS access credentials?

- A. Enable MFA for privileged users
- B. Create individual IAM users
- C. Keep rotating your secure access credentials at regular intervals
- D. Create strong access key and secret access key and attach to the root account

Answer: D

Explanation:

It is a recommended approach to avoid using the access and secret access keys of the root account.
Thus, do not download or delete it. Instead make the IAM user as powerful as the root account and use its credentials. The user cannot generate their own access and secret access keys as they are always generated by AWS.
Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/IAMBestPractices.html>

NEW QUESTION 82

You are building an online store on AWS that uses SQS to process your customer orders. Your backend system needs those messages in the same sequence the customer orders have been put in. How can you achieve that?

- A. You can do this with SQS but you also need to use SWF
- B. Messages will arrive in the same order by default
- C. You can use sequencing information on each message
- D. It is not possible to do this with SQS

Answer: C

Explanation:

Amazon SQS is engineered to always be available and deliver messages. One of the resulting tradeoffs is that SQS does not guarantee first in, first out delivery of messages. For many distributed applications, each message can stand on its own, and as long as all messages are delivered, the order is not important. If your system requires that order be preserved, you can place sequencing information in each message, so that you can reorder the messages when the queue returns them. Reference:
<http://docs.aws.amazon.com/AWSSimpleQueueService/latest/SQSDeveloperGuide/Welcome.html>

NEW QUESTION 87

When you use the AWS Elastic Beanstalk console to deploy a new application you'll need to upload a source bundle and it should .

- A. Consist of a single .zip file
- B. Consist of a single .war file
- C. Consist of a single .zip file or .war file
- D. Consist of a folder with all files

Answer: C

Explanation:

When you use the AWS Elastic Beanstalk console to deploy a new application or an application version, you'll need to upload a source bundle. Your source bundle must meet the following requirements: Consist of a single .zip file or .war file
Not exceed 512 MB
Not include a parent folder or top-level directory (subdirectories are fine) Reference:
<http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.deployment.source.html>

NEW QUESTION 88

A user had defined an IAM policy similar to the one given below on a bucket:

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Effect": "Allow",
    "Principal": {
      "AWS": "arn:aws:iam::12112112:user/test"
    },
    "Action": [ "s3:GetBucketLocation", "s3:ListBucket", "s3:GetObject" ],
    "Resource": [ "arn:aws:s3:::examkiller" ]
  }]
}
```

What will this do?

- A. It will result in an error saying invalid policy statement
- B. It will create an IAM policy for the user test
- C. Allows the user test of the AWS account ID 12112112 to perform GetBucketLocation, ListBucket and GetObject on the bucket examkiller
- D. It will allow all the IAM users of the account ID 12112112 to perform GetBucketLocation, ListBucket and GetObject on bucket examkiller

Answer: C

Explanation:

The IAM policy allows to test a user in the account 12112112 to perform: s3:GetBucketLocation
s3:ListBucket s3:GetObject
Amazon S3 permissions on the examkiller bucket.
Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/access-policy-language-overview.html>

NEW QUESTION 93

A user has configured a bucket S3 to host a static website. What difference will there be when static website hosting is enabled?

- A. It will help the user identify this bucket as the website root to map with the domain
- B. It will create a new version of the bucket
- C. It will not make any difference, but will help the user to configure the error page
- D. It will provide the region specific website endpoint

Answer: D

Explanation:

To host a static website, the user needs to configure an Amazon S3 bucket for website hosting and then upload the website contents to the bucket. The website is then available at the region-specific website endpoint of the bucket.
Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/WebsiteHosting.html>

NEW QUESTION 98

A user is trying to understand AWS SNS. To which of the below mentioned end points is SNS unable to send a notification?

- A. AWS SES
- B. Email JSON
- C. AWS SQS
- D. HTTP

Answer: A

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS) queues or to any HTTP endpoint. The user can select one of the following transports as part of the subscription requests: "HTTP", "HTTPS", "Email", "Email-JSON", "SQS", "and SMS".

Reference: <http://aws.amazon.com/sns/faqs/>

NEW QUESTION 100

Can one instance be registered with two ELBs in the same region?

- A. No
- B. Yes, provided both ELBs have the same health check configuration
- C. Yes, always
- D. Yes, provided both ELBs are in the same AZ

Answer: C

Explanation:

Yes, it is possible to have one instance part of two separate ELBs, though both ELBs have different configurations. ELBs are never launched in specific zones.

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/enable-disable-az.html>

NEW QUESTION 105

A user is trying to create a list of IAM users with the AWS console. When the IAM users are created which of the below mentioned credentials will be enabled by default for the user?

- A. IAM access key and secret access key
- B. IAM X.509 certificates
- C. Nothin
- D. Everything is disabled by default
- E. IAM passwords

Answer: C

Explanation:

Newly created IAM users have no password and no access key (access key ID and secret access key). If the user needs to administer your AWS resources using the AWS Management Console, you can create

a password for the user. If the user needs to interact with AWS programmatically (using the command line interface (CLI), the AWS SDK, or service-specific APIs), you can create an access key for that user. The credentials you create for users are what they use to uniquely identify themselves to AWS.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_WorkingWithGroupsAndUsers.html

NEW QUESTION 110

A user has created photo editing software and hosted it on EC2. The software accepts requests from the user about the photo format and resolution and sends a message to S3 to enhance the picture accordingly. Which of the below mentioned AWS services will help make a scalable software with the AWS infrastructure in this scenario?

- A. AWS Elastic Transcoder
- B. AWS Simple Notification Service
- C. AWS Simple Queue Service
- D. AWS Glacier

Answer: C

Explanation:

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. The user can configure SQS, which will decouple the call between the EC2 application and S3. Thus, the application does not keep waiting for S3 to provide the data.

Reference: <http://aws.amazon.com/sqs/faqs/>

NEW QUESTION 111

In DynamoDB, could you use IAM to grant access to Amazon DynamoDB resources and API actions?

- A. Yes
- B. Depended to the type of access
- C. In DynamoDB there is no need to grant access
- D. No

Answer: A

Explanation:

Amazon DynamoDB integrates with AWS Identity and Access Management (IAM). You can use AWS IAM to grant access to Amazon DynamoDB resources and API actions. To do this, you first write an AWS IAM policy, which is a document that explicitly lists the permissions you want to grant. You then attach that policy to an AWS IAM user or role.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/UsingIAMWithDDB.html>

NEW QUESTION 112

An organization is setting up their website on AWS. The organization is working on various security measures to be performed on the AWS EC2 instances. Which of the below mentioned security mechanisms will not help the organization to avoid future data leaks and identify security weaknesses?

- A. Perform SQL injection for application testing.
- B. Run penetration testing on AWS with prior approval from Amazon.
- C. Perform a hardening test on the AWS instance.
- D. Perform a Code Check for any memory leak

Answer: D

Explanation:

AWS security follows the shared security model where the user is as much responsible as Amazon. Since Amazon is a public cloud it is bound to be targeted by hackers. If an organization is planning to host their application on AWS EC2, they should perform the below mentioned security checks as a measure to find any security weakness/data leaks:

Perform penetration testing as performed by attackers to find any vulnerability. The organization must take an approval from AWS before performing penetration testing

Perform hardening testing to find if there are any unnecessary ports open Perform SQL injection to find any DB security issues

The code memory checks are generally useful when the organization wants to improve the application performance.

Reference: <http://aws.amazon.com/security/penetration-testing/>

NEW QUESTION 116

Regarding Amazon SQS, what happens if there is no activity against a queue for more than 30 consecutive days?

- A. Your account will be suspended
- B. The queue may be deleted
- C. Nothing
- D. The queue will be deleted

Answer: B

Explanation:

AWS reserves the right to delete a queue if none of the following requests have been issued against the queue for more than 30 consecutive days:

SendMessage ReceiveMessage DeleteMessage GetQueueAttributes SetQueueAttributes

You should design your application with this in mind. Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 117

A user has created a new EBS volume from an existing snapshot. The user mounts the volume on the instance to which it is attached. Which of the below mentioned options is a required step before the user can mount the volume?

- A. Run a cyclic check on the device for data consistency
- B. Create the file system of the volume
- C. Resize the volume as per the original snapshot size
- D. No step is required
- E. The user can directly mount the device

Answer: D

Explanation:

When a user is trying to mount a blank EBS volume, it is required that the user first creates a file system within the volume. If the volume is created from an existing snapshot then the user needs not to create a file system on the volume as it will wipe out the existing data.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-using-volumes.html>

NEW QUESTION 122

A user is creating multiple IAM users. What advice should be given to him to enhance the security?

- A. Grant least privileges to the individual user
- B. Grant all higher privileges to the group
- C. Grant less privileges for user, but higher privileges for the group
- D. Grant more privileges to the user, but least privileges to the group

Answer: A

Explanation:

It is a recommended rule that the root user should grant the least privileges to the IAM user or the group. The higher the privileges, the more problems it can create.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/IAMBestPractices.html>

NEW QUESTION 123

In regards to Amazon SQS how many times will you receive each message?

- A. At least twice
- B. Exactly once
- C. As many times as you want
- D. At least once

Answer: D

Explanation:

Amazon SQS is engineered to provide "at least once" delivery of all messages in its queues. Although most of the time, each message will be delivered to your application exactly once, you should design your system so that processing a message more than once does not create any errors or inconsistencies. Reference:

<https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 127

A user has set an IAM policy where it allows all requests if a request from IP 10.10.10.1/32. Another policy allows all the requests between 5 PM to 7 PM. What will happen when a user is requesting access from IP 10.10.10.1/32 at 6 PM?

- A. IAM will throw an error for policy conflict
- B. It is not possible to set a policy based on the time or IP
- C. It will deny access
- D. It will allow access

Answer: D

Explanation:

With regard to IAM, when a request is made, the AWS service decides whether a given request should be allowed or denied. The evaluation logic follows these rules:

By default, all requests are denied. (In general, requests made using the account credentials for resources in the account are always allowed.)

An explicit allow policy overrides this default. An explicit deny policy overrides any allows. Reference:

http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_EvaluationLogic.html

NEW QUESTION 132

A user has setup Multi AZ with the MS SQL RDS instance. Which of the below mentioned functionalities can be achieved by the user?

- A. High availability
- B. Scalability
- C. MS SQL does not support Multi AZ
- D. Disaster recovery

Answer: C

Explanation:

The Multi AZ feature allows the user to achieve High Availability. MS SQL does not support Multi AZ. Reference: <https://aws.amazon.com/rds/faqs/#36>

NEW QUESTION 136

Is it possible to create an S3 bucket accessible only by a certain IAM user, using policies in a CloudFormation template?

- A. No, you can only create the S3 bucket but not the IAM user.
- B. S3 is not supported by CloudFormation.
- C. Yes, all these resources can be created using a CloudFormation template
- D. No, in the same template you can only create the S3 bucket and the realtive polic

Answer: C

Explanation:

With AWS Identity and Access Management (IAM), you can create IAM users to control who has access to which resources in your AWS account. You can use IAM with AWS CloudFormation to control what AWS CloudFormation actions users can perform, such as view stack templates, create stacks, or delete stacks. In addition to AWS CloudFormation actions, you can manage what AWS services and resources are available to each user.

NEW QUESTION 138

A user has created an EBS instance in the US-East-1a AZ. The user has a volume of 30 GB in the US-East-1 b zone. How can the user attach the volume to an instance?

- A. Since both the volume and the instance are in the same region, the user can attach the volume
- B. Use the volume migrate function to move the volume from one AZ to another and attach to the instance
- C. Take a snapshot of the volum
- D. Create a new volume in the USEast-1a and attach that to the instance
- E. Use the volume replicate function to create a new volume in the US-East-1a and attach that to the volume

Answer: C

Explanation:

If an EBS volume is not in the same AZ of an EC2 instance, it cannot be attached to the instance. The only option is to take a snapshot of the volume and create a new volume in the instance's AZ. Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSSnapshots.html>

NEW QUESTION 139

A user is part of a group which has a policy allowing him just read only access to EC2. The user is part of another group which has full access to EC2. What happens when the user tries to launch an instance?

- A. It will allow the user to launch the instance
- B. It will fail since the user has just read only access
- C. It will allow or deny based on the group under which the user has logged into EC2
- D. It will not allow the user to add to the conflicting groups

Answer: A

Explanation:

The IAM group policy is always aggregated. In this case, if the user does not have permission for one group, but has permission for another group, he will have full access to EC2. Unless there is specific deny policy, the user will be able to access EC2.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/PoliciesOverview.html>

NEW QUESTION 140

A user has launched an RDS instance. The user has created 3 databases on the same server. What can the maximum size be for each database?

- A. The size of each DB cannot be more than 3 TB
- B. It is not possible to have more than one DB on a single instance
- C. The total instance storage size cannot be more than 3 TB
- D. The size of each DB cannot be more than 1 TB

Answer: C

Explanation:

The AWS RDS DB instance is an isolated DB environment provided by AWS in which the user can create more than 1 database. The maximum size of the instance should be between 5 GB and 3 TB. The size of each DB can be anything in this range.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 145

An organization has 10000 employees. The organization wants to give restricted AWS access to each employee. How can the organization achieve this?

- A. Create an IAM user for each employee and make them a part of the group
- B. It is not recommended to support 10000 users with IAM
- C. Use STS and create the users' run time
- D. Use Identity federation with SSO

Answer: D

Explanation:

Identity federation enables users from an existing directory to access resources within your AWS account, making it easier to manage your users by maintaining their identities in a single place. In this case, the federated user is the only solution since AWS does not allow creating more than 5000 IAM users. Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/LimitationsOnEntities.html>

NEW QUESTION 148

can be used to bootstrap both the Chef Server and Chef Client software on your EC2 instances.

- A. AWS CloudFormation
- B. AWS Elastic Beanstalk
- C. AWS OpsWorks
- D. Amazon Glacier

Answer: A

Explanation:

AWS CloudFormation can be used to bootstrap both the Chef Server and Chef Client software on your EC2 instances.

Reference: <http://aws.amazon.com/cloudformation/faqs/>

NEW QUESTION 151

In relation to Amazon Simple Workflow Service (Amazon SWF), what is an "Activity Worker"?

- A. An individual task undertaken by a workflow
- B. The automation of a business process
- C. A piece of software that implements tasks
- D. All answers listed are correct

Answer: C

Explanation:

In relation to Amazon Simple Workflow Service (Amazon SWF), an activity worker is a program that receives activity tasks, performs them, and provides results back. Which translates to a piece of software that implements tasks.

Reference: <http://docs.aws.amazon.com/amazonswf/latest/developerguide/swf-dg-develop-act.html>

NEW QUESTION 154

Which Amazon service is not used by Elastic Beanstalk?

- A. Amazon S3
- B. Amazon ELB
- C. Auto scaling
- D. Amazon EMR

Answer: D

Explanation:

Elastic Beanstalk leverages AWS services such as Amazon Elastic Cloud Compute (Amazon EC2), Amazon Simple Storage Service (Amazon S3), Amazon Simple Notification Service (Amazon SNS), Elastic Load Balancing and Auto Scaling to deliver the same highly reliable, scalable, and cost-effective infrastructure that hundreds of thousands of businesses depend on today.

Reference: <http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/welcome.html>

NEW QUESTION 159

Which of the below mentioned options can be a good use case for storing content in AWS RRS?

- A. Storing mission critical data Files
- B. Storing infrequently used log files
- C. Storing a video file which is not reproducible
- D. Storing image thumbnails

Answer: D

Explanation:

AWS RRS provides the same functionality as AWS S3, but at a cheaper rate. It is ideally suited for non-mission, critical applications, such as files which can be reproduced.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/UsingRRS.html>

NEW QUESTION 162

Which header received at the EC2 instance identifies the port used by the client while requesting ELB?

- A. X-Forwarded-Proto
- B. X-Requested-Proto
- C. X-Forwarded-Port
- D. X-Requested-Port

Answer: C

Explanation:

The X-Forwarded-Port request header helps the user identify the port used by the client while sending a request to ELB.

Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/TerminologyandKeyConcepts.html>

NEW QUESTION 163

A user has an S3 object in the US Standard region with the content "color=red". The user updates the object with the content as "color=white". If the user tries to read the value 1 minute after it was uploaded, what will S3 return?

- A. It will return "color=white"
- B. It will return "color=red"
- C. It will return an error saying that the object was not found
- D. It may return either "color=red" or "color=white" i.
- E. any of the value

Answer: D

Explanation:

AWS S3 follows the eventual consistent model in the US Standard Region. Once the object is updated it may return the new value or the old value based on whether all the content is replicated across multiple servers until it becomes consistent (eventual).

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/Introduction.html>

NEW QUESTION 166

AWS Elastic Beanstalk will change the health status of a web server environment tier to gray color when:

- A. AWS Elastic Beanstalk detects other problems with the environment that are known to make the application unavailable
- B. Your application hasn't responded to the application health check URL within the last one hour.
- C. Your application hasn't responded to the application health check URL within the last five minutes.
- D. Your application's health status is unknown because status is reported when the application is not in the ready state.

Answer: D

Explanation:

AWS Elastic Beanstalk will change the health status of a web server environment tier to gray color when your application's health status is unknown (because status is reported when the application is not in the ready state).

Reference: <http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.healthstatus.html>

NEW QUESTION 169

A user wants to access RDS from an EC2 instance using IP addresses. Both RDS and EC2 are in the same region, but different AZs. Which of the below mentioned options help configure that the instance is accessed faster?

- A. Configure the Private IP of the Instance in RDS security group
- B. Security group of EC2 allowed in the RDS security group
- C. Configuring the elastic IP of the instance in RDS security group
- D. Configure the Public IP of the instance in RDS security group

Answer: A

Explanation:

If the user is going to specify an IP range in RDS security group, AWS recommends using the private IP address of the Amazon EC2 instance. This provides a more direct network route from the Amazon EC2 instance to the Amazon RDS DB instance, and does not incur network charges for the data sent outside of the Amazon network.

Reference: http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_WorkingWithSecurityGroups.html

NEW QUESTION 171

A user is planning to use EBS for his DB requirement. The user already has an EC2 instance running in the VPC private subnet. How can the user attach the EBS volume to a running instance?

- A. The user must create EBS within the same VPC and then attach it to a running instance.
- B. The user can create EBS in the same zone as the subnet of instance and attach that EBS to instance.
- C. It is not possible to attach an EBS to an instance running in VPC until the instance is stopped.
- D. The user can specify the same subnet while creating EBS and then attach it to a running instance.

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. The VPC is always specific to a region. The user can create a VPC which can span multiple Availability Zones by adding one or more subnets in each Availability Zone. The instance launched will always be in the same availability zone of the respective subnet. When creating an EBS the user cannot specify the subnet or VPC. However, the user must create the EBS in the same zone as the instance so that it can attach the EBS volume to the running instance.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html#VPCSubnet

NEW QUESTION 175

Which of the following groups is AWS Elastic Beanstalk best suited for?

- A. Those who want to deploy and manage their applications within minutes in the AWS cloud
- B. Those who want to privately store and manage Git repositories in the AWS cloud.
- C. Those who want to automate the deployment of applications to instances and to update the applications as required
- D. Those who want to model, visualize, and automate the steps required to release software

Answer: A

Explanation:

AWS Elastic Beanstalk is best suited for those groups who want to deploy and manage their applications within minutes in the AWS cloud. As a bonus, you don't even need experience with cloud computing to get started.

Reference: <https://aws.amazon.com/elasticbeanstalk/faqs/>

NEW QUESTION 176

You are using Amazon SQS and are getting a "Queue Deleted Recently" error. What is wrong?

- A. The message is too big
- B. You have incorrect permissions
- C. Another user has deleted the queue
- D. If you delete a queue, you need to wait for at least 60 seconds before creating a queue with the same name

Answer: D

Explanation:

If you delete a queue, you need to wait for at least 60 seconds before creating a queue with the same name. Please note that when you delete a queue, the deletion process takes up to 60 seconds. Requests you send to a recently deleted queue might succeed during the 60-second period. For example, a `SendMessage` request might succeed, but after 60 seconds the queue and that message you sent no longer exists.

Reference: <https://aws.amazon.com/items/1343?externalID=1343>

NEW QUESTION 179

Your manager has requested you to tag EC2 instances to orgAMze and manage a load balancer. Which of the following statements about tag restrictions is incorrect?

- A. The maximum key length is 127 Unicode characters.
- B. The maximum value length is 255 Unicode characters.
- C. Tag keys and values are case sensitive.
- D. The maximum number of tags per load balancer is 20.

Answer: D

Explanation:

Tags help you to categorize your load balancers in different ways, for example, by purpose, owner, or environment. The following basic restrictions apply to tags: The maximum number of tags per resource is

10. The maximum key length is 127 Unicode characters. The maximum value length that can be used is 255 Unicode characters. The tag keys and values are case sensitive. Allowed characters are letters, spaces, and numbers representable in UTF-8, plus the following special characters: `+ - = . _ : / @`. Do not use leading or trailing spaces. Do not use the `aws:` prefix in your tag names or values because it is reserved for AWS use. You can't edit or delete tag names or values with this prefix. Tags with this prefix do not count against your tags per resource limit.

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/add-remove-tags.html#tag-restrictions>

NEW QUESTION 180

What is the maximum number of tags that a user can assign to an EC2 instance?

- A. 50
- B. 10
- C. 5
- D. 25

Answer:

B

Explanation:

To help manage EC2 instances as well as their usage in a better way, the user can tag the instances. The tags are metadata assigned by the user which consists of a key and a value. One resource can have a maximum of 10 tags.

Reference: http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/Using_Tags.html

NEW QUESTION 184

How do you configure SQS to support longer message retention?

- A. Set the IVmessageRetentionPeriod attribute using the SetQueueAttributes method
- B. Using a Lambda function
- C. You can't
- D. It is set to 14 days and cannot be changed
- E. You need to request it from AWS

Answer: A

Explanation:

To configure the message retention period, set the IVmessageRetentionPeriod attribute using the SetQueueAttributes method. This attribute is used to specify the number of seconds a message will be retained by SQS. Currently the default value for the message retention period is 4 days. Using the IVmessageRetentionPeriod attribute, the message retention period can be set anywhere from 60 seconds (1 minute), up to 1209600 seconds (14 days).

Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 188

The user has created multiple AutoScaling groups. The user is trying to create a new AS group but it fails. How can the user know that he has reached the AS group limit specified by AutoScaling in that region?

- A. Run the command: as-describe-account-limits
- B. Run the command: as-describe-group-limits
- C. Run the command: as-max-account-limits
- D. Run the command: as-list-account-limits

Answer: A

Explanation:

A user can see the number of AutoScaling resources currently allowed for the AWS account either by using the as-describe-account-limits command or by calling the DescribeAccountLimits action. Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/ts-as-capacity.html>

NEW QUESTION 189

What is the data model of DynamoDB?

- A. "Items", with Keys and one or more Attribute; and "Attribute", with Name and Value.
- B. "Database", which is a set of "Tables", which is a set of "Items", which is a set of "Attributes".
- C. "Table", a collection of Items; "Items", with Keys and one or more Attribute; and "Attribute", with Name and Value.
- D. "Database", a collection of Tables; "Tables", with Keys and one or more Attribute; and "Attribute", with Name and Value.

Answer: C

Explanation:

The data model of DynamoDB is: "Table", a collection of Items;

"Items", with Keys and one or more Attribute; "Attribute", with Name and Value.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/DataModel.html>

NEW QUESTION 191

In regard to DynamoDB, can I modify the index once it is created?

- A. Yes, if it is a primary hash key index
- B. Yes, if it is a Global secondary index
- C. No
- D. Yes, if it is a local secondary index

Answer: C

Explanation:

Currently, in DynamoDB, an index cannot be modified once it is created. Reference: http://aws.amazon.com/dynamodb/faqs/#security_anchor

NEW QUESTION 196

A user is planning to host MS SQL on an EBS volume. It was recommended to use the AWS RDS. What advantages will the user have if he uses RDS in comparison to an EBS based DB?

- A. Better throughput with PIOPS
- B. Automated backup
- C. MS SQL is not supported with RDS
- D. High availability with multi AZs

Answer: B

Explanation:

Comparing with on-premises or EC2 based NIS SQL, RDS provides an automated backup feature. PIOPS is available with both RDS and EBS. However, HA is not available with NIS SQL.

Reference: <https://aws.amazon.com/rds/faqs/>

NEW QUESTION 199

A user is setting up an Elastic Load Balancer(ELB). Which of the below parameters should the user consider so as the instance gets registered with the ELB?

- A. ELB DNS
- B. IP address
- C. Security group
- D. ELB IP

Answer: B

Explanation:

The EC2 instances are registered with the load balancer using the IP addresses associated with the instances. When an instance is stopped and then started, the IP address associated with the instance changes. This prevents the load balancer from routing traffic to the restarted instance. When the user stops and then starts registered EC2 instances, it is recommended that to de-register the stopped instance from load balancer, and then register the restarted instance. Failure to do so may prevent the load balancer from performing health checks and routing the traffic to the restarted instance.

NEW QUESTION 204

When you use the AWS Elastic Beanstalk console to deploy a new application .

- A. you'll need to upload each file separately
- B. you'll need to create each file and path
- C. you'll need to upload a source bundle
- D. you'll need to create each file

Answer: C

Explanation:

When you use the AWS Elastic Beanstalk console to deploy a new application or an application version, you'll need to upload a source bundle.

Reference:

<http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.deployment.source.html>

NEW QUESTION 205

A user is planning to use the AWS RDS with MySQL. Which of the below mentioned services the user is not going to pay?

- A. Data transfer
- B. RDS Cloudwatch metrics
- C. Data storage
- D. I/O requests per month

Answer: B

Explanation:

RDS charges the user on a pay as you go basis. It charges the user based on the instance type, number of hours that the instance is running, data transfer, storage cost as well for the I/O requests. The monitoring is free of cost.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 209

Which OS does the current version of AWS Elastic Beanstalk use?

- A. Amazon Linux AMI, Windows Server 2003 R2 AMI or the Windows Server 2008 R2 AMI
- B. Amazon Linux AMI only
- C. Amazon Linux AMI or the Windows Server 2008 R2 AMI
- D. Windows Sewer 2008 R2 AMI only

Answer: C

Explanation:

The current version of AWS Elastic Beanstalk uses the Amazon Linux AMI or the Windows Server 2008 R2 AMI.

Reference: <https://aws.amazon.com/elasticbeanstalk/faqs/>

NEW QUESTION 214

A user is creating an EBS volume. He asks for your advice. Which advice mentioned below should you not give to the user for creating an EBS volume?

- A. Take the snapshot of the volume when the instance is stopped
- B. Stripe multiple volumes attached to the same instance
- C. Create an AMI from the attached volume
- D. Attach multiple volumes to the same instance

Answer: C

Explanation:

When a user creates an EBS volume, the user can attach it to a running instance. The user can attach multiple volumes to the same instance and stripe them

together to increase the I/O. The user can take a snapshot from the existing volume but cannot create an AMI from the volume. However, the user can create an AMI from a snapshot.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumes.html>

NEW QUESTION 219

AWS Elastic Beanstalk stores your application files and optionally server log files in .

- A. Amazon Storage Gateway
- B. Amazon Glacier
- C. Amazon EC2
- D. Amazon S3

Answer: D

Explanation:

AWS Elastic Beanstalk stores your application files and optionally server log files in Amazon S3. If you are using the AWS Management Console, Git, the AWS Toolkit for Visual Studio, or AWS Toolkit for Eclipse, an Amazon S3 bucket will be created in your account for you and the files you upload will be automatically copied from your local client to Amazon S3. Optionally, you may configure Elastic Beanstalk to copy your server log files every hour to Amazon S3. You do this by editing the environment configuration settings.

Reference: <http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/AWSHowTo.html>

NEW QUESTION 224

An orgAMzation has created multiple components of a single application for compartmentalization. Currently all the components are hosted on a single EC2 instance. Due to security reasons the orgAMzation wants to implement two separate SSLs for the separate modules although it is already using VPC. How can the orgAMzation achieve this with a single instance?

- A. Create a VPC instance which will have both the ACL and the security group attached to it and have separate rules for each IP address.
- B. Create a VPC instance which will have multiple network interfaces with multiple elastic IP addresses.
- C. You have to launch two instances each in a separate subnet and allow VPC peering for a single IP.
- D. Create a VPC instance which will have multiple subnets attached to it and each will have a separate IP address.

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. With VPC the user can specify multiple private IP addresses for his instances.

The number of network interfaces and private IP addresses that a user can specify for an instance depends on the instance type. With each network interface the orgAMzation can assign an EIP. This scenario helps when the user wants to host multiple websites on a single EC2 instance by using multiple SSL certificates on a single server and associating each certificate with a specific EIP address. It also helps in scenarios for operating network appliances, such as firewalls or load balancers that have multiple private IP addresses for each network interface.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/MultipleIP.html>

NEW QUESTION 228

In regards to VPC, select the correct statement:

- A. You can associate multiple subnets with the same Route Table.
- B. You can associate multiple subnets with the same Route Table, but you can't associate a subnet with only one Route Table.
- C. You can't associate multiple subnets with the same Route Table.
- D. None of thes

Answer: A

Explanation:

Every subnet in your VPC must be associated with exactly one Route Table. However, multiple subnets can be associated with the same Route Table.

Reference: http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Route_Tables.html

NEW QUESTION 230

A user has hosted a website on AWS and uses ELB to load balance the multiple instances. The user application does not have any cookie management. How can the user bind the session of the requestor with a particular instance?

- A. Bind the IP address with a sticky cookie
- B. Create a cookie at the application level to set at ELB
- C. Use session synchronization with ELB
- D. Let ELB generate a cookie for a specified duration

Answer: D

Explanation:

The key to manage the sticky session is determining how long the load balancer should route the user's request to the same application instance. If the application has its own session cookie, then the user can set the Elastic Load Balancing to create the session cookie to follow the duration specified by the application's session cookie. If the user's application does not have its own session cookie, then he can set the Elastic Load Balancing to create a session cookie by specifying his own stickiness duration. Reference: http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/US_StickySessions.html

NEW QUESTION 233

A user is enabling a static website hosting on an S3 bucket. Which of the below mentioned parameters cannot be configured by the user?

- A. Error document
- B. Conditional error on object name

- C. Index document
- D. Conditional redirection on object name

Answer: B

Explanation:

To host a static website, the user needs to configure an Amazon S3 bucket for website hosting and then upload the website contents to the bucket. The user can configure the index, error document as well as configure the conditional routing of on object name.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/HowDoIWebsiteConfiguration.html>

NEW QUESTION 237

A user is uploading archives to Glacier. The user is trying to understand key Glacier resources. Which of the below mentioned options is not a Glacier resource?

- A. Notification configuration
- B. Archive ID
- C. Job
- D. Archive

Answer: B

Explanation:

AWS Glacier has four resources. Vault and Archives are core data model concepts. Job is required to initiate download of archive. The notification configuration is required to send user notification when archive is available for download.

Reference: <http://docs.aws.amazon.com/amazonglacier/latest/dev/amazon-glacier-data-model.html>

NEW QUESTION 239

An orgAMzation has 10 departments. The orgAMzation wants to track the AWS usage of each department. Which of the below mentioned options meets the requirement?

- A. Setup IAM groups for each department and track their usage
- B. Create separate accounts for each department, but use consolidated billing for payment and tracking
- C. Create separate accounts for each department and track them separately
- D. Setup IAM users for each department and track their usage

Answer: B

Explanation:

The cost of an IAM user or groups can never be tracked separately for the purpose of billing. The best solution in this case is to create a separate account for each department and use consolidated billing. Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/IAM_Introduction.html

NEW QUESTION 241

How can you peek at a message in Amazon SQS?

- A. Log the message ID and the receipt handle for your messages and correlate them to confirm when a message has been received and deleted
- B. Send the message to Amazon S3
- C. You can't
- D. Set up a CloudWatch alarm to auto send you the message

Answer: A

Explanation:

With version 2008-01-01, the PeekMessage action has been removed from Amazon SQS. This functionality was used mainly to debug small systems — specifically to confirm a message was successfully sent to the queue or deleted from the queue.

To do this with version 2008-01-01, you can log the message ID and the receipt handle for your messages and correlate them to confirm when a message has been received and deleted. Reference: <https://aws.amazon.com/items/1343?externalID=1343>

NEW QUESTION 246

An orgAMzation has created 10 IAM users. The orgAMzation wants those users to work independently and access AWS. Which of the below mentioned options is not a possible solution?

- A. Create the access key and secret access key for each user and provide access to AWS using the console
- B. Create the X.509 certificate for each user and provide them access to AWS CLI
- C. Enable MFA for each IAM user and assign them the virtual MFA device to access the console
- D. Provide each user with the IAM login and password for the AWS console

Answer: A

Explanation:

If an orgAMzation has created the IAM users, the users can access AWS services either with an IAM specific login/password or console. The orgAMzation can generate the IAM X.509 certificates to access AWS with CLI. The orgAMzation can also enable MFA for each IAM user, which allows an added security for each IAM user. If the orgAMzation has created the access key and secret key than the user cannot access the console using those keys. Access key and secret access key are useful for CLI or Webservices.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/IAM_Introduction.html

NEW QUESTION 251

What is the maximum size for messages stored in SQS?

- A. 256KB
- B. 128KB
- C. 1024KB
- D. 64KB

Answer: A

Explanation:

By default, SQS queues allow you to send the largest supported payload size, currently 256KB. You can choose to specify a limit on how many bytes can be sent per payload, using the `MaximumMessageSize` attribute of the `SetQueueAttributes` method.

Reference: <http://aws.amazon.com/sqs/faqs/>

NEW QUESTION 254

A user is planning to host data with RDS. Which of the below mentioned databases is not supported by RDS?

- A. PostgreSQL
- B. SQLDB
- C. Oracle
- D. MS SQL

Answer: B

Explanation:

Amazon Relational Database Service (Amazon RDS) is a web service that makes it easier to set up, operate, and scale a relational database in the cloud. AWS RDS supports popular DBs, such as MySQL, PostgreSQL, MS SQL and Oracle. This means that the code, applications, and tools user is already using with existing databases can be used with Amazon RDS too. In short, it is a managed Relation Database offering from AWS which manages backups, software patching, automatic failure detection, and recovery of Database.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 257

A root AWS account owner has created three IAM users: Bob, John and Michael. Michael is the IAM administrator. Bob and John are not the superpower users, but users with some pre-defined policies. John does not have access to modify his password. Thus, he asks Bob to change his password. How can Bob change John's password?

- A. This statement is false
- B. It should be Michael who changes the password for John
- C. It is not possible that John cannot modify his password
- D. Provided Bob is the manager of John
- E. Provided Michael has added Bob to a group, which has permissions to modify the IAM passwords

Answer: D

Explanation:

Generally with IAM users, the password can be modified in two ways. The first option is to define the IAM level policy which allows each user to modify their own passwords. The other option is to create a group and create a policy for the group which can change the passwords of various IAM users.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/HowToPwDIAMUser.html>

NEW QUESTION 262

To scale up the AWS resources using manual AutoScaling, which of the below mentioned parameters should the user change?

- A. Maximum capacity
- B. Desired capacity
- C. Preferred capacity
- D. Current capacity

Answer: B

Explanation:

The Manual Scaling as part of Auto Scaling allows the user to change the capacity of Auto Scaling group. The user can add / remove EC2 instances on the fly. To execute manual scaling, the user should modify the desired capacity. AutoScaling will adjust instances as per the requirements. If the user is trying to CLI, he can use command `as-set-desired-capacity <Auto Scaling Group Name> --desired-capacity <New Capacity>`

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/as-manual-scaling.html>

NEW QUESTION 267

Does DynamoDB support in-place atomic updates?

- A. It is not defined
- B. Yes
- C. It does support in-place non-atomic updates
- D. No

Answer: B

Explanation:

DynamoDB supports in-place atomic updates. Reference:

<http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/WorkingWithItems.html#WorkingWithItems.AtomicCounters>

NEW QUESTION 268

A user is launching an instance with EC2. Which of the below mentioned options does the user need to consider before launching an instance?

- A. Select the region where the instance is being launched.
- B. Select the instance type.
- C. All the options listed should be considered..
- D. Select the OS of the AM

Answer: C

Explanation:

Regarding Amazon EC2, when launching an instance, the user needs to select the region the instance would be launched from. While launching, the user needs to plan for the instance type and the OS of the instance.

Reference: http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ec2-launch-instance_linux.html

NEW QUESTION 269

A user has created an EBS volume with 1000 IOPS. What is the average IOPS that the user will get for most of the year as per EC2 SLA if the instance is attached to the EBS optimized instance?

- A. 900
- B. 990
- C. 950
- D. 1000

Answer: A

Explanation:

As per AWS SLA if the instance is attached to an EBS-Optimized instance, then the Provisioned IOPS volumes are designed to deliver within 10% of the provisioned IOPS performance 99.9% of the time in a given year. Thus, if the user has created a volume of 1000 IOPS, the user will get a minimum 900 IOPS 99.9% time of the year.

Reference: <http://aws.amazon.com/ec2/faqs/>

NEW QUESTION 270

Which statements about DynamoDB are true? Choose 2 answers

- A. DynamoDB uses a pessimistic locking model
- B. DynamoDB uses optimistic concurrency control
- C. DynamoDB uses conditional writes for consistency
- D. DynamoDB restricts item access during reads
- E. DynamoDB restricts item access during writes

Answer: BC

NEW QUESTION 272

You have an environment that consists of a public subnet using Amazon VPC and 3 instances that are running in this subnet. These three instances can successfully communicate with other hosts on the Internet. You launch a fourth instance in the same subnet, using the same AMI and security group configuration you used for the others, but find that this instance cannot be accessed from the Internet. What should you do to enable internet access?

- A. Deploy a NAT instance into the public subnet.
- B. Modify the routing table for the public subnet
- C. Configure a publically routable IP Address In the host OS of the fourth instance.
- D. Assign an Elastic IP address to the fourth instanc

Answer: D

NEW QUESTION 276

Which of the following is an example of a good DynamoDB hash key schema for provisioned throughput efficiency?

- A. User ID, where the application has many different users.
- B. Status Code where most status codes are the same
- C. Device ID, where one is by far more popular than all the others.
- D. Game Type, where there are three possible game types

Answer: A

NEW QUESTION 280

Which of the following statements about SWF are true? Choose 3 answers

- A. SWF tasks are assigned once and never duplicated
- B. SWF requires an S3 bucket for workflow storage
- C. SWF workflow executions can last up to a year
- D. SWF triggers SNS notifications on task assignment
- E. SWF uses deciders and workers to complete tasks
- F. SWF requires atleast 1 EC2 instance per domain

Answer: ACE

NEW QUESTION 285

Which of the following are correct statements with policy evaluation logic in AWS Identity and Access Management? Choose 2 answers

- A. By default, all requests are denied
- B. An explicit allow overrides an explicit deny
- C. An explicit allow overrides default deny.
- D. An explicit deny does not override an explicit allow
- E. By default, all request are allowed

Answer: AC

NEW QUESTION 286

If a message is retrieved from a queue in Amazon SQS, how long is the message inaccessible to other users by default?

- A. 0 seconds
- B. 1 hour
- C. 1 day
- D. forever
- E. 30 seconds

Answer: E

NEW QUESTION 290

Which of the following are valid SNS delivery transports? Choose 2 answers

- A. HTTP
- B. UDP
- C. SNIS
- D. DynamoDB
- E. Named Pipes

Answer: AC

NEW QUESTION 293

When uploading an object, what request header can be explicitly specified in a request to Amazon S3 to encrypt object data when saved on the server side?

- A. x-amz-storage-class
- B. Content-MD5
- C. x-amz-security-token
- D. x-amz-server-side-encryption

Answer: D

NEW QUESTION 294

In AWS, which security aspects are the customer's responsibility? Choose 4 answers

- A. Life-cycle management of IAM credentials
- B. Decommissioning storage devices
- C. Security Group and ACL (Access Control List) settings
- D. Encryption of EBS (Elastic Block Storage) volumes
- E. Controlling physical access to compute resources
- F. Patch management on the EC2 instance's operating system

Answer: ABCF

NEW QUESTION 299

You are providing AWS consulting services for a company developing a new mobile application that will be leveraging Amazon SNS Mobile Push for push notifications. In order to send direct notification messages to individual devices each device registration identifier or token needs to be registered with SNS; however the developers are not sure of the best way to do this.

You advise them to:

- A. Bulk upload the device tokens contained in a CSV file via the AWS Management Console.
- B. Let the push notification service (e.g. Amazon Device Messaging) handle the registration.
- C. Amazon Device Messaging handle the registration.
- D. Implement a token vending service to handle the registration.
- E. Call the CreatePlatformEndPoint API function to register multiple device token

Answer: B

NEW QUESTION 303

Which of the following are valid arguments for an SNS Publish request? Choose 3 answers

- A. TopicArn
- B. Subject
- C. Destination
- D. Format
- E. Message
- F. Language

Answer: ABE

NEW QUESTION 306

An application stores payroll information nightly in DynamoDB for a large number of employees across hundreds of offices. Item attributes consist of individual name, office identifier, and cumulative daily hours. Managers run reports for ranges of names working in their office. One query is. "Return all Items in this office for names starting with A through E". Which table configuration will result in the lowest impact on provisioned throughput for this query?

- A. Configure the table to have a hash index on the name attribute, and a range index on the office identifier
- B. Configure the table to have a range index on the name attribute, and a hash index on the office identifier
- C. Configure a hash index on the name attribute and no range index
- D. Configure a hash index on the office Identifier attribute and no range index

Answer: B

NEW QUESTION 310

EC2 instances are launched from Amazon Machine images (AMIs). A given public AMI can:

- A. be used to launch EC2 Instances in any AWS region.
- B. only be used to launch EC2 instances in the same country as the AMI is stored.
- C. only be used to launch EC2 instances in the same AWS region as the AMI is stored.
- D. only be used to launch EC2 instances in the same AWS availability zone as the AMI is stored

Answer: C

NEW QUESTION 312

You are inserting 1000 new items every second in a DynamoDB table. Once an hour these items are analyzed and then are no longer needed. You need to minimize provisioned throughput, storage, and API calls.

Given these requirements, what is the most efficient way to manage these Items after the analysis?

- A. Retain the items in a single table
- B. Delete items individually over a 24 hour period
- C. Delete the table and create a new table per hour
- D. Create a new table per hour

Answer: C

NEW QUESTION 315

When using a large Scan operation in DynamoDB, what technique can be used to minimize the impact of a scan on a table's provisioned throughput?

- A. Set a smaller page size for the scan
- B. Use parallel scans
- C. Define a range index on the table
- D. Prewarm the table by updating all items

Answer: C

NEW QUESTION 318

Which code snippet below returns the URL of a load balanced web site created in CloudFormation with an AWS::ElasticLoadBalancing::LoadBalancer resource name "ElasticLoad Balancer"?

- A. "Fn::Join" : ["" . ["http://", {"Fn::GetAttr" : ["ElasticLoadBalancer","DNSName"]}]]
- B. "Fn::Join" : ["" . ["http://", {"Fn::GetAttr" : ["ElasticLoadBalancer","Url"]}]]
- C. "Fn::Join" : ["" . ["http://", {"Ref" : "ElasticLoadBalancerUrl"}]]
- D. "Fn::Join" : ["http://", {"Ref" : "ElasticLoadBalancerDNSName"}]]

Answer: B

NEW QUESTION 320

How is provisioned throughput affected by the chosen consistency model when reading data from a DynamoDB table?

- A. Strongly consistent reads use the same amount of throughput as eventually consistent reads
- B. Strongly consistent reads use more throughput than eventually consistent reads.
- C. Strongly consistent reads use less throughput than eventually consistent reads
- D. Strongly consistent reads use variable throughput depending on read activity

Answer: B

NEW QUESTION 323

Which of the following services are included at no additional cost with the use of the AWS platform? Choose 2 answers

- A. Simple Storage Service
- B. Elastic Compute Cloud
- C. Auto Scaling
- D. Elastic Load Balancing
- E. CloudFormation

F. Simple Workflow Service

Answer: CE

NEW QUESTION 326

A corporate web application is deployed within an Amazon VPC, and is connected to the corporate data center via IPSec VPN. The application must authenticate against the on-premise LDAP server. Once authenticated, logged-in users can only access an S3 keyspace specific to the user.

Which two approaches can satisfy the objectives? Choose 2 answers

- A. The application authenticates against LDA
- B. The application then calls the IAM Security Service to login to IAM using the LDAP credential
- C. The application can use the IAM temporary credentials to access the appropriate S3 bucket.
- D. The application authenticates against LDAP, and retrieves the name of an IAM role associated with the use
- E. The application then calls the IAM Security Token Service to assume that IAM Rol
- F. The application can use the temporary credentials to access the appropriate S3 bucket.
- G. The application authenticates against IAM Security Token Service using the LDAP credential
- H. The application uses those temporary AWS security credentials to access the appropriate S3 bucket.
- I. Develop an identity broker which authenticates against LDAP, and then calls IAM Security Token Service to get IAM federated user credential
- J. The application calls the identity broker to get IAM federated user credentials with access to the appropriate S3 bucket.
- K. Develop an identity broker which authenticates against IAM Security Token Service to assume an IAM Role to get temporary AWS security credential
- L. The application calls the identity broker to get AWS temporary security credentials with access to the appropriate S3 bucket.

Answer: BD

NEW QUESTION 329

You attempt to store an object in the US-STANDARD region in Amazon S3, and receive a confirmation that it has been successfully stored. You then immediately make another API call and attempt to read this object. S3 tells you that the object does not exist

What could explain this behavior?

- A. US-STANDARD uses eventual consistency and it can take time for an object to be readable in a bucket
- B. Objects in Amazon S3 do not become visible until they are replicated to a second region.
- C. US-STANDARD imposes a 1 second delay before new objects are readable.
- D. You exceeded the bucket object limit, and once this limit is raised the object will be visible.

Answer: A

NEW QUESTION 334

Company A has an S3 bucket containing premier content that they intend to make available to only paid subscribers of their website. The S3 bucket currently has default permissions of all objects being private to prevent inadvertent exposure of the premier content to non-paying website visitors. How can Company A provide only paid subscribers the ability to download a premier content file in the S3 bucket?

- A. Apply a bucket policy that grants anonymous users to download the content from the S3 bucket
- B. Generate a pre-signed object URL for the premier content file when a paid subscriber requests a download
- C. Add a bucket policy that requires Multi-Factor Authentication for requests to access the S3 bucket objects
- D. Enable server side encryption on the S3 bucket for data protection against the non-paying website visitors

Answer: B

NEW QUESTION 339

Which of the following is chosen as the default region when making an API call with an AWS SDK?

- A. ap-northeast-1
- B. us-west-2
- C. us-east-1
- D. eu-west-1
- E. us-central-1

Answer: C

NEW QUESTION 340

Games-R-Us is launching a new game app for mobile devices. Users will log into the game using their existing Facebook account and the game will record player data and scoring information directly to a DynamoDB table.

What is the most secure approach for signing requests to the DynamoDB API?

- A. Create an IAM user with access credentials that are distributed with the mobile app to sign the requests
- B. Distribute the AWS root account access credentials with the mobile app to sign the requests
- C. Request temporary security credentials using web identity federation to sign the requests
- D. Establish cross account access between the mobile app and the DynamoDB table to sign the requests

Answer: C

NEW QUESTION 343

After launching an instance that you intend to serve as a NAT (Network Address Translation) device in a public subnet you modify your route tables to have the NAT device be the target of internet bound traffic of your private subnet. When you try and make an outbound connection to the Internet from an instance in the private subnet, you are not successful.

Which of the following steps could resolve the issue?

- A. Attaching a second Elastic Network interface (ENI) to the NAT instance, and placing it in the private subnet
- B. Attaching a second Elastic Network Interface (ENI) to the instance in the private subnet, and placing it in the public subnet
- C. Disabling the Source/Destination Check attribute on the NAT instance
- D. Attaching an Elastic IP address to the instance in the private subnet

Answer: C

NEW QUESTION 345

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual AWS-Certified-Developer-Associate Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the AWS-Certified-Developer-Associate Product From:

<https://www.2passeasy.com/dumps/AWS-Certified-Developer-Associate/>

Money Back Guarantee

AWS-Certified-Developer-Associate Practice Exam Features:

- * AWS-Certified-Developer-Associate Questions and Answers Updated Frequently
- * AWS-Certified-Developer-Associate Practice Questions Verified by Expert Senior Certified Staff
- * AWS-Certified-Developer-Associate Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * AWS-Certified-Developer-Associate Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year