



Cisco

Exam Questions 350-601

Implementing and Operating Cisco Data Center Core Technologies

About ExamBible

[Your Partner of IT Exam](#)

Found in 1998

ExamBible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, ExamBible has its unique advantages that other companies could not achieve.

Our Advances

* 99.9% Uptime

All examinations will be up to date.

* 24/7 Quality Support

We will provide service round the clock.

* 100% Pass Rate

Our guarantee that you will pass the exam.

* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

NEW QUESTION 1

Refer to the exhibit.

Which two statements about the routing table of the leaf switch are true? (Choose two.)

- A. 10.20.1.0/24 is a BD subnet in ACI.
- B. The next hop 10.0.1.14 for route 172.16.99.0/24 is the TEP address of a border leaf in ACI.
- C. 172.16.100.0/24 is a BD subnet in ACI.
- D. The next hop 10.1.168.95 for route 172.16.100.0/24 is the TEP address of a border leaf in ACI.
- E. The next hop 10.0.8.65 for route 10.20.1.0/24 is the TEP address of a border leaf in ACI.

Answer: AE

NEW QUESTION 2

Which mroute state is created when Bidirectional PIM is deployed at a site?

- A. *.G
- B. MVPN Type-6
- C. MVPN Type-7
- D. S.G

Answer: A

NEW QUESTION 3

Refer to the exhibit.

What must be connected to clear the HA NOT READY status?

- A. Layer 1-Layer 2 ports
- B. server chassis
- C. management ports
- D. network uplinks

Answer: B

NEW QUESTION 4

The engineer must configure SPAN on a Cisco Nexus 5000 Series Switch to get a capture of the traffic from these applications for an in-depth packet analysis. Which two SPAN characteristics must be considered? (Choose two.)

- A. SPAN source ports can be monitored in multiple SPAN sessions.
- B. The Ethernet, FC, vFC, port channel, SAN port channel can be used as SPAN source ports.
- C. A SPAN source port cannot be a destination SPAN port.
- D. Only Ethernet, FC, vFC, port channel port types can be used as SPAN source ports.
- E. The rx/tx option is available for VLAN or VSAN SPAN sessions.

Answer: BC

NEW QUESTION 5

Due to a major version change, an engineer must perform a software upgrade on a Cisco Nexus Series switch.

Which two technologies can be implemented to reduce disruptions to the network during the upgrade? (Choose two.)

- A. vPC
- B. HSRP
- C. VDC
- D. MLAG
- E. PAgP

Answer: AC

NEW QUESTION 6

An engineer is implementing an import operation in Cisco UCS Manager.

What is the impact of performing this operation?

- A. Information can be modified on the management plane only.
- B. A configuration can be imported from a higher release to a lower release.

- C. An import operation can be scheduled.
- D. Only a configuration file that was exported from the same Cisco UCS Manager can be imported.

Answer: A

NEW QUESTION 7

An engineer is asked to use SaaS to manage Cisco computing.
Which two items are needed to accomplish the task? (Choose two.)

- A. Intersight
- B. UCS Central
- C. Device/Claim ID
- D. Node name/Serial Number
- E. UCS Manager

Answer: AE

NEW QUESTION 8

An engineer must configure Cisco IMC server management NIC for autonegotiation.
Which setting should be selected?

- A. shared LOM
- B. Cisco card
- C. dedicated
- D. shared LOM EXT

Answer: C

NEW QUESTION 9

An engineer changed a configuration and must perform a rollback.
Which statement applies to a Cisco Nexus 5600 Series Switch?

- A. The configuration rollback functionality is disabled when FCoE is enabled.
- B. A system checkpoint is generated automatically when the running configuration is saved to NVRAM.
- C. A user who is assigned to the network-operator user role can perform a rollback.
- D. Errors are skipped when an atomic rollback type is triggered.

Answer: A

NEW QUESTION 10

Which two statements about the process of performing an EPLD upgrade on a Cisco MDS 9000 Series Switch are true? (Choose two.)

- A. The upgrade can be performed from the standby supervisor module.
- B. The upgrade process disrupts only the module that is being upgraded.
- C. The active supervisor can be upgraded.
- D. If an upgrade is interrupted, the upgrade continues after a connection is restored.
- E. Modules must be online to be upgraded.

Answer: AB

NEW QUESTION 10

Which two statements about the process at upgrading an EPLD on a Cisco MDS 9000 Series Switch are correct? (Choose two.)

- A. EPLDs can be upgraded only to the latest EPLD image.
- B. EPLD upgrades can be completed without powering down the module during the upgrade.
- C. An upgrade verification identifies the impact of each EPLD upgrade.
- D. The EPLDs for all the modules on a switch must be upgraded at the same time.
- E. EPLDs can be upgraded without replacing the hardware.

Answer: CE

NEW QUESTION 15

Refer to the exhibit.

What is the outcome of this command when the EPLD is updated on a Cisco Nexus 9000 Series Switch?

- A. displays the compatibility of the EPLD upgrade and the image in the bootflash
- B. shows a simulated upgrade of the EPLD
- C. upgrades the EPLD on the switch disruptively
- D. displays the impact of the upgrade on the operation of the switch

Answer: A

NEW QUESTION 17

DRAG DROP

An engineer is configuring VNTag between a virtualized server and a Cisco Nexus 5500 Series switch. Drag and drop the configuration steps from the left into the correct order on the right.

Select and Place:

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

NEW QUESTION 18

Multiple roles are applied to a user on the Cisco MDS 9000 Series Switch. Which statement is true?

- A. The last role assigned takes precedence over previous roles.
- B. Access to a command takes priority over being denied access to a command.
- C. Any commands that have conflicting settings between roles are denied.
- D. The first role assigned takes precedence over subsequent roles.

Answer: B

NEW QUESTION 19

Refer to the exhibit.

Which action must be taken before the maintenance policy can be committed?

- A. Specify a maintenance time by selecting a schedule.
- B. Associate a service profile to the maintenance policy.
- C. Set the soft shutdown timer to a specific time.
- D. Set the policy to apply the changes on the next reboot.

Answer: A

NEW QUESTION 23

Which statement is true about upgrading the firmware on a Cisco MDS storage switch with dual supervisors?

- A. Supervisors can be upgraded independently to test the new firmware.
- B. The new firmware is loaded on the standby supervisor first.
- C. Both supervisors load the new firmware and then the active supervisor reboots.
- D. The standby supervisor must be offline before the firmware upgrade begins.

Answer: B

NEW QUESTION 25

Which statement about the MAC address that the FCoE Initialization Protocol chooses for use by an E-Node in an FCoE implementation is true?

- A. The FCoE Initialization Protocol uses a 24-bit FC-MAP and concatenates a 24-bit Fibre Channel ID to create a fabric-provided MAC address.
- B. The FCoE Initialization Protocol uses the burned-in MAC address of the converged network adapter for all FCoE operations.
- C. FCoE does not use a MAC address
- D. The FCoE Initialization Protocol is used to acquire a Fibre Channel ID, and the address is used for all FCoE communications in the same way as Fibre Channel Protocol.
- E. The FCoE Initialization Protocol uses 01.00.0C as the first 24 bits of the MAC address and appends a 24-bit Fibre Channel ID to derive a full 48-bit FCoE MAC address.

Answer: AB

NEW QUESTION 30

Which statement about monitoring Fibre Channel traffic on a Cisco UCS 6332 Fabric Interconnect is true?

- A. Fibre Channel traffic can be monitored only on one vHBA per server.
- B. Fibre Channel traffic can be monitored as it is encapsulated as FCoE.
- C. The monitoring of Fibre Channel traffic is limited to the default VSAN.
- D. The destination port for monitoring must be an unassigned Fibre Channel port.

Answer: A

NEW QUESTION 35

An engineer is implementing NPV mode on a Cisco MDS 9000 Series Switch. Which action must be taken?

- A. NPIV must be enabled on the upstream switch.
- B. The FCNS database must be disabled in the fabric.
- C. A port channel must be configured to the upstream switch.
- D. All switches in the fabric must be Cisco MDS switches.

Answer: A

NEW QUESTION 36

Which two statements about modifying Cisco UCS user accounts are true? (Choose two.)

- A. Disabling a user account maintains all of the data in the Cisco UCS Fabric Interconnect.
- B. The admin account can be used to log on by using SSH only.
- C. The password of the user account must contain a minimum of 10 characters.
- D. Local user accounts override the same account on a remote authentication server, such as TACACS, RADIUS, or LDAP.
- E. The password of the user account expires in 30 days.

Answer: AD

NEW QUESTION 37

An engineer is converting a Cisco MDS switch to support NPIV mode. What should be considered when implementing the solution?

- A. It requires mapping of external interface traffic.
- B. It must be enabled on VSAN 1 only.
- C. It must be enabled globally on all VSANs.
- D. It requires the FLOGI database to be disabled.

Answer: C

NEW QUESTION 38

An administrator needs to configure an automated policy to shut down a link when a given threshold is exceeded on MDS switch. Which feature needs to be used?

- A. RMON
- B. EEM
- C. Call Home
- D. Scheduler

Answer: B

NEW QUESTION 41

An engineer enters these commands while in EEM on a Cisco Nexus 9000 Series Switch
event manager applet Backup-config event timer watchdog time 1800 name timer event cli match "copy running-config startup-config" What is the result of applying this configuration?

- A. It generates an error because no action is mentioned.
- B. It executes the copy running-config startup-coring command.
- C. It saves the running configuration every 1800 seconds.
- D. It blocks the copy running-config startup-config command.

Answer: A

NEW QUESTION 45

Which configuration generates a syslog message when CPU utilization is higher than 60%?

- A. event manager applet HIGH-CPU event snmp oid 1.3.6.1.4.1.9.9.109.1.1.1.1.6.1 get-type exact entry-op gt 60 poll-interval 5 action 1.0 syslog priority notifications msg "cpu high"
- B. event manager applet HIGH-CPU event snmp oid 1.3.6.1.4.1.9.9.109.1.1.1.1.6.1 get-type exact entry-op lt 60 poll-interval 5 action 1.0 syslog priority notifications msg "cpu high"
- C. event manager applet HIGH-CPU event snmp oid 1.3.6.1.4.1.9.9.109.1.1.1.1.6.1 get-type next entry-op gt 60 poll-interval 5 action 1.0 syslog priority notifications msg "cpu high"
- D. event manager applet HIGH-CPU event snmp oid 1.3.6.1.4.1.9.9.109.1.1.1.1.6.1 get-type next entry-op lt 60 poll-interval 5 action 1.0 syslog priority notifications msg "cpu high"

Answer: A

NEW QUESTION 46

What is a feature of NFS?

- A. zone-based access control
- B. Kerberos-based security model
- C. block-based file access
- D. role-based access control

Answer: B

NEW QUESTION 51

Port security is enabled on a Cisco MDS 9000 Series Switch.

Which statement is true?

- A. Port security can be enabled only globally and affects all VSANs.
- B. Any devices currently logged in must be added manually to the device database.
- C. Auto-learning is always enabled automatically when port security is enabled.
- D. Cisco Fabric Services must be disabled before enabling port security.

Answer: C

NEW QUESTION 52

DRAG DROP

Drag and drop the storage technologies from the left onto the correct descriptions on the right.

Select and Place:

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

NEW QUESTION 57

Refer to the exhibit.

What is the result of implementing this configuration?

- A. The switch queries the TACACS+ server by using an encrypted text PAP login.
- B. The TACACS+ server uses the type-6 encrypted format.
- C. The switch queries the TACACS+ server by using a clear text PAP login.
- D. The timeout value on the TACACS+ server is 10 seconds.

Answer: D

NEW QUESTION 61

.....

Relate Links

100% Pass Your 350-601 Exam with ExamBible Prep Materials

<https://www.exambible.com/350-601-exam/>

Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>