

300-715 Dumps

Implementing and Configuring Cisco Identity Services Engine (SISE)

<https://www.certleader.com/300-715-dumps.html>



NEW QUESTION 1

Which personas can a Cisco ISE node assume?

- A. policy service, gatekeeping, and monitoring
- B. administration, monitoring, and gatekeeping
- C. administration, policy service, and monitoring
- D. administration, policy service, gatekeeping

Answer: C

Explanation:

Reference: https://www.cisco.com/en/US/docs/security/ise/1.0/user_guide/ise10_dis_deploy.html

NEW QUESTION 2

Which two features are available when the primary admin node is down and the secondary admin node has not been promoted? (Choose two.)

- A. new AD user 802.1X authentication
- B. hotspot
- C. posture
- D. guest AUP
- E. BYOD

Answer: BD

NEW QUESTION 3

In which two ways can users and endpoints be classified for TrustSec? (Choose two.)

- A. VLAN
- B. dynamic
- C. QoS
- D. SGACL
- E. SXP

Answer: AD

NEW QUESTION 4

What are two requirements of generating a single certificate in Cisco ISE by using a certificate provisioning portal, without generating a certificate signing request? (Choose two.)

- A. Enter the IP address of the device.
- B. Enter the common name.
- C. Choose the hashing method.
- D. Locate the CSV file for the device MAC.
- E. Select the certificate template.

Answer: BE

Explanation:

Reference: <https://www.cisco.com/c/en/us/support/docs/security/identity-services-engine/200534-ISE-2-0-Certificate-Provisioning-Portal.html>

NEW QUESTION 5

Which two values are compared by the binary comparison function in authentication that is based on Active Directory?

- A. user-presented certificate and a certificate stored in Active Directory
- B. MS-CHAPv2 provided machine credentials and credentials stored in Active Directory
- C. user-presented password hash and a hash stored in Active Directory
- D. subject alternative name and the common name

Answer: D

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/security/ise/1-3/ISE-ADIntegrationDoc/b_ISE-ADIntegration.html

NEW QUESTION 6

What is the minimum certainty factor when creating a profiler policy?

- A. the minimum number that a predefined condition provides
- B. the maximum number that a predefined condition provides
- C. the minimum number that a device certainty factor must reach to become a member of the profile
- D. the maximum number that a device certainty factor must reach to become a member of the profile

Answer: C

NEW QUESTION 7

What service can be enabled on the Cisco ISE node to identify the types of devices connecting to a network?

- A. profiling
- B. central web authentication
- C. MAB
- D. posture

Answer: A

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/security/ise/2-1/admin_guide/b_ise_admin_guide_21/b_ise_admin_guide_20_chapter_010100.html

NEW QUESTION 8

Which two probes must be enabled for the ARP cache to function in the Cisco ISE profiling service so that a user can reliably bind the IP addresses and MAC addresses of endpoints? (Choose two.)

- A. SNMP
- B. HTTP
- C. RADIUS
- D. DHCP
- E. NetFlow

Answer: CD

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/security/ise/2-1/admin_guide/b_ise_admin_guide_21/b_ise_admin_guide_20_chapter_010100.html

NEW QUESTION 9

What allows an endpoint to obtain a digital certificate from Cisco ISE during a BYOD flow?

- A. Application Visibility and Control
- B. Supplicant Provisioning Wizard
- C. My Devices Portal
- D. Network Access Control

Answer: C

NEW QUESTION 10

Which two endpoint compliance statuses are possible? (Choose two.)

- A. compliant
- B. valid
- C. unknown
- D. known
- E. invalid

Answer: AC

NEW QUESTION 10

Which portal is used to customize the settings for a user to log in and download the compliance module?

- A. Client Provisioning
- B. Client Endpoint
- C. Client Profiling
- D. Client Guest

Answer: A

NEW QUESTION 12

What are two components of the posture requirement when configuring Cisco ISE posture? (Choose two.)

- A. Client Provisioning portal
- B. remediation actions
- C. updates
- D. access policy
- E. conditions

Answer: BE

NEW QUESTION 13

Which two features must be used on Cisco ISE to enable the TACACS+ feature? (Choose two.)

- A. Command Sets
- B. Server Sequence
- C. Device Administration License
- D. External TACACS Servers

E. Device Admin Service

Answer: CE

NEW QUESTION 18

Which are two characteristics of TACACS+? (Choose two.)

- A. It separates authorization and authentication functions.
- B. It combines authorization and authentication functions.
- C. It uses UDP port 49.
- D. It encrypts the password only.
- E. It uses TCP port 49.

Answer: AE

Explanation:

Reference: <https://www.cisco.com/c/en/us/support/docs/security-vpn/remote-authentication-dial-user-service-radius/13838-10.html>

NEW QUESTION 19

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your 300-715 Exam with Our Prep Materials Via below:

<https://www.certleader.com/300-715-dumps.html>