

# ISC2

## Exam Questions SSCP

System Security Certified Practitioner (SSCP)



#### NEW QUESTION 1

- (Topic 1)

The Terminal Access Controller Access Control System (TACACS) employs which of the following?

- A. a user ID and static password for network access
- B. a user ID and dynamic password for network access
- C. a user ID and symmetric password for network access
- D. a user ID and asymmetric password for network access

**Answer:** A

#### Explanation:

For networked applications, the Terminal Access Controller Access Control System (TACACS) employs a user ID and a static password for network access.  
Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, 2001, John Wiley & Sons, Page 44.

#### NEW QUESTION 2

- (Topic 1)

Which of the following pairings uses technology to enforce access control policies?

- A. Preventive/Administrative
- B. Preventive/Technical
- C. Preventive/Physical
- D. Detective/Administrative

**Answer:** B

#### Explanation:

The preventive/technical pairing uses technology to enforce access control policies.

##### TECHNICAL CONTROLS

Technical security involves the use of safeguards incorporated in computer hardware, operations or applications software, communications hardware and software, and related devices. Technical controls are sometimes referred to as logical controls.

##### Preventive Technical Controls

Preventive technical controls are used to prevent unauthorized personnel or programs from gaining remote access to computing resources. Examples of these controls include:

Access control software. Antivirus software. Library control systems. Passwords.

Smart cards. Encryption.

Dial-up access control and callback systems.

##### Preventive Physical Controls

Preventive physical controls are employed to prevent unauthorized personnel from entering computing facilities (i.e., locations housing computing resources, supporting utilities, computer hard copy, and input data media) and to help protect against natural disasters. Examples of these controls include:

Backup files and documentation. Fences.

Security guards. Badge systems. Double door systems. Locks and keys. Backup power.

Biometric access controls. Site selection.

Fire extinguishers.

##### Preventive Administrative Controls

Preventive administrative controls are personnel-oriented techniques for controlling people's behavior to ensure the confidentiality, integrity, and availability of computing data and programs. Examples of preventive administrative controls include:

Security awareness and technical training. Separation of duties.

Procedures for recruiting and terminating employees. Security policies and procedures.

Supervision.

Disaster recovery, contingency, and emergency plans. User registration for computer access.

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, 2001, John Wiley & Sons, Page 34.

#### NEW QUESTION 3

- (Topic 1)

Which access control model achieves data integrity through well-formed transactions and separation of duties?

- A. Clark-Wilson model
- B. Biba model
- C. Non-interference model
- D. Sutherland model

**Answer:** A

#### Explanation:

The Clark-Wilson model differs from other models that are subject- and object- oriented by introducing a third access element programs resulting in what is called an access triple, which prevents unauthorized users from modifying data or programs. The Biba model uses objects and subjects and addresses integrity based on a hierarchical

lattice of integrity levels. The non-interference model is related to the information flow model with restrictions on the information flow. The Sutherland model approaches integrity by focusing on the problem of inference.

Source: ANDRESS, Mandy, Exam Cram CISSP, Coriolis, 2001, Chapter 2: Access Control Systems and Methodology (page 12).

And: KRAUSE, Micki & TIPTON, Harold F., Handbook of Information Security Management, CRC Press, 1997, Domain 1: Access Control.

#### NEW QUESTION 4

- (Topic 1)

Which is the last line of defense in a physical security sense?

- A. people
- B. interior barriers
- C. exterior barriers
- D. perimeter barriers

**Answer:** A

**Explanation:**

"Ultimately, people are the last line of defense for your company??s assets" (Pastore & Dulaney, 2006, p. 529).  
Pastore, M. and Dulaney, E. (2006). CompTIA Security+ study guide: Exam SY0-101. Indianapolis, IN: Sybex.

**NEW QUESTION 5**

- (Topic 1)

Which of following is not a service provided by AAA servers (Radius, TACACS and DIAMETER)?

- A. Authentication
- B. Administration
- C. Accounting
- D. Authorization

**Answer:** B

**Explanation:**

Radius, TACACS and DIAMETER are classified as authentication, authorization, and accounting (AAA) servers.

Source: TIPTON, Harold F. & KRAUSE, MICKI, Information Security Management Handbook, 4th Edition, Volume 2, 2001, CRC Press, NY, Page 33.

also see:

The term "AAA" is often used, describing cornerstone concepts [of the AIC triad] Authentication, Authorization, and Accountability. Left out of the AAA acronym is Identification which is required before the three "A's" can follow. Identity is a claim, Authentication proves an identity, Authorization describes the action you can perform on a system once you have been identified and authenticated, and accountability holds users accountable for their actions.

Reference: CISSP Study Guide, Conrad Misenar, Feldman p. 10-11, (c) 2010 Elsevier.

**NEW QUESTION 6**

- (Topic 1)

What is the main concern with single sign-on?

- A. Maximum unauthorized access would be possible if a password is disclosed.
- B. The security administrator's workload would increase.
- C. The users' password would be too hard to remember.
- D. User access rights would be increased.

**Answer:** A

**Explanation:**

A major concern with Single Sign-On (SSO) is that if a user's ID and password are compromised, the intruder would have access to all the systems that the user was authorized for.

The following answers are incorrect:

The security administrator's workload would increase. Is incorrect because the security administrator's workload would decrease and not increase. The admin would not be responsible for maintaining multiple user accounts just the one.

The users' password would be too hard to remember. Is incorrect because the users would have less passwords to remember.

User access rights would be increased. Is incorrect because the user access rights would not be any different than if they had to log into systems manually.

**NEW QUESTION 7**

- (Topic 1)

Crime Prevention Through Environmental Design (CPTED) is a discipline that:

- A. Outlines how the proper design of a physical environment can reduce crime by directly affecting human behavior.
- B. Outlines how the proper design of the logical environment can reduce crime by directly affecting human behavior.
- C. Outlines how the proper design of the detective control environment can reduce crime by directly affecting human behavior.
- D. Outlines how the proper design of the administrative control environment can reduce crime by directly affecting human behavior.

**Answer:** A

**Explanation:**

Crime Prevention Through Environmental Design (CPTED) is a discipline that outlines how the proper design of a physical environment can reduce crime by directly affecting human behavior. It provides guidance about lost and crime prevention through proper facility construction and environmental components and procedures.

CPTED concepts were developed in the 1960s. They have been expanded upon and have matured as our environments and crime types have evolved. CPTED has been used not just to develop corporate physical security programs, but also for large-scale activities such as development of neighborhoods, towns, and cities. It addresses landscaping, entrances, facility and neighborhood layouts, lighting, road placement, and traffic circulation patterns. It looks at microenvironments, such as offices and rest-rooms, and macroenvironments, like campuses and cities.

Reference(s) used for this question:

Harris, Shon (2012-10-18). CISSP All-in-One Exam Guide, 6th Edition (p. 435). McGraw- Hill. Kindle Edition.

and

CPTED Guide Book

**NEW QUESTION 8**

- (Topic 1)

What is called the type of access control where there are pairs of elements that have the least upper bound of values and greatest lower bound of values?

- A. Mandatory model
- B. Discretionary model
- C. Lattice model
- D. Rule model

**Answer: C**

**Explanation:**

In a lattice model, there are pairs of elements that have the least upper bound of values and greatest lower bound of values.

Reference(s) used for this question:

KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, 2001, John Wiley & Sons, Page 34.

**NEW QUESTION 9**

- (Topic 1)

Which of the following is most affected by denial-of-service (DOS) attacks?

- A. Confidentiality
- B. Integrity
- C. Accountability
- D. Availability

**Answer: D**

**Explanation:**

Denial of service attacks obviously affect availability of targeted systems. Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, John Wiley & Sons, 2001, Chapter 3: Telecommunications and Network Security (page 61).

**NEW QUESTION 10**

- (Topic 1)

Which of the following access control techniques best gives the security officers the ability to specify and enforce enterprise-specific security policies in a way that maps naturally to an organization's structure?

- A. Access control lists
- B. Discretionary access control
- C. Role-based access control
- D. Non-mandatory access control

**Answer: C**

**Explanation:**

Role-based access control (RBAC) gives the security officers the ability to specify and enforce enterprise-specific security policies in a way that maps naturally to an organization's structure. Each user is assigned one or more roles, and each role is assigned one or more privileges that are given to users in that role. An access control list (ACL) is a table that tells a system which access rights each user has to a particular system object. With discretionary access control, administration is decentralized and owners of resources control other users' access. Non-mandatory access control is not a defined access control technique. Source: ANDRESS, Mandy, Exam Cram CISSP, Coriolis, 2001, Chapter 2: Access Control Systems and Methodology (page 9).

**NEW QUESTION 10**

- (Topic 1)

In the Bell-LaPadula model, the Star-property is also called:

- A. The simple security property
- B. The confidentiality property
- C. The confinement property
- D. The tranquility property

**Answer: B**

**Explanation:**

The Bell-LaPadula model focuses on data confidentiality and access to classified information, in contrast to the Biba Integrity Model which describes rules for the protection of data integrity.

In this formal model, the entities in an information system are divided into subjects and objects.

The notion of a "secure state" is defined, and it is proven that each state transition preserves security by moving from secure state to secure state, thereby proving that the system satisfies the security objectives of the model.

The Bell-LaPadula model is built on the concept of a state machine with a set of allowable states in a system. The transition from one state to another state is defined by transition functions.

A system state is defined to be "secure" if the only permitted access modes of subjects to objects are in accordance with a security policy.

To determine whether a specific access mode is allowed, the clearance of a subject is compared to the classification of the object (more precisely, to the combination of classification and set of compartments, making up the security level) to determine if the subject is authorized for the specific access mode.

The clearance/classification scheme is expressed in terms of a lattice. The model defines two mandatory access control (MAC) rules and one discretionary access control (DAC) rule with three security properties:

The Simple Security Property - a subject at a given security level may not read an object at a higher security level (no read-up).

The property (read "star"-property) - a subject at a given security level must not write to any object at a lower security level (no write-down). The property is also known as the Confinement property.

The Discretionary Security Property - use an access control matrix to specify the discretionary access control.

The transfer of information from a high-sensitivity document to a lower-sensitivity document may happen in the Bell-LaPadula model via the concept of trusted subjects. Trusted Subjects are not restricted by the property. Untrusted subjects are.

Trusted Subjects must be shown to be trustworthy with regard to the security policy. This security model is directed toward access control and is characterized by the phrase: "no read up, no write down." Compare the Biba model, the Clark-Wilson model and the Chinese Wall.

With Bell-LaPadula, users can create content only at or above their own security level (i.e. secret researchers can create secret or top-secret files but may not create public files; no write-down). Conversely, users can view content only at or below their own security level

(i.e. secret researchers can view public or secret files, but may not view top-secret files; no read-up).

Strong Property

The Strong Property is an alternative to the Property in which subjects may write to objects with only a matching security level. Thus, the write-up operation permitted in the usual Property is not present, only a write-to-same level operation. The Strong Property is usually discussed in the context of multilevel database management systems and is motivated by integrity concerns.

Tranquility principle

The tranquility principle of the Bell-LaPadula model states that the classification of a subject or object does not change while it is being referenced. There are two forms to the tranquility principle: the "principle of strong tranquility" states that security levels do not change during the normal operation of the system and the "principle of weak tranquility" states that security levels do not change in a way that violates the rules of a given security policy.

Another interpretation of the tranquility principles is that they both apply only to the period of time during which an operation involving an object or subject is occurring. That is, the strong tranquility principle means that an object's security level/label will not change during an operation (such as read or write); the weak tranquility principle means that an object's security level/label may change in a way that does not violate the security policy during an operation.

Reference(s) used for this question: [http://en.wikipedia.org/wiki/Biba\\_Model](http://en.wikipedia.org/wiki/Biba_Model)

[http://en.wikipedia.org/wiki/Mandatory\\_access\\_control](http://en.wikipedia.org/wiki/Mandatory_access_control) [http://en.wikipedia.org/wiki/Discretionary\\_access\\_control](http://en.wikipedia.org/wiki/Discretionary_access_control) [http://en.wikipedia.org/wiki/Clark-Wilson\\_model](http://en.wikipedia.org/wiki/Clark-Wilson_model)

[http://en.wikipedia.org/wiki/Brewer\\_and\\_Nash\\_model](http://en.wikipedia.org/wiki/Brewer_and_Nash_model)

### NEW QUESTION 13

- (Topic 1)

In discretionary access environments, which of the following entities is authorized to grant information access to other people?

- A. Manager
- B. Group Leader
- C. Security Manager
- D. Data Owner

**Answer: D**

#### Explanation:

In Discretionary Access Control (DAC) environments, the user who creates a file is also considered the owner and has full control over the file including the ability to set permissions for that file.

The following answers are incorrect:

manager. Is incorrect because in Discretionary Access Control (DAC) environments it is the owner/user that is authorized to grant information access to other people.

group leader. Is incorrect because in Discretionary Access Control (DAC) environments it is the owner/user that is authorized to grant information access to other people.

security manager. Is incorrect because in Discretionary Access Control (DAC) environments it is the owner/user that is authorized to grant information access to other people.

IMPORTANT NOTE:

The term Data Owner is also used within Classifications as well. Under the subject of classification the Data Owner is a person from management who has been entrusted with a data set that belongs to the company. For example it could be the Chief Financial Officer (CFO) who is entrusted with all of the financial data for a company. As such the CFO would determine the classification of the financial data and who can access as well. The Data Owner would then tell the Data Custodian (a technical person) what the classification and need to know is on the specific set of data.

The term Data Owner under DAC simply means whoever created the file and as the creator of the file the owner has full access and can grant access to other subjects based on their identity.

### NEW QUESTION 15

- (Topic 1)

Controls to keep password sniffing attacks from compromising computer systems include which of the following?

- A. static and recurring passwords.
- B. encryption and recurring passwords.
- C. one-time passwords and encryption.
- D. static and one-time passwords.

**Answer: C**

#### Explanation:

To minimize the chance of passwords being captured one-time passwords would prevent a password sniffing attack because once used it is no longer valid.

Encryption will also minimize these types of attacks.

The following answers are correct:

static and recurring passwords. This is incorrect because if there is no encryption then someone password sniffing would be able to capture the password much easier if it never changed.

encryption and recurring passwords. This is incorrect because while encryption helps, recurring passwords do nothing to minimize the risk of passwords being captured.

static and one-time passwords. This is incorrect because while one-time passwords will prevent these types of attacks, static passwords do nothing to minimize the risk of passwords being captured.

### NEW QUESTION 20

- (Topic 1)

Which of the following is NOT a type of motion detector?

- A. Photoelectric sensor
- B. Passive infrared sensors
- C. Microwave Sensor.
- D. Ultrasonic Sensor.

**Answer: A**

#### Explanation:



A photoelectric sensor does not "directly" sense motion there is a narrow beam that won't set off the sensor unless the beam is broken. Photoelectric sensors, along with dry contact switches, are a type of perimeter intrusion detector.

All of the other answers are valid types of motion detectors types.

The content below on the different types of sensors is from Wikipedia: Indoor Sensors

These types of sensors are designed for indoor use. Outdoor use would not be advised due to false alarm vulnerability and weather durability. Passive infrared detectors



C:\Users\MCS\Desktop\1.jpg Passive Infrared Sensor

The passive infrared detector (PIR) is one of the most common detectors found in household and small business environments because it offers affordable and reliable functionality. The term passive means the detector is able to function without the need to generate and radiate its own energy (unlike ultrasonic and microwave volumetric intrusion detectors that are ??active?? in operation). PIRs are able to distinguish if an infrared emitting object is present by first learning the ambient temperature of the monitored space and then detecting a change in the temperature caused by the presence of an object. Using the principle of differentiation, which is a check of presence or nonpresence, PIRs verify if an intruder or object is actually there. Creating individual zones of detection where each zone comprises one or more layers can achieve differentiation. Between the zones there are areas of no sensitivity (dead zones) that are used by the sensor for comparison.

Ultrasonic detectors

Using frequencies between 15 kHz and 75 kHz, these active detectors transmit ultrasonic sound waves that are inaudible to humans. The Doppler shift principle is the underlying method of operation, in which a change in frequency is detected due to object motion. This is caused when a moving object changes the frequency of sound waves around it. Two conditions must occur to successfully detect a Doppler shift event:

There must be motion of an object either towards or away from the receiver.

The motion of the object must cause a change in the ultrasonic frequency to the receiver relative to the transmitting frequency.

The ultrasonic detector operates by the transmitter emitting an ultrasonic signal into the area to be protected. The sound waves are reflected by solid objects (such as the surrounding floor, walls and ceiling) and then detected by the receiver. Because ultrasonic waves are transmitted through air, then hard-surfaced objects tend to reflect most of the ultrasonic energy, while soft surfaces tend to absorb most energy.

When the surfaces are stationary, the frequency of the waves detected by the receiver will be equal to the transmitted frequency. However, a change in frequency will occur as a result of the Doppler principle, when a person or object is moving towards or away from the detector. Such an event initiates an alarm signal. This technology is considered obsolete by many alarm professionals, and is not actively installed.

Microwave detectors

This device emits microwaves from a transmitter and detects any reflected microwaves or reduction in beam intensity using a receiver. The transmitter and receiver are usually combined inside a single housing (monostatic) for indoor applications, and separate housings (bistatic) for outdoor applications. To reduce false alarms this type of detector is usually combined with a passive infrared detector or "Dualtec" alarm.

Microwave detectors respond to a Doppler shift in the frequency of the reflected energy, by a phase shift, or by a sudden reduction of the level of received energy. Any of these effects may indicate motion of an intruder.

Photo-electric beams

Photoelectric beam systems detect the presence of an intruder by transmitting visible or infrared light beams across an area, where these beams may be obstructed. To improve the detection surface area, the beams are often employed in stacks of two or more. However, if an intruder is aware of the technology's presence, it can be avoided. The technology can be an effective long-range detection system, if installed in stacks of three or more where the transmitters and receivers are staggered to create a fence-like barrier. Systems are available for both internal and external applications. To prevent a clandestine attack using a secondary light source being used to hold the detector in a 'sealed' condition whilst an intruder passes through, most systems use and detect a modulated light source.

Glass break detectors

The glass break detector may be used for internal perimeter building protection. When glass breaks it generates sound in a wide band of frequencies. These can range from infrasonic, which is below 20 hertz (Hz) and can not be heard by the human ear, through the audio band from 20 Hz to 20 kHz which humans can hear, right up to ultrasonic, which is above 20 kHz and again cannot be heard. Glass break acoustic detectors are mounted in close proximity to the glass panes and listen for sound frequencies associated with glass breaking. Seismic glass break detectors are different in that they are installed on the glass pane. When glass breaks it produces specific shock frequencies which travel through the glass and often through the window frame and the surrounding walls and ceiling. Typically, the most intense frequencies generated are between 3 and 5 kHz, depending on the type of glass and the presence of a plastic interlayer. Seismic glass break detectors ??feel?? these shock frequencies and in turn generate an alarm condition.

The more primitive detection method involves gluing a thin strip of conducting foil on the inside of the glass and putting low-power electrical current through it.

Breaking the glass is practically guaranteed to tear the foil and break the circuit.

Smoke, heat, and carbon monoxide detectors



C:\Users\MCS\Desktop\1.jpg Heat Detection System

Most systems may also be equipped with smoke, heat, and/or carbon monoxide detectors. These are also known as 24 hour zones (which are on at all times). Smoke detectors and heat detectors protect from the risk of fire and carbon monoxide detectors protect from the risk of carbon monoxide. Although an intruder alarm panel may also have these detectors connected, it may not meet all the local fire code requirements of a fire alarm system.

Other types of volumetric sensors could be:  
Active Infrared  
Passive Infrared/Microwave combined Radar  
Accoustical Sensor/Audio Vibration Sensor (seismic) Air Turbulence

#### NEW QUESTION 23

- (Topic 1)

Which one of the following authentication mechanisms creates a problem for mobile users?

- A. Mechanisms based on IP addresses
- B. Mechanism with reusable passwords
- C. one-time password mechanism.
- D. challenge response mechanism.

**Answer:** A

#### Explanation:

Anything based on a fixed IP address would be a problem for mobile users because their location and its associated IP address can change from one time to the next. Many providers will assign a new IP every time the device would be restarted. For example an insurance adjuster using a laptop to file claims online. He goes to a different client each time and the address changes every time he connects to the ISP.

NOTE FROM CLEMENT:

The term MOBILE in this case is synonymous with Road Warriors where a user is constantly traveling and changing location. With smartphone today that may not be an issue but it would be an issue for laptops or WIFI tablets. Within a carrier network the IP will tend to be the same and would change rarely. So this question is more applicable to devices that are not cellular devices but in some cases this issue could affect cellular devices as well.

The following answers are incorrect:

mechanism with reusable password. This is incorrect because reusable password mechanism would not present a problem for mobile users. They are the least secure and change only at specific interval.

one-time password mechanism. This is incorrect because a one-time password mechanism would not present a problem for mobile users. Many are based on a clock and not on the IP address of the user.

challenge response mechanism. This is incorrect because challenge response mechanism would not present a problem for mobile users.

#### NEW QUESTION 26

- (Topic 1)

Which of the following access control models is based on sensitivity labels?

- A. Discretionary access control
- B. Mandatory access control
- C. Rule-based access control
- D. Role-based access control

**Answer:** B

#### Explanation:

Access decisions are made based on the clearance of the subject and the sensitivity label of the object.

Example: Eve has a "Secret" security clearance and is able to access the "Mugwump Missile Design Profile" because its sensitivity label is "Secret." She is denied access to the "Presidential Toilet Tissue Formula" because its sensitivity label is "Top Secret."

The other answers are not correct because:

Discretionary Access Control is incorrect because in DAC access to data is determined by the data owner. For example, Joe owns the "Secret Chili Recipe" and grants read access to Charles.

Role Based Access Control is incorrect because in RBAC access decisions are made based on the role held by the user. For example, Jane has the role "Auditor" and that role includes read permission on the "System Audit Log."

Rule Based Access Control is incorrect because it is a form of MAC. A good example would be a Firewall where rules are defined and apply to anyone connecting through the firewall.

References:

All in One third edition, page 164. Official ISC2 Guide page 187.

#### NEW QUESTION 29

- (Topic 1)

Which of the following biometric devices has the lowest user acceptance level?

- A. Retina Scan
- B. Fingerprint scan
- C. Hand geometry
- D. Signature recognition

**Answer:** A

#### Explanation:

According to the cited reference, of the given options, the Retina scan has the lowest user acceptance level as it is needed for the user to get his eye close to a device and it is not user friendly and very intrusive.

However, retina scan is the most precise with about one error per 10 millions usage. Look at the 2 tables below. If necessary right click on the image and save it on your

desktop for a larger view or visit the web site directly at

<https://sites.google.com/site/biometricsecuritysolutions/crossover-accuracy> . Biometric Comparison Chart

**BIOMETRICS COMPARISON CHART**

Biometric	Verify	ID	Accuracy	Reliability	Error Rate	Errors	False Pos.	False Neg.
Signature	Yes	Yes	Very High	High	1 in 1000+	Worness, ink, age	Ext. Diff.	Ext. Diff.
Facial Recognition	Yes	No	High	Medium	No data	Lighting, age, glasses, hair	Difficult	Easy
Hand Geometry	Yes	No	High	Medium	1 in 100	Hand injury, age	Very Diff.	Medium
Vein Recognition	Yes	No	Medium	Low	1 in 10	Wound, weather, cosmetics	Medium	Easy
iris to go	Yes	Yes	Very High	High	1 in 1,000,000	Good lighting	Very Diff.	Very Diff.
Retinal Scan	Yes	Yes	Very High	High	1 in 10,000,000	Glasses	Ext. Diff.	Ext. Diff.
Signature Recognition	Yes	No	Medium	Low	1 in 10	Changing signatures	Medium	Easy
Acoustic Recognition	Yes	No	Low	Low	No data	Hand injury, weakness	Difficult	Easy
Chin	Yes	Yes	Very High	High	No data	None	Ext. Diff.	Ext. Diff.

Biometric	Security Level	Long-term Stability	User Acceptance	Intrusiveness	Ease of Use	Low Cost	Hardware	Standards
Signature	High	High	Medium	Noninvasive	High	Yes	Special, cheap	Yes
Facial Recognition	Medium	Medium	Medium	Non	Medium	Yes	Common, cheap	1
Hand Geometry	Medium	Medium	Medium	Non	High	No	Special, mid-price	1
Vein Recognition	Medium	Medium	High	Non	High	Yes	Common, cheap	1
iris to go	High	High	Medium	Non	Medium	No	Special, expensive	1
Retinal Scan	High	High	Medium	Very	Low	No	Special, expensive	1
Signature Recognition	Medium	Medium	Medium	Non	High	Yes	Special, mid-price	1
Acoustic Recognition	Medium	Low	High	Non	High	Yes	Common, cheap	1
Chin	High	High	Low	Extremely	Low	No	Special, expensive	Yes

C:\Users\MCS\Desktop\1.jpg

Aspect descriptions:

<b>Verify</b>	Whether or not the Biometric is capable of verification. Verification is the process where an input is compared to specific data previously recorded from the user to see if the person is who they claim to be.
<b>ID</b>	Whether or not the Biometric is capable of identification. Identification is the process where an input is compared to a large data set previously recorded from many people to see which person the user is.
<b>Accuracy</b>	How well the Biometric is able to tell individuals apart. This is partially determined by the amount of information gathered as well as the number of possible different data results.
<b>Reliability</b>	How dependable the Biometric is for recognition purposes.
<b>Error Rate</b>	This is calculated as the crossing point when graphed of false positives and false negatives created using this Biometric.
<b>Errors</b>	Typical causes of errors for this Biometric.
<b>False Pos.</b>	How easy it is to create a false positive reading with this biometric (someone is able to impersonate someone else).
<b>False Neg.</b>	How easy it is to create a false negative reading with this biometric (someone is able to avoid identification as oneself).
<b>Security Level</b>	The highest level of security that this Biometric is capable of working at.
<b>Long-term Stability</b>	How well this Biometric continues to work without data updates over long periods of time.
<b>User Acceptance</b>	How willing the public is to use this Biometric.
<b>Intrusiveness</b>	How much the Biometric is considered to invade one's privacy or require interaction by the user.
<b>Ease of Use</b>	How easy this Biometric is for both the user and the personnel involved.
<b>Low Cost</b>	Whether or not there is a low-cost option for this Biometric to be used.
<b>Hardware</b>	Type and cost of hardware required to use this Biometric.
<b>Standards</b>	Whether or not standards exist for this Biometric.

C:\Users\MCS\Desktop\1.jpg

Biometric Aspect Descriptions Reference(s) used for this question:

RHODES, Keith A., Chief Technologist, United States General Accounting Office, National Preparedness, Technologies to Secure Federal Buildings, April 2002 (page 10).

and

<https://sites.google.com/site/biometricsecuritysolutions/crossover-accuracy>

### NEW QUESTION 33

- (Topic 1)

Which access control model provides upper and lower bounds of access capabilities for a subject?

- A. Role-based access control
- B. Lattice-based access control
- C. Biba access control
- D. Content-dependent access control

**Answer: B**

#### Explanation:

In the lattice model, users are assigned security clearances and the data is classified. Access decisions are made based on the clearance of the user and the classification of the object. Lattice-based access control is an essential ingredient of formal security models such as Bell-LaPadula, Biba, Chinese Wall, etc. The bounds concept comes from the formal definition of a lattice as a "partially ordered set for which every pair of elements has a greatest lower bound and a least upper bound." To see the application, consider a file classified as "SECRET" and a user Joe with a security clearance of "TOP SECRET." Under Bell-LaPadula, Joe's "least upper bound" access to the file is "READ" and his least lower bound is "NO WRITE" (star property).

Role-based access control is incorrect. Under RBAC, the access is controlled by the permissions assigned to a role and the specific role assigned to the user.

Biba access control is incorrect. The Biba integrity model is based on a lattice structure but the context of the question disqualifies it as the best answer.

Content-dependent access control is incorrect. In content dependent access control, the actual content of the information determines access as enforced by the arbiter.

References:

CBK, pp. 324-325.

AIO3, pp. 291-293. See particularly Figure 5-19 on p. 293 for an illustration of bounds in action.

### NEW QUESTION 36

- (Topic 1)

Which of the following statements pertaining to biometrics is FALSE?

- A. User can be authenticated based on behavior.
- B. User can be authenticated based on unique physical attributes.
- C. User can be authenticated by what he knows.
- D. A biometric system's accuracy is determined by its crossover error rate (CER).

**Answer: C**

#### Explanation:

As this is not a characteristic of Biometrics this is the right choice for this question. This is one of the three basic ways authentication can be performed and it is not related to Biometrics. Example of something you know would be a password or PIN for example.

Please make a note of the negative 'FALSE' within the question. This question may seem tricky to some of you but you would be amazed at how many people cannot deal with negative questions. There will be a few negative questions within the real exam, just like this one the keyword NOT or FALSE will be in Uppercase to clearly indicate that it is negative.

Biometrics verifies an individual's identity by analyzing a unique personal attribute or behavior, which is one of the most effective and accurate methods of performing authentication (one to one matching) or identification (a one to many matching).

A biometric system scans an attribute or behavior of a person and compares it to a template store within an authentication server database, such template would be created in an earlier enrollment process. Because this system inspects the grooves of a person's fingerprint, the pattern of someone's retina, or the pitches of



someone's voice, it has to be extremely sensitive.

The system must perform accurate and repeatable measurements of anatomical or physiological characteristics. This type of sensitivity can easily cause false positives or false negatives. The system must be calibrated so that these false positives and false negatives occur infrequently and the results are as accurate as possible.

There are two types of failures in biometric identification:

False Rejection also called False Rejection Rate (FRR) ?? The system fail to recognize a legitimate user. While it could be argued that this has the effect of keeping the protected area extra secure, it is an intolerable frustration to legitimate users who are refused access because the scanner does not recognize them.

False Acceptance or False Acceptance Rate (FAR) ?? This is an erroneous recognition, either by confusing one user with another or by accepting an imposter as a legitimate user.

Physiological Examples:

Unique Physical Attributes:

Fingerprint (Most commonly accepted) Hand Geometry

Retina Scan (Most accurate but most intrusive) Iris Scan

Vascular Scan Behavioral Examples:

Repeated Actions Keystroke Dynamics

(Dwell time (the time a key is pressed) and Flight time (the time between "key up" and the next "key down").

Signature Dynamics

(Stroke and pressure points)

EXAM TIP:

Retina scan devices are the most accurate but also the most invasive biometrics system available today. The continuity of the retinal pattern throughout life and the difficulty in fooling such a device also make it a great long-term, high-security option. Unfortunately, the cost of the proprietary hardware as well the stigma of users thinking it is potentially harmful to the eye makes retinal scanning a bad fit for most situations.

Remember for the exam that fingerprints are the most commonly accepted type of biometrics system.

The other answers are incorrect:

'Users can be authenticated based on behavior.' is incorrect as this choice is TRUE as it pertains to BIOMETRICS.

Biometrics systems makes use of unique physical characteristics or behavior of users.

'User can be authenticated based on unique physical attributes.' is also incorrect as this choice is also TRUE as it pertains to BIOMETRICS. Biometrics systems makes use of unique physical characteristics or behavior of users.

'A biometric system's accuracy is determined by its crossover error rate (CER)' is also incorrect as this is TRUE as it also pertains to BIOMETRICS. The CER is the point at which the false rejection rates and the false acceptance rates are equal. The smaller the value of the CER, the more accurate the system.

Reference(s) used for this question:

Hernandez CISSP, Steven (2012-12-21). Official (ISC)2 Guide to the CISSP CBK, Third Edition ((ISC)2 Press) (Kindle Locations 25353-25356). Auerbach Publications. Kindle Edition.

and

Hernandez CISSP, Steven (2012-12-21). Official (ISC)2 Guide to the CISSP CBK, Third Edition ((ISC)2 Press) (Kindle Locations 25297-25303). Auerbach Publications. Kindle Edition.

#### NEW QUESTION 41

- (Topic 1)

What is the PRIMARY use of a password?

- A. Allow access to files.
- B. Identify the user.
- C. Authenticate the user.
- D. Segregate various user's accesses.

**Answer: C**

#### Explanation:

Source: TIPTON, Hal, (ISC)2, Introduction to the CISSP Exam presentation.

#### NEW QUESTION 45

- (Topic 1)

Which of the following is used by RADIUS for communication between clients and servers?

- A. TCP
- B. SSL
- C. UDP
- D. SSH

**Answer: C**

#### Explanation:

Source: TIPTON, Harold F. & KRAUSE, MICKI, Information Security Management Handbook, 4th Edition, Volume 2, 2001, CRC Press, NY, Page 33.

#### NEW QUESTION 46

- (Topic 1)

The control measures that are intended to reveal the violations of security policy using software and hardware are associated with:

- A. Preventive/physical
- B. Detective/technical
- C. Detective/physical
- D. Detective/administrative

**Answer: B**

#### Explanation:

The detective/technical control measures are intended to reveal the violations of security policy using technical means.

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the

Ten Domains of Computer Security, 2001, John Wiley & Sons, Page 35.

#### NEW QUESTION 47

- (Topic 1)

Which of the following describes the major disadvantage of many Single Sign-On (SSO) implementations?

- A. Once an individual obtains access to the system through the initial log-on, they have access to all resources within the environment that the account has access to.
- B. The initial logon process is cumbersome to discourage potential intruders.
- C. Once a user obtains access to the system through the initial log-on, they only need to logon to some applications.
- D. Once a user obtains access to the system through the initial log-on, he has to logout from all other systems

**Answer:** A

#### Explanation:

Single Sign-On is a distributed Access Control methodology where an individual only has to authenticate once and would have access to all primary and secondary network domains. The individual would not be required to re-authenticate when they needed additional resources. The security issue that this creates is if a fraudster is able to compromise those credentials they too would have access to all the resources that account has access to. All the other answers are incorrect as they are distractors.

#### NEW QUESTION 52

- (Topic 1)

Which of the following would assist the most in Host Based intrusion detection?

- A. audit trails.
- B. access control lists.
- C. security clearances.
- D. host-based authentication.

**Answer:** A

#### Explanation:

To assist in Intrusion Detection you would review audit logs for access violations.

The following answers are incorrect:

access control lists. This is incorrect because access control lists determine who has access to what but do not detect intrusions.

security clearances. This is incorrect because security clearances determine who has access to what but do not detect intrusions.

host-based authentication. This is incorrect because host-based authentication determines who has been authenticated to the system but does not detect intrusions.

#### NEW QUESTION 53

- (Topic 1)

Which access control model enables the OWNER of the resource to specify what subjects can access specific resources based on their identity?

- A. Discretionary Access Control
- B. Mandatory Access Control
- C. Sensitive Access Control
- D. Role-based Access Control

**Answer:** A

#### Explanation:

Data owners decide who has access to resources based only on the identity of the person accessing the resource.

The following answers are incorrect :

Mandatory Access Control : users and data owners do not have as much freedom to determine who can access files. The operating system makes the final decision and can override the users' wishes and access decisions are based on security labels.

Sensitive Access Control : There is no such access control in the context of the above question.

Role-based Access Control : uses a centrally administered set of controls to determine how subjects and objects interact , also called as non discretionary access control.

In a mandatory access control (MAC) model, users and data owners do not have as much freedom to determine who can access files. The operating system makes the final decision and can override the users' wishes. This model is much more structured and strict and is based on a security label system. Users are given a security clearance (secret, top secret, confidential, and so on), and data is classified in the same way. The clearance and classification data is stored in the security labels, which are bound to the specific subjects and objects. When the system makes a decision about fulfilling a request to access an object, it is based on the clearance of the subject, the classification of the object, and the security policy of the system. The rules for how subjects access objects are made by the security officer, configured by the administrator, enforced by the operating system, and supported by security technologies

Reference : Shon Harris , AIO v3 , Chapter-4 : Access Control , Page : 163-165

#### NEW QUESTION 54

- (Topic 1)

Which security model is based on the military classification of data and people with clearances?

- A. Brewer-Nash model
- B. Clark-Wilson model
- C. Bell-LaPadula model
- D. Biba model

**Answer:** C

#### Explanation:

The Bell-LaPadula model is a confidentiality model for information security based on the military classification of data, on people with clearances and data with a

classification or sensitivity model. The Biba, Clark-Wilson and Brewer-Nash models are concerned with integrity.  
Source: HARE, Chris, Security Architecture and Models, Area 6 CISSP Open Study Guide, January 2002.

#### NEW QUESTION 59

- (Topic 1)

Pin, Password, Passphrases, Tokens, smart cards, and biometric devices are all items that can be used for Authentication. When one of these item listed above in conjunction with a second factor to validate authentication, it provides robust authentication of the individual by practicing which of the following?

- A. Multi-party authentication
- B. Two-factor authentication
- C. Mandatory authentication
- D. Discretionary authentication

**Answer:** B

#### Explanation:

Once an identity is established it must be authenticated. There exist numerous technologies and implementation of authentication methods however they almost all fall under three major areas.

There are three fundamental types of authentication: Authentication by knowledge??something a person knows

Authentication by possession??something a person has

Authentication by characteristic??something a person is Logical controls related to these types are called ??factors.??

Something you know can be a password or PIN, something you have can be a token fob or smart card, and something you are is usually some form of biometrics.

Single-factor authentication is the employment of one of these factors, two-factor authentication is using two of the three factors, and three-factor authentication is the combination of all three factors.

The general term for the use of more than one factor during authentication is multifactor authentication or strong authentication.

Reference(s) used for this question:

Hernandez CISSP, Steven (2012-12-21). Official (ISC)2 Guide to the CISSP CBK, Third Edition ((ISC)2 Press) (Kindle Locations 2367-2379). Auerbach Publications. Kindle Edition.

#### NEW QUESTION 64

- (Topic 1)

The end result of implementing the principle of least privilege means which of the following?

- A. Users would get access to only the info for which they have a need to know
- B. Users can access all systems.
- C. Users get new privileges added when they change positions.
- D. Authorization creep.

**Answer:** A

#### Explanation:

The principle of least privilege refers to allowing users to have only the access they need and not anything more. Thus, certain users may have no need to access any of the files on specific systems.

The following answers are incorrect:

Users can access all systems. Although the principle of least privilege limits what access and systems users have authorization to, not all users would have a need to know to access all of the systems. The best answer is still Users would get access to only the info for which they have a need to know as some of the users may not have a need to access a system.

Users get new privileges when they change positions. Although true that a user may indeed require new privileges, this is not a given fact and in actuality a user may require less privileges for a new position. The principle of least privilege would require that the rights required for the position be closely evaluated and where possible rights revoked.

Authorization creep. Authorization creep occurs when users are given additional rights with new positions and responsibilities. The principle of least privilege should actually prevent authorization creep.

The following reference(s) were/was used to create this question: ISC2 OIG 2007 p.101,123

Shon Harris AIO v3 p148, 902-903

#### NEW QUESTION 67

- (Topic 1)

Which of the following control pairings include: organizational policies and procedures, pre- employment background checks, strict hiring practices, employment agreements, employee termination procedures, vacation scheduling, labeling of sensitive materials, increased supervision, security awareness training, behavior awareness, and sign-up procedures to obtain access to information systems and networks?

- A. Preventive/Administrative Pairing
- B. Preventive/Technical Pairing
- C. Preventive/Physical Pairing
- D. Detective/Administrative Pairing

**Answer:** A

#### Explanation:

The Answer: Preventive/Administrative Pairing: These mechanisms include organizational policies and procedures, pre-employment background checks, strict hiring practices, employment agreements, friendly and unfriendly employee termination procedures, vacation scheduling, labeling of sensitive materials, increased supervision, security awareness training, behavior awareness, and sign-up procedures to obtain access to information systems and networks.

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, 2001, John Wiley & Sons, Page 34.

#### NEW QUESTION 72

- (Topic 1)

Which of the following statements relating to the Bell-LaPadula security model is FALSE (assuming the Strong Star property is not being used) ?

- A. A subject is not allowed to read up.

- B. The property restriction can be escaped by temporarily downgrading a high level subject.
- C. A subject is not allowed to read down.
- D. It is restricted to confidentiality.

**Answer:** C

**Explanation:**

It is not a property of Bell LaPadula model. The other answers are incorrect because:

A subject is not allowed to read up is a property of the 'simple security rule' of Bell LaPadula model.

The property restriction can be escaped by temporarily downgrading a high level subject can be escaped by temporarily downgrading a high level subject or by identifying a set of trusted objects which are permitted to violate the property as long as it is not in the middle of an operation.

It is restricted to confidentiality as it is a state machine model that enforces the confidentiality aspects of access control.

Reference: Shon Harris AIO v3 , Chapter-5 : Security Models and Architecture , Page:279-

282

**NEW QUESTION 74**

- (Topic 1)

A department manager has read access to the salaries of the employees in his/her department but not to the salaries of employees in other departments. A database security mechanism that enforces this policy would typically be said to provide which of the following?

- A. Content-dependent access control
- B. Context-dependent access control
- C. Least privileges access control
- D. Ownership-based access control

**Answer:** A

**Explanation:**

When access control is based on the content of an object, it is considered to be content dependent access control.

Content-dependent access control is based on the content itself. The following answers are incorrect:

context-dependent access control. Is incorrect because this type of control is based on what the context is, facts about the data rather than what the object contains.

least privileges access control. Is incorrect because this is based on the least amount of rights needed to perform their jobs and not based on what is contained in the database. ownership-based access control. Is incorrect because this is based on the owner of the data and and not based on what is contained in the database.

References:

OIG CBK Access Control (page 191)

**NEW QUESTION 77**

- (Topic 1)

The Orange Book is founded upon which security policy model?

- A. The Biba Model
- B. The Bell LaPadula Model
- C. Clark-Wilson Model
- D. TEMPEST

**Answer:** B

**Explanation:**

From the glossary of Computer Security Basics:

The Bell-LaPadula model is the security policy model on which the Orange Book requirements are based. From the Orange Book definition, "A formal state transition model of computer security policy that describes a set of access control rules. In this formal model, the entities in a computer system are divided into abstract sets of subjects and objects. The notion of secure state is defined and it is proven that each state transition preserves security by moving from secure state to secure state; thus, inductively proving the system is secure. A system state is defined to be 'secure' if the only permitted access modes of subjects to objects are in accordance with a specific security policy. In order to determine whether or not a specific access mode is allowed, the clearance of a subject is compared to the classification of the object and a determination is made as to whether the subject is authorized for the specific access mode."

The Biba Model is an integrity model of computer security policy that describes a set of rules. In this model, a subject may not depend on any object or other subject that is less trusted than itself.

The Clark Wilson Model is an integrity model for computer security policy designed for a commercial environment. It addresses such concepts as nondiscretionary access control, privilege separation, and least privilege. TEMPEST is a government program that prevents the compromising electrical and electromagnetic signals that emanate from computers and related equipment from being intercepted and deciphered.

Source: RUSSEL, Deborah & GANGEMI, G.T. Sr., Computer Security Basics, O'Reilly, 1991.

Also: U.S. Department of Defense, Trusted Computer System Evaluation Criteria (Orange Book), DOD 5200.28-STD. December 1985 (also available here).

**NEW QUESTION 79**

- (Topic 1)

How would nonrepudiation be best classified as?

- A. A preventive control
- B. A logical control
- C. A corrective control
- D. A compensating control

**Answer:** A

**Explanation:**

Systems accountability depends on the ability to ensure that senders cannot deny sending information and that receivers cannot deny receiving it. Because the mechanisms implemented in nonrepudiation prevent the ability to successfully repudiate an action, it can be considered as a preventive control.

Source: STONEBURNER, Gary, NIST Special Publication 800-33: Underlying Technical Models for Information Technology Security, National Institute of



Standards and Technology, December 2001, page 7.

**NEW QUESTION 84**

- (Topic 1)

In addition to the accuracy of the biometric systems, there are other factors that must also be considered:

- A. These factors include the enrollment time and the throughput rate, but not acceptability.
- B. These factors do not include the enrollment time, the throughput rate, and acceptability.
- C. These factors include the enrollment time, the throughput rate, and acceptability.
- D. These factors include the enrollment time, but not the throughput rate, neither the acceptability.

**Answer:** C

**Explanation:**

In addition to the accuracy of the biometric systems, there are other factors that must also be considered.

These factors include the enrollment time, the throughput rate, and acceptability. Enrollment time is the time it takes to initially "register" with a system by providing samples

of the biometric characteristic to be evaluated. An acceptable enrollment time is around two minutes.

For example, in fingerprint systems, the actual fingerprint is stored and requires approximately 250kb per finger for a high quality image. This level of information is required for one-to-many searches in forensics applications on very large databases.

In finger-scan technology, a full fingerprint is not stored-the features extracted from this fingerprint are stored using a small template that requires approximately 500 to 1000 bytes of storage. The original fingerprint cannot be reconstructed from this template.

Updates of the enrollment information may be required because some biometric characteristics, such as voice and signature, may change with time.

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, 2001, John Wiley & Sons, Page 37 & 38.

**NEW QUESTION 88**

- (Topic 1)

Who first described the DoD multilevel military security policy in abstract, formal terms?

- A. David Bell and Leonard LaPadula
- B. Rivest, Shamir and Adleman
- C. Whitfield Diffie and Martin Hellman
- D. David Clark and David Wilson

**Answer:** A

**Explanation:**

It was David Bell and Leonard LaPadula who, in 1973, first described the DoD multilevel military security policy in abstract, formal terms. The Bell-LaPadula is a Mandatory Access Control (MAC) model concerned with confidentiality. Rivest, Shamir and Adleman (RSA) developed the RSA encryption algorithm. Whitfield Diffie and Martin Hellman published the Diffie-Hellman key agreement algorithm in 1976. David Clark and David Wilson developed the Clark-Wilson integrity model, more appropriate for security in commercial activities.

Source: RUSSEL, Deborah & GANGEMI, G.T. Sr., Computer Security Basics, O'Reilly, July 1992 (pages 78,109).

**NEW QUESTION 90**

- (Topic 1)

Which of the following is true about Kerberos?

- A. It utilizes public key cryptography.
- B. It encrypts data after a ticket is granted, but passwords are exchanged in plain text.
- C. It depends upon symmetric ciphers.
- D. It is a second party authentication system.

**Answer:** C

**Explanation:**

Kerberos depends on secret keys (symmetric ciphers). Kerberos is a third party authentication protocol. It was designed and developed in the mid 1980's by MIT. It is considered open source but is copyrighted and owned by MIT. It relies on the user's secret keys. The password is used to encrypt and decrypt the keys.

The following answers are incorrect:

It utilizes public key cryptography. Is incorrect because Kerberos depends on secret keys (symmetric ciphers).

It encrypts data after a ticket is granted, but passwords are exchanged in plain text. Is incorrect because the passwords are not exchanged but used for encryption and decryption of the keys.

It is a second party authentication system. Is incorrect because Kerberos is a third party authentication system, you authenticate to the third party (Kerberos) and not the system you are accessing.

References:

MIT <http://web.mit.edu/kerberos/>

Wikipedi [http://en.wikipedia.org/wiki/Kerberos\\_%28protocol%29](http://en.wikipedia.org/wiki/Kerberos_%28protocol%29)

OIG CBK Access Control (pages 181 - 184) AIOv3 Access Control (pages 151 - 155)

**NEW QUESTION 95**

- (Topic 1)

Which type of control is concerned with avoiding occurrences of risks?

- A. Deterrent controls
- B. Detective controls
- C. Preventive controls
- D. Compensating controls

**Answer:** C

**Explanation:**

Preventive controls are concerned with avoiding occurrences of risks while deterrent controls are concerned with discouraging violations. Detecting controls identify occurrences and compensating controls are alternative controls, used to compensate weaknesses in other controls. Supervision is an example of compensating control. Source: TIPTON, Hal, (ISC)2, Introduction to the CISSP Exam presentation.

**NEW QUESTION 96**

- (Topic 1)

What is called the percentage at which the False Rejection Rate equals the False Acceptance Rate?

- A. False Rejection Rate (FRR) or Type I Error
- B. False Acceptance Rate (FAR) or Type II Error
- C. Crossover Error Rate (CER)
- D. Failure to enroll rate (FTE or FER)

**Answer:** C

**Explanation:**

The percentage at which the False Rejection Rate equals the False Acceptance Rate is called the Crossover Error Rate (CER). Another name for the CER is the Equal Error Rate (EER), any of the two terms could be used.

Equal error rate or crossover error rate (EER or CER)

It is the rate at which both accept and reject errors are equal. The EER is a quick way to compare the accuracy of devices with different ROC curves. In general, the device with the lowest EER is most accurate.

The other choices were all wrong answers:

The following are used as performance metrics for biometric systems:

false accept rate or false match rate (FAR or FMR): the probability that the system incorrectly matches the input pattern to a non-matching template in the database. It measures the percent of invalid inputs which are incorrectly accepted. This is when an impostor would be accepted by the system.

False reject rate or false non-match rate (FRR or FNMR): the probability that the system fails to detect a match between the input pattern and a matching template in the database. It measures the percent of valid inputs which are incorrectly rejected. This is when a valid company employee would be rejected by the system.

Failure to enroll rate (FTE or FER): the rate at which attempts to create a template from an input is unsuccessful. This is most commonly caused by low quality inputs.

Reference(s) used for this question:

KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, 2001, John Wiley & Sons, Page 38.

and <https://en.wikipedia.org/wiki/Biometrics>

**NEW QUESTION 101**

- (Topic 1)

Which of the following would be true about Static password tokens?

- A. The owner identity is authenticated by the token
- B. The owner will never be authenticated by the token.
- C. The owner will authenticate himself to the system.
- D. The token does not authenticates the token owner but the system.

**Answer:** A

**Explanation:**

Password Tokens

Tokens are electronic devices or cards that supply a user's password for them. A token system can be used to supply either a static or a dynamic password. There is a big difference between the static and dynamic systems, a static system will normally log a user in but a dynamic system the user will often have to log themselves in.

Static Password Tokens:

The owner identity is authenticated by the token. This is done by the person who issues the token to the owner (normally the employer). The owner of the token is now authenticated by "something you have". The token authenticates the identity of the owner to the information system. An example of this occurring is when an employee swipes his or her smart card over an electronic lock to gain access to a store room.

Synchronous Dynamic Password Tokens:

This system is a lot more complex then the static token password. The synchronous dynamic password tokens generate new passwords at certain time intervals that are synched with the main system. The password is generated on a small device similar to a pager or a calculator that can often be attached to the user's key ring. Each password is only valid for a certain time period, typing in the wrong password in the wrong time period will invalidate the authentication. The time factor can also be the systems downfall. If a clock on the system or the password token device becomes out of synch, a user can have troubles authenticating themselves to the system.

Asynchronous Dynamic Password Tokens:

The clock synching problem is eliminated with asynchronous dynamic password tokens. This system works on the same principal as the synchronous one but it does not have a time frame. A lot of big companies use this system especially for employee's who may work from home on the companies VPN (Virtual private Network).

Challenge Response Tokens:

This is an interesting system. A user will be sent special "challenge" strings at either random or timed intervals. The user inputs this challenge string into their token device and the device will respond by generating a challenge response. The user then types this response into the system and if it is correct they are authenticated.

Reference(s) used for this question: <http://www.informit.com/guides/content.aspx?g=security&seqNum=146>

and

KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, 2001, John Wiley & Sons, Page 37.

**NEW QUESTION 104**

- (Topic 1)

Why should batch files and scripts be stored in a protected area?

- A. Because of the least privilege concept.
- B. Because they cannot be accessed by operators.

- C. Because they may contain credentials.
- D. Because of the need-to-know concept.

**Answer:** C

**Explanation:**

Because scripts contain credentials, they must be stored in a protected area and the transmission of the scripts must be dealt with carefully. Operators might need access to batch files and scripts. The least privilege concept requires that each subject in a system be granted the most restrictive set of privileges needed for the performance of authorized tasks. The need-to-know principle requires a user having necessity for access to, knowledge of, or possession of specific information required to perform official tasks or services.

Source: WALLHOFF, John, CISSP Summary 2002, April 2002, CBK#1 Access Control System & Methodology (page 3)

**NEW QUESTION 107**

- (Topic 1)

What does the (star) integrity axiom mean in the Biba model?

- A. No read up
- B. No write down
- C. No read down
- D. No write up

**Answer:** D

**Explanation:**

The (star) integrity axiom of the Biba access control model states that an object at one level of integrity is not permitted to modify an object of a higher level of integrity (no write up).

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, John Wiley & Sons, 2001, Chapter 5: Security Architectures and Models (page 205).

**NEW QUESTION 110**

- (Topic 1)

What does the simple integrity axiom mean in the Biba model?

- A. No write down
- B. No read down
- C. No read up
- D. No write up

**Answer:** B

**Explanation:**

The simple integrity axiom of the Biba access control model states that a subject at one level of integrity is not permitted to observe an object of a lower integrity (no read down).

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, John Wiley & Sons, 2001, Chapter 5: Security Architectures and Models (page 205).

**NEW QUESTION 115**

- (Topic 1)

Which of the following is NOT a compensating measure for access violations?

- A. Backups
- B. Business continuity planning
- C. Insurance
- D. Security awareness

**Answer:** D

**Explanation:**

Security awareness is a preventive measure, not a compensating measure for access violations.

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, John Wiley & Sons, 2001, Chapter 2: Access control systems (page 50).

**NEW QUESTION 117**

- (Topic 1)

Which of the following is NOT part of the Kerberos authentication protocol?

- A. Symmetric key cryptography
- B. Authentication service (AS)
- C. Principals
- D. Public Key

**Answer:** D

**Explanation:**

There is no such component within kerberos environment. Kerberos uses only symmetric encryption and does not make use of any public key component.

The other answers are incorrect because :

Symmetric key cryptography is a part of Kerberos as the KDC holds all the users' and services' secret keys.

Authentication service (AS) : KDC (Key Distribution Center) provides an authentication service  
Principals : Key Distribution Center provides services to principals , which can be users , applications or network services.  
References: Shon Harris , AIO v3 , Chapter - 4: Access Control , Pages : 152-155.

#### NEW QUESTION 120

- (Topic 1)

What is one disadvantage of content-dependent protection of information?

- A. It increases processing overhead.
- B. It requires additional password entry.
- C. It exposes the system to data locking.
- D. It limits the user's individual address space.

**Answer:** A

#### Explanation:

Source: TIPTON, Hal, (ISC)2, Introduction to the CISSP Exam presentation.

#### NEW QUESTION 124

- (Topic 1)

The National Institute of Standards and Technology (NIST) standard pertaining to perimeter protection states that critical areas should be illuminated up to?

- A. Illuminated at nine feet high with at least three foot-candles
- B. Illuminated at eight feet high with at least three foot-candles
- C. Illuminated at eight feet high with at least two foot-candles
- D. Illuminated at nine feet high with at least two foot-candles

**Answer:** B

#### Explanation:

The National Institute of Standards and Technology (NIST) standard pertaining to perimeter protection states that critical areas should be illuminated eight feet high with at least two foot-candles.

It can also be referred to as illuminating to a height of eight feet, with a BRIGHTNESS of two foot-candles.

One footcandle 10.764 lux. The footcandle (or lumen per square foot) is a non-SI unit of illuminance. Like the BTU, it is obsolete but it is still in fairly common use in the United States, particularly in construction-related engineering and in building codes. Because lux and footcandles are different units of the same quantity, it is perfectly valid to convert footcandles to lux and vice versa.

The name "footcandle" conveys "the illuminance cast on a surface by a one-candela source one foot away." As natural as this sounds, this style of name is now frowned upon, because the dimensional formula for the unit is not foot • candela, but lumens per square foot.

Some sources do however note that the "lux" can be thought of as a "metre-candle" (i.e. the illuminance cast on a surface by a one-candela source one meter away). A source that is farther away casts less illumination than one that is close, so one lux is less illuminance than one footcandle. Since illuminance follows the inverse-square law, and since one foot = 0.3048 m, one lux = 0.30482 footcandle 1/10.764 footcandle.

TIPS FROM CLEMENT:

Illuminance (light level) ?C The amount of light, measured in foot-candles (US unit), that falls n a surface, either horizontal or vertical.

Parking lots lighting needs to be an average of 2 foot candles; uniformity of not more than 3:1, no area less than 1 fc.

All illuminance measurements are to be made on the horizontal plane with a certified light meter calibrated to NIST standards using traceable light sources.

The CISSP Exam Cram 2 from Michael Gregg says: Lighting is a commonly used form of perimeter protection.

Some studies have found that up to 80% of criminal acts at businesses and shopping centers happen in adjacent parking lots. Therefore, it's easy to see why lighting can be such an important concern.

Outside lighting discourages prowlers and thieves.

The National Institute of Standards and Technologies (NIST) states that, for effective perimeter control, buildings should be illuminated 8 feet high, with 2-foot candle power.

Reference used for this question:

HARRIS, Shon, All-In-One CISSP Certification Exam Guide, McGraw-Hill/Osborne, 2001, Page 325.

and

Shon's AIO v5 pg 459 and

<http://en.wikipedia.org/wiki/Foot-candle>

#### NEW QUESTION 128

- (Topic 1)

Because all the secret keys are held and authentication is performed on the Kerberos TGS and the authentication servers, these servers are vulnerable to:

- A. neither physical attacks nor attacks from malicious code.
- B. physical attacks only
- C. both physical attacks and attacks from malicious code.
- D. physical attacks but not attacks from malicious code.

**Answer:** C

#### Explanation:

Since all the secret keys are held and authentication is performed on the Kerberos TGS and the authentication servers, these servers are vulnerable to both physical attacks and attacks from malicious code.

Because a client's password is used in the initiation of the Kerberos request for the service protocol, password guessing can be used to impersonate a client.

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, 2001, John Wiley & Sons, Page 42.

#### NEW QUESTION 133

- (Topic 1)

In the context of access control, locks, gates, guards are examples of which of the following?

- A. Administrative controls



- B. Technical controls
- C. Physical controls
- D. Logical controls

**Answer: C**

**Explanation:**

Administrative, technical and physical controls are categories of access control mechanisms.

Logical and Technical controls are synonymous. So both of them could be eliminated as possible choices.

Physical Controls: These are controls to protect the organization's people and physical environment, such as locks, gates, and guards. Physical controls may be called "operational controls" in some contexts.

Physical security covers a broad spectrum of controls to protect the physical assets (primarily the people) in an organization. Physical Controls are sometimes referred to as "operational" controls in some risk management frameworks. These controls range from doors, locks, and windows to environment controls, construction standards, and guards. Typically, physical security is based on the notion of establishing security zones or concentric areas within a facility that require increased security as you get closer to the

valuable assets inside the facility. Security zones are the physical representation of the defense-in-depth principle discussed earlier in this chapter. Typically, security zones are associated with rooms, offices, floors, or smaller elements, such as a cabinet or storage locker. The design of the physical security controls within the facility must take into account the protection of the asset as well as the individuals working in that area.

Reference(s) used for this question:

Hernandez CISSP, Steven (2012-12-21). Official (ISC)2 Guide to the CISSP CBK, Third Edition ((ISC)2 Press) (Kindle Locations 1301-1303). Auerbach Publications. Kindle Edition.

and

Hernandez CISSP, Steven (2012-12-21). Official (ISC)2 Guide to the CISSP CBK, Third Edition ((ISC)2 Press) (Kindle Locations 1312-1318). Auerbach Publications. Kindle Edition.

**NEW QUESTION 135**

- (Topic 1)

Which of the following protection devices is used for spot protection within a few inches of the object, rather than for overall room security monitoring?

- A. Wave pattern motion detectors
- B. Capacitance detectors
- C. Field-powered devices
- D. Audio detectors

**Answer: B**

**Explanation:**

Capacitance detectors monitor an electrical field surrounding the object being monitored. They are used for spot protection within a few inches of the object, rather than for overall room security monitoring used by wave detectors. Penetration of this field changes the electrical capacitance of the field enough to generate and alarm. Wave pattern motion detectors generate a frequency wave pattern and send an alarm if the pattern is disturbed as it is reflected back to its receiver. Field-powered devices are a type of personnel access control devices. Audio detectors simply monitor a room for any abnormal sound wave generation and trigger an alarm.

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, John Wiley & Sons, 2001, Chapter 10: Physical security (page 344).

**NEW QUESTION 138**

- (Topic 1)

Which of the following biometric devices offers the LOWEST CER?

- A. Keystroke dynamics
- B. Voice verification
- C. Iris scan
- D. Fingerprint

**Answer: C**

**Explanation:**

From most effective (lowest CER) to least effective (highest CER) are: Iris scan, fingerprint, voice verification, keystroke dynamics.

Reference : Shon Harris Aio v3 , Chapter-4 : Access Control , Page : 131

Also see: [http://www.sans.org/reading\\_room/whitepapers/authentication/biometric-selection-body-parts-online\\_139](http://www.sans.org/reading_room/whitepapers/authentication/biometric-selection-body-parts-online_139)

**NEW QUESTION 141**

- (Topic 1)

Which of the following is not a preventive login control?

- A. Last login message
- B. Password aging
- C. Minimum password length
- D. Account expiration

**Answer: A**

**Explanation:**

The last login message displays the last login date and time, allowing a user to discover if their account was used by someone else. Hence, this is rather a detective control.

Source: RUSSEL, Deborah & GANGEMI, G.T. Sr., Computer Security Basics, O'Reilly, July 1992 (page 63).

**NEW QUESTION 142**

- (Topic 1)

Which of the following division is defined in the TCSEC (Orange Book) as minimal protection?

- A. Division D
- B. Division C
- C. Division B
- D. Division A

**Answer:** A

**Explanation:**

The criteria are divided into four divisions: D, C, B, and A ordered in a hierarchical manner with the highest division (A) being reserved for systems providing the most comprehensive security.

Each division represents a major improvement in the overall confidence one can place in the system for the protection of sensitive information.

Within divisions C and B there are a number of subdivisions known as classes. The classes are also ordered in a hierarchical manner with systems representative of division C and lower classes of division B being characterized by the set of computer security mechanisms that they possess.

Assurance of correct and complete design and implementation for these systems is gained mostly through testing of the security- relevant portions of the system.

The security-relevant portions of a system are referred to throughout this document as the Trusted Computing Base (TCB).

Systems representative of higher classes in division B and division A derive their security attributes more from their design and implementation structure.

Increased assurance that the required features are operative, correct, and tamperproof under all circumstances is gained through progressively more rigorous analysis during the design process.

TCSEC provides a classification system that is divided into hierarchical divisions of assurance levels:

Division D - minimal security Division C - discretionary protection Division B - mandatory protection Division A - verified protection

Reference: page 358 AIO V.5 Shon Harris

also

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, page 197.

Also:

THE source for all TCSEC "level" questions: <http://csrc.nist.gov/publications/secpubs/rainbow/std001.txt>

**NEW QUESTION 145**

- (Topic 1)

The throughput rate is the rate at which individuals, once enrolled, can be processed and identified or authenticated by a biometric system. Acceptable throughput rates are in the range of:

- A. 100 subjects per minute.
- B. 25 subjects per minute.
- C. 10 subjects per minute.
- D. 50 subjects per minute.

**Answer:** C

**Explanation:**

The throughput rate is the rate at which individuals, once enrolled, can be processed and identified or authenticated by a biometric system.

Acceptable throughput rates are in the range of 10 subjects per minute.

Things that may impact the throughput rate for some types of biometric systems may include:

A concern with retina scanning systems may be the exchange of body fluids on the eyepiece.

Another concern would be the retinal pattern that could reveal changes in a person's health, such as diabetes or high blood pressure.

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, 2001, John Wiley & Sons, Page 38.

**NEW QUESTION 149**

- (Topic 1)

How can an individual/person best be identified or authenticated to prevent local masquerading attacks?

- A. UserId and password
- B. Smart card and PIN code
- C. Two-factor authentication
- D. Biometrics

**Answer:** D

**Explanation:**

The only way to be truly positive in authenticating identity for access is to base the authentication on the physical attributes of the persons themselves (i.e., biometric

identification). Physical attributes cannot be shared, borrowed, or duplicated. They ensure that you do identify the person, however they are not perfect and they would have to be supplemented by another factor.

Some people are getting thrown off by the term Masquerade. In general, a masquerade is a disguise. In terms of communications security issues, a masquerade is a type of attack where the attacker pretends to be an authorized user of a system in order to gain access to it or to gain greater privileges than they are authorized for. A masquerade may be attempted through the use of stolen logon IDs and passwords, through finding security gaps in programs, or through bypassing the authentication mechanism. Spoofing is another term used to describe this type of attack as well.

A UserId only provides for identification.

A password is a weak authentication mechanism since passwords can be disclosed, shared, written down, and more.

A smart card can be stolen and its corresponding PIN code can be guessed by an intruder. A smartcard can be borrowed by a friend of yours and you would have no clue as to who is really logging in using that smart card.

Any form of two-factor authentication not involving biometrics cannot be as reliable as a biometric system to identify the person.

Biometric identifying verification systems control people. If the person with the correct hand, eye, face, signature, or voice is not present, the identification and verification cannot take place and the desired action (i.e., portal passage, data, or resource access) does not occur.

As has been demonstrated many times, adversaries and criminals obtain and successfully use access cards, even those that require the addition of a PIN. This is because these systems control only pieces of plastic (and sometimes information), rather than people. Real asset and resource protection can only be accomplished by people, not cards and information, because unauthorized persons can (and do) obtain the cards and information.

Further, life-cycle costs are significantly reduced because no card or PIN administration system or personnel are required. The authorized person does not lose physical characteristics (i.e., hands, face, eyes, signature, or voice), but cards and PINs are continuously lost, stolen, or forgotten. This is why card access systems require systems and people to administer, control, record, and issue (new) cards and PINs. Moreover, the cards are an expensive and recurring cost.

**NOTE FROM CLEMENT:**

This question has been generating lots of interest. The keyword in the question is: Individual (the person) and also the authenticated portion as well.

I totally agree with you that Two Factors or Strong Authentication would be the strongest means of authentication. However the question is not asking what is the strongest mean of authentication, it is asking what is the best way to identify the user (individual) behind the technology. When answering questions do not make assumptions to facts not presented in the question or answers.

Nothing can beat Biometrics in such case. You cannot lend your fingerprint and pin to someone else, you cannot borrow one of my eye balls to defeat the Iris or Retina scan. This is why it is the best method to authenticate the user.

I think the reference is playing with semantics and that makes it a bit confusing. I have improved the question to make it a lot clearer and I have also improve the explanations attached with the question.

The reference mentioned above refers to authenticating the identity for access. So the distinction is being made that there is identity and there is authentication. In the case of physical security the enrollment process is where the identity of the user would be validated and then the biometrics features provided by the user would authenticate the user on a one to one matching basis (for authentication) with the reference contained in the database of biometrics templates. In the case of system access, the user might have to provide a username, a pin, a passphrase, a smart card, and then provide his biometric attributes.

Biometric can also be used for Identification purpose where you do a one to many match. You take a facial scan of someone within an airport and you attempt to match it with a large database of known criminal and terrorists. This is how you could use biometric for Identification.

There are always THREE means of authentication, they are: Something you know (Type 1)

Something you have (Type 2)

Something you are (Type 3)

Reference(s) used for this question:

TIPTON, Harold F. & KRAUSE, Micki, Information Security Management Handbook, 4th edition (volume 1) , 2000, CRC Press, Chapter 1, Biometric Identification (page 7).

and

Search Security at <http://searchsecurity.techtarget.com/definition/masquerade>

**NEW QUESTION 152**

- (Topic 1)

Which of the following is the LEAST user accepted biometric device?

- A. Fingerprint
- B. Iris scan
- C. Retina scan
- D. Voice verification

**Answer: C**

**Explanation:**

The biometric device that is least user accepted is the retina scan, where a system scans the blood-vessel pattern on the backside of the eyeball. When using this device, an individual has to place their eye up to a device, and may require a puff of air to be blown into the eye. The iris scan only needs for an individual to glance at a camera that could be placed above a door.

Source: HARRIS, Shon, All-In-One CISSP Certification Exam Guide, McGraw- Hill/Osborne, 2002, Chapter 4: Access Control (page 131).

**NEW QUESTION 157**

- (Topic 1)

Examples of types of physical access controls include all EXCEPT which of the following?

- A. badges
- B. locks
- C. guards
- D. passwords

**Answer: D**

**Explanation:**

Passwords are considered a Preventive/Technical (logical) control. The following answers are incorrect:

badges Badges are a physical control used to identify an individual. A badge can include a smart device which can be used for authentication and thus a Technical control, but the actual badge itself is primarily a physical control.

locks Locks are a Preventative Physical control and has no Technical association. guards Guards are a Preventative Physical control and has no Technical association.

The following reference(s) were/was used to create this question:

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, John Wiley & Sons, 2001, Chapter 2: Access control systems (page 35).

**NEW QUESTION 161**

- (Topic 1)

Which of the following is NOT an advantage that TACACS+ has over TACACS?

- A. Event logging
- B. Use of two-factor password authentication
- C. User has the ability to change his password
- D. Ability for security tokens to be resynchronized

**Answer: A**

**Explanation:**

Although TACACS+ provides better audit trails, event logging is a service that is provided with TACACS.

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, John Wiley & Sons, 2001, Chapter 3: Telecommunications and Network Security (page 121).

**NEW QUESTION 165**

- (Topic 1)

Like the Kerberos protocol, SESAME is also subject to which of the following?

- A. timeslot replay
- B. password guessing
- C. symmetric key guessing
- D. asymmetric key guessing

**Answer: B**

**Explanation:**

Sesame is an authentication and access control protocol, that also supports communication confidentiality and integrity. It provides public key based authentication along with the Kerberos style authentication, that uses symmetric key cryptography. Sesame supports the Kerberos protocol and adds some security extensions like public key based authentication and an ECMA-style Privilege Attribute Service.

The users under SESAME can authenticate using either symmetric encryption as in Kerberos or Public Key authentication. When using Symmetric Key authentication as in Kerberos, SESAME is also vulnerable to password guessing just like Kerberos would be.

The Symmetric key being used is based on the password used by the user when he logged on the system. If the user has a simple password it could be guessed or compromise. Even thou Kerberos or SESAME may be use, there is still a need to have strong password discipline.

The Basic Mechanism in Sesame for strong authentication is as follow:

The user sends a request for authentication to the Authentication Server as in Kerberos, except that SESAME is making use of public key cryptography for authentication where the client will present his digital certificate and the request will be signed using a digital signature. The signature is communicated to the authentication server through the preauthentication fields. Upon receipt of this request, the authentication server will verifies the certificate, then validate the signature, and if all is fine the AS will issue a ticket granting ticket (TGT) as in Kerberos. This TGT will be use to communicate with the privilege attribute server (PAS) when access to a resource is needed.

Users may authenticate using either a public key pair or a conventional (symmetric) key. If public key cryptography is used, public key data is transported in preauthentication data fields to help establish identity.

Kerberos uses tickets for authenticating subjects to objects and SESAME uses Privileged Attribute Certificates (PAC), which contain the subject's identity, access capabilities for the object, access time period, and lifetime of the PAC. The PAC is digitally signed so that the object can validate that it came from the trusted authentication server, which is referred to as the privilege attribute server (PAS). The PAS holds a similar role as the KDC within Kerberos. After a user successfully authenticates to the authentication service (AS), he is presented with a token to give to the PAS. The PAS then creates a PAC for the user to present to the resource he is trying to access.

Reference(s) used for this question: <http://srg.cs.uiuc.edu/Security/nephilim/Internal/SESAME.txt>

and

KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, 2001, John Wiley & Sons, Page 43.

**NEW QUESTION 170**

- (Topic 1)

Controls like guards and general steps to maintain building security, securing of server rooms or laptops, the protection of cables, and usage of magnetic switches on doors and windows are some of the examples of:

- A. Administrative controls
- B. Logical controls
- C. Technical controls
- D. Physical controls

**Answer: D**

**Explanation:**

Controls like guards and general steps to maintain building security, securing of server rooms or laptops, the protection of cables, and usage of magnetic switches on doors and windows are all examples of Physical Security.

Reference(s) used for this question:

KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, 2001, John Wiley & Sons, Page 33.

**NEW QUESTION 172**

- (Topic 1)

Which access control model is best suited in an environment where a high security level is required and where it is desired that only the administrator grants access control?

- A. DAC
- B. MAC
- C. Access control matrix
- D. TACACS

**Answer: B**

**Explanation:**

MAC provides high security by regulating access based on the clearance of individual users and sensitivity labels for each object. Clearance levels and sensitivity levels cannot be modified by individual users -- for example, user Joe (SECRET clearance) cannot reclassify the "Presidential Doughnut Recipe" from "SECRET" to "CONFIDENTIAL" so that his friend Jane (CONFIDENTIAL clearance) can read it. The administrator is ultimately responsible for configuring this protection in accordance with security policy and directives from the Data Owner.

DAC is incorrect. In DAC, the data owner is responsible for controlling access to the object. Access control matrix is incorrect. The access control matrix is a way of thinking about the

access control needed by a population of subjects to a population of objects. This access control can be applied using rules, ACL's, capability tables, etc.

TACACS is incorrect. TACACS is a tool for performing user authentication. References:

CBK, p. 187, Domain 2: Access Control. AIO3, Chapter 4, Access Control.

**NEW QUESTION 175**

- (Topic 1)

What does the simple security (ss) property mean in the Bell-LaPadula model?



- A. No read up
- B. No write down
- C. No read down
- D. No write up

**Answer:** A

**Explanation:**

The ss (simple security) property of the Bell-LaPadula access control model states that reading of information by a subject at a lower sensitivity level from an object at a higher sensitivity level is not permitted (no read up).

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, John Wiley & Sons, 2001, Chapter 5: Security Architectures and Models (page 202).

**NEW QUESTION 180**

- (Topic 1)

Which type of attack involves impersonating a user or a system?

- A. Smurfing attack
- B. Spoofing attack
- C. Spamming attack
- D. Sniffing attack

**Answer:** B

**Explanation:**

A spoofing attack is when an attempt is made to gain access to a computer system by posing as an authorized user or system. Spamming refers to sending out or posting junk advertising and unsolicited mail. A smurf attack is a type of denial-of-service attack using PING and a spoofed address. Sniffing refers to observing packets passing on a network.

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, John Wiley & Sons, 2001, Chapter 3: Telecommunications and Network Security (page 77).

**NEW QUESTION 181**

- (Topic 1)

Which one of the following factors is NOT one on which Authentication is based?

- A. Type 1. Something you know, such as a PIN or password
- B. Type 2. Something you have, such as an ATM card or smart card
- C. Type 3. Something you are (based upon one or more intrinsic physical or behavioral traits), such as a fingerprint or retina scan
- D. Type 4. Something you are, such as a system administrator or security administrator

**Answer:** D

**Explanation:**

Authentication is based on the following three factor types:

Type 1. Something you know, such as a PIN or password

Type 2. Something you have, such as an ATM card or smart card

Type 3. Something you are (Unique physical characteristic), such as a fingerprint or retina scan

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, 2001, John Wiley & Sons, Page 36.

Also: HARRIS, Shon, All-In-One CISSP Certification Exam Guide, McGraw-Hill/Osborne, 2002, chapter 4: Access Control (pages 132-133).

**NEW QUESTION 186**

- (Topic 1)

Which of the following statements pertaining to using Kerberos without any extension is false?

- A. A client can be impersonated by password-guessing.
- B. Kerberos is mostly a third-party authentication protocol.
- C. Kerberos uses public key cryptography.
- D. Kerberos provides robust authentication.

**Answer:** C

**Explanation:**

Kerberos is a trusted, credential-based, third-party authentication protocol that uses symmetric (secret) key cryptography to provide robust authentication to clients accessing services on a network.

Because a client's password is used in the initiation of the Kerberos request for the service protocol, password guessing can be used to impersonate a client.

Here is a nice overview of HOW Kerberos is implement as described in RFC 4556:

1. Introduction

The Kerberos V5 protocol [RFC4120] involves use of a trusted third party known as the Key Distribution Center (KDC) to negotiate shared session keys between clients and services and provide mutual authentication between them.

The corner-stones of Kerberos V5 are the Ticket and the Authenticator. A Ticket encapsulates a symmetric key (the ticket session key) in an envelope (a public message) intended for a specific service. The contents of the Ticket are encrypted with a symmetric key shared between the service principal and the issuing KDC. The encrypted part of the Ticket contains the client principal name, among other items. An Authenticator is a record that can be shown to have been recently generated using the ticket session key in the associated Ticket. The ticket session key is known by the client who requested the ticket. The contents of the Authenticator are encrypted with the associated ticket session key. The encrypted part of an Authenticator contains a timestamp and the client principal name, among other items.

As shown in Figure 1, below, the Kerberos V5 protocol consists of the following message exchanges between the client and the KDC, and the client and the application service:

The Authentication Service (AS) Exchange

The client obtains an "initial" ticket from the Kerberos authentication server (AS), typically a Ticket Granting Ticket

(TGT). The AS-REQ message and the AS-REP message are the request and the reply message, respectively, between the client and the

AS.

The Ticket Granting Service (TGS) Exchange

The client subsequently uses the TGT to authenticate and request a service ticket for a particular service, from the Kerberos

ticket-granting server (TGS). The TGS-REQ message and the TGS-REP message are the request and the reply message respectively between the client and the TGS.

The Client/Server Authentication Protocol (AP) Exchange

The client then makes a request with an AP-REQ message, consisting of a service ticket and an authenticator that certifies the

client's possession of the ticket session key. The server may optionally reply with an AP-REP message. AP exchanges typically negotiate session-specific symmetric keys.

Usually, the AS and TGS are integrated in a single device also known as the KDC.

```
+-----+
+----->| KDC |
AS-REQ / +-----| |
// +-----+
// ^|
/|AS-REP / |
| | / TGS-REQ + TGS-REP
| | /
| | /
| | / +-----+
| | /
| | /
| | /
| v / v
++-----+-----+ +-----+
| Client +----->| Application | |
| | AP-REQ | Server |
| |<-----| |
+-----+ AP-REP +-----+
```

Figure 1: The Message Exchanges in the Kerberos V5 Protocol

In the AS exchange, the KDC reply contains the ticket session key, among other items, that is encrypted using a key (the AS reply key) shared between the client and the KDC. The AS reply key is typically derived from the client's password for human users. Therefore, for human users, the attack resistance strength of the Kerberos protocol is no stronger than the strength of their passwords.

Source: KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, John Wiley & Sons, 2001, Chapter 2: Access control systems (page 40).

And

HARRIS, Shon, All-In-One CISSP Certification Exam Guide, McGraw-Hill/Osborne, 2002, chapter 4: Access Control (pages 147-151).

and <http://www.ietf.org/rfc/rfc4556.txt>

## NEW QUESTION 189

- (Topic 1)

What kind of certificate is used to validate a user identity?

- A. Public key certificate
- B. Attribute certificate
- C. Root certificate
- D. Code signing certificate

**Answer: A**

### Explanation:

In cryptography, a public key certificate (or identity certificate) is an electronic document which incorporates a digital signature to bind together a public key with an identity ?? information such as the name of a person or an organization, their address, and so forth. The certificate can be used to verify that a public key belongs to an individual.

In a typical public key infrastructure (PKI) scheme, the signature will be of a certificate authority (CA). In a web of trust scheme, the signature is of either the user (a self-signed certificate) or other users ("endorsements"). In either case, the signatures on a certificate are attestations by the certificate signer that the identity information and the public key belong together.

In computer security, an authorization certificate (also known as an attribute certificate) is a digital document that describes a written permission from the issuer to use a service or a resource that the issuer controls or has access to use. The permission can be delegated.

Some people constantly confuse PKCs and ACs. An analogy may make the distinction clear. A PKC can be considered to be like a passport: it identifies the holder, tends to last for a long time, and should not be trivial to obtain. An AC is more like an entry visa: it is typically issued by a different authority and does not last for as long a time. As acquiring an entry visa typically requires presenting a passport, getting a visa can be a simpler process.

A real life example of this can be found in the mobile software deployments by large service providers and are typically applied to platforms such as Microsoft Smartphone (and related), Symbian OS, J2ME, and others.

In each of these systems a mobile communications service provider may customize the mobile terminal client distribution (ie. the mobile phone operating system or application environment) to include one or more root certificates each associated with a set of capabilities or permissions such as "update firmware", "access address book", "use radio interface", and the most basic one, "install and execute". When a developer wishes to enable distribution and execution in one of these controlled environments they must acquire a certificate from an appropriate CA, typically a large commercial CA, and in the process they usually have their identity verified using out-of-band mechanisms such as a combination of phone call, validation of their legal entity through government and commercial databases, etc., similar to the high assurance SSL certificate vetting process, though often there are additional specific requirements imposed on would-be developers/publishers. Once the identity has been validated they are issued an identity certificate they can use to sign their software; generally the software signed by the developer or publisher's identity certificate is not distributed but rather it is submitted to processor to possibly test or profile the content before generating an authorization certificate which is unique to the particular software release. That certificate is then used with an ephemeral asymmetric key-pair to sign the software as the last step of preparation for distribution. There are many advantages to separating the identity and authorization certificates especially relating to risk mitigation of new content being accepted into the system and key management as well as recovery from errant software which can be used as attack vectors.

References:

HARRIS, Shon, All-In-One CISSP Certification Exam Guide, 2001, McGraw-Hill/Osborne, page 540.

[http://en.wikipedia.org/wiki/Attribute\\_certificate](http://en.wikipedia.org/wiki/Attribute_certificate) [http://en.wikipedia.org/wiki/Public\\_key\\_certificate](http://en.wikipedia.org/wiki/Public_key_certificate)

## NEW QUESTION 190

- (Topic 1)

Why do buffer overflows happen? What is the main cause?

- A. Because buffers can only hold so much data
- B. Because of improper parameter checking within the application
- C. Because they are an easy weakness to exploit
- D. Because of insufficient system memory

**Answer: B**

**Explanation:**

Buffer Overflow attack takes advantage of improper parameter checking within the application. This is the classic form of buffer overflow and occurs because the programmer accepts whatever input the user supplies without checking to make sure that the length of the input is less than the size of the buffer in the program. The buffer overflow problem is one of the oldest and most common problems in software development and programming, dating back to the introduction of interactive computing. It can result when a program fills up the assigned buffer of memory with more data than its buffer can hold. When the program begins to write beyond the end of the buffer, the program's execution path can be changed, or data can be written into areas used by the operating system itself. This can lead to the insertion of malicious code that can be used to gain administrative privileges on the program or system.

As explained by Gaurab, it can become very complex. At the time of input even if you are checking the length of the input, it has to be checked against the buffer size. Consider a case where entry point of data is stored in Buffer1 of Application1 and then you copy it to Buffer2 within Application2 later on, if you are just checking the length of data against Buffer1, it will

not ensure that it will not cause a buffer overflow in Buffer2 of Application2.

A bit of reassurance from the ISC2 book about level of Coding Knowledge needed for the exam:

It should be noted that the CISSP is not required to be an expert programmer or know the inner workings of developing application software code, like the FORTRAN programming language, or how to develop Web applet code using Java. It is not even necessary that the CISSP know detailed security-specific coding practices such as the major divisions of buffer overflow exploits or the reason for preferring `strncpy` to `strcpy` in the C language (although all such knowledge is, of course, helpful). Because the CISSP may be the person responsible for ensuring that security is included in such developments, the CISSP should know the basic procedures and concepts involved during the design and development of software programming. That is, in order for the CISSP to monitor the software development process and verify that security is included, the CISSP must understand the fundamental concepts of programming developments and the security strengths and weaknesses of various application development processes.

The following are incorrect answers:

"Because buffers can only hold so much data" is incorrect. This is certainly true but is not the best answer because the finite size of the buffer is not the problem -- the problem is that the programmer did not check the size of the input before moving it into the buffer.

"Because they are an easy weakness to exploit" is incorrect. This answer is sometimes true but is not the best answer because the root cause of the buffer overflow is that the programmer did not check the size of the user input.

"Because of insufficient system memory" is incorrect. This is irrelevant to the occurrence of a buffer overflow.

Reference(s) used for this question:

Hernandez CISSP, Steven (2012-12-21). Official (ISC)2 Guide to the CISSP CBK, Third Edition ((ISC)2 Press) (Kindle Locations 13319-13323). Auerbach Publications. Kindle Edition.

**NEW QUESTION 193**

- (Topic 1)

Another type of access control is lattice-based access control. In this type of control a lattice model is applied. How is this type of access control concept applied?

- A. The pair of elements is the subject and object, and the subject has an upper bound equal or higher than the upper bound of the object being accessed.
- B. The pair of elements is the subject and object, and the subject has an upper bound lower than the upper bound of the object being accessed.
- C. The pair of elements is the subject and object, and the subject has no special upper or lower bound needed within the lattice.
- D. The pair of elements is the subject and object, and the subject has no access rights in relation to an object.

**Answer: A**

**Explanation:**

To apply this concept to access control, the pair of elements is the subject and object, and the subject has to have an upper bound equal or higher than the object being accessed.

WIKIPEDIA has a great explanation as well:

In computer security, lattice-based access control (LBAC) is a complex access control based on the interaction between any combination of objects (such as resources, computers, and applications) and subjects (such as individuals, groups or organizations). In this type of label-based mandatory access control model, a lattice is used to define the levels of security that an object may have and that a subject may have access to. The subject is only allowed to access an object if the security level of the subject is greater than or equal to that of the object.

Reference(s) used for this question:

KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, 2001, John Wiley & Sons, Page 34.

and

[http://en.wikipedia.org/wiki/Lattice-based\\_access\\_control](http://en.wikipedia.org/wiki/Lattice-based_access_control)

**NEW QUESTION 194**

- (Topic 1)

What is called the act of a user professing an identity to a system, usually in the form of a log-on ID?

- A. Authentication
- B. Identification
- C. Authorization
- D. Confidentiality

**Answer: B**

**Explanation:**

Identification is the act of a user professing an identity to a system, usually in the form of a log-on ID to the system.

Identification is nothing more than claiming you are somebody. You identify yourself when you speak to someone on the phone that you don't know, and they ask you who they're speaking to. When you say, "I'm Jason", you've just identified yourself.

In the information security world, this is analogous to entering a username. It's not analogous to entering a password. Entering a password is a method for verifying that you are who you identified yourself as.

NOTE: The word "professing" used above means: "to say that you are, do, or feel something when other people doubt what you say". This is exactly what happens



when you provide your identifier (identification), you claim to be someone but the system cannot take your word for it, you must further Authenticate to the system to prove who you claim to be.

The following are incorrect answers:

Authentication: is how one proves that they are who they say they are. When you claim to be Jane Smith by logging into a computer system as ??jsmith??, it??s most likely going to ask you for a password. You??ve claimed to be that person by entering the name into the username field (that??s the identification part), but now you have to prove that you are really that person.

Many systems use a password for this, which is based on ??something you know??, i.e. a secret between you and the system.

Another form of authentication is presenting something you have, such as a driver??s license, an RSA token, or a smart card.

You can also authenticate via something you are. This is the foundation for biometrics. When you do this, you first identify yourself and then submit a thumb print, a retina scan, or another form of bio-based authentication.

Once you??ve successfully authenticated, you have now done two things: you??ve claimed to be someone, and you??ve proven that you are that person. The only thing that??s left is for the system to determine what you??re allowed to do.

Authorization: is what takes place after a person has been both identified and authenticated; it??s the step determines what a person can then do on the system.

An example in people terms would be someone knocking on your door at night. You say, ??Who is it???, and wait for a response. They say, ??It??s John.?? in order to identify themselves. You ask them to back up into the light so you can see them through the peephole. They do so, and you authenticate them based on what they look like (biometric). At that point you decide they can come inside the house.

If they had said they were someone you didn??t want in your house (identification), and you then verified that it was that person (authentication), the authorization phase would not include access to the inside of the house.

Confidentiality: Is one part of the CIA triad. It prevents sensitive information from reaching the wrong people, while making sure that the right people can in fact get it. A good example is a credit card number while shopping online, the merchant needs it to clear the transaction but you do not want your informaiton exposed over the network, you would use a secure link such as SSL, TLS, or some tunneling tool to protect the information from prying eyes between point A and point B. Data encryption is a common method of ensuring confidentiality.

The other parts of the CIA triad are listed below:

Integrity involves maintaining the consistency, accuracy, and trustworthiness of data over its entire life cycle. Data must not be changed in transit, and steps must be taken to ensure that data cannot be altered by unauthorized people (for example, in a breach of confidentiality). In addition, some means must be in place to detect any changes in data that might occur as a result of non-human-caused events such as an electromagnetic pulse (EMP) or server crash. If an unexpected change occurs, a backup copy must be available to restore the affected data to its correct state.

Availability is best ensured by rigorously maintaining all hardware, performing hardware repairs immediately when needed, providing a certain measure of redundancy and failover, providing adequate communications bandwidth and preventing the occurrence of bottlenecks, implementing emergency backup power systems, keeping current with all necessary system upgrades, and guarding against malicious actions such as denial-of- service (DoS) attacks.

Reference used for this question:

<http://whatis.techtarget.com/definition/Confidentiality-integrity-and-availability-CIA> <http://www.danielmiessler.com/blog/security-identification-authentication-and-authorization> <http://www.merriam-webster.com/dictionary/profess>

KRUTZ, Ronald L. & VINES, Russel D., The CISSP Prep Guide: Mastering the Ten Domains of Computer Security, 2001, John Wiley & Sons, Page 36.

#### NEW QUESTION 195

- (Topic 1)

Which of the following does not apply to system-generated passwords?

- A. Passwords are harder to remember for users.
- B. If the password-generating algorithm gets to be known, the entire system is in jeopardy.
- C. Passwords are more vulnerable to brute force and dictionary attacks.
- D. Passwords are harder to guess for attackers.

**Answer: C**

#### Explanation:

Users tend to choose easier to remember passwords. System-generated passwords can provide stronger, harder to guess passwords. Since they are based on rules provided by the administrator, they can include combinations of uppercase/lowercase letters, numbers and special characters, making them less vulnerable to brute force and dictionary attacks. One danger is that they are also harder to remember for users, who will tend to write them down, making them more vulnerable to anyone having access to the user's desk. Another danger with system-generated passwords is that if the password- generating algorithm gets to be known, the entire system is in jeopardy.

Source: RUSSEL, Deborah & GANGEMI, G.T. Sr., Computer Security Basics, O'Reilly, July 1992 (page 64).

#### NEW QUESTION 196

- (Topic 1)

What is the Biba security model concerned with?

- A. Confidentiality
- B. Reliability
- C. Availability
- D. Integrity

**Answer: D**

#### Explanation:

The Biba security model addresses the integrity of data being threatened when subjects at lower security levels are able to write to objects at higher security levels and when subjects can read data at lower levels.

Source: HARRIS, Shon, All-In-One CISSP Certification Exam Guide, McGraw- Hill/Osborne, 2002, Chapter 5: Security Models and Architecture (Page 244).

#### NEW QUESTION 201

- (Topic 1)

Which of the following statements pertaining to the Bell-LaPadula is TRUE if you are NOT making use of the strong star property?

- A. It allows "read up."
- B. It addresses covert channels.
- C. It addresses management of access controls.
- D. It allows "write up."



**Answer:** D

**Explanation:**

Bell?CLaPadula Confidentiality Model10 The Bell?CLaPadula model is perhaps the most well-known and significant security model, in addition to being one of the oldest models used in the creation of modern secure computing systems. Like the Trusted Computer System Evaluation Criteria (or TCSEC), it was inspired by early U.S. Department of Defense security policies and the need to prove that confidentiality could be maintained. In other words, its primary goal is to prevent disclosure as the model system moves from one state (one point in time) to another.

When the strong star property is not being used it means that both the property and the

Simple Security Property rules would be applied.

The Star (\*) property rule of the Bell-LaPadula model says that subjects cannot write down, this would compromise the confidentiality of the information if someone at the secret layer would write the object down to a confidential container for example.

The Simple Security Property rule states that the subject cannot read up which means that a subject at the secret layer would not be able to access objects at Top Secret for example.

You must remember: The model tells you about are NOT allowed to do. Anything else would be allowed. For example within the Bell LaPadula model you would be allowed to write up as it does not compromise the security of the information. In fact it would upgrade it to the point that you could lock yourself out of your own information if you have only a secret security clearance.

The following are incorrect answers because they are all FALSE:

"It allows read up" is incorrect. The "simple security" property forbids read up.

"It addresses covert channels" is incorrect. Covert channels are not addressed by the Bell- LaPadula model.

"It addresses management of access controls" is incorrect. Management of access controls are beyond the scope of the Bell-LaPadula model.

Reference(s) used for this question:

Hernandez CISSP, Steven (2012-12-21). Official (ISC)2 Guide to the CISSP CBK, Third Edition ((ISC)2 Press) (Kindle Locations 17595-17600). Auerbach Publications. Kindle Edition.

**NEW QUESTION 205**

- (Topic 1)

How are memory cards and smart cards different?

- A. Memory cards normally hold more memory than smart cards
- B. Smart cards provide a two-factor authentication whereas memory cards don't
- C. Memory cards have no processing power
- D. Only smart cards can be used for ATM cards

**Answer:** C

**Explanation:**

The main difference between memory cards and smart cards is their capacity to process information. A memory card holds information but cannot process information. A smart card holds information and has the necessary hardware and software to actually process that information.

A memory card holds a user?s authentication information, so that this user needs only type in a user ID or PIN and presents the memory card to the system. If the entered information and the stored information match and are approved by an authentication service, the user is successfully authenticated.

A common example of a memory card is a swipe card used to provide entry to a building. The user enters a PIN and swipes the memory card through a card reader. If this is the correct combination, the reader flashes green and the individual can open the door and enter the building.

Memory cards can also be used with computers, but they require a reader to process the information. The reader adds cost to the process, especially when one is needed for every computer. Additionally, the overhead of PIN and card generation adds additional overhead and complexity to the whole authentication process. However, a memory card provides a more secure authentication method than using only a password because the attacker would need to obtain the card and know the correct PIN.

Administrators and management need to weigh the costs and benefits of a memory card implementation as well as the security needs of the organization to determine if it is the right authentication mechanism for their environment.

One of the most prevalent weaknesses of memory cards is that data stored on the card are not protected. Unencrypted data on the card (or stored on the magnetic strip) can be extracted or copied. Unlike a smart card, where security controls and logic are embedded in the integrated circuit, memory cards do not employ an inherent mechanism to protect the data from exposure.

Very little trust can be associated with confidentiality and integrity of information on the memory cards.

The following answers are incorrect:

"Smart cards provide two-factor authentication whereas memory cards don't" is incorrect. This is not necessarily true. A memory card can be combined with a pin or password to offer two factors authentication where something you have and something you know are used for factors.

"Memory cards normally hold more memory than smart cards" is incorrect. While a memory card may or may not have more memory than a smart card, this is certainly not the best answer to the question.

"Only smart cards can be used for ATM cards" is incorrect. This depends on the decisions made by the particular institution and is not the best answer to the question.

Reference(s) used for this question:

Shon Harris, CISSP All In One, 6th edition , Access Control, Page 199 and also for people using the Kindle edition of the book you can look at Locations 4647-4650.

Schneider, Andrew (2013-04-15). Official (ISC)2 Guide to the CISSP CBK, Third Edition : Access Control ((ISC)2 Press) (Kindle Locations 2124-2139). Auerbach Publications. Kindle Edition.

**NEW QUESTION 208**

- (Topic 1)

Which access control model is also called Non Discretionary Access Control (NDAC)?

- A. Lattice based access control
- B. Mandatory access control
- C. Role-based access control
- D. Label-based access control

**Answer:** C

**Explanation:**

RBAC is sometimes also called non-discretionary access control (NDAC) (as Ferraiolo says "to distinguish it from the policy-based specifics of MAC"). Another model that fits within the NDAC category is Rule-Based Access Control (RuBAC or RBAC). Most of the CISSP books use the same acronym for both models but NIST tend to use a lowercase "u" in between R and B to differentiate the two models.

You can certainly mimic MAC using RBAC but true MAC makes use of Labels which contains the sensitivity of the objects and the categories they belong to. No labels means MAC is not being used.

One of the most fundamental data access control decisions an organization must make is the amount of control it will give system and data owners to specify the level of access users of that data will have. In every organization there is a balancing point between the access controls enforced by organization and system policy and the ability for information owners to determine who can have access based on specific business requirements. The process of translating that balance into a workable access control model can be defined by three general access frameworks:

Discretionary access control Mandatory access control Nondiscretionary access control

A role-based access control (RBAC) model bases the access control authorizations on the roles (or functions) that the user is assigned within an organization. The determination of what roles have access to a resource can be governed by the owner of the data, as with DACs, or applied based on policy, as with MACs. Access control decisions are based on job function, previously defined and governed by policy, and each role (job function) will have its own access capabilities. Objects associated with a role will inherit privileges assigned to that role. This is also true for groups of users, allowing administrators to simplify access control strategies by assigning users to groups and groups to roles.

There are several approaches to RBAC. As with many system controls, there are variations on how they can be applied within a computer system. There are four basic RBAC architectures:

1. Non-RBAC: Non-RBAC is simply a user-granted access to data or an application by traditional mapping, such as with ACLs. There are no formal roles associated with the mappings, other than any identified by the particular user.
2. Limited RBAC: Limited RBAC is achieved when users are mapped to roles within a single application rather than through an organization-wide role structure. Users in a limited RBAC system are also able to access non-RBAC-based applications or data. For example, a user may be assigned to multiple roles within several applications and, in addition, have direct access to another application or system independent of his or her assigned role. The key attribute of limited RBAC is that the role for that user is defined within an application and not necessarily based on the user's organizational job function.
3. Hybrid RBAC: Hybrid RBAC introduces the use of a role that is applied to multiple applications or systems based on a user's specific role within the organization. That role is then applied to applications or systems that subscribe to the organization's role-based model. However, as the term "hybrid" suggests, there are instances where the subject may also be assigned to roles defined solely within specific applications, complimenting (or, perhaps, contradicting) the larger, more encompassing organizational role used by other systems.
4. Full RBAC: Full RBAC systems are controlled by roles defined by the organization's policy and access control infrastructure and then applied to applications and systems across the enterprise. The applications, systems, and associated data apply permissions based on that enterprise definition, and not one defined by a specific application or system. Be careful not to try to make MAC and DAC opposites of each other -- they are two different access control strategies with RBAC being a third strategy that was defined later to address some of the limitations of MAC and DAC.

The other answers are not correct because:

Mandatory access control is incorrect because though it is by definition not discretionary, it is not called "non-discretionary access control." MAC makes use of label to indicate the sensitivity of the object and it also makes use of categories to implement the need to know.

Label-based access control is incorrect because this is not a name for a type of access control but simply a bogus detractor.

Lattice based access control is not adequate either. A lattice is a series of levels and a subject will be granted an upper and lower bound within the series of levels. These levels could be sensitivity levels or they could be confidentiality levels or they could be integrity levels.

Reference(s) used for this question: All in One, third edition, page 165.  
Ferraiolo, D., Kuhn, D. & Chandramouli, R. (2003). Role-Based Access Control, p. 18.  
Ferraiolo, D., Kuhn, D. (1992). Role-Based Access Controls. [http://csrc.nist.gov/rbac/Role\\_Based\\_Access\\_Control-1992.html](http://csrc.nist.gov/rbac/Role_Based_Access_Control-1992.html)  
Schneiter, Andrew (2013-04-15). Official (ISC)2 Guide to the CISSP CBK, Third Edition : Access Control ((ISC)2 Press) (Kindle Locations 1557-1584). Auerbach Publications. Kindle Edition.  
Schneiter, Andrew (2013-04-15). Official (ISC)2 Guide to the CISSP CBK, Third Edition : Access Control ((ISC)2 Press) (Kindle Locations 1474-1477). Auerbach Publications. Kindle Edition.

## NEW QUESTION 210

.....

## Thank You for Trying Our Product

### We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

### SSCP Practice Exam Features:

- \* SSCP Questions and Answers Updated Frequently
- \* SSCP Practice Questions Verified by Expert Senior Certified Staff
- \* SSCP Most Realistic Questions that Guarantee you a Pass on Your First Try
- \* SSCP Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

**100% Actual & Verified — Instant Download, Please Click**  
**[Order The SSCP Practice Test Here](#)**