

Amazon-Web-Services

Exam Questions DOP-C02

AWS Certified DevOps Engineer - Professional



NEW QUESTION 1

A DevOps engineer manages a web application that runs on Amazon EC2 instances behind an Application Load Balancer (ALB). The instances run in an EC2 Auto Scaling group across multiple Availability Zones. The engineer needs to implement a deployment strategy that:

- Launches a second fleet of instances with the same capacity as the original fleet. Maintains the original fleet unchanged while the second fleet is launched.
- Transitions traffic to the second fleet when the second fleet is fully deployed. Terminates the original fleet automatically 1 hour after transition.

Which solution will satisfy these requirements?

- A. Use an AWS CloudFormation template with a retention policy for the ALB set to 1 hour
- B. Update the Amazon Route 53 record to reflect the new ALB.
- C. Use two AWS Elastic Beanstalk environments to perform a blue/green deployment from the original environment to the new one
- D. Create an application version lifecycle policy to terminate the original environment in 1 hour.
- E. Use AWS CodeDeploy with a deployment group configured with a blue/green deployment configuration. Select the option Terminate the original instances in the deployment group with a waiting period of 1 hour.
- F. Use AWS Elastic Beanstalk with the configuration set to Immutable
- G. Create an .ebextension using the Resources key that sets the deletion policy of the ALB to 1 hour, and deploy the application.

Answer: C

Explanation:

https://docs.aws.amazon.com/codedeploy/latest/APIReference/API_BlueInstanceTerminationOption.html The original revision termination settings are configured to wait 1 hour after traffic has been rerouted before terminating the blue task set. <https://docs.aws.amazon.com/AmazonECS/latest/developerguide/deployment-type-bluegreen.html>

NEW QUESTION 2

A company is using an AWS CodeBuild project to build and package an application. The packages are copied to a shared Amazon S3 bucket before being deployed across multiple AWS accounts. The buildspec.yml file contains the following:

```
version: 0.2
phases:
  build:
    commands:
      - go build -o myapp
  post_build:
    commands:
      - aws s3 cp --acl authenticated-read myapp s3://artifacts/
```

The DevOps engineer has noticed that anybody with an AWS account is able to download the artifacts. What steps should the DevOps engineer take to stop this?

- A. Modify the post_build command to use --acl public-read and configure a bucket policy that grants read access to the relevant AWS accounts only.
- B. Configure a default ACL for the S3 bucket that defines the set of authenticated users as the relevant AWS accounts only and grants read-only access.
- C. Create an S3 bucket policy that grants read access to the relevant AWS accounts and denies read access to the principal “*”.
- D. Modify the post_build command to remove --acl authenticated-read and configure a bucket policy that allows read access to the relevant AWS accounts only.

Answer: D

Explanation:

When setting the flag authenticated-read in the command line, the owner gets FULL_CONTROL. The AuthenticatedUsers group (Anyone with an AWS account) gets READ access. Reference: <https://docs.aws.amazon.com/AmazonS3/latest/userguide/acl-overview.html>

NEW QUESTION 3

A company has multiple AWS accounts. The company uses AWS IAM Identity Center (AWS Single Sign-On) that is integrated with AWS Toolkit for Microsoft Azure DevOps. The attributes for access control feature is enabled in IAM Identity Center. The attribute mapping list contains two entries. The department key is mapped to \${path:enterprise.department}. The costCenter key is mapped to \${path:enterprise.costCenter}. All existing Amazon EC2 instances have a department tag that corresponds to three company departments (d1, d2, d3). A DevOps engineer must create policies based on the matching attributes. The policies must minimize administrative effort and must grant each Azure AD user access to only the EC2 instances that are tagged with the user's respective department name. Which condition key should the DevOps engineer include in the custom permissions policies to meet these requirements?

- A.

```
"Condition": {
  "ForAllValues:StringEquals": {
    "aws:TagKeys": ["department"]
  }
}
```
- B.

```
"Condition": {
  "StringEquals": {
    "aws:PrincipalTag/department": "${aws:ResourceTag/department}"
  }
}
```
- C.

```
"Condition": {  
  "StringEquals": {  
    "ec2:ResourceTag/department": "${aws:PrincipalTag/department}"  
  }  
}
```

D.

```
"Condition": {  
  "ForAllValues:StringEquals": {  
    "ec2:ResourceTag/department": ["d1", "d2", "d3"]  
  }  
}
```

Answer: C

Explanation:

<https://docs.aws.amazon.com/singlesignon/latest/userguide/configure-abac.html>

NEW QUESTION 4

A company is performing vulnerability scanning for all Amazon EC2 instances across many accounts. The accounts are in an organization in AWS Organizations. Each account's VPCs are attached to a shared transit gateway. The VPCs send traffic to the internet through a central egress VPC. The company has enabled Amazon Inspector in a delegated administrator account and has enabled scanning for all member accounts.

A DevOps engineer discovers that some EC2 instances are listed in the "not scanning" tab in Amazon Inspector.

Which combination of actions should the DevOps engineer take to resolve this issue? (Choose three.)

- A. Verify that AWS Systems Manager Agent is installed and is running on the EC2 instances that Amazon Inspector is not scanning.
- B. Associate the target EC2 instances with security groups that allow outbound communication on port 443 to the AWS Systems Manager service endpoint.
- C. Grant `inspector:StartAssessmentRun` permissions to the IAM role that the DevOps engineer is using.
- D. Configure EC2 Instance Connect for the EC2 instances that Amazon Inspector is not scanning.
- E. Associate the target EC2 instances with instance profiles that grant permissions to communicate with AWS Systems Manager.
- F. Create a managed-instance activation
- G. Use the Activation Code and the Activation ID to register the EC2 instances.

Answer: ABE

Explanation:

<https://docs.aws.amazon.com/inspector/latest/user/scanning-ec2.html>

NEW QUESTION 5

A company has deployed an application in a production VPC in a single AWS account. The application is popular and is experiencing heavy usage. The company's security team wants to add additional security, such as AWS WAF, to the application deployment. However, the application's product manager is concerned about cost and does not want to approve the change unless the security team can prove that additional security is necessary.

The security team believes that some of the application's demand might come from users that have IP addresses that are on a deny list. The security team provides the deny list to a DevOps engineer. If any of the IP addresses on the deny list access the application, the security team wants to receive automated notification in near real time so that the security team can document that the application needs additional security. The DevOps engineer creates a VPC flow log for the production VPC.

Which set of additional steps should the DevOps engineer take to meet these requirements MOST cost-effectively?

- A. Create a log group in Amazon CloudWatch Log
- B. Configure the VPC flow log to capture accepted traffic and to send the data to the log group
- C. Create an Amazon CloudWatch metric filter for IP addresses on the deny list
- D. Create a CloudWatch alarm with the metric filter as input
- E. Set the period to 5 minutes and the datapoints to alarm to 1. Use an Amazon Simple Notification Service (Amazon SNS) topic to send alarm notices to the security team.
- F. Create an Amazon S3 bucket for log file
- G. Configure the VPC flow log to capture all traffic and to send the data to the S3 bucket
- H. Configure Amazon Athena to return all log files in the S3 bucket for IP addresses on the deny list
- I. Configure Amazon QuickSight to accept data from Athena and to publish the data as a dashboard that the security team can access
- J. Create a threshold alert of 1 for successful access
- K. Configure the alert to automatically notify the security team as frequently as possible when the alert threshold is met.
- L. Create an Amazon S3 bucket for log file
- M. Configure the VPC flow log to capture accepted traffic and to send the data to the S3 bucket
- N. Configure an Amazon OpenSearch Service cluster and domain for the log file
- O. Create an AWS Lambda function to retrieve the logs from the S3 bucket, format the logs, and load the logs into the OpenSearch Service cluster
- P. Schedule the Lambda function to run every 5 minutes
- Q. Configure an alert and condition in OpenSearch Service to send alerts to the security team through an Amazon Simple Notification Service (Amazon SNS) topic when access from the IP addresses on the deny list is detected.
- R. Create a log group in Amazon CloudWatch Log
- S. Create an Amazon S3 bucket to hold query results. Configure the VPC flow log to capture all traffic and to send the data to the log group
- T. Deploy an Amazon Athena CloudWatch connector in AWS Lambda
- U. Connect the connector to the log group
- V. Configure Athena to periodically query for all accepted traffic from the IP addresses on the deny list and to store the results in the S3 bucket
- W. Configure an S3 event notification to automatically notify the security team through an Amazon Simple Notification Service (Amazon SNS) topic when new objects are added to the S3 bucket.

Answer: A

NEW QUESTION 6

A company requires an RPO of 2 hours and an RTO of 10 minutes for its data and application at all times. An application uses a MySQL database and Amazon EC2 web servers. The development team needs a strategy for failover and disaster recovery. Which combination of deployment strategies will meet these requirements? (Select TWO.)

- A. Create an Amazon Aurora cluster in one Availability Zone across multiple Regions as the data store. Use Aurora's automatic recovery capabilities in the event of a disaster.
- B. Create an Amazon Aurora global database in two Regions as the data store.
- C. In the event of a failure, promote the secondary Region as the primary for the application.
- D. Create an Amazon Aurora multi-master cluster across multiple Regions as the data store.
- E. Use a Network Load Balancer to balance the database traffic in different Regions.
- F. Set up the application in two Regions and use Amazon Route 53 failover-based routing that points to the Application Load Balancers in both Regions.
- G. Use health checks to determine the availability in a given Region.
- H. Use Auto Scaling groups in each Region to adjust capacity based on demand.
- I. Set up the application in two Regions and use a multi-Region Auto Scaling group behind Application Load Balancers to manage the capacity based on demand.
- J. In the event of a disaster, adjust the Auto Scaling group's desired instance count to increase baseline capacity in the failover Region.

Answer: BD

NEW QUESTION 7

A large enterprise is deploying a web application on AWS. The application runs on Amazon EC2 instances behind an Application Load Balancer. The instances run in an Auto Scaling group across multiple Availability Zones. The application stores data in an Amazon RDS for Oracle DB instance and Amazon DynamoDB. There are separate environments for development testing and production. What is the MOST secure and flexible way to obtain password credentials during deployment?

- A. Retrieve an access key from an AWS Systems Manager securestring parameter to access AWS services. Retrieve the database credentials from a Systems Manager SecureString parameter.
- B. Launch the EC2 instances with an EC2 IAM role to access AWS services. Retrieve the database credentials from AWS Secrets Manager.
- C. Retrieve an access key from an AWS Systems Manager plaintext parameter to access AWS services. Retrieve the database credentials from a Systems Manager SecureString parameter.
- D. Launch the EC2 instances with an EC2 IAM role to access AWS services. Store the database passwords in an encrypted config file with the application artifacts.

Answer: B

Explanation:

AWS Secrets Manager is a secrets management service that helps you protect access to your applications, services, and IT resources. This service enables you to easily rotate, manage, and retrieve database credentials, API keys, and other secrets throughout their lifecycle. Using Secrets Manager, you can secure and manage secrets used to access resources in the AWS Cloud, on third-party services, and on-premises. SSM parameter store and AWS Secret manager are both a secure option. However, Secrets manager is more flexible and has more options like password generation. Reference: <https://www.1strategy.com/blog/2019/02/28/aws-parameter-store-vs-aws-secrets-manager/>

NEW QUESTION 8

A company wants to set up a continuous delivery pipeline. The company stores application code in a private GitHub repository. The company needs to deploy the application components to Amazon Elastic Container Service (Amazon ECS), Amazon EC2, and AWS Lambda. The pipeline must support manual approval actions. Which solution will meet these requirements?

- A. Use AWS CodePipeline with Amazon EC2.
- B. Amazon EC2, and Lambda as deployment providers.
- C. Use AWS CodePipeline with AWS CodeDeploy as the deployment provider.
- D. Use AWS CodePipeline with AWS Elastic Beanstalk as the deployment provider.
- E. Use AWS CodeDeploy with GitHub integration to deploy the application.

Answer: B

Explanation:

<https://docs.aws.amazon.com/codedeploy/latest/userguide/deployment-steps.html>

NEW QUESTION 9

A company runs an application on one Amazon EC2 instance. Application metadata is stored in Amazon S3 and must be retrieved if the instance is restarted. The instance must restart or relaunch automatically if the instance becomes unresponsive. Which solution will meet these requirements?

- A. Create an Amazon CloudWatch alarm for the StatusCheckFailed metric.
- B. Use the recover action to stop and start the instance.
- C. Use an S3 event notification to push the metadata to the instance when the instance is back up and running.
- D. Configure AWS OpsWorks, and use the auto healing feature to stop and start the instance.
- E. Use a lifecycle event in OpsWorks to pull the metadata from Amazon S3 and update it on the instance.
- F. Use EC2 Auto Recovery to automatically stop and start the instance in case of a failure.
- G. Use an S3 event notification to push the metadata to the instance when the instance is back up and running.
- H. Use AWS CloudFormation to create an EC2 instance that includes the UserData property for the EC2 resource.
- I. Add a command in UserData to retrieve the application metadata from Amazon S3.

Answer: B

Explanation:

<https://aws.amazon.com/blogs/mt/how-to-set-up-aws-opsworks-stacks-auto-healing-notifications-in-amazon-clo>

NEW QUESTION 10

A DevOps team is merging code revisions for an application that uses an Amazon RDS Multi-AZ DB cluster for its production database. The DevOps team uses continuous integration to periodically verify that the application works. The DevOps team needs to test the changes before the changes are deployed to the production database.

Which solution will meet these requirements'?

- A. Use a buildspec file in AWS CodeBuild to restore the DB cluster from a snapshot of the production database run integration tests, and drop the restored database after verification.
- B. Deploy the application to productio
- C. Configure an audit log of data control language (DCL) operations to capture database activities to perform if verification fails.
- D. Create a snapshot of the DB duster before deploying the application Use the Update requires Replacement property on the DB instance in AWS CloudFormation to deploy the application and apply the changes.
- E. Ensure that the DB cluster is a Multi-AZ deploymen
- F. Deploy the application with the update
- G. Fail over to the standby instance if verification fails.

Answer: A

Explanation:

This solution will meet the requirements because it will create a temporary copy of the production database using a snapshot, run the integration tests on the copy, and delete the copy after the tests are done. This way, the production database will not be affected by the code revisions, and the DevOps team can test the changes before deploying them to production. A buildspec file is a YAML file that contains the commands and settings that CodeBuild uses to run a build1. The buildspec file can specify the steps to restore the DB cluster from a snapshot, run the integration tests, and drop the restored database2

NEW QUESTION 10

A DevOps engineer at a company is supporting an AWS environment in which all users use AWS IAM Identity Center (AWS Single Sign-On). The company wants to immediately disable credentials of any new IAM user and wants the security team to receive a notification.

Which combination of steps should the DevOps engineer take to meet these requirements? (Choose three.)

- A. Create an Amazon EventBridge rule that reacts to an IAM CreateUser API call in AWS CloudTrail.
- B. Create an Amazon EventBridge rule that reacts to an IAM GetLoginProfile API call in AWS CloudTrail.
- C. Create an AWS Lambda function that is a target of the EventBridge rul
- D. Configure the Lambda function to disable any access keys and delete the login profiles that are associated with the IAM user.
- E. Create an AWS Lambda function that is a target of the EventBridge rul
- F. Configure the Lambda function to delete the login profiles that are associated with the IAM user.
- G. Create an Amazon Simple Notification Service (Amazon SNS) topic that is a target of the EventBridge rul
- H. Subscribe the security team's group email address to the topic.
- I. Create an Amazon Simple Queue Service (Amazon SQS) queue that is a target of the Lambda function.Subscribe the security team's group email address to the queue.

Answer: ACE

NEW QUESTION 15

A video-sharing company stores its videos in Amazon S3. The company has observed a sudden increase in video access requests, but the company does not know which videos are most popular. The company needs to identify the general access pattern for the video files. This pattern includes the number of users who access a certain file on a given day, as well as the numb A DevOps engineer manages a large commercial website that runs on Amazon EC2 The website uses Amazon Kinesis Data Streams to collect and process web togs The DevOps engineer manages the Kinesis consumer application, which also runs on Amazon EC2 Sudden increases of data cause the Kinesis consumer application to (all behind and the Kinesis data streams drop records before the records can be processed The DevOps engineer must implement a solution to improve stream handling

Which solution meets these requirements with the MOST operational efficiency" er of pull requests for certain files.

How can the company meet these requirements with the LEAST amount of effort?

- A. Activate S3 server access login
- B. Import the access logs into an Amazon Aurora databas
- C. Use an Aurora SQL query to analyze the access patterns.
- D. Activate S3 server access login
- E. Use Amazon Athena to create an external table with the log file
- F. Use Athena to create a SQL query to analyze the access patterns.
- G. Invoke an AWS Lambda function for every S3 object access even
- H. Configure the Lambda function to write the file access information, such as use
- I. S3 bucket, and file key, to an Amazon Aurora databas
- J. Use an Aurora SQL query to analyze the access patterns.
- K. Record an Amazon CloudWatch Logs log message for every S3 object access even
- L. Configure a CloudWatch Logs log stream to write the file access information, such as user, S3 bucket, and file key, to an Amazon Kinesis Data Analytics for SQL applicatio
- M. Perform a sliding window analysis.

Answer: B

Explanation:

Activating S3 server access logging and using Amazon Athena to create an external table with the log files is the easiest and most cost-effective way to analyze access patterns. This option requires minimal setup and allows for quick analysis of the access patterns with SQL queries. Additionally, Amazon Athena scales automatically to match the query load, so there is no need for additional infrastructure provisioning or management.

NEW QUESTION 18

A company must encrypt all AMIs that the company shares across accounts. A DevOps engineer has access to a source account where an unencrypted custom AMI has been built. The DevOps engineer also has access to a target account where an Amazon EC2 Auto Scaling group will launch EC2 instances from the AMI.

The DevOps engineer must share the AMI with the target account.

The company has created an AWS Key Management Service (AWS KMS) key in the source account. Which additional steps should the DevOps engineer perform to meet the requirements? (Choose three.)

- A. In the source account, copy the unencrypted AMI to an encrypted AM
- B. Specify the KMS key in the copy action.
- C. In the source account, copy the unencrypted AMI to an encrypted AM
- D. Specify the default Amazon Elastic Block Store (Amazon EBS) encryption key in the copy action.
- E. In the source account, create a KMS grant that delegates permissions to the Auto Scaling group service-linked role in the target account.
- F. In the source account, modify the key policy to give the target account permissions to create a gran
- G. In the target account, create a KMS grant that delegates permissions to the Auto Scaling groupservice-linked role.
- H. In the source account, share the unencrypted AMI with the target account.
- I. In the source account, share the encrypted AMI with the target account.

Answer: ADF

Explanation:

The Auto Scaling group service-linked role must have a specific grant in the source account in order to decrypt the encrypted AMI. This is because the service-linked role does not have permissions to assume the default IAM role in the source account.

The following steps are required to meet the requirements:

- In the source account, copy the unencrypted AMI to an encrypted AMI. Specify the KMS key in the copy action.
- In the source account, create a KMS grant that delegates permissions to the Auto Scaling group service-linked role in the target account.
- In the source account, share the encrypted AMI with the target account.
- In the target account, attach the KMS grant to the Auto Scaling group service-linked role.

The first three steps are the same as the steps that I described earlier. The fourth step is required to grant the Auto Scaling group service-linked role permissions to decrypt the AMI in the target account.

NEW QUESTION 23

A company uses AWS Organizations and AWS Control Tower to manage all the company's AWS accounts. The company uses the Enterprise Support plan. A DevOps engineer is using Account Factory for Terraform (AFT) to provision new accounts. When new accounts are provisioned, the DevOps engineer notices that the support plan for the new accounts is set to the Basic Support plan. The DevOps engineer needs to implement a solution to provision the new accounts with the Enterprise Support plan. Which solution will meet these requirements?

- A. Use an AWS Config conformance pack to deploy the account-part-of-organizations AWS Config rule and to automatically remediate any noncompliant accounts.
- B. Create an AWS Lambda function to create a ticket for AWS Support to add the account to the Enterprise Support pla
- C. Grant the Lambda function the support:ResolveCase permission.
- D. Add an additional value to the control_tower_parameters input to set the AWSEnterpriseSupport parameter as the organization's management account number.
- E. Set the aft_feature_enterprise_support feature flag to True in the AFT deployment input configuration.Redeploy AFT and apply the changes.

Answer: D

Explanation:

AWS Organizations is a service that helps to manage multiple AWS accounts. AWS Control Tower is a service that makes it easy to set up and govern secure, compliant multi-account AWS environments. Account Factory for Terraform (AFT) is an AWS Control Tower feature that provisions new accounts using Terraform templates. To provision new accounts with the Enterprise Support plan, the DevOps engineer can set the aft_feature_enterprise_support feature flag to True in the AFT deployment input configuration. This flag enables the Enterprise Support plan for newly provisioned accounts.

<https://docs.aws.amazon.com/controltower/latest/userguide/aft-feature-options.html>

NEW QUESTION 27

A DevOps engineer needs to apply a core set of security controls to an existing set of AWS accounts. The accounts are in an organization in AWS Organizations. Individual teams will administer individual accounts by using the AdministratorAccess AWS managed policy. For all accounts. AWS CloudTrail and AWS Config must be turned on in all available AWS Regions. Individual account administrators must not be able to edit or delete any of the baseline resources. However, individual account administrators must be able to edit or delete their own CloudTrail trails and AWS Config rules. Which solution will meet these requirements in the MOST operationally efficient way?

- A. Create an AWS CloudFormation template that defines the standard account resource
- B. Deploy the template to all accounts from the organization's management account by using CloudFormation StackSet
- C. Set the stack policy to deny Update:Delete actions.
- D. Enable AWS Control Towe
- E. Enroll the existing accounts in AWS Control Towe
- F. Grant the individual account administrators access to CloudTrail and AWS Config.
- G. Designate an AWS Config management accoun
- H. Create AWS Config recorders in all accounts by using AWS CloudFormation StackSet
- I. Deploy AWS Config rules to the organization by using the AWS Config management account
- J. Create a CloudTrail organization trail in the organization's management account
- K. Deny modification or deletion of the AWS Config recorders by using an SCP.
- L. Create an AWS CloudFormation template that defines the standard account resource
- M. Deploy the template to all accounts from the organization's management account by using Cloud Formation StackSets Create an SCP that prevents updates or deletions to CloudTrail resources or AWS Config resources unless the principal is an administrator of the organization's management account.

Answer: D

NEW QUESTION 28

A DevOps engineer is creating an AWS CloudFormation template to deploy a web service. The web service will run on Amazon EC2 instances in a private subnet behind an Application Load Balancer (ALB). The DevOps engineer must ensure that the service can accept requests from clients that have IPv6 addresses. What should the DevOps engineer do with the CloudFormation template so that IPv6 clients can access the web service?

- A. Add an IPv6 CIDR block to the VPC and the private subnet for the EC2 instance
- B. Create route table entries for the IPv6 network, use EC2 instance types that support IPv6, and assign IPv6 addresses to each EC2 instance.
- C. Assign each EC2 instance an IPv6 Elastic IP address
- D. Create a target group, and add the EC2 instances as target
- E. Create a listener on port 443 of the ALB, and associate the target group with the ALB.
- F. Replace the ALB with a Network Load Balancer (NLB). Add an IPv6 CIDR block to the VPC and subnets for the NLB, and assign the NLB an IPv6 Elastic IP address.
- G. Add an IPv6 CIDR block to the VPC and subnets for the AL
- H. Create a listener on port 443. and specify the dualstack IP address type on the AL
- I. Create a target group, and add the EC2 instances as target
- J. Associate the target group with the ALB.

Answer: D

Explanation:

it involves adding an IPv6 CIDR block to the VPC and subnets for the ALB and specifying the dualstack IP address type on the ALB listener. This allows the ALB to listen on both IPv4 and IPv6 addresses, and forward requests to the EC2 instances that are added as targets to the target group associated with the ALB.

NEW QUESTION 30

A company requires that its internally facing web application be highly available. The architecture is made up of one Amazon EC2 web server instance and one NAT instance that provides outbound internet access for updates and accessing public data.

Which combination of architecture adjustments should the company implement to achieve high availability? (Choose two.)

- A. Add the NAT instance to an EC2 Auto Scaling group that spans multiple Availability Zone
- B. Update the route tables.
- C. Create additional EC2 instances spanning multiple Availability Zone
- D. Add an Application Load Balancer to split the load between them.
- E. Configure an Application Load Balancer in front of the EC2 instance
- F. Configure Amazon CloudWatch alarms to recover the EC2 instance upon host failure.
- G. Replace the NAT instance with a NAT gateway in each Availability Zone
- H. Update the route tables.
- I. Replace the NAT instance with a NAT gateway that spans multiple Availability Zone
- J. Update the route tables.

Answer: BD

Explanation:

<https://docs.aws.amazon.com/vpc/latest/userguide/vpc-nat-gateway.html>

NEW QUESTION 34

A company's DevOps engineer is working in a multi-account environment. The company uses AWS Transit Gateway to route all outbound traffic through a network operations account. In the network operations account all account traffic passes through a firewall appliance for inspection before the traffic goes to an internet gateway.

The firewall appliance sends logs to Amazon CloudWatch Logs and includes event severities of CRITICAL, HIGH, MEDIUM, LOW, and INFO. The security team wants to receive an alert if any CRITICAL events occur.

What should the DevOps engineer do to meet these requirements?

- A. Create an Amazon CloudWatch Synthetics canary to monitor the firewall stat
- B. If the firewall reaches a CRITICAL state or logs a CRITICAL event use a CloudWatch alarm to publish a notification to an Amazon Simple Notification Service (Amazon SNS) topic Subscribe the security team's email address to the topic.
- C. Create an Amazon CloudWatch metric filter by using a search for CRITICAL events Publish a custom metric for the findin
- D. Use a CloudWatch alarm based on the custom metric to publish a notification to an Amazon Simple Notification Service (Amazon SNS) topic
- E. Subscribe the security team's email address to the topic.
- F. Enable Amazon GuardDuty in the network operations account
- G. Configure GuardDuty to monitor flow logs Create an Amazon EventBridge event rule that is invoked by GuardDuty events that are CRITICAL Define an Amazon Simple Notification Service (Amazon SNS) topic as a target Subscribe the security team's email address to the topic.
- H. Use AWS Firewall Manager to apply consistent policies across all account
- I. Create an Amazon.EventBridge event rule that is invoked by Firewall Manager events that are CRITICAL Define an Amazon Simple Notification Service (Amazon SNS) topic as a target Subscribe the security team's email address to the topic.

Answer: B

Explanation:

"The firewall appliance sends logs to Amazon CloudWatch Logs and includes event severities of CRITICAL, HIGH, MEDIUM, LOW, and INFO"

NEW QUESTION 36

A company has migrated its container-based applications to Amazon EKS and want to establish automated email notifications. The notifications sent to each email address are for specific activities related to EKS components. The solution will include Amazon SNS topics and an AWS Lambda function to evaluate incoming log events and publish messages to the correct SNS topic.

Which logging solution will support these requirements?

- A. Enable Amazon CloudWatch Logs to log the EKS component
- B. Create a CloudWatch subscription filter for each component with Lambda as the subscription feed destination.
- C. Enable Amazon CloudWatch Logs to log the EKS component
- D. Create CloudWatch Logs Insights queries linked to Amazon EventBridge events that invoke Lambda.
- E. Enable Amazon S3 logging for the EKS component
- F. Configure an Amazon CloudWatch subscription filter for each component with Lambda as the subscription feed destination.
- G. Enable Amazon S3 logging for the EKS component
- H. Configure S3 PUT Object event notifications with AWS Lambda as the destination.

Answer: A

Explanation:

<https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/SubscriptionFilters.html#LambdaFunctionExamp>
<https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/SubscriptionFilters.html>

NEW QUESTION 38

A company has an organization in AWS Organizations. The organization includes workload accounts that contain enterprise applications. The company centrally manages users from an operations account. No users can be created in the workload accounts. The company recently added an operations team and must provide the operations team members with administrator access to each workload account.

Which combination of actions will provide this access? (Choose three.)

- A. Create a SysAdmin role in the operations account
- B. Attach the AdministratorAccess policy to the role. Modify the trust relationship to allow the sts:AssumeRole action from the workload accounts.
- C. Create a SysAdmin role in each workload account
- D. Attach the AdministratorAccess policy to the role. Modify the trust relationship to allow the sts:AssumeRole action from the operations account.
- E. Create an Amazon Cognito identity pool in the operations account
- F. Attach the SysAdmin role as an authenticated role.
- G. In the operations account, create an IAM user for each operations team member.
- H. In the operations account, create an IAM user group that is named SysAdmin
- I. Add an IAM policy that allows the sts:AssumeRole action for the SysAdmin role in each workload account
- J. Add all operations team members to the group.
- K. Create an Amazon Cognito user pool in the operations account
- L. Create an Amazon Cognito user for each operations team member.

Answer: BDE

Explanation:

https://docs.aws.amazon.com/IAM/latest/UserGuide/tutorial_cross-account-with-roles.html

NEW QUESTION 42

A company is deploying a new application that uses Amazon EC2 instances. The company needs a solution to query application logs and AWS account API activity. Which solution will meet these requirements?

- A. Use the Amazon CloudWatch agent to send logs from the EC2 instances to Amazon CloudWatch Logs. Configure AWS CloudTrail to deliver the API logs to Amazon S3. Use CloudWatch to query both sets of logs.
- B. Use the Amazon CloudWatch agent to send logs from the EC2 instances to Amazon CloudWatch Logs. Configure AWS CloudTrail to deliver the API logs to CloudWatch Logs. Use CloudWatch Logs Insights to query both sets of logs.
- C. Use the Amazon CloudWatch agent to send logs from the EC2 instances to Amazon Kinesis. Configure AWS CloudTrail to deliver the API logs to Kinesis. Use Kinesis to load the data into Amazon Redshift. Use Amazon Redshift to query both sets of logs.
- D. Use the Amazon CloudWatch agent to send logs from the EC2 instances to Amazon S3. Use AWS CloudTrail to deliver the API logs to Amazon S3. Use Amazon Athena to query both sets of logs in Amazon S3.

Answer: D

Explanation:

This solution will meet the requirements because it will use Amazon S3 as a common data lake for both the application logs and the API logs. Amazon S3 is a service that provides scalable, durable, and secure object storage for any type of data. You can use the Amazon CloudWatch agent to send logs from your EC2 instances to S3 buckets, and use AWS CloudTrail to deliver the API logs to S3 buckets as well. You can also use Amazon Athena to query both sets of logs in S3 using standard SQL, without loading or transforming them. Athena is a serverless interactive query service that allows you to analyze data in S3 using a variety of data formats, such as JSON, CSV, Parquet, and ORC.

NEW QUESTION 46

A company's production environment uses an AWS CodeDeploy blue/green deployment to deploy an application. The deployment includes Amazon EC2 Auto Scaling groups that launch instances that run Amazon Linux 2.

A working appspec. yml file exists in the code repository and contains the following text.

```
version: 0.0
os: linux
files:
  - source: /
    destination: /var/www/html/application
```

A DevOps engineer needs to ensure that a script downloads and installs a license file onto the instances before the replacement instances start to handle request traffic. The DevOps engineer adds a hooks section to the appspec. yml file.

Which hook should the DevOps engineer use to run the script that downloads and installs the license file?

- A. AfterBlockTraffic
- B. BeforeBlockTraffic
- C. BeforeInstall
- D. DownloadBundle

Answer: C

Explanation:

This hook runs before the new application version is installed on the replacement instances. This is the best place to run the script because it ensures that the license file is downloaded and installed before the replacement instances start to handle request traffic. If you use any other hook, you may encounter errors or inconsistencies in your application.

NEW QUESTION 47

A company recently migrated its legacy application from on-premises to AWS. The application is hosted on Amazon EC2 instances behind an Application Load Balancer which is behind Amazon API Gateway. The company wants to ensure users experience minimal disruptions during any deployment of a new version of the application. The company also wants to ensure it can quickly roll back updates if there is an issue. Which solution will meet these requirements with MINIMAL changes to the application?

- A. Introduce changes as a separate environment parallel to the existing one Configure API Gateway to use a canary release deployment to send a small subset of user traffic to the new environment.
- B. Introduce changes as a separate environment parallel to the existing one Update the application's DNS alias records to point to the new environment.
- C. Introduce changes as a separate target group behind the existing Application Load Balancer Configure API Gateway to route user traffic to the new target group in steps.
- D. Introduce changes as a separate target group behind the existing Application Load Balancer Configure API Gateway to route all traffic to the Application Load Balancer which then sends the traffic to the new target group.

Answer: A

Explanation:

API Gateway supports canary deployment on a deployment stage before you direct all traffic to that stage. A parallel environment means we will create a new ALB and a target group that will target a new set of EC2 instances on which the newer version of the app will be deployed. So the canary setting associated to the new version of the API will connect with the new ALB instance which in turn will direct the traffic to the new EC2 instances on which the newer version of the application is deployed.

NEW QUESTION 49

A company has enabled all features for its organization in AWS Organizations. The organization contains 10 AWS accounts. The company has turned on AWS CloudTrail in all the accounts. The company expects the number of AWS accounts in the organization to increase to 500 during the next year. The company plans to use multiple OUs for these accounts.

The company has enabled AWS Config in each existing AWS account in the organization. A DevOps engineer must implement a solution that enables AWS Config automatically for all future AWS accounts that are created in the organization. Which solution will meet this requirement?

- A. In the organization's management account, create an Amazon EventBridge rule that reacts to a CreateAccount API call.
- B. Configure the rule to invoke an AWS Lambda function that enables trusted access to AWS Config for the organization.
- C. In the organization's management account, create an AWS CloudFormation stack set to enable AWS Config.
- D. Configure the stack set to deploy automatically when an account is created through Organizations.
- E. In the organization's management account, create an SCP that allows the appropriate AWS Config API calls to enable AWS Config.
- F. Apply the SCP to the root-level OU.
- G. In the organization's management account, create an Amazon EventBridge rule that reacts to a CreateAccount API call.
- H. Configure the rule to invoke an AWS Systems Manager Automation runbook to enable AWS Config for the account.

Answer: B

NEW QUESTION 51

A company has containerized all of its in-house quality control applications. The company is running Jenkins on Amazon EC2 instances, which require patching and upgrading. The compliance officer has requested a DevOps engineer begin encrypting build artifacts since they contain company intellectual property. What should the DevOps engineer do to accomplish this in the MOST maintainable manner?

- A. Automate patching and upgrading using AWS Systems Manager on EC2 instances and encrypt Amazon EBS volumes by default.
- B. Deploy Jenkins to an Amazon ECS cluster and copy build artifacts to an Amazon S3 bucket with default encryption enabled.
- C. Leverage AWS CodePipeline with a build action and encrypt the artifacts using AWS Secrets Manager.
- D. Use AWS CodeBuild with artifact encryption to replace the Jenkins instance running on EC2 instances.

Answer: D

Explanation:

The following are the steps involved in accomplishing this in the most maintainable manner:

- Configure CodeBuild to encrypt the build artifacts using AWS Secrets Manager.
- Deploy the containerized quality control applications to CodeBuild.

This approach is the most maintainable because it eliminates the need to manage Jenkins on EC2 instances. CodeBuild is a managed service, so the DevOps engineer does not need to worry about patching or upgrading the service.

<https://docs.aws.amazon.com/codebuild/latest/userguide/security-encryption.html> Build artifact encryption - CodeBuild requires access to an AWS KMS CMK in order to encrypt its build output artifacts. By default, CodeBuild uses an AWS Key Management Service CMK for Amazon S3 in your AWS account. If you do not want to use this CMK, you must create and configure a customer-managed CMK. For more information Creating keys.

NEW QUESTION 54

A company wants to use a grid system for a proprietary enterprise in-memory data store on top of AWS. This system can run in multiple server nodes in any Linux-based distribution. The system must be able to reconfigure the entire cluster every time a node is added or removed. When adding or removing nodes an `/etc./cluster/nodes` config file must be updated listing the IP addresses of the current node members of that cluster.

The company wants to automate the task of adding new nodes to a cluster. What can a DevOps engineer do to meet these requirements?

- A. Use AWS OpsWorks Stacks to layer the server nodes of that cluster.
- B. Create a Chef recipe that populates the content of the `/etc./cluster/nodes` config file and restarts the service by using the current members of the layer.
- C. Assign that recipe to the Configure lifecycle event.
- D. Put the file `nodes` config in version control.
- E. Create an AWS CodeDeploy deployment configuration and deployment group based on an Amazon EC2 tag value for the cluster node.
- F. When adding a new node to the cluster update the file with all tagged instances and make a commit in version control.
- G. Deploy the new file and restart the services.
- H. Create an Amazon S3 bucket and upload a version of the `/etc./cluster/nodes` config file. Create a crontab script that will poll for that S3 file and download it frequently.
- I. Use a process manager such as Monit or systemd, to restart the cluster services when it detects that the new file was modified.

- J. When adding a node to the cluster edit the file's most recent members Upload the new file to the S3 bucket.
- K. Create a user data script that lists all members of the current security group of the cluster and automatically updates the /etc/cluster/. nodes confi
- L. Tile whenever a new instance is added to the cluster.

Answer: A

Explanation:

You can run custom recipes manually, but the best approach is usually to have AWS OpsWorks Stacks run them automatically. Every layer has a set of built-in recipes assigned each of five lifecycle events—Setup, Configure, Deploy, Undeploy, and Shutdown. Each time an event occurs for an instance, AWS OpsWorks Stacks runs the associated recipes for each of the instance's layers, which handle the corresponding tasks. For example, when an instance finishes booting, AWS OpsWorks Stacks triggers a Setup event. This event runs the associated layer's Setup recipes, which typically handle tasks such as installing and configuring packages

NEW QUESTION 57

A company has chosen AWS to host a new application. The company needs to implement a multi-account strategy. A DevOps engineer creates a new AWS account and an organization in AWS Organizations. The DevOps engineer also creates the OU structure for the organization and sets up a landing zone by using AWS Control Tower.

The DevOps engineer must implement a solution that automatically deploys resources for new accounts that users create through AWS Control Tower Account Factory. When a user creates a new account, the solution must apply AWS CloudFormation templates and SCPs that are customized for the OU or the account to automatically deploy all the resources that are attached to the account. All the OUs are enrolled in AWS Control Tower.

Which solution will meet these requirements in the MOST automated way?

- A. Use AWS Service Catalog with AWS Control Towe
- B. Create portfolios and products in AWS ServiceCatalo
- C. Grant granular permissions to provision these resource
- D. Deploy SCPs by using the AWS CLI and JSON documents.
- E. Deploy CloudFormation stack sets by using the required template
- F. Enable automatic deployment.Deploy stack instances to the required account
- G. Deploy a CloudFormation stack set to the organization's management account to deploy SCPs.
- H. Create an Amazon EventBridge rule to detect the CreateManagedAccount even
- I. Configure AWS Service Catalog as the target to deploy resources to any new account
- J. Deploy SCPs by using the AWS CLI and JSON documents.
- K. Deploy the Customizations for AWS Control Tower (CfCT) solutio
- L. Use an AWS CodeCommit repository as the sourc
- M. In the repository, create a custom package that includes the CloudFormation templates and the SCP JSON documents.

Answer: D

Explanation:

The CfCT solution is designed for the exact purpose stated in the question. It extends the capabilities of AWS Control Tower by providing you with a way to automate resource provisioning and apply custom configurations across all AWS accounts created in the Control Tower environment. This enables the company to implement additional account customizations when new accounts are provisioned via the Control Tower Account Factory. The CloudFormation templates and SCPs can be added to a CodeCommit repository and will be automatically deployed to new accounts when they are created. This provides a highly automated solution that does not require manual intervention to deploy resources and SCPs to new accounts.

NEW QUESTION 61

A company recently created a new AWS Control Tower landing zone in a new organization in AWS Organizations. The landing zone must be able to demonstrate compliance with the Center for Internet Security (CIS) Benchmarks for AWS Foundations.

The company's security team wants to use AWS Security Hub to view compliance across all accounts Only the security team can be allowed to view aggregated Security Hub Findings. In addition specific users must be able to view findings from their own accounts within the organization All accounts must be enrolled in Security Hub after the accounts are created.

Which combination of steps will meet these requirements in the MOST automated way? (Select THREE.)

- A. Turn on trusted access for Security Hub in the organization's management account
- B. Create a new security account by using AWS Control Tower Configure the new security account as the delegated administrator account for Security Hu
- C. In the new security account provid
- D. Security Hub with the CIS Benchmarks for AWS Foundations standards.
- E. Turn on trusted access for Security Hub in the organ ration's management account
- F. From the management account, provide Security Hub with the CIS Benchmarks for AWS Foundations standards.
- G. Create an AWS IAM identity Center (AWS Single Sign-On) permission set that includes the required permissions Use the CreateAccountAssignment API operation to associate the security team users with the permission set and with the delegated security account.
- H. Create an SCP that explicitly denies any user who is not on the security team from accessing Security Hub.
- I. In Security Hub, turn on automatic enablement.
- J. In the organization's management account create an Amazon EventBridge rule that reacts to the CreateManagedAccount event Create an AWS Lambda function that uses the Security Hub CreateMembers API operation to add new accounts to Security Hu
- K. Configure the EventBridge rule to invoke the Lambda function.

Answer: ACE

Explanation:

<https://docs.aws.amazon.com/securityhub/latest/userguide/accounts-orgs-auto-enable.html>

NEW QUESTION 65

A production account has a requirement that any Amazon EC2 instance that has been logged in to manually must be terminated within 24 hours. All applications in the production account are using Auto Scaling groups with the Amazon CloudWatch Logs agent configured.

How can this process be automated?

- A. Create a CloudWatch Logs subscription to an AWS Step Functions applicatio
- B. Configure an AWS Lambda function to add a tag to the EC2 instance that produced the login event and mark the instance to be decommissioned
- C. Create an Amazon EventBridge rule to invoke a second Lambda function once a day that will terminate all instances with this tag.

- D. Create an Amazon CloudWatch alarm that will be invoked by the login even
- E. Send the notification to an Amazon Simple Notification Service (Amazon SNS) topic that the operations team is subscribed to, and have them terminate the EC2 instance within 24 hours.
- F. Create an Amazon CloudWatch alarm that will be invoked by the login even
- G. Configure the alarm to send to an Amazon Simple Queue Service (Amazon SQS) queue
- H. Use a group of worker instances to process messages from the queue, which then schedules an Amazon EventBridge rule to be invoked.
- I. Create a CloudWatch Logs subscription to an AWS Lambda function
- J. Configure the function to add a tag to the EC2 instance that produced the login event and mark the instance to be decommissioned. Create an Amazon EventBridge rule to invoke a daily Lambda function that terminates all instances with this tag.

Answer: D

Explanation:

"You can use subscriptions to get access to a real-time feed of log events from CloudWatch Logs and have it delivered to other services such as an Amazon Kinesis stream, an Amazon Kinesis Data Firehose stream, or AWS Lambda for custom processing, analysis, or loading to other systems. When log events are sent to the receiving service, they are Base64 encoded and compressed with the gzip format." See <https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/Subscriptions.html>

NEW QUESTION 67

A company is hosting a static website from an Amazon S3 bucket. The website is available to customers at example.com. The company uses an Amazon Route 53 weighted routing policy with a TTL of 1 day. The company has decided to replace the existing static website with a dynamic web application. The dynamic web application uses an Application Load Balancer (ALB) in front of a fleet of Amazon EC2 instances.

On the day of production launch to customers, the company creates an additional Route 53 weighted DNS record entry that points to the ALB with a weight of 255 and a TTL of 1 hour. Two days later, a DevOps engineer notices that the previous static website is displayed sometimes when customers navigate to example.com.

How can the DevOps engineer ensure that the company serves only dynamic content for example.com?

- A. Delete all objects, including previous versions, from the S3 bucket that contains the static website content.
- B. Update the weighted DNS record entry that points to the S3 bucket
- C. Apply a weight of 0. Specify the domain reset option to propagate changes immediately.
- D. Configure webpage redirect requests on the S3 bucket with a hostname that redirects to the ALB.
- E. Remove the weighted DNS record entry that points to the S3 bucket from the example.com hosted zone. Wait for DNS propagation to become complete.

Answer: D

NEW QUESTION 69

An AWS CodePipeline pipeline has implemented a code release process. The pipeline is integrated with AWS CodeDeploy to deploy versions of an application to multiple Amazon EC2 instances for each CodePipeline stage.

During a recent deployment the pipeline failed due to a CodeDeploy issue. The DevOps team wants to improve monitoring and notifications during deployment to decrease resolution times.

What should the DevOps engineer do to create notifications. When issues are discovered?

- A. Implement Amazon CloudWatch Logs for CodePipeline and CodeDeploy create an AWS Config rule to evaluate code deployment issues, and create an Amazon Simple Notification Service (Amazon SNS) topic to notify stakeholders of deployment issues.
- B. Implement Amazon EventBridge for CodePipeline and CodeDeploy create an AWS Lambda function to evaluate code deployment issues, and create an Amazon Simple Notification Service (Amazon SNS) topic to notify stakeholders of deployment issues.
- C. Implement AWS CloudTrail to record CodePipeline and CodeDeploy API call information create an AWS Lambda function to evaluate code deployment issues and create an Amazon Simple Notification Service (Amazon SNS) topic to notify stakeholders of deployment issues.
- D. Implement Amazon EventBridge for CodePipeline and CodeDeploy create an Amazon
- E. Inspector assessment target to evaluate code deployment issues and create an Amazon Simple
- F. Notification Service (Amazon SNS) topic to notify stakeholders of deployment issues.

Answer: B

Explanation:

AWS CloudWatch Events can be used to monitor events across different AWS resources, and a CloudWatch Event Rule can be created to trigger an AWS Lambda function when a deployment issue is detected in the pipeline. The Lambda function can then evaluate the issue and send a notification to the appropriate stakeholders through an Amazon SNS topic. This approach allows for real-time notifications and faster resolution times.

NEW QUESTION 74

An IT team has built an AWS CloudFormation template so others in the company can quickly and reliably deploy and terminate an application. The template creates an Amazon EC2 instance with a user data script to install the application and an Amazon S3 bucket that the application uses to serve static webpages while it is running.

All resources should be removed when the CloudFormation stack is deleted. However, the team observes that CloudFormation reports an error during stack deletion, and the S3 bucket created by the stack is not deleted.

How can the team resolve the error in the MOST efficient manner to ensure that all resources are deleted without errors?

- A. Add a DeletionPolicy attribute to the S3 bucket resource, with the value Delete forcing the bucket to be removed when the stack is deleted.
- B. Add a custom resource with an AWS Lambda function with the DependsOn attribute specifying the S3 bucket, and an IAM role
- C. Write the Lambda function to delete all objects from the bucket when RequestType is Delete.
- D. Identify the resource that was not deleted
- E. Manually empty the S3 bucket and then delete it.
- F. Replace the EC2 and S3 bucket resources with a single AWS OpsWorks Stacks resource
- G. Define a custom recipe for the stack to create and delete the EC2 instance and the S3 bucket.

Answer: B

Explanation:

<https://aws.amazon.com/premiumsupport/knowledge-center/cloudformation-s3-custom-resources/>

NEW QUESTION 75

A DevOps engineer needs to back up sensitive Amazon S3 objects that are stored within an S3 bucket with a private bucket policy using S3 cross-Region replication functionality. The objects need to be copied to a target bucket in a different AWS Region and account. Which combination of actions should be performed to enable this replication? (Choose three.)

- A. Create a replication IAM role in the source account
- B. Create a replication IAM role in the target account.
- C. Add statements to the source bucket policy allowing the replication IAM role to replicate objects.
- D. Add statements to the target bucket policy allowing the replication IAM role to replicate objects.
- E. Create a replication rule in the source bucket to enable the replication.
- F. Create a replication rule in the target bucket to enable the replication.

Answer: ADE

Explanation:

S3 cross-Region replication (CRR) automatically replicates data between buckets across different AWS Regions. To enable CRR, you need to add a replication configuration to your source bucket that specifies the destination bucket, the IAM role, and the encryption type (optional). You also need to grant permissions to the IAM role to perform replication actions on both the source and destination buckets. Additionally, you can choose the destination storage class and enable additional replication options such as S3 Replication Time Control (S3 RTC) or S3 Batch Replication.

<https://medium.com/cloud-techies/s3-same-region-replication-srr-and-cross-region-replication-crr-34d446806ba> <https://aws.amazon.com/getting-started/hands-on/replicate-data-using-amazon-s3-replication/> <https://docs.aws.amazon.com/AmazonS3/latest/userguide/replication.html>

NEW QUESTION 76

A company builds a container image in an AWS CodeBuild project by running Docker commands. After the container image is built, the CodeBuild project uploads the container image to an Amazon S3 bucket. The CodeBuild project has an IAM service role that has permissions to access the S3 bucket.

A DevOps engineer needs to replace the S3 bucket with an Amazon Elastic Container Registry (Amazon ECR) repository to store the container images. The DevOps engineer creates an ECR private image repository in the same AWS Region of the CodeBuild project. The DevOps engineer adjusts the IAM service role with the permissions that are necessary to work with the new ECR repository. The DevOps engineer also places new repository information into the docker build command and the docker push command that are used in the buildspec.yml file.

When the CodeBuild project runs a build job, the job fails when the job tries to access the ECR repository. Which solution will resolve the issue of failed access to the ECR repository?

- A. Update the buildspec.yml file to log in to the ECR repository by using the `aws ecr get-login-password` AWS CLI command to obtain an authentication token
- B. Update the docker login command to use the authentication token to access the ECR repository.
- C. Add an environment variable of type `SECRETS_MANAGER` to the CodeBuild project
- D. In the environment variable, include the ARN of the CodeBuild project's IAM service role
- E. Update the buildspec.yml file to use the new environment variable to log in with the docker login command to access the ECR repository.
- F. Update the ECR repository to be a public image repository
- G. Add an ECR repository policy that allows the IAM service role to have access.
- H. Update the buildspec.yml file to use the AWS CLI to assume the IAM service role for ECR operations. Add an ECR repository policy that allows the IAM service role to have access.

Answer: A

Explanation:

(A) When Docker communicates with an Amazon Elastic Container Registry (ECR) repository, it requires authentication. You can authenticate your Docker client to the Amazon ECR registry with the help of the AWS CLI (Command Line Interface). Specifically, you can use the `"aws ecr get-login-password"` command to get an authorization token and then use Docker's `"docker login"` command with that token to authenticate to the registry. You would need to perform these steps in your buildspec.yml file before attempting to push or pull images from/to the ECR repository.

NEW QUESTION 79

A company updated the AWS CloudFormation template for a critical business application. The stack update process failed due to an error in the updated template and AWS CloudFormation automatically began the stack rollback process. Later a DevOps engineer discovered that the application was still unavailable and that the stack was in the `UPDATE_ROLLBACK_FAILED` state.

Which combination of actions should the DevOps engineer perform so that the stack rollback can complete successfully? (Select TWO.)

- A. Attach the AWS CloudFormation FullAccess IAM policy to the AWS CloudFormation role.
- B. Automatically recover the stack resources by using AWS CloudFormation drift detection.
- C. Issue a `ContinueUpdateRollback` command from the AWS CloudFormation console or the AWS CLI.
- D. Manually adjust the resources to match the expectations of the stack.
- E. Update the existing AWS CloudFormation stack by using the original template.

Answer: CD

Explanation:

<https://docs.aws.amazon.com/cli/latest/reference/cloudformation/continue-update-rollback.html> For a specified stack that is in the `UPDATE_ROLLBACK_FAILED` state, continues rolling it back to the `UPDATE_ROLLBACK_COMPLETE` state. Depending on the cause of the failure, you can manually fix the error and continue the rollback. By continuing the rollback, you can return your stack to a working state (the `UPDATE_ROLLBACK_COMPLETE` state), and then try to update the stack again.

NEW QUESTION 80

A company runs applications in AWS accounts that are in an organization in AWS Organizations. The applications use Amazon EC2 instances and Amazon S3. The company wants to detect potentially compromised EC2 instances, suspicious network activity, and unusual API activity in its existing AWS accounts and in any AWS accounts that the company creates in the future. When the company detects one of these events, the company wants to use an existing Amazon Simple Notification Service (Amazon SNS) topic to send a notification to its operational support team for investigation and remediation. Which solution will meet these requirements in accordance with AWS best practices?

- A. In the organization's management account, configure an AWS account as the Amazon GuardDuty administrator account.
- B. In the GuardDuty administrator account, add the company's existing AWS accounts to GuardDuty as members. In the GuardDuty administrator account, create an Amazon EventBridge rule with an event pattern to match GuardDuty events and to forward matching events to the SNS topic.

- C. In the organization's management account configure Amazon GuardDuty to add newly created AWS accounts by invitation and to send invitations to the existing AWS accounts Create an AWS Cloud Formation stack set that accepts the GuardDuty invitation and creates an Amazon EventBridge rule Configure the rule with an event pattern to match GuardDuty events and to forward matching events to the SNS topic
- D. GuardDuty events and to forward matching events to the SNS topic
- E. Configure the Cloud Formation stack set to deploy into all AWS accounts in the organization.
- F. In the organization's management account create an AWS CloudTrail organization trail Activate the organization trail in all AWS accounts in the organization
- G. Create an SCP that enables VPC Flow Logs in each account in the organization
- H. Create an Amazon EventBridge rule with an event pattern to match Security Hub events and to forward matching events to the SNS topic.
- I. In the organization's management account configure an AWS account as the AWS CloudTrail administrator account in the CloudTrail administrator account create a CloudTrail organization trail
- J. Add the company's existing AWS accounts to the organization trail Create an SCP that enables VPC Flow Logs in each account in the organization
- K. Configure AWS Security Hub for the organization
- L. Create an Amazon EventBridge rule with an event pattern to match Security Hub events and to forward matching events to the SNS topic.

Answer: B

Explanation:

It allows the company to detect potentially compromised EC2 instances, suspicious network activity, and unusual API activity in its existing AWS accounts and in any AWS accounts that the company creates in the future using Amazon GuardDuty. It also provides a solution for automatically adding future AWS accounts to GuardDuty by configuring GuardDuty to add newly created AWS accounts by invitation and to send invitations to the existing AWS accounts.

NEW QUESTION 82

A development team uses AWS CodeCommit, AWS CodePipeline, and AWS CodeBuild to develop and deploy an application. Changes to the code are submitted by pull requests. The development team reviews and merges the pull requests, and then the pipeline builds and tests the application.

Over time, the number of pull requests has increased. The pipeline is frequently blocked because of failing tests. To prevent this blockage, the development team wants to run the unit and integration tests on each pull request before it is merged.

Which solution will meet these requirements?

- A. Create a CodeBuild project to run the unit and integration test
- B. Create a CodeCommit approval rule template
- C. Configure the template to require the successful invocation of the CodeBuild project
- D. Attach the approval rule to the project's CodeCommit repository.
- E. Create an Amazon EventBridge rule to match pullRequestCreated events from CodeCommit Create a CodeBuild project to run the unit and integration test
- F. Configure the CodeBuild project as a target of the EventBridge rule that includes a custom event payload with the CodeCommit repository and branch information from the event.
- G. Create an Amazon EventBridge rule to match pullRequestCreated events from CodeCommit
- H. Modify the existing CodePipeline pipeline to not run the deploy steps if the build is started from a pull request
- I. Configure the EventBridge rule to run the pipeline with a custom payload that contains the CodeCommit repository and branch information from the event.
- J. Create a CodeBuild project to run the unit and integration test
- K. Create a CodeCommit notification rule that matches when a pull request is created or updated
- L. Configure the notification rule to invoke the CodeBuild project.

Answer: B

Explanation:

CodeCommit generates events in CloudWatch, CloudWatch triggers the CodeBuild project <https://aws.amazon.com/es/blogs/devops/complete-ci-cd-with-aws-codecommit-aws-codebuild-aws-codedeploy>

NEW QUESTION 86

A company manages an application that stores logs in Amazon CloudWatch Logs. The company wants to archive the logs to an Amazon S3 bucket Logs are rarely accessed after 90 days and must be retained for 10 years.

Which combination of steps should a DevOps engineer take to meet these requirements? (Select TWO.)

- A. Configure a CloudWatch Logs subscription filter to use AWS Glue to transfer all logs to an S3 bucket.
- B. Configure a CloudWatch Logs subscription filter to use Amazon Kinesis Data Firehose to stream all logs to an S3 bucket.
- C. Configure a CloudWatch Logs subscription filter to stream all logs to an S3 bucket.
- D. Configure the S3 bucket lifecycle policy to transition logs to S3 Glacier after 90 days and to expire logs after 3,650 days.
- E. Configure the S3 bucket lifecycle policy to transition logs to Reduced Redundancy after 90 days and to expire logs after 3,650 days.

Answer: BD

Explanation:

<https://docs.aws.amazon.com/AmazonCloudWatch/latest/logs/SubscriptionFilters.html>

NEW QUESTION 89

A highly regulated company has a policy that DevOps engineers should not log in to their Amazon EC2 instances except in emergencies. It a DevOps engineer does log in the security team must be notified within 15 minutes of the occurrence.

Which solution will meet these requirements?

- A. Install the Amazon Inspector agent on each EC2 instance Subscribe to Amazon EventBridge notifications Invoke an AWS Lambda function to check if a message is about user logins If it is send a notification to the security team using Amazon SNS.
- B. Install the Amazon CloudWatch agent on each EC2 instance Configure the agent to push all logs to Amazon CloudWatch Logs and set up a CloudWatch metric filter that searches for user login
- C. If a login is found send a notification to the security team using Amazon SNS.
- D. Set up AWS CloudTrail with Amazon CloudWatch Log
- E. Subscribe CloudWatch Logs to Amazon Kinesis Attach AWS Lambda to Kinesis to parse and determine if a log contains a user login If it does, send a notification to the security team using Amazon SNS.
- F. Set up a script on each Amazon EC2 instance to push all logs to Amazon S3 Set up an S3 event to invoke an AWS Lambda function which invokes an Amazon

Athena query to ru

G. The Athena query checks for logins and sends the output to the security team using Amazon SNS.

Answer: B

Explanation:

<https://aws.amazon.com/blogs/security/how-to-monitor-and-visualize-failed-ssh-access-attempts-to-amazon-ec2>

NEW QUESTION 90

An Amazon EC2 instance is running in a VPC and needs to download an object from a restricted Amazon S3 bucket. When the DevOps engineer tries to download the object, an AccessDenied error is received. What are the possible causes for this error? (Select TWO,)

- A. The S3 bucket default encryption is enabled.
- B. There is an error in the S3 bucket policy.
- C. The object has been moved to S3 Glacier.
- D. There is an error in the IAM role configuration.
- E. S3 Versioning is enabled.

Answer: BD

Explanation:

These are the possible causes for the AccessDenied error because they affect the permissions to access the S3 object from the EC2 instance. An S3 bucket policy is a resource-based policy that defines who can access the bucket and its objects, and what actions they can perform. An IAM role is an identity that can be assumed by an EC2 instance to grant it permissions to access AWS services and resources. If there is an error in the S3 bucket policy or the IAM role configuration, such as a missing or incorrect statement, condition, or principal, then the EC2 instance may not have the necessary permissions to download the object from the S3 bucket .

<https://docs.aws.amazon.com/AmazonS3/latest/userguide/example-bucket-policies.html> <https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/iam-roles-for-amazon-ec2.html>

NEW QUESTION 93

A company hosts a security auditing application in an AWS account. The auditing application uses an IAM role to access other AWS accounts. All the accounts are in the same organization in AWS Organizations.

A recent security audit revealed that users in the audited AWS accounts could modify or delete the auditing application's IAM role. The company needs to prevent any modification to the auditing application's IAM role by any entity other than a trusted administrator IAM role.

Which solution will meet these requirements?

- A. Create an SCP that includes a Deny statement for changes to the auditing application's IAM role. Include a condition that allows the trusted administrator IAM role to make change
- B. Attach the SCP to the root of the organization.
- C. Create an SCP that includes an Allow statement for changes to the auditing application's IAM role by the trusted administrator IAM role
- D. Include a Deny statement for changes by all other IAM principal
- E. Attach the SCP to the IAM service in each AWS account where the auditing application has an IAM role.
- F. Create an IAM permissions boundary that includes a Deny statement for changes to the auditing application's IAM role
- G. Include a condition that allows the trusted administrator IAM role to make change
- H. Attach the permissions boundary to the audited AWS accounts.
- I. Create an IAM permissions boundary that includes a Deny statement for changes to the auditing application's IAM role
- J. Include a condition that allows the trusted administrator IAM role to make change
- K. Attach the permissions boundary to the auditing application's IAM role in the AWS accounts.

Answer: A

Explanation:

https://docs.aws.amazon.com/organizations/latest/userguide/orgs_manage_policies_scps.html?icmpid=docs_org

NEW QUESTION 95

A company's application development team uses Linux-based Amazon EC2 instances as bastion hosts. Inbound SSH access to the bastion hosts is restricted to specific IP addresses, as defined in the associated security groups. The company's security team wants to receive a notification if the security group rules are modified to allow SSH access from any IP address.

What should a DevOps engineer do to meet this requirement?

- A. Create an Amazon EventBridge rule with a source of aws.cloudtrail and the event name AuthorizeSecurityGroupIngress
- B. Define an Amazon Simple Notification Service (Amazon SNS) topic as the target.
- C. Enable Amazon GuardDuty and check the findings for security groups in AWS Security Hub
- D. Configure an Amazon EventBridge rule with a custom pattern that matches GuardDuty events with an output of NON_COMPLIANT
- E. Define an Amazon Simple Notification Service (Amazon SNS) topic as the target.
- F. Create an AWS Config rule by using the restricted-ssh managed rule to check whether security groups disallow unrestricted incoming SSH traffic
- G. Configure automatic remediation to publish a message to an Amazon Simple Notification Service (Amazon SNS) topic.
- H. Enable Amazon Inspector
- I. Include the Common Vulnerabilities and Exposures-1.1 rules package to check the security groups that are associated with the bastion host
- J. Configure Amazon Inspector to publish a message to an Amazon Simple Notification Service (Amazon SNS) topic.

Answer: A

Explanation:

<https://aws.amazon.com/premiumsupport/knowledge-center/monitor-security-group-changes-ec2/>

NEW QUESTION 99

A space exploration company receives telemetry data from multiple satellites. Small packets of data are received through Amazon API Gateway and are placed

directly into an Amazon Simple Queue Service (Amazon SQS) standard queue. A custom application is subscribed to the queue and transforms the data into a standard format.

Because of inconsistencies in the data that the satellites produce, the application is occasionally unable to transform the data. In these cases, the messages remain in the SQS queue. A DevOps engineer must develop a solution that retains the failed messages and makes them available to scientists for review and future processing.

Which solution will meet these requirements?

- A. Configure AWS Lambda to poll the SQS queue and invoke a Lambda function to check whether the queue messages are valid
- B. If validation fails, send a copy of the data that is not valid to an Amazon S3 bucket so that the scientists can review and correct the data
- C. When the data is corrected, amend the message in the SQS queue by using a replay Lambda function with the corrected data.
- D. Convert the SQS standard queue to an SQS FIFO queue
- E. Configure AWS Lambda to poll the SQS queue every 10 minutes by using an Amazon EventBridge schedule
- F. Invoke the Lambda function to identify any messages with a `SentTimestamp` value that is older than 5 minutes, push the data to the same location as the application's output location, and remove the messages from the queue.
- G. Create an SQS dead-letter queue
- H. Modify the existing queue by including a redrive policy that sets the `Maximum Receives` setting to 1 and sets the dead-letter queue ARN to the ARN of the newly created queue
- I. Instruct the scientists to use the dead-letter queue to review the data that is not valid
- J. Reprocess this data at a later time.
- K. Configure API Gateway to send messages to different SQS virtual queues that are named for each of the satellite
- L. Update the application to use a new virtual queue for any data that it cannot transform, and send the message to the new virtual queue
- M. Instruct the scientists to use the virtual queue to review the data that is not valid
- N. Reprocess this data at a later time.

Answer: C

Explanation:

Create an SQS dead-letter queue. Modify the existing queue by including a redrive policy that sets the `Maximum Receives` setting to 1 and sets the dead-letter queue ARN to the ARN of the newly created queue. Instruct the scientists to use the dead-letter queue to review the data that is not valid. Reprocess this data at a later time.

NEW QUESTION 104

A company hosts its staging website using an Amazon EC2 instance backed with Amazon EBS storage. The company wants to recover quickly with minimal data losses in the event of network connectivity issues or power failures on the EC2 instance.

Which solution will meet these requirements?

- A. Add the instance to an EC2 Auto Scaling group with the minimum, maximum, and desired capacity set to 1.
- B. Add the instance to an EC2 Auto Scaling group with a lifecycle hook to detach the EBS volume when the EC2 instance shuts down or terminates.
- C. Create an Amazon CloudWatch alarm for the `StatusCheckFailed System` metric and select the EC2 action to recover the instance.
- D. Create an Amazon CloudWatch alarm for the `StatusCheckFailed Instance` metric and select the EC2 action to reboot the instance.

Answer: C

Explanation:

<https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ec2-instance-recover.html>

NEW QUESTION 109

A company wants to migrate its content sharing web application hosted on Amazon EC2 to a serverless architecture. The company currently deploys changes to its application by creating a new Auto Scaling group of EC2 instances and a new Elastic Load Balancer, and then shifting the traffic away using an Amazon Route 53 weighted routing policy.

For its new serverless application, the company is planning to use Amazon API Gateway and AWS Lambda. The company will need to update its deployment processes to work with the new application. It will also need to retain the ability to test new features on a small number of users before rolling the features out to the entire user base.

Which deployment strategy will meet these requirements?

- A. Use AWS CDK to deploy API Gateway and Lambda function
- B. When code needs to be changed, update the AWS CloudFormation stack and deploy the new version of the APIs and Lambda function
- C. Use a Route 53 failover routing policy for the canary release strategy.
- D. Use AWS CloudFormation to deploy API Gateway and Lambda functions using Lambda function version
- E. When code needs to be changed, update the CloudFormation stack with the new Lambda code and update the API versions using a canary release strategy
- F. Promote the new version when testing is complete.
- G. Use AWS Elastic Beanstalk to deploy API Gateway and Lambda function
- H. When code needs to be changed, deploy a new version of the API and Lambda function
- I. Shift traffic gradually using an Elastic Beanstalk blue/green deployment.
- J. Use AWS OpsWorks to deploy API Gateway in the service layer and Lambda functions in a custom layer
- K. When code needs to be changed, use OpsWorks to perform a blue/green deployment and shift traffic gradually.

Answer: B

Explanation:

<https://docs.aws.amazon.com/serverless-application-model/latest/developerguide/automating-updates-to-serverless.html>

NEW QUESTION 111

A company uses AWS CodePipeline pipelines to automate releases of its application. A typical pipeline consists of three stages: build, test, and deployment. The company has been using a separate AWS CodeBuild project to run scripts for each stage. However, the company now wants to use AWS CodeDeploy to handle the deployment stage of the pipelines.

The company has packaged the application as an RPM package and must deploy the application to a fleet of Amazon EC2 instances. The EC2 instances are in an EC2 Auto Scaling group and are launched from a common AMI.

Which combination of steps should a DevOps engineer perform to meet these requirements? (Choose two.)

- A. Create a new version of the common AMI with the CodeDeploy agent installed
- B. Update the IAM role of the EC2 instances to allow access to CodeDeploy.
- C. Create a new version of the common AMI with the CodeDeploy agent installed
- D. Create an AppSpec file that contains application deployment scripts and grants access to CodeDeploy.
- E. Create an application in CodeDeploy
- F. Configure an in-place deployment type
- G. Specify the Auto Scaling group as the deployment target
- H. Add a step to the CodePipeline pipeline to use EC2 Image Builder to create a new AMI
- I. Configure CodeDeploy to deploy the newly created AMI.
- J. Create an application in CodeDeploy
- K. Configure an in-place deployment type
- L. Specify the Auto Scaling group as the deployment target
- M. Update the CodePipeline pipeline to use the CodeDeploy action to deploy the application.
- N. Create an application in CodeDeploy
- O. Configure an in-place deployment type
- P. Specify the EC2 instances that are launched from the common AMI as the deployment target
- Q. Update the CodePipeline pipeline to use the CodeDeploy action to deploy the application.

Answer: AD

Explanation:

<https://docs.aws.amazon.com/codedeploy/latest/userguide/integrations-aws-auto-scaling.html>

NEW QUESTION 115

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

DOP-C02 Practice Exam Features:

- * DOP-C02 Questions and Answers Updated Frequently
- * DOP-C02 Practice Questions Verified by Expert Senior Certified Staff
- * DOP-C02 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * DOP-C02 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The DOP-C02 Practice Test Here](#)