

1z0-934 Dumps

Oracle Cloud Platform Application Integration 2018 Associate

<https://www.certleader.com/1z0-934-dumps.html>



NEW QUESTION 1

Which Process type should you choose to model non-sequential process type in Oracle Integration Cloud (OIC)?

- A. Adaptive Case Management process
- B. Structured Process
- C. Dynamic process
- D. Unstructured Process

Answer: C

Explanation:

<https://docs.oracle.com/en/cloud/paas/integration-cloud/user-processes/using-processes-oracle-integration-cloud>

NEW QUESTION 2

Which four Client Software Libraries can be used for developing applications with Oracle Internet of Things (IoT) Cloud Service?

- A. C POSIX
- B. Java SE
- C. .NET
- D. JavaScript
- E. Android
- F. VB Script

Answer: ABDE

NEW QUESTION 3

Which two are ways the Oracle Internet of Things (IoT) Cloud Service environment can be accessed?

- A. using SOAP Interface
- B. using REST Interface
- C. Using a desktop client
- D. using Web Browser

Answer: BD

NEW QUESTION 4

Which four are states that a device can be in throughout its lifecycle?

- A. Activated
- B. Decommissioned
- C. Disabled
- D. Saved
- E. Deactivated
- F. Registered

Answer: ABEF

Explanation:

<https://docs.oracle.com/en/cloud/paas/iot-cloud/iotgs/developing-applications-oracle-internet-things-cloud-servi>

NEW QUESTION 5

Which three are ways enterprise applications can interact with Oracle Internet of Things (IoT) Cloud Service?

- A. send commands/messages
- B. insert/update/delete data
- C. subscribe to data
- D. query data
- E. subscribe to commands/messages

Answer: ABD

NEW QUESTION 6

Which four are valid for integration using Service Oriented Architecture Cloud Service (SOACS)?

- A. Retrieve/Update supported data elements on the SaaS applications using REST Services in real time.
- B. SOACS has read access to HCM and ERP Cloud (SaaS) Applications data.
- C. Create Files in the required format and Orchestrate PBL data loads into the HCM/ERP Cloud.
- D. Create Files in the required format and Orchestrate FBDL data loads into the HCM/ERP Cloud.
- E. Create Files in the required format and Orchestrate ADFDi data loads into the HCM/ERP Cloud.
- F. Create Files in the required format and Orchestrate HDL data loads into the HCM/ERP Cloud.

Answer: ABEF

NEW QUESTION 7

Which three are characteristics of Device Virtualization?

- A. Oracle Internet of Things (IoT) Cloud Service does not support Device Virtualization.
- B. You can monitor each device endpoint's health, performance, and location via the client software library API or with REST calls made to those devices.
- C. You can collect data from your devices using APIs delivered with Oracle Internet of Things (IoT) Cloud Service Client Software Libraries or Oracle IoT Cloud Service Gateway.
- D. The APIs provided enable you to send telemetry messages and device data from your devices to Oracle Internet of Things (IoT) Cloud Service, control your devices, and deploy applications to your gateway devices.
- E. Devices used are not real.
- F. They are virtual devices and linked with Oracle Internet of Things (IoT) CS.

Answer: BCD

NEW QUESTION 8

Which two are types of Authentication that are supported for Services in Integration API Platform Cloud Service?

- A. Kerberos
- B. WSS Username Token
- C. OAuth2
- D. BasicAuth

Answer: CD

Explanation:

https://cloud.oracle.com/opc/paas/datasheets/APIPCSDataSheet_Jan2018.pdf

NEW QUESTION 9

Which four are types of links that can be created to read data and events from devices, access different data sources for reading and writing data, and to deliver the results of analytics processing?

- A. Device Message and Analyzed Message
- B. Oracle Storage Cloud Service
- C. Spark SQL and Oracle NoSQL
- D. Oracle Database as a Service
- E. Local File System

Answer: ABCD

Explanation:

<https://docs.oracle.com/en/cloud/paas/iot-cloud/iotgs/developing-applications-oracle-internet-things-cloud-servi>

NEW QUESTION 10

You receive an exception message: "java.security.cert.CertPathValidatorException: Path does not chain with any of the trust anchors" What needs to be verified when this exception message is received?

- A. Run this command to verify code.keystore has system certificates: keytool -list -stotetype JKS -keystore config\code.keystore
- B. Run this command to verify code.truststore has system certificates: keytool -list -storetype JKS -keystore config\code.truststore
- C. Run this command to verify cacerts has system certificates: keytool -list -storetype JKS -keystore security\cacerts
- D. Run this command to verify code.certstore has system certificates: keytool -list -storetype JKS -keystore config\code.certstore

Answer: A

NEW QUESTION 10

You provision an Oracle SOA Cloud Service instance and specify a compute shape so that the JVM heap size for WebLogic Serve, and Load Balancer processes are determined automatically.

Which statement is correct after provisioning the instance in this scenario?

- A. You can change the heap size to a maximum of 32GB.
- B. You can change the heap size by logging a Oracle Cloud Support Service Request.
- C. You can change the heap size by using the Weblogic Server Administration Console.
- D. You cannot change the heap size once the Service Instance is provisioned.

Answer: C

NEW QUESTION 15

Which three background colors are displayed for autocomplete in Process Cloud Service?

- A. Blue for complex binding names (their children may contain valid binding names)
- B. Red for invalid binding names
- C. Green for valid binding names
- D. Orange for unmatched binding names

Answer: ABC

Explanation:

<https://docs.oracle.com/en/cloud/paas/process-cloud/user/binding-form-data-controls.html#GUID-CECD2F13-1> The background colors displayed for the autocomplete options are:

- ▶ Green for valid binding names
- ▶ Red for invalid binding names
- ▶ Blue for complex binding names (their children may contain valid binding names)

If a control isn't linked to an attribute or if a control is linked to an invalid attribute, an error message is displayed in the Binding field and an error icon is displayed in the canvas. When a control doesn't have a valid binding, any value entered into the control in runtime is not passed on to the form payload.

NEW QUESTION 16

You receive a status code: 502 Proxy Error. Which is a possible event cause for this error?

- A. when the proxy setup is incorrect
- B. while registering a large number of devices using the Batch Registration feature under the Devices menu
- C. while adding proxy for an enterprise application device
- D. while the proxy server is not responding to the request

Answer: B

Explanation:

<https://docs.oracle.com/en/cloud/paas/iot-cloud/iotgs/troubleshooting-management-console-issues.html>

NEW QUESTION 18

Which four statements are correct regarding the differences between WSDL/SOAP and REST/JSON?

- A. REST is typically invoked with HTTP verbs.
- B. WSLD is simpler, REST is richer
- C. Modern API-First architectures prefer to use thed-and-true WSDUSOAP services over REST services because they are richer and provide a tighter contract
- D. WSDL is a request for a service; REST is a request for a resource
- E. WSDL is a tight contract; REST is a loose contract
- F. REST more easily used in developing UIs than WSDUSOA
- G. REST is gaining popularity in application development.

Answer: BCDF

NEW QUESTION 22

Which setting is used for a system that is hosting a web application to be allowed to access Oracle Internet of Things (IoT) Cloud Service resources?

- A. Cross-Origin Resource Sharing (CORS)
- B. Management Console Timeout Interval
- C. Message Storage and Command Notification
- D. OAuth Access Token Lifetime

Answer: A

Explanation:

The cross origin resource sharing setting specifies if the system that is hosting a web application is allowed to access Oracle IoT Cloud Service resources. The assumption is that the web application is running in a browser that is also implementing the CORS specification. Any browser based JavaScript client running on the specified host can access Oracle IoT REST APIs. However they will need to follow the Oracle IoT REST API authorization process to run any operations. <https://docs.oracle.com/en/cloud/paas/iot-cloud/iotsu/setting-cross-origin-resource-sharing-value.html>

NEW QUESTION 25

What are the four steps required to complete the task 'create a connection'?

- A. Configure Connection Properties
- B. Import SSL Certificate
- C. Test Connection
- D. Select an Adapter
- E. Configure Lookup
- F. Configure Connection Security

Answer: ACDF

NEW QUESTION 26

Which APIs does Oracle Internet of Things (IoT) Cloud Service use to perform an analysis?

- A. Native Spark Java APIs
- B. SQL Queries
- C. JavaScript APIs
- D. Big Data APIs

Answer: A

Explanation:

Oracle IoT Cloud Service uses native Spark Java APIs to perform the analysis. Developers can use the Batch and Streaming spark APIs to write the analytics processing logic.

Developers can also import external APIs and use them in their application. <https://docs.oracle.com/en/cloud/paas/iot-cloud/iotgs/analytics-oracle-iot-cloud-service.html>

NEW QUESTION 31

What is the default value for Command Notification Timeout?

- A. 5 seconds
- B. 2 seconds
- C. 10 seconds
- D. 1 second

Answer: A

Explanation:

<https://docs.oracle.com/en/cloud/paas/iot-cloud/iotsu/setting-command-notification-timeout-value.html>

NEW QUESTION 34

What are two possible reasons for a Gateway not getting started?

- A. The IoT Service may be down.
- B. The provisioning file may contain correct Activation ID and Activation Secret.
- C. There is an invalid certificate.
- D. The provisioning file may contain incorrect Activation ID and incorrect Activation Secret.

Answer: AD

NEW QUESTION 36

What two grants allow an API Manager to use a service in their API?

- A. Manage Service
- B. View All Details
- C. Deploy Service
- D. Reference Service

Answer: BC

Explanation:

<https://docs.oracle.com/en/cloud/paas/api-platform-cloud/apfad/managing-api-grants.html#GUID-18A50B0C-F>

NEW QUESTION 41

When a connection is in edit mode and the browser crashes, the connection becomes locked, which then prevents it from being edited. Which two users can unlock the connection?

- A. a user with the Designer Role
- B. the same user who has edited the connection
- C. any user
- D. a user with the Administrator Role

Answer: BD

Explanation:

<https://docs.oracle.com/en/cloud/paas/integration-cloud-service/icsug/creating-connections.html#GUID-085410> Unlocking a Connection

When a connection is in edit mode and the browser crashes, the connection becomes locked, which prevents it from being edited.

To unlock the connection:

- ▶ Log in again as the same user who was editing the connection when the browser crashed, then log out. For example, if you were logged in as icsdeveloper when the browser crashed, log in again as icsdeveloper, and log out. This action unlocks the connection.
or
- ▶ Log in as a user with the Administrators role.
- ▶ On the Oracle Integration Cloud Service home page, click Cthoennections diagram.
- ▶ For the connection that is locked, click the menu at the far right, then selUecntlock.

NEW QUESTION 42

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your 1z0-934 Exam with Our Prep Materials Via below:

<https://www.certleader.com/1z0-934-dumps.html>