

Exam Questions 1z0-082

Oracle Database Administration I

<https://www.2passeasy.com/dumps/1z0-082/>



NEW QUESTION 1

Which two statements are true about space-saving features in an Oracle Database? (Choose two.)

- A. Private Temporary Tables (PTTS) store metadata in memory only
- B. An index created with the UNUSABLE attribute has no segment
- C. If they exist for a session, Private Temporary Tables (PTTs) are always dropped at the next COMMIT OR ROLLBACK statement
- D. An index that is altered to be UNUSABLE will retain its segment
- E. A table that is truncated will always have its segment removed

Answer: BC

NEW QUESTION 2

Which three statements are true about dropping and unused columns in an Oracle database? (Choose three.)

- A. A primary key column referenced by another column as a foreign key can be dropped if using the CASCADE option.
- B. An UNUSED column's space is reclaimed automatically when the block containing that column is next queried.
- C. An UNUSED column's space is reclaimed automatically when the row containing that column is next queried.
- D. Partition key columns cannot be dropped.
- E. A DROP COLUMN command can be rolled back
- F. A column that is set to UNUSED still counts towards the limit of 1000 columns per table

Answer: ABF

NEW QUESTION 3

Examine the description of the BOOKS table:

Name	Null?	Type
TRANSACTION_ID	NOT NULL	VARCHAR2 (6)
TRANSACTION_DATE		DATE
AMOUNT		NUMBER (10, 2)
CUSTOMER_ID		VARCHAR2 (6)

The table has 100 rows.

Examine this sequence of statements issued in a new session:

```
INSERT INTO books VALUES ('ADV112', 'Adventures of Tom Sawyer', NULL, NULL); SAVEPOINT a;
DELETE FROM books; ROLLBACK TO SAVEPOINT a; ROLLBACK;
```

Which two statements are true? (Choose two.)

- A. The second ROLLBACK command does nothing
- B. The second ROLLBACK command replays the delete
- C. The first ROLLBACK command restores the 101 rows that were deleted, leaving the inserted row still to be committed
- D. The second ROLLBACK command undoes the insert
- E. The first ROLLBACK command restores the 101 rows that were deleted and commits the inserted row

Answer: DE

NEW QUESTION 4

The INVOICE table has a QTY_SOLD column of data type NUMBER and an INVOICE_DATE column of data type DATE. NLS_DATE_FORMAT is set to DD-MON-RR.

Which two are true about data type conversions involving these columns in query expressions? (Choose two.)

- A. CONCAT (qty_sold, invoice_date) : requires explicit conversion
- B. invoice_date = '15-march-2019' : uses implicit conversion
- C. invoice_date > '01-02-2019' : uses implicit conversion
- D. qty_sold BETWEEN '101' AND '110' : uses implicit conversion
- E. qty_sold = '0554982' uses implicit conversion

Answer: BD

NEW QUESTION 5

Examine this command and some partial output:

```
LSNRCTL> start LISTENER_1

Listening Endpoints Summary...
  (DESCRIPTION=(ADDRESS=PROTOCOL=tcp) (HOST=host01.abc.com) (PORT=1562))
Services Summary...
Service "DB01.abc.com " has 1 instance(s).
  Instance "DB01", status UNKNOWN, has 1 handler(s) for this service...
The command completed successfully
```

Why does the DB01.abc.com service show unknown status?

- A. The service DB01.abc.com is dynamically registered
- B. The LOCAL_LISTENER database parameter is not set to a service name that refers to LISTENER_1
- C. The service DB01.abc.com is statically registered
- D. The listener is not listening on the default port 1521
- E. The SID_LIST_LISTENER section is not contained in the LISTENER.ORA file

Answer: B

NEW QUESTION 6

Which three statements are true about undo segments and the use of undo by transactions in an Oracle database instance? (Choose three.)

- A. An undo segment may be used by multiple transactions simultaneously
- B. Undo segments can wrap around to the first extent when a transaction fills the last extent of the undo segment
- C. Undo segments have a minimum of three extents
- D. Undo segments can extend when a transaction fills the last extent of the undo segment
- E. A single transaction may use multiple undo segments simultaneously
- F. Undo segments must be stored in a BIGFILE tablespace
- G. Undo segments must be stored in a SMALLFILE tablespace

Answer: ADG

NEW QUESTION 7

Which three statements are true about the Oracle join and ANSI join syntax? (Choose three.)

- A. The Oracle join syntax supports creation of a Cartesian product of two tables
- B. The Oracle join syntax performs better than the SQL:1999 compliant ANSI join syntax
- C. The SQL:1999 compliant ANSI join syntax supports natural joins
- D. The SQL:1999 compliant ANSI join syntax supports creation of a Cartesian product of two tables
- E. The Oracle join syntax only supports right outer joins
- F. The Oracle join syntax supports natural joins
- G. The Oracle join syntax performs less well than the SQL:1999 compliant ANSI join syntax

Answer: CDF

NEW QUESTION 8

Which three statements are true about single-row functions? (Choose three.)

- A. They can be used only in the WHERE clause of a SELECT statement
- B. The argument can be a column name, variable, literal or an expression
- C. The data type returned can be different from the data type of the argument
- D. They can be nested to any level
- E. They can accept only one argument
- F. They return a single result row per table

Answer: BCF

NEW QUESTION 9

Which three statements are true regarding indexes? (Choose three.)

- A. A UNIQUE index can be altered to be non-unique
- B. A SELECT statement can access one or more indices without accessing any tables
- C. A table belonging to one user can have an index that belongs to a different user
- D. An update to a table can result in updates to any or all of the table's indexes
- E. When a table is dropped and is moved to the RECYCLE BIN, all indexes built on that table are permanently dropped
- F. An update to a table can result in no updates to any of the table's indexes

Answer: ADE

NEW QUESTION 10

Which three statements are true about a self-join? (Choose three.)

- A. The ON clause must be used
- B. The query must use two different aliases for the table
- C. It must be an equi join
- D. It must be an inner join
- E. The ON clause can be used
- F. It can be an outer join

Answer: BDE

NEW QUESTION 10

View the Exhibits and examine the structure of the COSTS and PROMOTIONS tables.

You want to display PROD_IDS whose promotion cost is less than the highest cost PROD_ID in a promotion time interval.

Examine this SQL statement:

```
SELECT prod_id
FROM costs
WHERE promo_id IN
  (SELECT promo_id
   FROM promotions
   WHERE promo_cost < ALL
    (SELECT MAX(promo_cost)
     FROM promotions
     GROUP BY (promo_end_date - promo_begin_date)));
```

Exhibit 1.

Table COSTS		
Name	Null?	Type
PROD_ID	NOT NULL	NUMBER
TIME_ID	NOT NULL	DATE
PROMO_ID	NOT NULL	NUMBER
CHANNEL_ID	NOT NULL	NUMBER
UNIT_COST	NOT NULL	NUMBER(10,2)
UNIT_PRICE	NOT NULL	NUMBER(10,2)

Exhibit 2.

Table PROMOTIONS		
Name	Null?	Type
PROMO_ID	NOT NULL	NUMBER(6)
PROMO_NAME	NOT NULL	VARCHAR2(30)
PROMO_SUBCATEGORY	NOT NULL	VARCHAR2(30)
PROMO_SUBCATEGORY_ID	NOT NULL	NUMBER
PROMO_CATEGORY	NOT NULL	VARCHAR2(30)
PROMO_CATEGORY_ID	NOT NULL	NUMBER
PROMO_COST	NOT NULL	NUMBER(10,2)
PROMO_BEGIN_DATE	NOT NULL	DATE
PROMO_END_DATE	NOT NULL	DATE

What will be the result?

- A. It gives an error because the ALL keyword is not valid
- B. It gives an error because the GROUP BY clause is not valid
- C. It executes successfully but does not give the required result
- D. It executes successfully and gives the required result

Answer: D

NEW QUESTION 15

Which two statements are true about the rules of precedence for operators? (Choose two.)

- A. The concatenation operator || is always evaluated before addition and subtraction in an expression
- B. NULLS influence the precedence of operators in an expression
- C. The + binary operator has the highest precedence in an expression in a SQL statement
- D. Arithmetic operators with equal precedence are evaluated from left to right within an expression
- E. Multiple parentheses can be used to override the default precedence of operators in an expression

Answer: CE

NEW QUESTION 17

Which two statements are true about the DUAL table? (Choose two.)

- A. It can be accessed only by the SYS user
- B. It consists of a single row and single column of VARCHAR2 data type
- C. It can display multiple rows but only a single column
- D. It can be used to display only constants or pseudo columns
- E. It can be accessed by any user who has the SELECT privilege in any schema
- F. It can display multiple rows and columns

Answer: AB

NEW QUESTION 21

What is true about non-equijoin statement performance? (Choose two.)

- A. Table aliases can improve performance
- B. The BETWEEN condition always performs better than using the >= and <= conditions
- C. The join syntax used makes no difference to performance
- D. The BETWEEN condition always performs less well than using the >= and <= conditions
- E. The Oracle join syntax performs better than the SQL:1999 compliant ANSI join syntax

Answer: AE

NEW QUESTION 23

Which two statements are true about the results of using the INTERSECT operator in compound queries? (Choose two.)

- A. Column names in each SELECT in the compound query can be different
- B. The number of columns in each SELECT in the compound query can be different
- C. Reversing the order of the intersected tables can sometimes affect the output
- D. INTERSECT returns rows common to both sides of the compound query
- E. INTERSECT ignores NULLs

Answer: AE

NEW QUESTION 24

Examine the description of the CUSTOMERS table:

Name	Null?	Type
CUST_ID	NOT NULL	VARCHAR2(6)
FIRST_NAME		VARCHAR2(50)
LAST_NAME	NOT NULL	VARCHAR2(50)
ADDRESS		VARCHAR2(50)
CITY		VARCHAR2(25)

You want to display details of all customers who reside in cities starting with the letter D followed by at least two characters. Which query can be used?

- A. SELECT * FROM customers WHERE city LIKE 'D_%';
- B. SELECT * FROM customers WHERE city = '%D_%';
- C. SELECT * FROM customers WHERE city LIKE 'D_';
- D. SELECT * FROM customers WHERE city = 'D_%';

Answer: A

NEW QUESTION 29

Which three statements are true about inner and outer joins? (Choose three.)

- A. A full outer join returns matched and unmatched rows
- B. An inner join returns matched rows
- C. Outer joins can only be used between two tables per query
- D. A full outer join must use Oracle syntax
- E. Outer joins can be used when there are multiple join conditions on two tables
- F. A left or right outer join returns only unmatched rows

Answer: ABF

NEW QUESTION 31

Which two statements are true about UNDO and REDO? (Choose two.)

- A. The generation of UNDO generates REDO
- B. DML modifies Oracle database objects and only generates UNDO
- C. The generation of REDO generates UNDO
- D. DML modifies Oracle database objects and only generates REDO

Answer: AC

NEW QUESTION 35

Which three statements are true about the Oracle Data Dictionary? (Choose three.)

- A. Data dictionary views are created by joins of dictionary base tables and DBA-defined tables
- B. The data dictionary is created and maintained by the database administrator
- C. Views with the same name but different prefixes, such as CDB, DBA, ALL and USER, reference the same base tables from the data dictionary
- D. Base tables can be queried directly
- E. It is owned by the SYSTEM user
- F. Usernames of all users including database administrators are stored in the data dictionary

Answer: CDF

NEW QUESTION 40

A script abc.sql must be executed to perform a job.

A database user HR, who is defined in this database, executes this command:

```
$ sqlplus hr/hr@orcl @abc.sql
```

 What will happen upon execution?

- A. The command succeeds and HR will be connected to the orcl and abc.sql databases
- B. The command succeeds and HR will be connected to the orcl database instance, and the abc.sql script will be executed
- C. The command fails because the script must refer to the full path name
- D. The command fails and reports an error because @ is used twice

Answer: B

NEW QUESTION 42

In which three situations does a new transaction always start? (Choose three.)

- A. when issuing a SELECT FOR UPDATE statement after a CREATE TABLE AS SELECT statement was issued in the same session
- B. when issuing a TRUNCATE statement after a SELECT statement was issued in the same session
- C. when issuing a CREATE TABLE statement after a SELECT statement was issued in the same session
- D. when issuing the first Data Manipulation Language (DML) statement after a COMMIT OR ROLLBACK statement was issued in the same session
- E. when issuing a CREATE INDEX statement after a CREATE TABLE statement completed successfully in the same session
- F. when issuing a DML statement after a DML statement failed in the same session

Answer: ADF

NEW QUESTION 45

Which two are true about a SQL statement using SET operators such as UNION? (Choose two.)

- A. The data type group of each column returned by the second query must match the data type group of the corresponding column returned by the first query.
- B. The number, but not names, of columns must be identical for all SELECT statements in the query.
- C. The data type of each column returned by the second query must exactly match the data type of the corresponding column returned by the first query.
- D. The names and number of columns must be identical for all SELECT statements in the query.
- E. The data type of each column returned by the second query must be implicitly convertible to the data type of the corresponding column returned by the first query.

Answer: AC

NEW QUESTION 46

Which three instance situations are possible with the Oracle Database server without multi-tenant? (Choose three.)

- A. two or more instances on separate servers all associated with one database
- B. one instance on one server associated with one database
- C. one instance on one server associated with two or more databases on the same server
- D. one instance on one server not associated with any database
- E. one instance on one server associated with two or more databases on separate servers

Answer: CDE

NEW QUESTION 47

The ORCL database has RESUMABLE TIMEOUT = 7200 and DEFERRED_SEGMENT_CREATION = FALSE

User U1 has a 1 MB quota in tablespace DATA. U1 executes this command:

```
SQL> CREATE TABLE t1 AS
```

```
(SELECT object_name, sharing, created FROM dba_objects);
```

U1 complains that the command is taking too long to execute.

In the alert log, the database administrator (DBA) finds this: 2017-03-06T12:15:17.183438+05:30

statement in resumable session 'User U1(136), Session 1, Instance 1' was suspended due to ORA-01536: space quota exceeded for tablespace 'DATA'

Which are three actions any one of which the DBA could take to resume the session? (Choose three.)

- A. Add a data file to DATA
- B. Drop other U1 objects in DATA
- C. Increase U1's quota sufficiently in DATA
- D. Set DEFERRED_SEGMENT_CREATION to TRUE
- E. Grant UNLIMITED TABLESPACE to U1
- F. Set AUTOEXTEND ON for data files in DATA

Answer: CDF

NEW QUESTION 51

The SCOTT/TIGER user exists in two databases, BOSTON_DB and DALLAS_DB, in two different locations.

Each database has a tnsnames.ora file defining DALLAS_DB as a service name. Examine this command:

```
CREATE DATABASE LINK dblink1 CONNECT TO scott IDENTIFIED BY tiger USING 'dallas_db';
```

How do you execute the command so that only SCOTT in BOSTON_DB can access the SCOTT schema in DALLAS_DB?

- A. as SCOTT in DALLAS_DB
- B. as SCOTT in BOSTON_DB
- C. as SCOTT in BOSTON_DB and SYS in DALLAS_DB
- D. as SYS in both the databases
- E. as SCOTT in both the databases

Answer: D

NEW QUESTION 52

Which three statements are true concerning logical and physical database structures? (Choose three.)

- A. All tablespaces may have one or more data files
- B. The extents of a segment must always reside in the same datafile
- C. A smallfile tablespace might be bigger than a bigfile tablespace
- D. A segment can span multiple data files in some tablespaces
- E. A segment's blocks can be of different sizes
- F. A segment might have only one extent
- G. Segments can span multiple tablespaces

Answer: CFG

NEW QUESTION 57

Which four account management capabilities can be configured using Oracle profiles? (Choose four.)

- A. the number of hours for which an account is locked after the configured number of login attempts has been reached
- B. the number of days for which an account may be inactive before it is locked
- C. the maximum amount of CPU time allowed for a user's sessions before their account is locked
- D. the ability to prevent a password from ever being reused
- E. the number of password changes required within a period of time before a password can be reused
- F. the number of days for which an account is locked after the configured number of login attempts has been reached
- G. the maximum number of sessions permitted for a user before the account is locked

Answer: DEFG

NEW QUESTION 58

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual 1z0-082 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the 1z0-082 Product From:

<https://www.2passeasy.com/dumps/1z0-082/>

Money Back Guarantee

1z0-082 Practice Exam Features:

- * 1z0-082 Questions and Answers Updated Frequently
- * 1z0-082 Practice Questions Verified by Expert Senior Certified Staff
- * 1z0-082 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 1z0-082 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year