

SOA-C01 Dumps

AWS Certified SysOps Administrator - Associate

<https://www.certleader.com/SOA-C01-dumps.html>



NEW QUESTION 1

When preparing for a compliance assessment of your system built inside of AWS. what are three best-practices for you to prepare for an audit?
Choose 3 answers

- A. Gather evidence of your IT operational controls
- B. Request and obtain applicable third-party audited AWS compliance reports and certifications
- C. Request and obtain a compliance and security tour of an AWS data center for a pre-assessment security review
- D. Request and obtain approval from AWS to perform relevant network scans and in-depth penetration tests of your system's Instances and endpoints
- E. Schedule meetings with AWS's third-party auditors to provide evidence of AWS compliance that maps to your control objectives

Answer: ABD

NEW QUESTION 2

You have identified network throughput as a bottleneck on your m1.small EC2 instance when uploading data Into Amazon S3 In the same region.
How do you remedy this situation?

- A. Add an additional ENI
- B. Change to a larger Instance
- C. Use DirectConnect between EC2 and S3
- D. Use EBS PIOPS on the local volume

Answer: B

Explanation:

Reference:

https://media.amazonwebservices.com/AWS_Amazon_EMR_Best_Practices.pdf

NEW QUESTION 3

When attached to an Amazon VPC which two components provide connectivity with external networks? Choose 2 answers

- A. Elastic IPS (EIP)
- B. NAT Gateway (NAT)
- C. Internet Gateway (IGW)
- D. Virtual Private Gateway (VGW)

Answer: CD

NEW QUESTION 4

Which two AWS services provide out-of-the-box user configurable automatic backup-as-a-service and backup rotation options? Choose 2 answers

- A. Amazon S3
- B. Amazon RDS
- C. Amazon EBS
- D. Amazon Redshift

Answer: BD

Explanation:

By default: at no additional charge, Amazon RDS enables automated backups of your DB Instance with a 1-day retention period. By default: Amazon Redshift enables automated backups of your data warehouse cluster with a 1- day retention period.

NEW QUESTION 5

You are creating an Auto Scaling group whose Instances need to insert a custom metric into CloudWatch.
Which method would be the best way to authenticate your CloudWatch PUT request?

- A. Create an IAM role with the Put MetricData permission and modify the Auto Scaling launch configuration to launch instances in that role
- B. Create an IAM user with the Put MetricData permission and modify the Auto Scaling launch configuration to inject the users credentials into the instance User Data
- C. Modify the appropriate Cloud Watch metric policies to allow the Put MetricData permission to instances from the Auto Scaling group
- D. Create an IAM user with the Put MetricData permission and put the credentials in a private repository and have applications on the server pull the credentials as needed

Answer: A

NEW QUESTION 6

When an EC2 instance that is backed by an S3-based AMI Is terminated, what happens to the data on me root volume?

- A. Data is automatically saved as an EBS volume.
- B. Data is automatically saved as an ESS snapshot.
- C. Data is automatically deleted.
- D. Data is unavailable until the instance is restarted.

Answer: C

Explanation:

Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ComponentsAMIs.html>

NEW QUESTION 7

What is a placement group?

- A. A collection of Auto Scaling groups in the same Region
- B. Feature that enables EC2 instances to interact with each other via high bandwidth, low latency connections
- C. A collection of Elastic Load Balancers in the same Region or Availability Zone
- D. A collection of authorized Cloud Front edge locations for a distribution

Answer: B

Explanation:

Reference:

<http://aws.amazon.com/ec2/faqs/>

A placement group is a logical grouping of instances within a single Availability Zone. Using placement groups enables applications to participate in a low-latency, 10 Gigabits per second (Gbps) network. Placement groups are recommended for applications that benefit from low network latency, high network throughput, or both

NEW QUESTION 8

You have two Elastic Compute Cloud (EC2) instances inside a Virtual Private Cloud (VPC) in the same Availability Zone (AZ) but in different subnets. One instance is running a database and the other instance an application that will interface with the database. You want to confirm that they can talk to each other for your application to work properly.

Which two things do we need to confirm in the VPC settings so that these EC2 instances can communicate inside the VPC?

Choose 2 answers

- A. A network ACL that allows communication between the two subnets.
- B. Both instances are the same instance class and using the same Key-pair.
- C. That the default route is set to a NAT instance or internet Gateway (IGW) for them to communicate.
- D. Security groups are set to allow the application host to talk to the database on the right port/protocol.

Answer: AD

NEW QUESTION 9

You have a web-style application with a stateless but CPU and memory-intensive web tier running on

a cc2 8xlarge EC2 instance inside of a VPC. The instance when under load is having problems returning requests within the SLA as defined by your business. The application maintains its state in a DynamoDB table, but the data tier is properly provisioned and responses are consistently fast.

How can you best resolve the issue of the application responses not meeting your SLA?

- A. Add another cc2 8xlarge application instance, and put both behind an Elastic Load Balancer
- B. Move the cc2 8xlarge to the same Availability Zone as the DynamoDB table
- C. Cache the database responses in ElastiCache for more rapid access
- D. Move the database from DynamoDB to RDS MySQL in scale-out read-replica configuration

Answer: C

Explanation:

But it is possibly A as DynamoDB is automatically available across three facilities in an AWS Region. So moving in to a same AZ is not possible / necessary.

In this case the DB layer is not the issue, the EC2 8xlarge is the issue; so add another one with a ELB in-front of it.

See also: <https://aws.amazon.com/dynamodb/faqs/>

NEW QUESTION 10

Which of the following statements about this S3 bucket policy is true?

```
{
  "Id": "IPAllowPolicy",
  "Statement": [
    {
      "Sid": "IPAllow",
      "Action": "s3:*",
      "Effect": "Allow",
      "Resource": "arn:aws:s3::mybucket/*",
      "Condition": {
        "IpAddress": {
          "aws:SourceIp": "192.168.100.0/24"
        },
        "NotIpAddress": {
          "aws:SourceIp": "192.168.100.188/32"
        }
      }
    }
  ],
  "Principal": {
    "AWS": [
      "*"
    ]
  }
}
```

- A. Denies the server with the IP address 192.168.100.0 full access to the "mybucket" bucket
- B. Denies the server with the IP address 192.168.100.188 full access to the "mybucket" bucket
- C. Grants all the servers within the 192.168.100.0/24 subnet full access to the "mybucket" bucket
- D. Grants all the servers within the 192.168.100.188/32 subnet full access to the "mybucket" bucket

Answer: B

NEW QUESTION 10

Which of the following requires a custom CloudWatch metric to monitor?

- A. Data transfer of an EC2 instance
- B. Disk usage activity of an EC2 instance
- C. Memory Utilization of an EC2 instance
- D. CPU Utilization of an EC2 instance

Answer: C

Explanation:

Reference:

<http://aws.amazon.com/cloudwatch/>

NEW QUESTION 11

You run a web application where web servers on EC2 Instances are In an Auto Scaling group Monitoring over the last 6 months shows that 6 web servers are necessary to handle the minimum load During the day up to 12 servers are needed Five to six days per year, the number of web servers required might go up to 15.

What would you recommend to minimize costs while being able to provide high availability?

- A. 6 Reserved instances (heavy utilization). 6 Reserved instances (medium utilization), rest covered by On-Demand instances
- B. 6 Reserved instances (heavy utilization). 6 On-Demand instances, rest covered by Spot Instances
- C. 6 Reserved instances (heavy utilization) 6 Spot instances, rest covered by On-Demand instances
- D. 6 Reserved instances (heavy utilization) 6 Reserved instances (medium utilization) rest covered by Spot instances

Answer: A

Explanation:

The only plausible answer is A because all other answers include Spot Instances that can be removed without warning and that would not be highly available.

NEW QUESTION 15

You have been asked to propose a multi-region deployment of a web-facing application where a controlled portion of your traffic is being processed by an alternate region.

Which configuration would achieve that goal?

- A. Route53 record sets with weighted routing policy
- B. Route53 record sets with latency based routing policy
- C. Auto Scaling with scheduled scaling actions set
- D. Elastic Load Balancing with health checks enabled

Answer: A

Explanation:

The question is asking ??a controlled portion of your traffic??, that would be established with weighted routing policy.

See: <http://docs.aws.amazon.com/Route53/latest/DeveloperGuide/routing-policy.html>

NEW QUESTION 17

Your EC2-Based Multi-tier application includes a monitoring instance that periodically makes application -level read only requests of various application components and if any of those fail more than three times 30 seconds calls CloudWatch to fire an alarm, and the alarm notifies your operations team by email and SMS of a possible application health problem. However, you also need to ??watch the watcher?? --the monitoring instance itself - and be notified if it becomes unhealthy.

Which of the following is a simple way to achieve that goal?

- A. Run another monitoring instance that pings the monitoring instance and fires a CloudWatch alarm that notifies your operations team should the primary monitoring instance become unhealthy.
- B. Set a CloudWatch alarm based on EC2 system and instance status checks and have the alarm notify your operations team of any detected problem with the monitoring instance.
- C. Set a CloudWatch alarm based on the CPU utilization of the monitoring instance and have the alarm notify your operations team if the CPU usage exceeds 50% for more than one minute; then have your monitoring application go into a CPU-bound loop should it detect any application problems.
- D. Have the monitoring instances post messages to an SQS queue and then dequeue those messages on another instance should the queue cease to have new messages, the second instance should first terminate the original monitoring instance start another backup monitoring instance and assume the role of the previous monitoring instance and begin adding messages to the SQS queue.

Answer: B

NEW QUESTION 18

You have decided to change the Instance type for instances running in your application tier that are using Auto Scaling. In which area below would you change the instance type definition?

- A. Auto Scaling launch configuration
- B. Auto Scaling group
- C. Auto Scaling policy
- D. Auto Scaling tags

Answer: A

Explanation:

Reference:

<http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/WhatIsAutoScaling.html>

NEW QUESTION 20

You are attempting to connect to an instance in Amazon VPC without success. You have already verified that the VPC has an Internet Gateway (IGW) the instance has an associated Elastic IP (EIP) and correct security group rules are in place.

Which VPC component should you evaluate next?

- A. The configuration of a NAT instance
- B. The configuration of the Routing Table
- C. The configuration of the Internet Gateway (IGW)
- D. The configuration of SRC/DST checking

Answer: B

Explanation:

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/UserScenariosForVPC.html>

NEW QUESTION 21

Your organization's security policy requires that all privileged users either use frequently rotated passwords or one-time access credentials in addition to username/password.

Which two of the following options would allow an organization to enforce this policy for AWS users? Choose 2 answers

- A. Configure multi-factor authentication for privileged IAM users
- B. Create IAM users for privileged accounts
- C. Implement identity federation between your organization's Identity provider leveraging the IAM Security Token Service
- D. Enable the IAM single-use password policy option for privileged users

Answer: AB

Explanation:

See also: <http://docs.aws.amazon.com/IAM/latest/UserGuide/best-practices.html>

Enable MFA for privileged users

For extra security, enable multifactor authentication (MFA) for privileged IAM users (users who are allowed access to sensitive resources or APIs). With MFA, users have a device that generates a unique authentication code (a one-time password, or OTP) and users must provide both their normal credentials (like their user name and password) and the OTP. The MFA device can either be a special piece of hardware, or it can be a virtual device (for example, it can run in an app on a smartphone).

NEW QUESTION 22

You use S3 to store critical data for your company. Several users within your group currently have full permissions to your S3 buckets. You need to come up with a solution that does not impact your users and also protect against the accidental deletion of objects.

Which two options will address this issue? Choose 2 answers

- A. Enable versioning on your S3 Buckets
- B. Configure your S3 Buckets with MFA delete
- C. Create a Bucket policy and only allow read only permissions to all users at the bucket level

D. Enable object life cycle policies and configure the data older than 3 months to be archived in Glacier

Answer: AD

NEW QUESTION 26

An organization's security policy requires multiple copies of all critical data to be replicated across at least a primary and backup data center. The organization has decided to store some critical data on Amazon S3.

Which option should you implement to ensure this requirement is met?

- A. Use the S3 copy API to replicate data between two S3 buckets in different regions
- B. You do not need to implement anything since S3 data is automatically replicated between regions
- C. Use the S3 copy API to replicate data between two S3 buckets in different facilities within an AWS Region
- D. You do not need to implement anything since S3 data is automatically replicated between multiple facilities within an AWS Region

Answer: D

Explanation:

It seems that this question wants to emphasize below (S3 Faq ?V <https://aws.amazon.com/s3/faqs/>) You specify a region when you create your Amazon S3 bucket. Within that region, your objects are redundantly stored on multiple devices across multiple facilities. Please refer to Regional Products and Services for details of Amazon S3 service availability by region.

NEW QUESTION 27

You have a server with a 500GB Amazon EBS data volume. The volume is 80% full. You need to back up the volume at regular intervals and be able to re-create the volume in a new Availability Zone in the shortest time possible. All applications using the volume can be paused for a period of a few minutes with no discernible user impact.

Which of the following backup methods will best fulfill your requirements?

- A. Take periodic snapshots of the EBS volume
- B. Use a third party Incremental backup application to back up to Amazon Glacier
- C. Periodically back up all data to a single compressed archive and archive to Amazon S3 using a parallelized multi-part upload
- D. Create another EBS volume in the second Availability Zone attach it to the Amazon EC2 instance, and use a disk manager to mirror the two disks

Answer: A

Explanation:

Since an EBS volume should be in the same AZ as the EC2 instance. You cannot connect a EBS volume in another AZ.

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-restoring-volume.html> EBS volumes can only be attached to EC2 instances within the same Availability Zone.

NEW QUESTION 30

Your company is moving towards tracking web page users with a small tracking image loaded on each page. Currently you are serving this image out of US-East, but are starting to get concerned about the time it takes to load the image for users on the west coast.

What are the two best ways to speed up serving this image? Choose 2 answers

- A. Use Route 53's Latency Based Routing and serve the image out of US-West-2 as well as US-East-1
- B. Serve the image out through CloudFront
- C. Serve the image out of S3 so that it isn't being served off of your web application tier
- D. Use EBS PIOPs to serve the image faster out of your EC2 instances

Answer: AB

Explanation:

CloudFront gets the image closer to the user and Route53 ensures the best connection based on network latency. Option D does not address the issue.

NEW QUESTION 34

If you want to launch Amazon Elastic Compute Cloud (EC2) Instances and assign each Instance a predetermined private IP address you should:

- A. Assign a group or sequential Elastic IP address to the instances
- B. Launch the instances in a Placement Group
- C. Launch the instances in the Amazon virtual Private Cloud (VPC).
- D. Use standard EC2 instances since each instance gets a private Domain Name Service (DNS) already
- E. Launch the Instance from a private Amazon Machine image (AMI)

Answer: C

Explanation:

When you launch an instance into a VPC, a primary private IP address from the address range of the subnet is assigned to the default network interface (eth0) of the instance. If you don't specify a primary private IP address, we select an available IP address in the subnet range for you

<http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/vpc-ip-addressing.html>

NEW QUESTION 35

An organization has created 5 IAM users. The organization wants to give them the same login ID but different passwords. How can the organization achieve this?

- A. The organization should create a separate login ID but give the IAM users the same alias so that each one can login with their alias
- B. The organization should create each user in a separate region so that they have their own URL to login
- C. It is not possible to have the same login ID for multiple IAM users of the same account
- D. The organization should create various groups and add each user with the same login ID to different group

E. The user can login with their own group ID

Answer: C

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Whenever the organization is creating an IAM user, there should be a unique ID for each user. It is not possible to have the same login ID for multiple users. The names of users, groups, roles, instance profiles must be alphanumeric, including the following common characters: plus (+), equal (=), comma (,), period (.), at (@), and dash (-).

NEW QUESTION 36

A user is planning to evaluate AWS for their internal use. The user does not want to incur any charge on his account during the evaluation. Which of the below mentioned AWS services would incur a charge if used?

- A. AWS S3 with 1 GB of storage
- B. AWS micro instance running 24 hours daily
- C. AWS ELB running 24 hours a day
- D. AWS PIOPS volume of 10 GB size

Answer: D

Explanation:

AWS is introducing a free usage tier for one year to help the new AWS customers get started in Cloud. The free tier can be used for anything that the user wants to run in the Cloud. AWS offers a handful of AWS services as a part of this which includes 750 hours of free micro instances and 750 hours of ELB. It includes the AWS S3 of 5 GB and AWS EBS general purpose volume upto 30 GB. PIOPS is not part of free usage tier.

NEW QUESTION 39

A user has developed an application which is required to send the data to a NoSQL database. The user wants to decouple the data sending such that the application keeps processing and sending data but does not wait for an acknowledgement of DB. Which of the below mentioned applications helps in this scenario?

- A. AWS Simple Notification Service
- B. AWS Simple Workflow
- C. AWS Simple Queue Service
- D. AWS Simple Query Service

Answer: C

Explanation:

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. In this case, the user can use AWS SQS to send messages which are received from an application and sent to DB. The application can continue processing data without waiting for any acknowledgement from DB. The user can use SQS to transmit any volume of data without losing messages or requiring other services to always be available.

NEW QUESTION 41

An organization has created 50 IAM users. The organization has introduced a new policy which will change the access of an IAM user. How can the organization implement this effectively so that there is no need to apply the policy at the individual user level?

- A. Use the IAM groups and add users as per their role to different groups and apply policy to group
- B. The user can create a policy and apply it to multiple users in a single go with the AWS CLI
- C. Add each user to the IAM role as per their organization role to achieve effective policy setup
- D. Use the IAM role and implement access at the role level

Answer: A

Explanation:

With AWS IAM, a group is a collection of IAM users. A group allows the user to specify permissions for a collection of users, which can make it easier to manage the permissions for those users. A group helps an organization manage access in a better way; instead of applying at the individual level, the organization can apply at the group level which is applicable to all the users who are a part of that group.

NEW QUESTION 45

A user is planning to use AWS Cloud formation for his automatic deployment requirements. Which of the below mentioned components are required as a part of the template?

- A. Parameters
- B. Outputs
- C. Template version
- D. Resources

Answer: D

Explanation:

AWS Cloud formation is an application management tool which provides application modelling, deployment, configuration, management and related activities. The template is a JSON-format, text-based file that describes all the AWS resources required to deploy and run an application. It can have option fields, such as Template Parameters, Output, Data tables, and Template file format version. The only mandatory value is Resource. The user can define the AWS services which will be used/ created by this template inside the Resource section

NEW QUESTION 48

A user has recently started using EC2. The user launched one EC2 instance in the default subnet in EC2-VPC. Which of the below mentioned options is not attached or available with the EC2 instance when it is launched?

- A. Public IP address
- B. Internet gateway
- C. Elastic IP
- D. Private IP address

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to a user's AWS account. A subnet is a range of IP addresses in the VPC. The user can launch the AWS resources into a subnet. There are two supported platforms into which a user can launch instances: EC2-Classic and EC2-VPC (default subnet). A default VPC has all the benefits of EC2-VPC and the ease of use of EC2-Classic. Each instance that the user launches into a default subnet has a private IP address and a public IP address. These instances can communicate with the internet through an internet gateway. An internet gateway enables the EC2 instances to connect to the internet through the Amazon EC2 network edge.

NEW QUESTION 50

A user has launched an EC2 instance. The user is planning to setup the CloudWatch alarm. Which of the below mentioned actions is not supported by the CloudWatch alarm?

- A. Notify the Auto Scaling launch config to scale up
- B. Send an SMS using SNS
- C. Notify the Auto Scaling group to scale down
- D. Stop the EC2 instance

Answer: A

Explanation:

A user can create a CloudWatch alarm that takes various actions when the alarm changes state. An alarm watches a single metric over the time period that the user has specified, and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The actions could be sending a notification to an Amazon Simple Notification Service topic (SNS, Email, and HTTP end point) notifying the Auto Scaling policy or changing the state of the instance to Stop/Terminate.

CloudWatch cannot change the auto-scaling launch configuration.

B ?V It can send an SMS with SNS

C ?V Auto-scaling uses CloudWatch metrics to scale up and down.

D ?V CloudWatch can stop instances

NEW QUESTION 52

A user has deployed an application on his private cloud. The user is using his own monitoring tool. He wants to configure that whenever there is an error, the monitoring tool should notify him via SMS. Which of the below mentioned AWS services will help in this scenario?

- A. None because the user infrastructure is in the private cloud
- B. AWS SNS
- C. AWS SES
- D. AWS SMS

Answer: B

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS can be used to make push notifications to mobile devices. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS) queues or to any HTTP endpoint. In this case, the user can use the SNS APIs to send SMS.

NEW QUESTION 56

A user has created a web application with Auto Scaling. The user is regularly monitoring the application and he observed that the traffic is highest on Thursday and Friday between 8 AM to 6 PM. What is the best solution to handle scaling in this case?

- A. Add a new instance manually by 8 AM Thursday and terminate the same by 6 PM Friday
- B. Schedule Auto Scaling to scale up by 8 AM Thursday and scale down after 6 PM on Friday
- C. Schedule a policy which may scale up every day at 8 AM and scale down by 6 PM
- D. Configure a batch process to add an instance by 8 AM and remove it by Friday 6 PM

Answer: B

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. In this case, the load increases by Thursday and decreases by Friday. Thus, the user can setup the scaling activity based on the predictable traffic patterns of the web application using Auto Scaling scale by Schedule.

<http://docs.aws.amazon.com/cli/latest/reference/opsworks/set-time-based-auto-scaling.html>

NEW QUESTION 59

A user has setup a CloudWatch alarm on an EC2 action when the CPU utilization is above 75%. The alarm sends a notification to SNS on the alarm state. If the user wants to simulate the alarm action, how can he achieve this?

- A. Run activities on the CPU such that its utilization reaches above 75%
- B. From the AWS console, change the state to ??Alarm??
- C. The user can set the alarm state to ??Alarm?? using CLI

D. Run the SNS action manually

Answer: C

Explanation:

Amazon CloudWatch alarms watch a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The user can test an alarm by setting it to any state using the SetAlarmState API (mon-set-alarm-state command.. This temporary state change lasts only until the next alarm comparison occurs.
[http://docs.aws.amazon.com/AmazonCloudWatch/latest/DeveloperGuide/AlarmThatSendsEmail.ht ml](http://docs.aws.amazon.com/AmazonCloudWatch/latest/DeveloperGuide/AlarmThatSendsEmail.html)

NEW QUESTION 64

A user is trying to setup a scheduled scaling activity using Auto Scaling. The user wants to setup the recurring schedule. Which of the below mentioned parameters is not required in this case?

- A. Maximum size
- B. Auto Scaling group name
- C. End time
- D. Recurrence value

Answer: A

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. The user can also configure the recurring schedule action which will follow the Linux cron format. If the user is setting a recurring event, it is required that the user specifies the Recurrence value (in a cron format., end time (not compulsory but recurrence will stop after this. and the Auto Scaling group for which the scaling activity is to be scheduled.

NEW QUESTION 67

A sysadmin has created the below mentioned policy and applied to an S3 object named aws.jpg. The aws.jpg is inside a bucket named cloudacademy. What does this policy define?

```
"Statement": [{  
  "Sid": "Stmt1388811069831",  
  "Effect": "Allow", "Principal": { "AWS": "*" },  
  "Action": [ "s3:GetObjectAcl", "s3:ListBucket", "s3:GetObject"], "Resource": [ "arn:aws:s3:::cloudacademy/* .jpg"]  
}]
```

- A. It is not possible to define a policy at the object level
- B. It will make all the objects of the bucket cloudacademy as public
- C. It will make the bucket cloudacademy as public
- D. the aws.jpg object as public

Answer: A

NEW QUESTION 71

A user is trying to save some cost on the AWS services. Which of the below mentioned options will not help him save cost?

- A. Delete the unutilized EBS volumes once the instance is terminated
- B. Delete the AutoScaling launch configuration after the instances are terminated
- C. Release the elastic IP if not required once the instance is terminated
- D. Delete the AWS ELB after the instances are terminated

Answer: B

Explanation:

AWS bills the user on a as pay as you go model. AWS will charge the user once the AWS resource is allocated. Even though the user is not using the resource, AWS will charge if it is in service or allocated. Thus, it is advised that once the user's work is completed he should:
Terminate the EC2 instance Delete the EBS volumes Release the unutilized Elastic IPs Delete ELB The AutoScaling launch configuration does not cost the user. Thus, it will not make any difference to the cost whether it is deleted or not.

NEW QUESTION 74

A user has created a subnet with VPC and launched an EC2 instance in that subnet with only default settings. Which of the below mentioned options is ready to use on the EC2 instance as soon as it is launched?

- A. Elastic IP
- B. Private IP
- C. Public IP
- D. Internet gateway

Answer: B

Explanation:

A Virtual Private Cloud (VPC. is a virtual network dedicated to a user's AWS account? A subnet is a range of IP addresses in the VPC. The user can launch the AWS resources into a subnet. There are two supported platforms into which a user can launch instances: EC2-Classic and EC2-VPC. When the user launches an instance which is not a part of the non-default subnet, it will only have a private IP assigned to it. The instances part of a subnet can communicate with each other but cannot communicate over the internet or to the AWS services, such as RDS / S3.

NEW QUESTION 77

A user has configured the Auto Scaling group with the minimum capacity as 3 and the maximum capacity as 5. When the user configures the AS group, how many

instances will Auto Scaling launch?

- A. 3
- B. 5
- C. 2

Answer: A

Explanation:

The default launch is going to configure 3 instances. It will only go to 5 under certain conditions. It won't launch initially 5 instances. This question doesn't give enough information to answer fully.

NEW QUESTION 81

A system admin is planning to setup event notifications on RDS. Which of the below mentioned services will help the admin setup notifications?

- A. AWS SES
- B. AWS Cloudtrail
- C. AWS Cloudwatch
- D. AWS SNS

Answer: D

Explanation:

Amazon RDS uses the Amazon Simple Notification Service to provide a notification when an Amazon RDS event occurs. These notifications can be in any notification form supported by Amazon SNS for an AWS region, such as an email, a text message or a call to an HTTP endpoint

NEW QUESTION 84

An organization wants to move to Cloud. They are looking for a secure encrypted database storage option. Which of the below mentioned AWS functionalities helps them to achieve this?

- A. AWS MFA with EBS
- B. AWS EBS encryption
- C. Multi-tier encryption with Redshift
- D. AWS S3 server side storage

Answer: B

Explanation:

AWS EBS supports encryption of the volume while creating new volumes. It also supports creating volumes from existing snapshots provided the snapshots are created from encrypted volumes. The data at rest, the I/O as well as all the snapshots of EBS will be encrypted. The encryption occurs on the servers that host the EC2 instances, providing encryption of data as it moves between the EC2 instances and EBS storage. EBS encryption is based on the AES-256 cryptographic algorithm, which is the industry standard.

NEW QUESTION 86

A user wants to disable connection draining on an existing ELB. Which of the below mentioned statements helps the user disable connection draining on the ELB?

- A. The user can only disable connection draining from CLI
- B. It is not possible to disable the connection draining feature once enabled
- C. The user can disable the connection draining feature from EC2 -> ELB console or from CLI
- D. The user needs to stop all instances before disabling connection draining

Answer: C

Explanation:

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that inflight requests continue to be served. The user can enable or disable connection draining from the AWS EC2 console -> ELB or using CLI.

NEW QUESTION 90

An organization has created 50 IAM users. The organization wants that each user can change their password but cannot change their access keys. How can the organization achieve this?

- A. The organization has to create a special password policy and attach it to each user
- B. The root account owner has to use CLI which forces each IAM user to change their password on first login
- C. By default, each IAM user can modify their passwords
- D. The root account owner can set the policy from the IAM console under the password policy screen

Answer: D

Explanation:

With AWS IAM, organizations can use the AWS Management Console to display, create, change or delete a password policy. As a part of managing the password policy, the user can enable all users to manage their own passwords. If the user has selected the option which allows the IAM users to modify their password, he does not need to set a separate policy for the users. This option in the AWS console allows changing only the password.

NEW QUESTION 92

A user has created an S3 bucket which is not publicly accessible. The bucket is having thirty objects which are also private. If the user wants to make the objects public, how can he configure this with minimal efforts?

- A. The user should select all objects from the console and apply a single policy to mark them public
- B. The user can write a program which programmatically makes all objects public using S3 SDK
- C. Set the AWS bucket policy which marks all objects as public
- D. Make the bucket ACL as public so it will also mark all objects as public

Answer: C

Explanation:

A system admin can grant permission of the S3 objects or buckets to any user or make the objects public using the bucket policy and user policy. Both use the JSON-based access policy language.

Generally, if the user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket.

NEW QUESTION 95

A sys admin is maintaining an application on AWS. The application is installed on EC2 and user has configured ELB and Auto Scaling. Considering future load increase, the user is planning to launch new servers proactively so that they get registered with ELB. How can the user add these instances with Auto Scaling?

- A. Increase the desired capacity of the Auto Scaling group
- B. Increase the maximum limit of the Auto Scaling group
- C. Launch an instance manually and register it with ELB on the fly
- D. Decrease the minimum limit of the Auto Scaling group

Answer: A

Explanation:

A user can increase the desired capacity of the Auto Scaling group and Auto Scaling will launch a new instance as per the new capacity. The newly launched instances will be registered with ELB if Auto Scaling group is configured with ELB. If the user decreases the minimum size the instances will be removed from Auto Scaling. Increasing the maximum size will not add instances but only set the maximum instance cap.

NEW QUESTION 98

An organization, which has the AWS account ID as 999988887777, has created 50 IAM users. All the users are added to the same group cloudacademy. If the organization has enabled that each IAM user can login with the AWS console, which AWS login URL will the IAM users use?

- A. <https://999988887777.signin.aws.amazon.com/console/>
- B. <https://signin.aws.amazon.com/cloudacademy/>
- C. <https://cloudacademy.signin.aws.amazon.com/999988887777/console/>
- D. <https://999988887777.aws.amazon.com/cloudacademy/>

Answer: A

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Once the organization has created the IAM users, they will have a separate AWS console URL to login to the AWS console. The console login URL for the IAM user will be https://AWS_Account_ID.signin.aws.amazon.com/console/. It uses only the AWS account ID and does not depend on the group or user ID.

NEW QUESTION 103

A user has setup connection draining with ELB to allow in-flight requests to continue while the instance is being deregistered through Auto Scaling. If the user has not specified the draining time, how long will ELB allow inflight requests traffic to continue?

- A. 600 seconds
- B. 3600 seconds
- C. 300 seconds
- D. 0 seconds

Answer: C

Explanation:

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that inflight requests continue to be served. The user can specify a maximum time (3600 seconds) for the load balancer to keep the connections alive before reporting the instance as deregistered. If the user does not specify the maximum timeout period, by default, the load balancer will close the connections to the deregistering instance after 300 seconds.

NEW QUESTION 105

A root AWS account owner is trying to understand various options to set the permission to AWS S3. Which of the below mentioned options is not the right option to grant permission for S3?

- A. User Access Policy
- B. S3 Object Access Policy
- C. S3 Bucket Access Policy
- D. S3 ACL

Answer: B

Explanation:

Amazon S3 provides a set of operations to work with the Amazon S3 resources. Managing S3 resource access refers to granting others permissions to work with S3. There are three ways the root account owner can define access with S3:

S3 ACL: The user can use ACLs to grant basic read/write permissions to other AWS accounts.

S3 Bucket Policy: The policy is used to grant other AWS accounts or IAM users permissions for the bucket and the objects in it.

User Access Policy: Define an IAM user and assign him the IAM policy which grants him access to S3.

NEW QUESTION 107

A sysadmin has created a shopping cart application and hosted it on EC2. The EC2 instances are running behind ELB. The admin wants to ensure that the end user request will always go to the EC2 instance where the user session has been created. How can the admin configure this?

- A. Enable ELB cross zone load balancing
- B. Enable ELB cookie setup
- C. Enable ELB sticky session
- D. Enable ELB connection draining

Answer: C

Explanation:

Generally, AWS ELB routes each request to a zone with the minimum load. The Elastic Load Balancer provides a feature called sticky session which binds the user's session with a specific EC2 instance. If the sticky session is enabled the first request from the user will be redirected to any of the EC2 instances. But, henceforth, all requests from the same user will be redirected to the same EC2 instance. This ensures that all requests coming from the user during the session will be sent to the same application instance.

NEW QUESTION 109

A user has configured ELB with three instances. The user wants to achieve High Availability as well as redundancy with ELB. Which of the below mentioned AWS services helps the user achieve this for ELB?

- A. Route 53
- B. AWS Mechanical Turk
- C. Auto Scaling
- D. AWS EMR

Answer: A

Explanation:

The user can provide high availability and redundancy for applications running behind Elastic Load Balancer by enabling the Amazon Route 53 Domain Name System (DNS) failover for the load balancers. Amazon Route 53 is a DNS service that provides reliable routing to the user's infrastructure.

NEW QUESTION 111

A user has launched an ELB which has 5 instances registered with it. The user deletes the ELB by mistake. What will happen to the instances?

- A. ELB will ask the user whether to delete the instances or not
- B. Instances will be terminated
- C. ELB cannot be deleted if it has running instances registered with it
- D. Instances will keep running

Answer: D

Explanation:

When the user deletes the Elastic Load Balancer, all the registered instances will be deregistered. However, they will continue to run. The user will incur charges if he does not take any action on those instances.

NEW QUESTION 112

A user is planning to setup notifications on the RDS DB for a snapshot. Which of the below mentioned event categories is not supported by RDS for this snapshot source type?

- A. Backup
- B. Creation
- C. Deletion
- D. Restoration

Answer: A

Explanation:

Amazon RDS uses the Amazon Simple Notification Service to provide a notification when an Amazon RDS event occurs. Event categories for a snapshot source type include: Creation, Deletion, and Restoration. The Backup is a part of DB instance source type.

NEW QUESTION 117

A customer is using AWS for Dev and Test. The customer wants to setup the Dev environment with Cloudformation. Which of the below mentioned steps are not required while using Cloudformation?

- A. Create a stack
- B. Configure a service
- C. Create and upload the template
- D. Provide the parameters configured as part of the template

Answer: B

Explanation:

AWS Cloudformation is an application management tool which provides application modelling, deployment, configuration, management and related activities. AWS CloudFormation introduces two concepts: the template and the stack. The template is a JSON-format, text-based file that describes all the AWS resources

required to deploy and run an application. The stack is a collection of AWS resources which are created and managed as a single unit when AWS CloudFormation instantiates a template. While creating a stack, the user uploads the template and provides the data for the parameters if required.

NEW QUESTION 120

A user is accessing RDS from an application. The user has enabled the Multi AZ feature with the MS SQL RDS DB. During a planned outage how will AWS ensure that a switch from DB to a standby replica will not affect access to the application?

- A. RDS will have an internal IP which will redirect all requests to the new DB
- B. RDS uses DNS to switch over to stand by replica for seamless transition
- C. The switch over changes Hardware so RDS does not need to worry about access
- D. RDS will have both the DBs running independently and the user has to manually switch over

Answer: B

Explanation:

In the event of a planned or unplanned outage of a DB instance, Amazon RDS automatically switches to a standby replica in another Availability Zone if the user has enabled Multi AZ. The automatic failover mechanism simply changes the DNS record of the DB instance to point to the standby DB instance. As a result, the user will need to re-establish any existing connections to the DB instance. However, as the DNS is the same, the application can access DB seamlessly.

NEW QUESTION 121

An organization has configured the custom metric upload with CloudWatch. The organization has given permission to its employees to upload data using CLI as well SDK. How can the user track the calls made to CloudWatch?

- A. The user can enable logging with CloudWatch which logs all the activities
- B. Use CloudTrail to monitor the API calls
- C. Create an IAM user and allow each user to log the data using the S3 bucket
- D. Enable detailed monitoring with CloudWatch

Answer: B

Explanation:

AWS CloudTrail is a web service which will allow the user to monitor the calls made to the Amazon CloudWatch API for the organization's account, including calls made by the AWS Management Console, Command Line Interface (CLI), and other services. When CloudTrail logging is turned on, CloudWatch will write log files into the Amazon S3 bucket, which is specified during the CloudTrail configuration.

NEW QUESTION 123

A user has created a queue named myqueue with SQS. There are four messages published to queue which are not received by the consumer yet. If the user tries to delete the queue, what will happen?

- A. A user can never delete a queue manually
- B. AWS deletes it after 30 days of inactivity on queue
- C. It will delete the queue
- D. It will initiate the delete but wait for four days before deleting until all messages are deleted automatically.
- E. It will ask user to delete the messages first

Answer: B

Explanation:

SQS allows the user to move data between distributed components of applications so they can perform different tasks without losing messages or requiring each component to be always available. The user can delete a queue at any time, whether it is empty or not. It is important to note that queues retain messages for a set period of time. By default, a queue retains messages for four days.

NEW QUESTION 127

A user has created numerous EBS volumes. What is the general limit for each AWS account for the maximum number of EBS volumes that can be created?

- A. 10000
- B. 5000
- C. 100
- D. 1000

Answer: B

Explanation:

A user can attach multiple EBS volumes to the same instance within the limits specified by his AWS account. Each AWS account has a limit on the number of Amazon EBS volumes that the user can create, and the total storage available. The default limit for the maximum number of volumes that can be created is 5000.

NEW QUESTION 132

A user has stored data on an encrypted EBS volume. The user wants to share the data with his friend's AWS account. How can user achieve this?

- A. Create an AMI from the volume and share the AMI
- B. Copy the data to an unencrypted volume and then share
- C. Take a snapshot and share the snapshot with a friend
- D. If both the accounts are using the same encryption key then the user can share the volume directly

Answer: B

Explanation:

AWS EBS supports encryption of the volume. It also supports creating volumes from existing snapshots provided the snapshots are created from encrypted volumes. If the user is having data on an encrypted volume and is trying to share it with others, he has to copy the data from the encrypted volume to a new unencrypted volume. Only then can the user share it as an encrypted volume data. Otherwise the snapshot cannot be shared.

NEW QUESTION 133

An organization is using cost allocation tags to find the cost distribution of different departments and projects. One of the instances has two separate tags with the key/ value as ??InstanceName/HR??. ??CostCenter/HR??. What will AWS do in this case?

- A. InstanceName is a reserved tag for AW
- B. Thus, AWS will not allow this tag
- C. AWS will not allow the tags as the value is the same for different keys
- D. AWS will allow tags but will not show correctly in the cost allocation report due to the same value of the two separate keys
- E. AWS will allow both the tags and show properly in the cost distribution report

Answer: D

Explanation:

AWS provides cost allocation tags to categorize and track the AWS costs. When the user applies tags to his AWS resources, AWS generates a cost allocation report as a comma-separated value (CSV file. with the usage and costs aggregated by those tags. Each tag will have a key-value and can be applied to services, such as EC2, S3, RDS, EMR, etc. It is required that the key should be different for each tag. The value can be the same for different keys. In this case since the value is different, AWS will properly show the distribution report with the correct values.

NEW QUESTION 137

A user is publishing custom metrics to CloudWatch. Which of the below mentioned statements will help the user understand the functionality better?

- A. The user can use the CloudWatch Import tool
- B. The user should be able to see the data in the console after around 15 minutes
- C. If the user is uploading the custom data, the user must supply the namespace, timezone, and metric name as part of the command
- D. The user can view as well as upload data using the console, CLI and APIs

Answer: B

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user has to always include the namespace as a part of the request. However, the other parameters are optional. If the user has uploaded data using CLI, he can view it as a graph inside the console. The data will take around 2 minutes to upload but can be viewed only after around 15 minutes.

NEW QUESTION 141

A user has setup Auto Scaling with ELB on the EC2 instances. The user wants to configure that whenever the CPU utilization is below 10%, Auto Scaling should remove one instance. How can the user configure this?

- A. The user can get an email using SNS when the CPU utilization is less than 10%. The user can use the desired capacity of Auto Scaling to remove the instance
- B. Use CloudWatch to monitor the data and Auto Scaling to remove the instances using scheduled actions
- C. Configure CloudWatch to send a notification to Auto Scaling Launch configuration when the CPU utilization is less than 10% and configure the Auto Scaling policy to remove the instance
- D. Configure CloudWatch to send a notification to the Auto Scaling group when the CPU Utilization is less than 10% and configure the Auto Scaling policy to remove the instance

Answer: D

Explanation:

Amazon CloudWatch alarms watch a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The user can setup to receive a notification on the Auto Scaling group with the CloudWatch alarm when the CPU utilization is below a certain threshold. The user can configure the Auto Scaling policy to take action for removing the instance. When the CPU utilization is below 10% CloudWatch will send an alarm to the Auto Scaling group to execute the policy.

NEW QUESTION 144

An organization (Account ID 123412341234. has attached the below mentioned IAM policy to a user. What does this policy statement entitle the user to perform?

```
"Statement": [  
{  
  "Sid": "AllowUsersAllActionsForCredentials", "Effect": "Allow",  
  "Action": [  
    "iam:*AccessKey*",  
  ],  
  "Resource": ["arn:aws:iam:: 123412341234:user/${aws:username}"]  
}]
```

- A. The policy allows the IAM user to modify all IAM user??s credentials using the console, SDK, CLI or APIs
- B. The policy will give an invalid resource error
- C. The policy allows the IAM user to modify all credentials using only the console
- D. The policy allows the user to modify all IAM user??s password, sign in certificates and access keys using only CLI, SDK or APIs

Answer: D

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the organization (Account ID 123412341234. wants some of their users to manage keys (access and secret access keys. of all IAM users, the organization should set

the below mentioned policy which entitles the IAM user to modify keys of all IAM users with CLI, SDK or API.

```
"Statement": [
{
  "Sid": "AllowUsersAllActionsForCredentials", "Effect": "Allow",
  "Action": [ "iam:*AccessKey*",
  ],
  "Resource": ["arn:aws:iam:: 123412341234:user/${aws:username}"]
}
]
```

NEW QUESTION 145

A user is trying to connect to a running EC2 instance using SSH. However, the user gets a connection time out error. Which of the below mentioned options is not a possible reason for rejection?

- A. The access key to connect to the instance is wrong
- B. The security group is not configured properly
- C. The private key used to launch the instance is not correct
- D. The instance CPU is heavily loaded

Answer: A

Explanation:

If the user is trying to connect to a Linux EC2 instance and receives the connection time out error the probable reasons are:

Security group is not configured with the SSH port
The private key pair is not right

The user name to login is wrong

The instance CPU is heavily loaded, so it does not allow more connections

NEW QUESTION 150

A sys admin is trying to understand EBS snapshots. Which of the below mentioned statements will not be useful to the admin to understand the concepts about a snapshot?

- A. The snapshot is synchronous
- B. It is recommended to stop the instance before taking a snapshot for consistent data
- C. The snapshot is incremental
- D. The snapshot captures the data that has been written to the hard disk when the snapshot command was executed

Answer: A

Explanation:

The AWS snapshot is a point in time backup of an EBS volume. When the snapshot command is executed it will capture the current state of the data that is written on the drive and take a backup. For a better and consistent snapshot of the root EBS volume, AWS recommends stopping the instance. For additional volumes it is recommended to unmount the device. The snapshots are asynchronous and incremental.

NEW QUESTION 154

An organization has setup consolidated billing with 3 different AWS accounts. Which of the below mentioned advantages will organization receive in terms of the AWS pricing?

- A. The consolidated billing does not bring any cost advantage for the organization
- B. All AWS accounts will be charged for S3 storage by combining the total storage of each account
- C. The EC2 instances of each account will receive a total of 750*3 micro instance hours free
- D. The free usage tier for all the 3 accounts will be 3 years and not a single year

Answer: B

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS. accounts within a single organization by making a single paying account. For billing purposes, AWS treats all the accounts on the consolidated bill as one account. Some services, such as Amazon EC2 and Amazon S3 have volume pricing tiers across certain usage dimensions that give the user lower prices when he uses the service more.

NEW QUESTION 156

An organization has added 3 of his AWS accounts to consolidated billing. One of the AWS accounts has purchased a Reserved Instance (RI. of a small instance size in the US-East-1a zone. All other AWS accounts are running instances of a small size in the same zone. What will happen in this case for the RI pricing?

- A. Only the account that has purchased the RI will get the advantage of RI pricing
- B. One instance of a small size and running in the US-East-1a zone of each AWS account will get the benefit of RI pricing
- C. Any single instance from all the three accounts can get the benefit of AWS RI pricing if they are running in the same zone and are of the same size
- D. If there are more than one instances of a small size running across multiple accounts in the same zone no one will get the benefit of RI

Answer: C

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS. accounts within a single organization by making a single paying account. For billing purposes, consolidated billing treats all the accounts on the consolidated bill as one account. This means that all accounts on a consolidated bill can receive the hourly cost benefit of the Amazon EC2 Reserved Instances purchased by any other account. In this case only one Reserved Instance has been purchased by one account. Thus, only a single instance from any of the accounts will get the advantage of RI. AWS will implement the blended rate for each instance if more than one instance is running concurrently.

NEW QUESTION 157

An organization is planning to use AWS for 5 different departments. The finance department is responsible to pay for all the accounts. However, they want the cost separation for each account to map with the right cost centre. How can the finance department achieve this?

- A. Create 5 separate accounts and make them a part of one consolidate billing
- B. Create 5 separate accounts and use the IAM cross account access with the roles for better management
- C. Create 5 separate IAM users and set a different policy for their access
- D. Create 5 separate IAM groups and add users as per the department??s employees

Answer: A

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS. accounts within a single organization by making a single paying account. Consolidated billing enables the organization to see a combined view of the AWS charges incurred by each account as well as obtain a detailed cost report for each of the individual AWS accounts associated with the paying account.

NEW QUESTION 160

A user is trying to setup a recurring Auto Scaling process. The user has setup one process to scale up every day at 8 am and scale down at 7 PM. The user is trying to setup another recurring process which scales up on the 1st of every month at 8 AM and scales down the same day at 7 PM. What will Auto Scaling do in this scenario?

- A. Auto Scaling will execute both processes but will add just one instance on the 1st
- B. Auto Scaling will add two instances on the 1st of the month
- C. Auto Scaling will schedule both the processes but execute only one process randomly
- D. Auto Scaling will throw an error since there is a conflict in the schedule of two separate Auto Scaling Processes

Answer: D

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. The user can also configure the recurring schedule action which will follow the Linux cron format. As per Auto Scaling, a scheduled action must have a unique time value. If the user attempts to schedule an activity at a time when another existing activity is already scheduled, the call will be rejected with an error message noting the conflict.

NEW QUESTION 163

A user is planning to setup infrastructure on AWS for the Christmas sales. The user is planning to use Auto Scaling based on the schedule for proactive scaling. What advise would you give to the user?

- A. It is good to schedule now because if the user forgets later on it will not scale up
- B. The scaling should be setup only one week before Christmas
- C. Wait till end of November before scheduling the activity
- D. It is not advisable to use scheduled based scaling

Answer: C

Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. The user can specify any date in the future to scale up or down during that period. As per Auto Scaling the user can schedule an action for up to a month in the future. Thus, it is recommended to wait until end of November before scheduling for Christmas.

NEW QUESTION 166

A user is trying to understand the ACL and policy for an S3 bucket. Which of the below mentioned policy permissions is equivalent to the WRITE ACL on a bucket?

- A. s3:GetObjectAcl
- B. s3:GetObjectVersion
- C. s3:ListBucketVersions
- D. s3:DeleteObject

Answer: D

Explanation:

Amazon S3 provides a set of operations to work with the Amazon S3 resources. Each AWS S3 bucket can have an ACL (Access Control List. or bucket policy associated with it. The WRITE ACL list allows the other AWS accounts to write/modify to that bucket. The equivalent S3 bucket policy permission for it is s3:DeleteObject.

NEW QUESTION 167

A user has created an ELB with Auto Scaling. Which of the below mentioned offerings from ELB helps the user to stop sending new requests traffic from the load balancer to the EC2 instance when the instance is being deregistered while continuing in-flight requests?

- A. ELB sticky session
- B. ELB deregistration check
- C. ELB connection draining
- D. ELB auto registration Off

Answer: C

Explanation:

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that in-flight requests continue to be served.

NEW QUESTION 169

A user has configured a VPC with a new subnet. The user has created a security group. The user wants to configure that instances of the same subnet communicate with each other. How can the user configure this with the security group?

- A. There is no need for a security group modification as all the instances can communicate with each other inside the same subnet
- B. Configure the subnet as the source in the security group and allow traffic on all the protocols and ports
- C. Configure the security group itself as the source and allow traffic on all the protocols and ports
- D. The user has to use VPC peering to configure this

Answer: C

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. AWS provides two features that the user can use to increase security in VPC: security groups and network ACLs. Security groups work at the instance level. If the user is using the default security group it will have a rule which allows the instances to communicate with other. For a new security group the user has to specify the rule, add it to define the source as the security group itself, and select all the protocols and ports for that source.

NEW QUESTION 170

A user is launching an instance. He is on the "Tag the instance" screen. Which of the below mentioned information will not help the user understand the functionality of an AWS tag?

- A. Each tag will have a key and value
- B. The user can apply tags to the S3 bucket
- C. The maximum value of the tag key length is 64 Unicode characters
- D. AWS tags are used to find the cost distribution of various resources

Answer: C

Explanation:

AWS provides cost allocation tags to categorize and track the AWS costs. When the user applies tags to his AWS resources, AWS generates a cost allocation report as a comma-separated value (CSV) file, with the usage and costs aggregated by those tags. Each tag will have a key-value and can be applied to services, such as EC2, S3, RDS, EMR, etc. The maximum size of a tag key is 128 Unicode characters.

NEW QUESTION 175

A user has created a VPC with CIDR 20.0.0.0/16. The user has created public and VPN only subnets along with hardware VPN access to connect to the user's datacenter. The user wants to make so that all traffic coming to the public subnet follows the organization's proxy policy. How can the user make this happen?

- A. Setting up a NAT with the proxy protocol and configure that the public subnet receives traffic from NAT
- B. Setting up a proxy policy in the internet gateway connected with the public subnet
- C. It is not possible to setup the proxy policy for a public subnet
- D. Setting the route table and security group of the public subnet which receives traffic from a virtual private gateway

Answer: D

Explanation:

The user can create subnets within a VPC. If the user wants to connect to VPC from his own data centre, he can setup public and VPN only subnets which uses hardware VPN access to connect with his data centre. When the user has configured this setup, it will update the main route table used with the VPN-only subnet, create a custom route table and associate it with the public subnet. It also creates an internet gateway for the public subnet. By default, the internet traffic of the VPN subnet is routed to a virtual private gateway while the internet traffic of the public subnet is routed through the internet gateway. The user can set up the route and security group rules. These rules enable the traffic to come from the organization's network over the virtual private gateway to the public subnet to allow proxy settings on that public subnet.

NEW QUESTION 178

A user has created a VPC with CIDR 20.0.0.0/24. The user has created a public subnet with CIDR 20.0.0.0/25 and a private subnet with CIDR 20.0.0.128/25. The user has launched one instance each in the private and public subnets. Which of the below mentioned options cannot be the correct IP address (private IP) assigned to an instance in the public or private subnet?

- A. 20.0.0.255
- B. 20.0.0.132
- C. 20.0.0.122
- D. 20.0.0.55

Answer: A

Explanation:

When the user creates a subnet in VPC, he specifies the CIDR block for the subnet. In this case the user has created a VPC with the CIDR block 20.0.0.0/24, which supports 256 IP addresses (20.0.0.0 to 20.0.0.255). The public subnet will have IP addresses between 20.0.0.0 - 20.0.0.127 and the private subnet will have IP addresses between 20.0.0.128 - 20.0.0.255. AWS reserves the first four IP addresses and the last IP address in each subnet's CIDR block. These are not available for the user to use. Thus, the instance cannot have an IP address of 20.0.0.255

NEW QUESTION 182

A user has setup a web application on EC2. The user is generating a log of the application performance at every second. There are multiple entries for each second. If the user wants to send that data to CloudWatch every minute, what should he do?

- A. The user should send only the data of the 60th second as CloudWatch will map the receive data timezone with the sent data timezone
- B. It is not possible to send the custom metric to CloudWatch every minute
- C. Give CloudWatch the Min, Max, Sum, and SampleCount of a number of every minute
- D. Calculate the average of one minute and send the data to CloudWatch

Answer: C

Explanation:

Amazon CloudWatch aggregates statistics according to the period length that the user has specified while getting data from CloudWatch. The user can publish as many data points as he wants with the same or similar time stamps. CloudWatch aggregates them by the period length when the user calls get statistics about those data points. CloudWatch records the average (sum of all items divided by the number of items. of the values received for every 1-minute period, as well as the number of samples, maximum value, and minimum value for the same time period. CloudWatch will aggregate all the data which have time stamps within a one-minute period.

NEW QUESTION 184

An AWS root account owner is trying to create a policy to access RDS. Which of the below mentioned statements is true with respect to the above information?

- A. Create a policy which allows the users to access RDS and apply it to the RDS instances
- B. The user cannot access the RDS database if he is not assigned the correct IAM policy
- C. The root account owner should create a policy for the IAM user and give him access to the RDS services
- D. The policy should be created for the user and provide access for RDS

Answer: C

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the account owner wants to create a policy for RDS, the owner has to create an IAM user and define the policy which entitles the IAM user with various RDS services such as Launch Instance, Manage security group, Manage parameter group etc.

NEW QUESTION 186

A user is displaying the CPU utilization, and Network in and Network out CloudWatch metrics data of a single instance on the same graph. The graph uses one Y-axis for CPU utilization and Network in and another Y-axis for Network out. Since Network in is too high, the CPU utilization data is not visible clearly on graph to the user. How can the data be viewed better on the same graph?

- A. It is not possible to show multiple metrics with the different units on the same graph
- B. Add a third Y-axis with the console to show all the data in proportion
- C. Change the axis of Network by using the Switch command from the graph
- D. Change the units of CPU utilization so it can be shown in proportion with Network

Answer: C

Explanation:

Amazon CloudWatch provides the functionality to graph the metric data generated either by the AWS services or the custom metric to make it easier for the user to analyse. It is possible to show the multiple metrics with different units on the same graph. If the graph is not plotted properly due to a difference in the unit data over two metrics, the user can change the Y-axis of one of the graph by selecting that graph and clicking on the Switch option.

NEW QUESTION 191

A user is planning to schedule a backup for an EBS volume. The user wants security of the snapshot data. How can the user achieve data encryption with a snapshot?

- A. Use encrypted EBS volumes so that the snapshot will be encrypted by AWS
- B. While creating a snapshot select the snapshot with encryption
- C. By default the snapshot is encrypted by AWS
- D. Enable server side encryption for the snapshot using S3

Answer: A

Explanation:

AWS EBS supports encryption of the volume. It also supports creating volumes from existing snapshots provided the snapshots are created from encrypted volumes. The data at rest, the I/O as well as all the snapshots of the encrypted EBS will also be encrypted. EBS encryption is based on the AES-256 cryptographic algorithm, which is the industry standard.

NEW QUESTION 192

A user has created a public subnet with VPC and launched an EC2 instance within it. The user is trying to delete the subnet. What will happen in this scenario?

- A. It will delete the subnet and make the EC2 instance as a part of the default subnet
- B. It will not allow the user to delete the subnet until the instances are terminated
- C. It will delete the subnet as well as terminate the instances
- D. The subnet can never be deleted independently, but the user has to delete the VPC first

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. When an instance is launched it will have a network interface attached with it. The user cannot delete the subnet until he terminates the instance and deletes the network interface.

NEW QUESTION 197

A user has launched an EC2 instance from an instance store backed AMI. The infrastructure team wants to create an AMI from the running instance. Which of the below mentioned credentials is not required while creating the AMI?

- A. AWS account ID

- B. X.509 certificate and private key
- C. AWS login ID to login to the console
- D. Access key and secret access key

Answer: C

Explanation:

When the user has launched an EC2 instance from an instance store backed AMI and the admin team wants to create an AMI from it, the user needs to setup the AWS AMI or the API tools first. Once the tool is setup the user will need the following credentials:

AWS account ID;
AWS access and secret access key;
X.509 certificate with private key.

NEW QUESTION 201

A user has configured an SSL listener at ELB as well as on the back-end instances. Which of the below mentioned statements helps the user understand ELB traffic handling with respect to the SSL listener?

- A. It is not possible to have the SSL listener both at ELB and back-end instances
- B. ELB will modify headers to add requestor details
- C. ELB will intercept the request to add the cookie details if sticky session is enabled
- D. ELB will not modify the headers

Answer: D

Explanation:

When the user has configured Transmission Control Protocol (TCP. or Secure Sockets Layer (SSL. for both front-end and back-end connections of the Elastic Load Balancer, the load balancer forwards the request to the back-end instances without modifying the request headers unless the proxy header is enabled. SSL does not support sticky sessions. If the user has enabled a proxy protocol it adds the source and destination IP to the header.

NEW QUESTION 205

A user has created a Cloudformation stack. The stack creates AWS services, such as EC2 instances, ELB, AutoScaling, and RDS. While creating the stack it created EC2, ELB and AutoScaling but failed to create RDS. What will Cloudformation do in this scenario?

- A. Cloudformation can never throw an error after launching a few services since it verifies all the steps before launching
- B. It will warn the user about the error and ask the user to manually create RDS
- C. Rollback all the changes and terminate all the created services
- D. It will wait for the user's input about the error and correct the mistake after the input

Answer: C

Explanation:

AWS Cloudformation is an application management tool which provides application modelling, deployment, configuration, management and related activities. The AWS Cloudformation stack is a collection of AWS resources which are created and managed as a single unit when AWS CloudFormation instantiates a template. If any of the services fails to launch, Cloudformation will rollback all the changes and terminate or delete all the created services.

NEW QUESTION 207

A user has launched an EBS backed instance with EC2-Classic. The user stops and starts the instance. Which of the below mentioned statements is not true with respect to the stop/start action?

- A. The instance gets new private and public IP addresses
- B. The volume is preserved
- C. The Elastic IP remains associated with the instance
- D. The instance may run on a new host computer

Answer: C

Explanation:

A user can always stop/start an EBS backed EC2 instance. When the user stops the instance, it first enters the stopping state, and then the stopped state. AWS does not charge the running cost but charges only for the EBS storage cost. If the instance is running in EC2-Classic, it receives a new private IP address; as the Elastic IP address (EIP. associated with the instance is no longer associated with that instance.

NEW QUESTION 212

A user has launched an RDS PostgreSQL DB with AWS. The user did not specify the maintenance window during creation. The user has configured RDS to update the DB instance type from micro to large. If the user wants to have it during the maintenance window, what will AWS do?

- A. AWS will not allow to update the DB until the maintenance window is configured
- B. AWS will select the default maintenance window if the user has not provided it
- C. AWS will ask the user to specify the maintenance window during the update
- D. It is not possible to change the DB size from micro to large with RDS

Answer: B

Explanation:

AWS RDS has a compulsory maintenance window which by default is 30 minutes. If the user does not specify the maintenance window during the creation of RDS then AWS will select a 30-minute maintenance window randomly from an 8-hour block of time per region. In this case, Amazon RDS assigns a 30-minute maintenance window on a randomly selected day of the week.

NEW QUESTION 216

A user has created a subnet in VPC and launched an EC2 instance within it. The user has not selected the option to assign the IP address while launching the instance. The user has 3 elastic IPs and is trying to assign one of the Elastic IPs to the VPC instance from the console. The console does not show any instance in the IP assignment screen. What is a possible reason that the instance is unavailable in the assigned IP console?

- A. The IP address may be attached to one of the instances
- B. The IP address belongs to a different zone than the subnet zone
- C. The user has not created an internet gateway
- D. The IP addresses belong to EC2 Classic; so they cannot be assigned to VPC

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. When the user is launching an instance he needs to select an option which attaches a public IP to the instance. If the user has not selected the option to attach the public IP then it will only have a private IP when launched. If the user wants to connect to an instance from the internet he should create an elastic IP with VPC. If the elastic IP is a part of EC2 Classic it cannot be assigned to a VPC instance.

NEW QUESTION 218

A user has created a VPC with CIDR 20.0.0.0/16 using VPC Wizard. The user has created a public CIDR (20.0.0.0/24) and a VPN only subnet CIDR (20.0.1.0/24) along with the hardware VPN access to connect to the user's data centre. Which of the below mentioned components is not present when the VPC is setup with the wizard?

- A. Main route table attached with a VPN only subnet
- B. A NAT instance configured to allow the VPN subnet instances to connect with the internet
- C. Custom route table attached with a public subnet
- D. An internet gateway for a public subnet

Answer: B

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will update the main route table used with the VPN-only subnet, create a custom route table and associate it with the public subnet. It also creates an internet gateway for the public subnet. The wizard does not create a NAT instance by default. The user can create it manually and attach it with a VPN only subnet.

NEW QUESTION 221

A user has setup an Auto Scaling group. The group has failed to launch a single instance for more than 24 hours. What will happen to Auto Scaling in this condition?

- A. Auto Scaling will keep trying to launch the instance for 72 hours
- B. Auto Scaling will suspend the scaling process
- C. Auto Scaling will start an instance in a separate region
- D. The Auto Scaling group will be terminated automatically

Answer: B

Explanation:

If Auto Scaling is trying to launch an instance and if the launching of the instance fails continuously, it will suspend the processes for the Auto Scaling groups since it repeatedly failed to launch an instance. This is known as an administrative suspension. It commonly applies to the Auto Scaling group that has no running instances which is trying to launch instances for more than 24 hours, and has not succeeded in that to do so.

NEW QUESTION 224

A user is planning to set up the Multi AZ feature of RDS. Which of the below mentioned conditions won't take advantage of the Multi AZ feature?

- A. Availability zone outage
- B. A manual failover of the DB instance using Reboot with failover option
- C. Region outage
- D. When the user changes the DB instance's server type

Answer: C

Explanation:

Amazon RDS when enabled with Multi AZ will handle failovers automatically. Thus, the user can resume database operations as quickly as possible without administrative intervention. The primary DB instance switches over automatically to the standby replica if any of the following conditions occur:

An Availability Zone outage
The primary DB instance fails

The DB instance's server type is changed

The DB instance is undergoing software patching

A manual failover of the DB instance was initiated using Reboot with failover

NEW QUESTION 225

An AWS account wants to be part of the consolidated billing of his organization's payee account. How can the owner of that account achieve this?

- A. The payee account has to request AWS support to link the other accounts with his account
- B. The owner of the linked account should add the payee account to his master account list from the billing console
- C. The payee account will send a request to the linked account to be a part of consolidated billing
- D. The owner of the linked account requests the payee account to add his account to consolidated billing

Answer:

C

Explanation:

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. To add a particular account (linked to the master (payee) account, the payee account has to request the linked account to join consolidated billing. Once the linked account accepts the request henceforth all charges incurred by the linked account will be paid by the payee account.

NEW QUESTION 230

A sysadmin has created the below mentioned policy on an S3 bucket named cloudacademy. What does this policy define?

```
"Statement": [{
  "Sid": "Stmt1388811069831",
  "Effect": "Allow", "Principal": { "AWS": "*" },
  "Action": [ "s3:GetObjectAcl", "s3:ListBucket"], "Resource": [ "arn:aws:s3:::cloudacademy"]
}]
```

- A. It will make the cloudacademy bucket as well as all its objects as public
- B. It will allow everyone to view the ACL of the bucket
- C. It will give an error as no object is defined as part of the policy while the action defines the rule about the object
- D. It will make the cloudacademy bucket as public

Answer: D**Explanation:**

A sysadmin can grant permission to the S3 objects or the buckets to any user or make objects public using the bucket policy and user policy. Both use the JSON-based access policy language. Generally if the user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket. In the sample policy the action says `s3:ListBucket` for effect Allow on Resource `arn:aws:s3:::cloudacademy`. This will make the cloudacademy bucket public.

```
"Statement": [{
  "Sid": "Stmt1388811069831",
  "Effect": "Allow", "Principal": { "AWS": "*" },
  "Action": [ "s3:GetObjectAcl", "s3:ListBucket"], "Resource": [ "arn:aws:s3:::cloudacademy"]
}]
```

NEW QUESTION 232

A user has launched two EBS backed EC2 instances in the US-East-1a region. The user wants to change the zone of one of the instances. How can the user change it?

- A. The zone can only be modified using the AWS CLI
- B. It is not possible to change the zone of an instance after it is launched
- C. Stop one of the instances and change the availability zone
- D. From the AWS EC2 console, select the Actions - > Change zones and specify the new zone

Answer: B**Explanation:**

With AWS EC2, when a user is launching an instance he can select the availability zone (AZ) at the time of launch. If the zone is not selected, AWS selects it on behalf of the user. Once the instance is launched, the user cannot change the zone of that instance unless he creates an AMI of that instance and launches a new instance from it.

NEW QUESTION 237

A user is trying to connect to a running EC2 instance using SSH. However, the user gets a Host key not found error. Which of the below mentioned options is a possible reason for rejection?

- A. The user has provided the wrong user name for the OS login
- B. The instance CPU is heavily loaded
- C. The security group is not configured properly
- D. The access key to connect to the instance is wrong

Answer: A**Explanation:**

If the user is trying to connect to a Linux EC2 instance and receives the Host Key not found error the probable reasons are:
The private key pair is not right
The user name to login is wrong

NEW QUESTION 241

A user has hosted an application on EC2 instances. The EC2 instances are configured with ELB and Auto Scaling. The application server session time out is 2 hours. The user wants to configure connection draining to ensure that all in-flight requests are supported by ELB even though the instance is being deregistered. What time out period should the user specify for connection draining?

- A. 5 minutes
- B. 1 hour
- C. 30 minutes
- D. 2 hours

Answer: B**NEW QUESTION 242**

A user has created a queue named `awsmodule` with SQS. One of the consumers of queue is down for 3 days and then becomes available. Will that

component receive message from queue?

- A. Yes, since SQS by default stores message for 4 days
- B. No, since SQS by default stores message for 1 day only
- C. No, since SQS sends message to consumers who are available that time
- D. Yes, since SQS will not delete message until it is delivered to all consumers

Answer: A

Explanation:

SQS allows the user to move data between distributed components of applications so they can perform different tasks without losing messages or requiring each component to be always available. Queues retain messages for a set period of time. By default, a queue retains messages for four days. However, the user can configure a queue to retain messages for up to 14 days after the message has been sent.

NEW QUESTION 243

An organization has setup multiple IAM users. The organization wants that each IAM user accesses the IAM console only within the organization and not from outside. How can it achieve this?

- A. Create an IAM policy with the security group and use that security group for AWS console login
- B. Create an IAM policy with a condition which denies access when the IP address range is not from the organization
- C. Configure the EC2 instance security group which allows traffic only from the organization??s IP range
- D. Create an IAM policy with VPC and allow a secure gateway between the organization and AWS Console

Answer: B

Explanation:

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. The user can add conditions as a part of the IAM policies. The condition can be set on AWS Tags, Time, and Client IP as well as on many other parameters. If the organization wants the user to access only from a specific IP range, they should set an IAM policy condition which denies access when the IP is not in a certain range. E.g. The sample policy given below denies all traffic when the IP is not in a certain range.

```
"Statement": [{  
  "Effect": "Deny",  
  "Action": "*",  
  "Resource": "*", "Condition": { "NotIpAddress": {  
    "aws:SourceIp": ["10.10.10.0/24", "20.20.30.0/24"]  
  }  
}  
}]
```

NEW QUESTION 246

A user has enabled session stickiness with ELB. The user does not want ELB to manage the cookie; instead he wants the application to manage the cookie. What will happen when the server instance, which is bound to a cookie, crashes?

- A. The response will have a cookie but stickiness will be deleted
- B. The session will not be sticky until a new cookie is inserted
- C. ELB will throw an error due to cookie unavailability
- D. The session will be sticky and ELB will route requests to another server as ELB keeps replicating the Cookie

Answer: B

Explanation:

With Elastic Load Balancer, if the admin has enabled a sticky session with application controlled stickiness, the load balancer uses a special cookie generated by the application to associate the session with the original server which handles the request. ELB follows the lifetime of the application-generated cookie corresponding to the cookie name specified in the ELB policy configuration. The load balancer only inserts a new stickiness cookie if the application response includes a new application cookie. The load balancer stickiness cookie does not update with each request. If the application cookie is explicitly removed or expires, the session stops being sticky until a new application cookie is issued.

NEW QUESTION 247

A user has created an Auto Scaling group with default configurations from CLI. The user wants to setup the CloudWatch alarm on the EC2 instances, which are launched by the Auto Scaling group. The user has setup an alarm to monitor the CPU utilization every minute. Which of the below mentioned statements is true?

- A. It will fetch the data at every minute but the four data points [corresponding to 4 minutes] will not have value since the EC2 basic monitoring metrics are collected every five minutes
- B. It will fetch the data at every minute as detailed monitoring on EC2 will be enabled by the default launch configuration of Auto Scaling
- C. The alarm creation will fail since the user has not enabled detailed monitoring on the EC2 instances
- D. The user has to first enable detailed monitoring on the EC2 instances to support alarm monitoring at every minute

Answer: B

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. To enable detailed instance monitoring for a new Auto Scaling group, the user does not need to take any extra steps. When the user creates an Auto Scaling launch config using CLI, each launch configuration contains a flag named InstanceMonitoring.Enabled. The default value of this flag is true. Thus, by default detailed monitoring will be enabled for Auto Scaling as well as for all the instances launched by that Auto Scaling group.

NEW QUESTION 248

A user has created a VPC with public and private subnets using the VPC wizard. Which of the below mentioned statements is not true in this scenario?

- A. The VPC will create a routing instance and attach it with a public subnet

- B. The VPC will create two subnets
- C. The VPC will create one internet gateway and attach it to VPC
- D. The VPC will launch one NAT instance with an elastic IP

Answer: A

Explanation:

A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create a NAT instance with an elastic IP. Wizard will also create two subnets with route tables. It will also create an internet gateway and attach it to the VPC.

NEW QUESTION 249

A user has configured ELB with a TCP listener at ELB as well as on the back-end instances. The user wants to enable a proxy protocol to capture the source and destination IP information in the header. Which of the below mentioned statements helps the user understand a proxy protocol with TCP configuration?

- A. If the end user is requesting behind a proxy server then the user should not enable a proxy protocol on ELB
- B. ELB does not support a proxy protocol when it is listening on both the load balancer and the back- end instances
- C. Whether the end user is requesting from a proxy server or directly, it does not make a difference for the proxy protocol
- D. If the end user is requesting behind the proxy then the user should add the `??isproxy??` flag to the ELB Configuration

Answer: A

Explanation:

When the user has configured Transmission Control Protocol (TCP. or Secure Sockets Layer (SSL. for both front-end and back-end connections of the Elastic Load Balancer, the load balancer forwards the request to the back-end instances without modifying the request headers unless the proxy header is enabled. If the end user is requesting from a Proxy Protocol enabled proxy server, then the ELB admin should not enable the Proxy Protocol on the load balancer. If the Proxy Protocol is enabled on both the proxy server and the load balancer, the load balancer will add another header to the request which already has a header from the proxy server. This duplication may result in errors.

NEW QUESTION 251

A user has created a subnet in VPC and launched an EC2 instance within it. The user has not selected the option to assign the IP address while launching the instance. Which of the below mentioned statements is true with respect to this scenario?

- A. The instance will always have a public DNS attached to the instance by default
- B. The user can directly attach an elastic IP to the instance
- C. The instance will never launch if the public IP is not assigned
- D. The user would need to create an internet gateway and then attach an elastic IP to the instance to connect from internet

Answer: D

Explanation:

A Virtual Private Cloud (VPC. is a virtual network dedicated to the user??s AWS account. A user can create a subnet with VPC and launch instances inside that subnet. When the user is launching an instance he needs to select an option which attaches a public IP to the instance. If the user has not selected the option to attach the public IP then it will only have a private IP when launched. The user cannot connect to the instance from the internet. If the user wants an elastic IP to connect to the instance from the internet he should create an internet gateway and assign an elastic IP to instance.

NEW QUESTION 256

A user is configuring a CloudWatch alarm on RDS to receive a notification when the CPU utilization of RDS is higher than 50%. The user has setup an alarm when there is some inactivity on RDS, such as RDS unavailability. How can the user configure this?

- A. Setup the notification when the CPU is more than 75% on RDS
- B. Setup the notification when the state is Insufficient Data
- C. Setup the notification when the CPU utilization is less than 10%
- D. It is not possible to setup the alarm on RDS

Answer: B

Explanation:

Amazon CloudWatch alarms watch a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The alarm has three states: Alarm, OK and Insufficient data. The Alarm will change to Insufficient Data when any of the three situations arise: when the alarm has just started, when the metric is not available or when enough data is not available for the metric to determine the alarm state. If the user wants to find that RDS is not available, he can setup to receive the notification when the state is in Insufficient data.

NEW QUESTION 261

George has shared an EC2 AMI created in the US East region from his AWS account with Stefano. George copies the same AMI to the US West region. Can Stefano access the copied AMI of George??s account from the US West region?

- A. No, copy AMI does not copy the permission
- B. It is not possible to share the AMI with a specific account
- C. Yes, since copy AMI copies all private account sharing permissions
- D. Yes, since copy AMI copies all the permissions attached with the AMI

Answer: A

Explanation:

Within EC2, when the user copies an AMI, the new AMI is fully independent of the source AMI; there is no link to the original (source. AMI. AWS does not copy launch the permissions, user-defined tags or the Amazon S3 bucket permissions from the source AMI to the new AMI. Thus, in this case by default Stefano will not

have access to the AMI in the US West region.

NEW QUESTION 264

A user has created a VPC with a subnet and a security group. The user has launched an instance in that subnet and attached a public IP. The user is still unable to connect to the instance. The internet gateway has also been created. What can be the reason for the error?

- A. The internet gateway is not configured with the route table
- B. The private IP is not present
- C. The outbound traffic on the security group is disabled
- D. The internet gateway is not configured with the security group

Answer: A

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. AWS provides two features the user can use to increase security in VPC: security groups and network ACLs. Security groups work at the instance level. When a user launches an instance and wants to connect to an instance, he needs an internet gateway. The internet gateway should be configured with the route table to allow traffic from the internet.

NEW QUESTION 265

A user has configured ELB with Auto Scaling. The user suspended the Auto Scaling AlarmNotification (which notifies Auto Scaling for CloudWatch alarms) process for a while. What will Auto Scaling do during this period?

- A. AWS will not receive the alarms from CloudWatch
- B. AWS will receive the alarms but will not execute the Auto Scaling policy
- C. Auto Scaling will execute the policy but it will not launch the instances until the process is resumed
- D. It is not possible to suspend the AlarmNotification process

Answer: B

Explanation:

Auto Scaling performs various processes, such as Launch, Terminate Alarm Notification etc. The user can also suspend individual process. The AlarmNotification process type accepts notifications from the Amazon CloudWatch alarms that are associated with the Auto Scaling group. If the user suspends this process type, Auto Scaling will not automatically execute the scaling policies that would be triggered by the alarms.

NEW QUESTION 267

A user had aggregated the CloudWatch metric data on the AMI ID. The user observed some abnormal behaviour of the CPU utilization metric while viewing the last 2 weeks of data. The user wants to share that data with his manager. How can the user achieve this easily with the AWS console?

- A. The user can use the copy URL functionality of CloudWatch to share the exact details
- B. The user can use the export data option from the CloudWatch console to export the current data point
- C. The user has to find the period and data and provide all the aggregation information to the manager
- D. The user can use the CloudWatch data copy functionality to copy the current data points

Answer: A

Explanation:

Amazon CloudWatch provides the functionality to graph the metric data generated either by the AWS services or the custom metric to make it easier for the user to analyse. The console provides the option to save the URL or bookmark it so that it can be used in the future by typing the same URL. The Copy URL functionality is available under the console when the user selects any metric to view.

NEW QUESTION 270

A user has configured ELB with SSL using a security policy for secure negotiation between the client and load balancer. Which of the below mentioned SSL protocols is not supported by the security policy?

- A. TLS 1.3
- B. TLS 1.2
- C. SSL 2.0
- D. SSL 3.0

Answer: A

Explanation:

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. Elastic Load Balancing supports the following versions of the SSL protocol:

TLS 1.2
TLS 1.1
TLS 1.0
SSL 3.0
SSL 2.0

NEW QUESTION 274

A user is trying to create a PIOPS EBS volume with 4000 IOPS and 100 GB size. AWS does not allow the user to create this volume. What is the possible root cause for this?

- A. The ratio between IOPS and the EBS volume is higher than 30
- B. The maximum IOPS supported by EBS is 3000
- C. The ratio between IOPS and the EBS volume is lower than 50
- D. PIOPS is supported for EBS higher than 500 GB size

Answer: A

Explanation:

A provisioned IOPS EBS volume can range in size from 10 GB to 1 TB and the user can provision up to 4000 IOPS per volume. The ratio of IOPS provisioned to the volume size requested should be a maximum of 30; for example, a volume with 3000 IOPS must be at least 100 GB.

NEW QUESTION 278

A user has enabled versioning on an S3 bucket. The user is using server side encryption for data at Rest. If the user is supplying his own keys for encryption (SSE-C.), which of the below mentioned statements is true?

- A. The user should use the same encryption key for all versions of the same object
- B. It is possible to have different encryption keys for different versions of the same object
- C. AWS S3 does not allow the user to upload his own keys for server side encryption
- D. The SSE-C does not work when versioning is enabled

Answer: B

Explanation:

AWS S3 supports client side or server side encryption to encrypt all data at rest. The server side encryption can either have the S3 supplied AES-256 encryption key or the user can send the key along with each API call to supply his own encryption key (SSE-C.. If the bucket is versioning-enabled, each object version uploaded by the user using the SSE-C feature can have its own encryption key. The user is responsible for tracking which encryption key was used for which object's version

NEW QUESTION 282

A user has created a VPC with CIDR 20.0.0.0/16. The user has created one subnet with CIDR 20.0.0.0/16 in this VPC. The user is trying to create another subnet with the same VPC for CIDR 20.0.0.1/24. What will happen in this scenario?

- A. The VPC will modify the first subnet CIDR automatically to allow the second subnet IP range
- B. It is not possible to create a subnet with the same CIDR as VPC
- C. The second subnet will be created
- D. It will throw a CIDR overlaps error

Answer: D

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. The user can create a subnet with the same size of VPC. However, he cannot create any other subnet since the CIDR of the second subnet will conflict with the first subnet.

NEW QUESTION 283

A user has launched an RDS MySQL DB with the Multi AZ feature. The user has scheduled the scaling of instance storage during maintenance window. What is the correct order of events during maintenance window?

Perform maintenance on standby Promote standby to primary

Perform maintenance on original primary Promote original master back as primary

- A. 1, 2, 3, 4
- B. 1, 2, 3
- C. 2, 3, 1, 4

Answer: B

Explanation:

Running MySQL on the RDS DB instance as a Multi-AZ deployment can help the user reduce the impact of a maintenance event, as the Amazon will conduct maintenance by following the steps in the below mentioned order:

Perform maintenance on standby Promote standby to primary

Perform maintenance on original primary, which becomes the new standby.

NEW QUESTION 287

A sys admin is using server side encryption with AWS S3. Which of the below mentioned statements helps the user understand the S3 encryption functionality?

- A. The server side encryption with the user supplied key works when versioning is enabled
- B. The user can use the AWS console, SDK and APIs to encrypt or decrypt the content for server side encryption with the user supplied key
- C. The user must send an AES-128 encrypted key
- D. The user can upload his own encryption key to the S3 console

Answer: A

Explanation:

AWS S3 supports client side or server side encryption to encrypt all data at rest. The server side encryption can either have the S3 supplied AES-256 encryption key or the user can send the key along with each API call to supply his own encryption key. The encryption with the user supplied key (SSE-C) does not work with the AWS console. The S3 does not store the keys and the user has to send a key with each request. The SSE-C works when the user has enabled versioning.

NEW QUESTION 288

A user has created a VPC with CIDR 20.0.0.0/16 using the wizard. The user has created a public subnet CIDR (20.0.0.0/24) and VPN only subnets CIDR (20.0.1.0/24) along with the VPN gateway (vgw-12345) to connect to the user's data centre. The user's data centre has CIDR 172.28.0.0/12. The user has also setup a NAT instance (i-123456) to allow traffic to the internet from the VPN subnet. Which of the below mentioned options is not a valid entry for the main route table in this scenario?

- A. Destination: 20.0.1.0/24 and Target: i-12345
- B. Destination: 0.0.0.0/0 and Target: i-12345
- C. Destination: 172.28.0.0/12 and Target: vgw-12345
- D. Destination: 20.0.0.0/16 and Target: local

Answer: A

Explanation:

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will create a virtual private gateway to route all traffic of the VPN subnet. If the user has setup a NAT instance to route all the internet requests then all requests to the internet should be routed to it. All requests to the organization's DC will be routed to the VPN gateway.

Here are the valid entries for the main route table in this scenario:

Destination: 0.0.0.0/0 & Target: i-12345 (To route all internet traffic to the NAT Instance.

Destination: 172.28.0.0/12 & Target: vgw-12345 (To route all the organization's data centre traffic to the VPN gateway.

Destination: 20.0.0.0/16 & Target: local (To allow local routing in VPC.

NEW QUESTION 292

A root account owner has given full access of his S3 bucket to one of the IAM users using the bucket ACL. When the IAM user logs in to the S3 console, which actions can he perform?

- A. He can just view the content of the bucket
- B. He can do all the operations on the bucket
- C. It is not possible to give access to an IAM user using ACL
- D. The IAM user can perform all operations on the bucket using only API/SDK

Answer: C

Explanation:

Each AWS S3 bucket and object has an ACL (Access Control List. associated with it. An ACL is a list of grants identifying the grantee and the permission granted. The user can use ACLs to grant basic read/write permissions to other AWS accounts. ACLs use an Amazon S3's specific XML schema. The user cannot grant permissions to other users (IAM users. in his account.

NEW QUESTION 295

An organization has configured Auto Scaling with ELB. There is a memory issue in the application which is causing CPU utilization to go above 90%. The higher CPU usage triggers an event for Auto Scaling as per the scaling policy. If the user wants to find the root cause inside the application without triggering a scaling activity, how can he achieve this?

- A. Stop the scaling process until research is completed
- B. It is not possible to find the root cause from that instance without triggering scaling
- C. Delete Auto Scaling until research is completed
- D. Suspend the scaling process until research is completed

Answer: D

Explanation:

Auto Scaling allows the user to suspend and then resume one or more of the Auto Scaling processes in the Auto Scaling group. This is very useful when the user wants to investigate a configuration problem or some other issue, such as a memory leak with the web application and then make changes to the application, without triggering the Auto Scaling process.

NEW QUESTION 296

A sys admin is planning to subscribe to the RDS event notifications. For which of the below mentioned source categories the subscription cannot be configured?

- A. DB security group
- B. DB snapshot
- C. DB options group
- D. DB parameter group

Answer: C

Explanation:

Amazon RDS uses the Amazon Simple Notification Service (SNS. to provide a notification when an Amazon RDS event occurs. These events can be configured for source categories, such as DB instance, DB security group, DB snapshot and DB parameter group.

NEW QUESTION 299

A user has launched an EC2 instance. The instance got terminated as soon as it was launched. Which of the below mentioned options is not a possible reason for this?

- A. The user account has reached the maximum EC2 instance limit
- B. The snapshot is corrupt
- C. The AMI is missin
- D. It is the required part
- E. The user account has reached the maximum volume limit

Answer: A

Explanation:

When the user account has reached the maximum number of EC2 instances, it will not be allowed to launch an instance. AWS will throw an

??InstanceLimitExceeded?? error. For all other reasons, such as ??AMI is missing part??. ??Corrupt Snapshot?? or ??Volume limit has reached?? it will launch an EC2 instance and then terminate it.

NEW QUESTION 302

A user is measuring the CPU utilization of a private data centre machine every minute. The machine provides the aggregate of data every hour, such as Sum of data??. ??Min value??. ??Max value, and ??Number of Data points??.

The user wants to send these values to CloudWatch. How can the user achieve this?

- A. Send the data using the put-metric-data command with the aggregate-values parameter
- B. Send the data using the put-metric-data command with the average-values parameter
- C. Send the data using the put-metric-data command with the statistic-values parameter
- D. Send the data using the put-metric-data command with the aggregate ?Vdata parameter

Answer: C

Explanation:

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user can publish the data to CloudWatch as single data points or as an aggregated set of data points called a statistic set using the command put- metric-data. When sending the aggregate data, the user needs to send it with the parameter statistic-values:

```
awscloudwatch put-metric-data --metric-name <Name> --namespace <Custom namespace -- timestamp  
<UTC Format> --statistic-values Sum=XX,Minimum=YY,Maximum=AA,SampleCount=BB --unit Milliseconds
```

NEW QUESTION 304

A user has enabled detailed CloudWatch monitoring with the AWS Simple Notification Service. Which of the below mentioned statements helps the user understand detailed monitoring better?

- A. SNS will send data every minute after configuration
- B. There is no need to enable since SNS provides data every minute
- C. AWS CloudWatch does not support monitoring for SNS
- D. SNS cannot provide data every minute

Answer: D

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. The AWS SNS service sends data every 5 minutes. Thus, it supports only the basic monitoring. The user cannot enable detailed monitoring with SNS.

NEW QUESTION 309

A user wants to find the particular error that occurred on a certain date in the AWS MySQL RDS DB. Which of the below mentioned activities may help the user to get the data easily?

- A. It is not possible to get the log files for MySQL RDS
- B. Find all the transaction logs and query on those records
- C. Direct the logs to the DB table and then query that table
- D. Download the log file to DynamoDB and search for the record

Answer: C

Explanation:

The user can view, download, and watch the database logs using the Amazon RDS console, the Command Line Interface (CLI. or the Amazon RDS API. For the MySQL RDS, the user can view the error log, slow query log, and general logs. The user can also view the MySQL logs easily by directing the logs to a database table in the main database and querying that table.

NEW QUESTION 313

An AWS account owner has setup multiple IAM users. One IAM user only has CloudWatch access. He has setup the alarm action which stops the EC2 instances when the CPU utilization is below the threshold limit. What will happen in this case?

- A. It is not possible to stop the instance using the CloudWatch alarm
- B. CloudWatch will stop the instance when the action is executed
- C. The user cannot set an alarm on EC2 since he does not have the permission
- D. The user can setup the action but it will not be executed if the user does not have EC2 rights

Answer: D

Explanation:

Amazon CloudWatch alarms watch a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The user can setup an action which stops the instances when their CPU utilization is below a certain threshold for a certain period of time. The EC2 action can either terminate or stop the instance as part of the EC2 action. If the IAM user has read/write permissions for Amazon CloudWatch but not for Amazon EC2, he can still create an alarm. However, the stop or terminate actions will not be performed on the Amazon EC2 instance.

NEW QUESTION 315

A user is configuring the Multi AZ feature of an RDS DB. The user came to know that this RDS DB does not use the AWS technology, but uses server mirroring to achieve H

- A. Which DB is the user using right now?

- B. My SQL
- C. Oracle
- D. MS SQL
- E. PostgreSQL

Answer: C

Explanation:

Amazon RDS provides high availability and failover support for DB instances using Multi AZ deployments. In a Multi AZ deployment, Amazon RDS automatically provisions and maintains a synchronous standby replica in a different Availability Zone. Multi AZ deployments for Oracle, PostgreSQL, and MySQL DB instances use Amazon technology, while SQL Server (MS SQL) DB instances use SQL Server Mirroring.

NEW QUESTION 317

A user is receiving a notification from the RDS DB whenever there is a change in the DB security group. The user does not want to receive these notifications for only a month. Thus, he does not want to delete the notification. How can the user configure this?

- A. Change the Disable button for notification to ??Yes?? in the RDS console
- B. Set the send mail flag to false in the DB event notification console
- C. The only option is to delete the notification from the console
- D. Change the Enable button for notification to ??No?? in the RDS console

Answer: D

Explanation:

Amazon RDS uses the Amazon Simple Notification Service to provide a notification when an Amazon RDS event occurs. Event notifications are sent to the addresses that the user has provided while creating the subscription. The user can easily turn off the notification without deleting a subscription by setting the Enabled radio button to No in the Amazon RDS console or by setting the Enabled parameter to false using the CLI or Amazon RDS API.

NEW QUESTION 320

A user is trying to understand the detailed CloudWatch monitoring concept. Which of the below mentioned services provides detailed monitoring with CloudWatch without charging the user extra?

- A. AWS Auto Scaling
- B. AWS Route 53
- C. AWS EMR
- D. AWS SNS

Answer: B

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. Services, such as RDS, ELB, OpsWorks, and Route 53 can provide the monitoring data every minute without charging the user.

NEW QUESTION 323

A system admin is planning to encrypt all objects being uploaded to S3 from an application. The system admin does not want to implement his own encryption algorithm; instead he is planning to use server side encryption by supplying his own key (SSE-C). Which parameter is not required while making a call for SSE-C?

- A. x-amz-server-side-encryption-customer-key-AES-256
- B. x-amz-server-side-encryption-customer-key
- C. x-amz-server-side-encryption-customer-algorithm
- D. x-amz-server-side-encryption-customer-key-MD5

Answer: A

Explanation:

AWS S3 supports client side or server side encryption to encrypt all data at rest. The server side encryption can either have the S3 supplied AES-256 encryption key or the user can send the key along with each API call to supply his own encryption key (SSE-C). When the user is supplying his own encryption key, the user has to send the below mentioned parameters as a part of the API calls:

x-amz-server-side-encryption-customer-algorithm: Specifies the encryption algorithm

x-amz-server-side-encryption-customer-key: To provide the base64-encoded encryption key

x-amz-server-side-encryption-customer-key-MD5: To provide the base64-encoded 128-bit MD5 digest of the encryption key

NEW QUESTION 326

A user has launched an EC2 instance from an instance store backed AMI. If the user restarts the instance, what will happen to the ephemeral storage data?

- A. All the data will be erased but the ephemeral storage will stay connected
- B. All data will be erased and the ephemeral storage is released
- C. It is not possible to restart an instance launched from an instance store backed AMI
- D. The data is preserved

Answer: D

Explanation:

A user can reboot an EC2 instance using the AWS console, the Amazon EC2 CLI or the Amazon EC2 API. Rebooting an instance is equivalent to rebooting an operating system. However, it is recommended that the user use Amazon EC2 to reboot the instance instead of running the operating system reboot command from the instance. When an instance launched from an instance store backed AMI is rebooted all the ephemeral storage data is still preserved.

NEW QUESTION 329

A user has created a VPC with CIDR 20.0.0.0/24. The user has used all the IPs of CIDR and wants to increase the size of the VPC. The user has two subnets: public (20.0.0.0/28. and private (20.0.1.0/28.. How can the user change the size of the VPC?

- A. The user can delete all the instances of the subne
- B. Change the size of the subnets to 20.0.0.0/32 and 20.0.1.0/32, respective
- C. Then the user can increase the size of the VPC using CLI
- D. It is not possible to change the size of the VPC once it has been created
- E. The user can add a subnet with a higher range so that it will automatically increase the size of the VPC
- F. The user can delete the subnets first and then modify the size of the VPC

Answer: B

Explanation:

Once the user has created a VPC, he cannot change the CIDR of that VPC. The user has to terminate all the instances, delete the subnets and then delete the VPC. Create a new VPC with a higher size and launch instances with the newly created VPC and subnets.

NEW QUESTION 330

A user has configured an ELB to distribute the traffic among multiple instances. The user instances are facing some issues due to the back-end servers. Which of the below mentioned CloudWatch metrics helps the user understand the issue with the instances?

- A. HTTPCode_Backend_3XX
- B. HTTPCode_Backend_4XX
- C. HTTPCode_Backend_2XX
- D. HTTPCode_Backend_5XX

Answer: D

Explanation:

CloudWatch is used to monitor AWS as well as the custom services. For ELB, CloudWatch provides various metrics including error code by ELB as well as by back-end servers (instances.. It gives data for the count of the number of HTTP response codes generated by the back-end instances. This metric does not include any response codes generated by the load balancer. These metrics are:

The 2XX class status codes represents successful actions

The 3XX class status code indicates that the user agent requires action The 4XX class status code represents client errors

The 5XX class status code represents back-end server errors

NEW QUESTION 332

A user has launched an EC2 instance store backed instance in the US-East-1a zone. The user created AMI #1 and copied it to the Europe region. After that, the user made a few updates to the application running in the US-East-1a zone. The user makes an AMI#2 after the changes. If the user launches a new instance in Europe from the AMI #1 copy, which of the below mentioned statements is true?

- A. The new instance will have the changes made after the AMI copy as AWS just copies the reference of the original AMI during the copyin
- B. Thus, the copied AMI will have all the updated data
- C. The new instance will have the changes made after the AMI copy since AWS keeps updating the AMI
- D. It is not possible to copy the instance store backed AMI from one region to another
- E. The new instance in the EU region will not have the changes made after the AMI copy

Answer: D

Explanation:

Within EC2, when the user copies an AMI, the new AMI is fully independent of the source AMI; there is no link to the original (source. AMI. The user can modify the source AMI without affecting the new AMI and vice a versa. Therefore, in this case even if the source AMI is modified, the copied AMI of the EU region will not have the changes. Thus, after copy the user needs to copy the new source AMI to the destination region to get those changes.

NEW QUESTION 335

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your SOA-C01 Exam with Our Prep Materials Via below:

<https://www.certleader.com/SOA-C01-dumps.html>