

F5-Networks

Exam Questions 201

TMOS Administration



NEW QUESTION 1

A BIG-IP Administrator adds new Pool Members into an existing, highly utilized pool. Soon after, there are reports that the application is failing to load for some users. What pool level setting should the BIG-IP Administrator check?

- A. Availability Requirement
- B. Allow SNAT
- C. Action On Service Down
- D. Slow Ramp Time

Answer: D

Explanation:

Option ABC is a global configuration, has nothing to do with the new pool member, select D after excluding

NEW QUESTION 2

Interface 1.2 on a BIG-IP VE has a status of UNINITIALIZED. What is the reason for this status?

- A. Interface 1.2 has been added to a trunk.
- B. Interface 1.2 has NOT been assigned to a VLAN.
- C. Interface 1.2 has been disabled.
- D. No default route has been created.

Answer: B

Explanation:

trunk is a portchannel, you need to add a physical interface.

NEW QUESTION 3

How should a BIG-IP Administrator control the amount of traffic that a newly enabled pool member receives.

- A. set the Slow Ramp Time
- B. set a Connection Limit
- C. set the Priority Group Activation
- D. set a Health Monitor

Answer: A

Explanation:

Slow Ramp Time

Specifies the duration during which the system sends less traffic to a newly-enabled pool member. The amount of traffic is based on the ratio of how long the pool member has been available compared to the slow ramp time, in seconds. Once the pool member has been online for a time greater than the slow ramp time, the pool member receives a full proportion of the incoming traffic. Slow ramp time is particularly useful for the least connections load balancing mode.

Setting this to a nonzero value can cause unexpected Priority Group behavior, such as load balancing to a low-priority member even with enough high-priority servers.

NEW QUESTION 4

A virtual server is defined per the charts. The last five client connections were to members C, D, A, B, B. Given the conditions shown in the above graphic, if a client with IP address 205.12.45.52 opens a connection to the virtual server, which member will be used for the connection.

- A. 172.16.20.1:80
- B. 172.16.20.2:80
- C. 172.16.20.3:80
- D. 172.16.20.4:80
- E. 172.16.20.5:80

Answer: D

NEW QUESTION 5

What should the BIG-IP Administrator do to apply and activate a hotfix to a BIG-IP device that is currently running version 11.0.0 on active partition HD1.1?

- A. * 1. confirm that 11.0.0 is installed on inactive partition HD1.2* 2. apply a hotfix to partition HD 1.2* 3. activate partition HD1.2
- B. * 1. reactivate the license on partition HD1.1* 2. apply a hotfix to partition HD1.1
- C. * 1. activate partition HD1.2* 2 confirm version 11.0.0 on partition HD1.2* 3. install a hotfix on partition HD1.2
- D. * 1. set partition HD1.2 active* 2. apply a hotfix to partition HD1.2

Answer: A

NEW QUESTION 6

A BIG-IP Administrator plans to upgrade a BIG-IP device to the latest TMOS version.

Which two tools could the administrator leverage to verify known issues for the target versions? (Choose two.)

- A. F5 University
- B. F5 Downloads
- C. F5 End User Diagnostics (EUD)
- D. FSiHealth

E. F5 Bug Tracker

Answer: DE

Explanation:

F5 University -- F5 learning materials F5 Downloads - iso download page

F5 End User Diagnostics (EUD) -- Hardware detection

NEW QUESTION 7

Where is persistence mirroring configured?

- A. It is always enabled.
- B. It is part of a pool definition.
- C. It is part of a profile definition.
- D. It is part of a virtual server definition.

Answer: C

NEW QUESTION 8

A site has six members in a pool. All of the servers have been designed, built, and configured with the same applications. It is known that each client's interactions vary significantly and can affect the performance of the servers. If traffic should be sent to all members on a regular basis, which loadbalancing mode is most effective if the goal is to maintain a relatively even load across all servers?

- A. Ratio
- B. Priority
- C. Observed
- D. Round Robin

Answer: C

NEW QUESTION 9

A BIG-IP Administrator is conducting maintenance on one BIG-IP appliance in an HA Pair. Why should the BIG-IP Administrator put the appliance into FORCED_OFFLINE state?

- A. To preserve existing connections to Virtual Servers and reduce the CPU load
- B. To allow new connections to Virtual Servers and ensure the appliance becomes active
- C. To terminate connections to the management IP and decrease persistent connections
- D. To terminate existing connections to Virtual Servers and prevent the appliance from becoming active

Answer: D

NEW QUESTION 10

A BIG-IP Administrator is configuring an SSH Pool with five members.

Which Health Monitor should be applied to ensure that available pool members are monitored accordingly?

- A. https
- B. udp
- C. http
- D. tcp

Answer: D

NEW QUESTION 10

A site would like to ensure that a given web server's default page is being served correctly prior to sending it client traffic. They assigned the default HTTP monitor to the pool. What would the member status be if it sent an unexpected response to the GET request.?

- A. The pool member would be marked offline (red).
- B. The pool member would be marked online (green).
- C. The pool member would be marked unknown (blue).
- D. The pool member would alternate between red and green.

Answer: B

NEW QUESTION 14

When network failover is enabled, which of the following is true?

- A. The failover cable status is ignore
- B. Failover is determined by the network status only.
- C. Either a network failure or loss of voltage across the failover cable will cause a failover.
- D. A network failure will not cause a failover as long as there is a voltage across the failover cable.
- E. The presence or absence of voltage over the fail over cable takes precedence over network failover.

Answer: C

NEW QUESTION 19

How is persistence configured?

- A. Persistence is an option within each pool's definition.
- B. Persistence is a profile type; an appropriate profile is created and associated with virtual server.
- C. Persistence is a global setting; once enabled, loadbalancing choices are superceded by the persistence method that is specified.
- D. Persistence is an option for each pool member
- E. When a pool is defined, each member's definition includes the option for persistence.

Answer: B

NEW QUESTION 23

Which statement is true concerning cookie persistence?

- A. Cookie persistence allows persistence independent of IP addresses.
- B. Cookie persistence allows persistence even if the data are encrypted from client to pool member.
- C. Cookie persistence uses a cookie that stores the virtual server, pool name, and member IP address in clear text.
- D. If a client's browser accepts cookies, cookie persistence will always cause a cookie to be written to the client's file system.

Answer: A

NEW QUESTION 25

Refer to the exhibit.



<input checked="" type="checkbox"/>	Status	Member	Address	Service Port
<input type="checkbox"/>		10.200.50.210:80	10.200.50.210	80
<input type="checkbox"/>		10.200.50.210:21	10.200.50.210	21
<input type="checkbox"/>		10.200.50.211:443	10.200.50.211	443
<input type="checkbox"/>		10.200.50.211:22	10.200.50.211	22

Buttons: Enable, Disable, Force Offline, Remove

A BIG-IP Administrator needs to configure health monitors for a newly configured server pool named Pool_B.

Which health monitor settings will ensure that all pool members will be accurately marked as available or unavailable?

- A. HTTPS, HTTP, FTP, and ICMP, with the Availability Requirement of all health monitors
- B. HTTPS, HTTP, FTP, and SSH, with the Availability Requirement of at least one monitor
- C. HTTPS and HTTP with the Availability Requirement of at least one health monitor
- D. HTTPS, HTTP, FTP, and SSH with the Availability Requirement of all health monitors

Answer: B

Explanation:

From the port, the four members are HTTP, FTP, HTTPS, and SSH applications. If you want to monitor at the same time, you must configure at least one.

NEW QUESTION 30

A BIG-IP Administrator remotely connects to the appliance via out-of-band management using <https://mybigip.mycompany.net>. The management portal has been working all week. When the administrator attempts to login today, the connection times out. Which two aspects should the administrator verify? (Choose two)

- A. DNS is properly resolving the FQDN of the device.
- B. The device is NOT redirecting them to http.
- C. The administrator has the latest version of the web browser.
- D. Packet Filters on the device are blocking port 80.
- E. The administrator has TCP connectivity to the device.

Answer: AE

NEW QUESTION 34

Assume a client's traffic is being processed only by a NAT; no SNAT or virtual server processing takes place. Also assume that the NAT definition specifies a NAT address and an origin address while all other settings are left at their defaults. If the origin server were to initiate traffic via the BIG-IP, what changes, if any, would take place when the BIG-IP processes such packets?

- A. The BIG-IP would drop the request since the traffic didn't arrive destined to the NAT address.
- B. The source address would not change, but the destination address would be changed to the NAT address.
- C. The source address would be changed to the NAT address and destination address would be left unchanged.
- D. The source address would not change, but the destination address would be changed to a self-IP of the BIG-IP.

Answer: C

NEW QUESTION 35

An LTM device has a virtual server mapped to www.f5.com with a pool assigned. Users report that when browsing, they are periodically required to re-login to resources/201.1.7.b.2_l.com. The objects are defined as follows:

Virtual server. Destination 192.168.245.100:443 netmask 255.255.255.0 Persistence: SSL session persistence

Profiles: HTTP/TCP

Which persistence method should the BIG-IP Administrator apply to resolve this issue?

- A. Source address affinity
- B. hexadecimal
- C. SIP
- D. Destination address affinity

Answer: A

NEW QUESTION 37

A BIG-IP Administrator finds the following log entry:

tmm tmm[7141]: 011e0002:4: sweeperijpdate: aggressive mode activated. Which action should the BIG-IP Administrator to mitigate this memory issue?

- A. Configure the redundant par to be active-active
- B. Decrease the TCP profile ide Timeout value
- C. increase the TCP profile ide Timeout value
- D. Configure the serve to use Connection Mirroring

Answer: D

NEW QUESTION 40

A BIG-IP Administrator reviews the log files to determine the cause of a recent problem and finds the following entry.

Mar 27.07.58.48 local/BIG-IP notice mcpd {5140} 010707275 Pool member 172.16.20.1.10029 monitor status down.

What is the cause of this log message?

- A. The pool member has been disabled.
- B. The pool member has been marked as Down by the BIG-IP Administrator.
- C. The monitor attached to the pool member needs a higher timeout value.
- D. The monitor attached to the pool member has failed.

Answer: D

NEW QUESTION 41

You have a pool of servers that need to be tested. All of the servers but one should be tested every 10 seconds, but one is slower and should only be tested every 20 seconds. How do you proceed?

- A. It cannot be don
- B. All monitors test every five seconds.
- C. It can be done, but will require assigning monitors to each pool member.
- D. It cannot be don
- E. All of the members of a pool must be tested at the same frequency.
- F. It can be done by assigning one monitor to the pool and a different monitor to the slower pool member.

Answer: D

NEW QUESTION 46

A node is a member of various pools and hosts different web applications. If a web application is unavailable, the BIG-IP appliance needs to mark the pool member down for that application pool. What should a BIG-IP Administrator deploy at the pool level to accomplish this?

- A. A UDP monitor with a custom interval/timeout
- B. A combination of ICMP + TCP monitor
- C. An HTTP monitor with custom send/receive strings
- D. A TCP monitor with a custom interval/timeout

Answer: C

Explanation:

Requiring all traffic to be HTTPS access requires HTTP requests to be redirected directly to HTTPS.

NEW QUESTION 50

A BIG-IP Administrator is checking the BIG-IP device for known vulnerabilities. What should the 8IG-IP Administrator upload to BIG-IP iHealth for further analysis?

- A. QKView
- B. EUD
- C. UCS
- D. tcpdump

Answer: A

NEW QUESTION 54

A BIG-IP Administrator needs to check the memory utilization on a BIG-IP system. Which two methods can the UIG IP Administrator use? (Choose two.)

- A. Run the tmsh show/sys memory command
- B. Run the tmsh show/sys traffic command
- C. Go to Statistics > Module Statistics > Traffic Summary in the configuration utility

- D. Go to Statistics > Module Statistics > Memory in the configuration utility
- E. Go to System > Disk Management in the configuration utility

Answer: AD

NEW QUESTION 59

A site needs a virtual server that will use an iRule to parse HTTPS traffic based on HTTP header values. Which two profile types must be associated with such a virtual server? (Choose two.)

- A. TCP
- B. HTTP
- C. HTTPS
- D. ServerSSL

Answer: AB

NEW QUESTION 60

A BIG-IP Administrator needs to collect HTTP status code and HTTP method for traffic flowing through a virtual server. Which default profile provides this information?

- A. HTTP
- B. Analytics
- C. Request Adapt
- D. Statistics

Answer: A

NEW QUESTION 65

A BIG-IP device is replaced with an RMA device. The BIG-IP Administrator renews the license and tries to restore the configuration from a previously generated UCS archive on the RMA device. The device configuration is NOT fully loading. What is causing the configuration load to fail?

- A. The Device Group is NOT configured for Full Sync.
- B. The UCS does NOT contain the full config
- C. The clock is NOT set correctly
- D. The Master Key is NOT restored

Answer: D

NEW QUESTION 66

When initially configuring the BIG-IP system using the config utility, which two parameters can be set? (Choose two.)

- A. the netmask of the SCCP
- B. the IP address of the SCCP
- C. the port lockdown settings for the SCCP
- D. the netmask of the host via the management port
- E. the IP address of the host via the management port
- F. the port lockdown settings for the host via the management port

Answer: DE

NEW QUESTION 71

On the VCMP system, a BIG-IP host administrator imports a new ISO image into the host's /shared/images folder. The new ISO images that reside on the vCMP host are available for installation on the guest. How should the BIG-IP Administrator install one image from within the guest?

- A. Install the new software on the host and wait for it to automatically be installed on all guests.
- B. Run the following command on guesttmsh install sys software block-device-image image_name volume < volume_name>
- C. Run the following command on guesttmsh install sys software image image_name volume < volume_name>
- D. Run the following command on hosttmsh install sys software block-device-image image_name volume < volume_name>

Answer: D

NEW QUESTION 76

The BIG-IP Administrator generates QKView using tmsh command "qkview -SO". In which directory does the BIG-IP appliance save the QKView?

- A. /etc/tmp
- B. /var/tmp
- C. /shared/qkview
- D. /var /tmp/qkview

Answer: B

NEW QUESTION 77

A virtual server is listening at 10.10.1.100:any and has the following iRule associated with it: when CLIENT_ACCEPTED { if {[TCP::local_port] equals 21 } { pool ftppool } elseif {[TCP::local_port] equals 23 } { pool telnetpool }
If a user connects to 10.10.1.100 and port 22, which pool will receive the request?

- A. ftppool
- B. telnetpool
- C. Non
- D. The request will be dropped.
- E. Unknow
- F. The pool cannot be determined from the information provided.

Answer: D

NEW QUESTION 81

An ecommerce company is experiencing latency issues with online shops during Black Friday's peak season. The BIG-IP Administrator detects an overall high CPU load on the BIG-IP device and wants to move the top utilized Virtual Servers to a dedicated BIG-IP device. Where should the BIG-IP Administrator determine the problematic Virtual Servers?

- A. System > Plattform
- B. Local Traffic > Virtual Servers > Virtual Server List
- C. Local Traffic > Network Map
- D. Statistics > Module Statistics > Local Traffic > Virtual Servers

Answer: D

NEW QUESTION 84

A BIG-IP Administrator opens a case with F5 Support. The support engineer requests the BIG-IP appliance chassis serial number. Which TMSH command will provide this information?

- A. . list /sys software
- B. show /sys version
- C. list/sys diags
- D. show /sys hardware

Answer: D

NEW QUESTION 85

Generally speaking, should the monitor templates be used as production monitors or should they be customized prior to use.

- A. Most templates, such as http and tcp, are as effective as customized monitors.
- B. Monitor template customization is only a matter of preference, not an issue of effectiveness or performance.
- C. Most templates, such as https, should have the receive rule customized to make the monitor more robust.
- D. While some templates, such as ftp, must be customized, those that can be used without modification are not improved by specific changes.

Answer: C

NEW QUESTION 90

A new BIG-IP VE is deployed with default settings. The BIG-IP Administrator completes the setup utility in the Configuration Utility. The internal self IP address fails to respond to a ping request. What is a possible cause of this issue?

- A. Port lockdown on internal self IP is set to Allow None
- B. Route is NOT assigned to internal self IP.
- C. Internal interface VLAN is set to untagged
- D. Internal interface VLAN is set to tagged

Answer: D

NEW QUESTION 93

Users are unable to reach an application. The BIG-IP Administrator checks the Configuration Utility and observes that the Virtual Server has a red diamond in front of the status. What is causing this issue?

- A. All pool members are down.
- B. The Virtual Server is receiving HTTPS traffic over HTTP virtual.
- C. The Virtual Server is disabled.
- D. All pool members have been disabled.

Answer: A

NEW QUESTION 98

Which log file should the BIG-IP Administrator check to determine if a specific user tried to log in to the BIG-IP Configuration by utility?

- A. /var/log/pam/tally/log
- B. /var/log/secure
- C. /var/log/trn
- D. /var/log/httpd

Answer: B

NEW QUESTION 101

Refer to the exhibit.

A BIG-IP Administrator configures the Virtual Server to pass HTTP traffic. Users report that they are unable to access the application. What should the administrator do to resolve this issue?

- A. Change the Virtual Server name
- B. Disable the State
- C. Reconfigure the Source Address
- D. Reconfigure the Pool Members

Answer: D

NEW QUESTION 103

A BIG-IP Administrator is setting up a new BIG-IP device. The network administrator reports that the interface has an incompatible media speed. The BIG-IP Administrator needs to change this setting manually.

From which location should the BIG-IP Administrator perform this task?

- A. On the Front Console
- B. In the TMOS Shell Command line
- C. In the Configuration Utility, Network > Interface
- D. In the Configuration Utility, System > Configuration

Answer: C

NEW QUESTION 105

A Virtual Server uses an iRule to send traffic to pool members depending on the URI. The BIG-IP Administrator needs to modify the pool member in the iRule. Which event declaration does the BIG-IP Administrator need to change to accomplish this?

- A. CLIENT_ACCEPTED
- B. HTTP_RESPONSE
- C. HTTP_REQUEST
- D. SERVER_CONNECTED

Answer: C

Explanation:

According to the URI distribution is the category of HTTP requests, need to trigger HTTP_REQUEST event.

NEW QUESTION 106

A BIG-IP Administrator uses a device group to share the workload and needs to perform service on a BIG-IP device currently active for a traffic group. The administrator needs to enable the traffic group to run on another BIG-IP device in the device group. What should the administrator do to meet the requirement?

- A. Create a new Traffic Group and then fail to Standby Unit
- B. Select Traffic Group and then select Failover
- C. Select Traffic Group and then select Force to Standby
- D. Select Traffic Group on Primary Unit and then select Demote

Answer: C

NEW QUESTION 111

A BIG-IP Administrator needs to have a BIG-IP linked to two upstream switches for resilience of the external network. The network engineer who is going to configure the switch instructs the BIG-IP Administrator to configure interface binding with LACP. Which configuration should the administrator use?

- A. A virtual server with an LACP profile and the switches' management IPs as pool members.
- B. A virtual server with an LACP profile and the interfaces connected to the switches as pool members.
- C. A Trunk listing the allowed VLAN IDs and MAC addresses configured on the switches.
- D. A Trunk containing an interface connected to each switch.

Answer: D

NEW QUESTION 116

In the BIG-IP Configuration Utility, a user requests a single screen view to determine the status of all Virtual Servers and associated pool members, as well as any iRules in use. Where should the BIG-IP Administrator instruct the user to find this view?

- A. Local Traffic > Monitors
- B. Local Traffic > Virtual Servers
- C. Local Traffic > Network Map
- D. Statistics

Answer: C

Explanation:

Network Map can display vs and its associated pool, pool member, and irule, can be retrieved, and can be quickly linked.

NEW QUESTION 119

A BIG-IP Administrator is making adjustments to an iRule and needs to identify which of the 235 virtual

server configured on the BIG-IP device will be affected.
 How should the administrator obtain this information in an effective way?

- A. Local Traffic > Virtual Server
- B. Local traffic Pools
- C. LOCAL Traffic > Network Map
- D. Local traffic > Rules

Answer: C

NEW QUESTION 121

Assume the bigd daemon fails on the active system. Which three are possible results? (Choose three.)

- A. The active system will restart the bigd daemon and continue in active mode.
- B. The active system will restart the tmm daemon and continue in active mode.
- C. The active system will reboot and the standby system will go into active mode.
- D. The active system will failover and the standby system will go into active mode.
- E. The active system will continue in active mode but gather member and node state information from the standby system.

Answer: ACD

NEW QUESTION 123

The BIG-IP Administrator needs to ensure the correct health monitor is being used for a new HTTP pool named P_example. Where should the BIG-IP Administrator validate these settings in the Configuration Utility?

- A. Local Traffic > Nodes > Default Monitor
- B. Local Traffic > Profiles > Services > HTTP > http
- C. Local Traffic > Monitors > http
- D. Local Traffic > Pools > P_example

Answer: D

NEW QUESTION 127


A BIG-IP Administrator plans to resolve a non-critical issue with a BIG-IP device in 2 weeks. What Severity level should be assigned to this type of F5 support ticket?


- A. 4
- B. 2
- C. 3
- D. 1

Answer: A

NEW QUESTION 129

Refer to the exhibit





The network team creates a new VLAN on the switches. The BIG-IP Administrator needs to create a configuration on the BIG-IP device. The BIG-IP Administrator creates a new VLAN and Self IP, but the servers on the new VLAN are NOT reachable from the BIG-IP device. Which action should the BIG-IP Administrators to resolve this issue?

- A. Set Port Lockdown of Set IP to Allow All
- B. Change Auto Last Hop to enabled
- C. Assign a physical interface to the new VLAN
- D. Create a Floating Set IP Address

Answer: C

NEW QUESTION 132

A user needs to determine known security vulnerabilities on an existing BIG-IP appliance and how to remediate these vulnerabilities. Which action should the BIG-IP Administrator recommend?

- A. Verify the TMOS version and review the release notes
- B. Create a UCS archive and upload to Health
- C. Create a UCS archive and open an F5 Support request
- D. Generate a view and upload to Heath

Answer: D

NEW QUESTION 137

The BIG-IP Administrator configures an HTTP monitor with a specific receive string. The status is marked 'down'. Which tool should the administrator use to identify the problem?

- A. Ping
- B. Health
- C. tcpdump
- D. ifconfig

Answer: C

NEW QUESTION 140

Refer to the exhibit

Zoom Out Zoom In 04.11.2020 09:36:29					
<input type="checkbox"/>	fwd_8080_vs	any	8080	Forwarding (IP)	Edit
<input type="checkbox"/>	fwd_vs	any	0 (Any)	Forwarding (IP)	Edit
<input type="checkbox"/>	host_8080_vs	1.1.1.0/24	8080	Standard	Edit
<input type="checkbox"/>	host_vs	1.1.1.1	0 (Any)	Standard	Edit
Enable Disable Delete					

A connection is being established to IP 1.1.1.1 on port 8080. Which virtual server will handle the connection?

- A. fwd_8080_vs
- B. host_vs
- C. host_8080_VS
- D. fwdvs

Answer: B

NEW QUESTION 142

Assuming other failover settings are at their default state, what would occur if the failover cable were to be disconnected for five seconds and then reconnected?

- A. As long as network communication is not lost, no change will occur.
- B. Nothin
- C. Failover due to loss of voltage will not occur if the voltage is lost for less than ten seconds.
- D. When the cable is disconnected, both systems will become activ
- E. When the voltage is restored, unit two will revert to standby mode.
- F. When the cable is disconnected, both systems will become activ
- G. When the voltage is restored, both systems will maintain active mode.

Answer: C

NEW QUESTION 143

A BIG-IP Administrator creates an HTTP Virtual Server using an iApp template. After the Virtual Server is created, the user requests to change the destination IP addresses. The BIG-IP Administrator tries to change the destination IP address from 10.1.1.1 to 10.2.1.1 in Virtual Server settings, but receives the following error: The application service must be updated using an application management interface What is causing this error?

- A. The Application Service was NOT deleted before making the IP address change.
- B. The IP addresses are already in use.
- C. The Application Services have Strict Updates enabled.
- D. The IP addresses used are NOT from the same subnet as the Self IP.

Answer: C

Explanation:

Strict Updates : Indicates whether the application service is tied to the template, so when the template is updated, the application service changes to reflect the updates.

NEW QUESTION 147

Refer to the exhibit.



How many nodes are represented on the network map shown?

- A. Four
- B. Three
- C. One
- D. Two

Answer: B

NEW QUESTION 148


Which statement accurately describes the difference between two loadbalancing modes specified as "member" and "node"?

- A. There is no difference; the two terms are referenced for backward compatibility purposes.
- B. When the loadbalancing choice references "node", priority group activation is unavailable.
- C. Loadbalancing options referencing "nodes" are available only when the pool members are defined for the "any" port.
- D. When the loadbalancing choice references "node", the addresses' parameters are used to make the loadbalancing choice rather than the member's parameters.

Answer: B

NEW QUESTION 149

Refer to the exhibit.



Which Pool Members are receiving traffic?

- A. Serv1, serv2, serv3, serv4
- B. serv1, serv3
- C. serv1, serv3, serv4
- D. serv1

Answer: C

NEW QUESTION 150

Which three statements describe a characteristic of profiles? (Choose three.)

- A. Default profiles cannot be created or deleted.
- B. Custom profiles are always based on a parent profile.
- C. A profile can be a child of one profile and a parent of another.
- D. All changes to parent profiles are propagated to their child profiles.
- E. While most virtual servers have at least one profile associated with them, it is not required.

Answer: ABC

NEW QUESTION 153

Users report that traffic is negatively affected every time a BIG-IP device fails over. The traffic becomes stabilized after a few minutes. What should the BIG-IP Administrator do to reduce the impact of future failovers?

- A. Enable Failover Multicast Configuration
- B. Set up Failover Method to HA Order
- C. Configure MAC Masquerade
- D. Configure a global SNAT Listener

Answer: C

NEW QUESTION 154

Assume a virtual server is configured with a ClientSSL profile. What would the result be if the virtual server's destination port were not 443?

- A. SSL termination could not be performed if the virtual server's port was not port 443.
- B. Virtual servers with a ClientSSL profile are always configured with a destination port of 443.
- C. As long as client traffic was directed to the alternate port, the virtual server would work as intended.
- D. Since the virtual server is associated with a ClientSSL profile, it will always process traffic sent to port 443.

Answer: C

NEW QUESTION 159

A BIG-IP Administrator needs to restore a UCS file to an F5 device using the Configuration Utility. Which section of the Configuration Utility should the BIG-IP Administrator access to perform this task?

- A. Local Traffic > Virtual Servers
- B. Local Traffic > Policies
- C. System > Archives
- D. System > Configuration

Answer: C

NEW QUESTION 161

Refer to the exhibit. The BIG-IP Administrator needs to avoid overloading any of the Pool Members with connections, when they become active. What should the BIG-IP Administrator configure to meet this requirement?

- A. Different Ratio for each member
- B. Same Priority Group to each member

- C. Action On Service Down to Reselect
- D. Slow Ramp Time to the Pool

Answer: D

NEW QUESTION 165

New Syslog servers have been deployed in an organization. The BIG-IP Administrator must reconfigure the BIG-IP system to send log messages to these servers. In which location in the Configuration Utility can the BIG-IP Administrator make the needed configuration changes to accomplish this?

- A. System > Logs > Configuration
- B. System > Configuration > Local Traffic
- C. System > Logs > Audit
- D. System > Configuration > Device

Answer: A

NEW QUESTION 168

Which two statements describe differences between the active and standby systems? (Choose two.)

- A. Monitors are performed only by the active system.
- B. Failover triggers only cause changes on the active system.
- C. Virtual server addresses are hosted only by the active system.
- D. Configuration changes can only be made on the active system.
- E. Floating selfIP addresses are hosted only by the active system.

Answer: CE

NEW QUESTION 172

A BIG-IP Administrator needs to configure the BIG-IP system to perform load balancing for FTP servers running passive mode FTP. How should the administrator configure the Virtual Server to perform this load balancing?

- A. A Standard Virtual Server + FTP profile
- B. A Forwarding Virtual Server
- C. A Performance Layer 4 Virtual Server + FTP profile
- D. A Message Routing Virtual Server

Answer: A

NEW QUESTION 173

The BIG-IP Administrator needs to perform a BIG-IP device upgrade to the latest version of TMOS. Where can the administrator obtain F5 documentation on upgrade requirements?

- A. iHealth
- B. Network > Interfaces
- C. Local Traffic > Pools
- D. AsKFS
- E. Local Traffic > Virtual Servers

Answer: C

NEW QUESTION 175

Which must be sent to the license server to generate a new license?

- A. the system's dossier
- B. the system's host name
- C. the system's base license
- D. the system's purchase order number

Answer: A

NEW QUESTION 180

The BIG-IP Administrator disable all pool members in a pool Users are still able to reach the pool members. What is allowing users to continue to reach the disabled pool! members?

- A. A slow to time on Pool
- B. A persistence profile on the Virtual Server
- C. A slow ramp time on virtual Server
- D. A persistence profile on the Pool

Answer: B

NEW QUESTION 183

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

201 Practice Exam Features:

- * 201 Questions and Answers Updated Frequently
- * 201 Practice Questions Verified by Expert Senior Certified Staff
- * 201 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 201 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The 201 Practice Test Here](#)