Exam Questions 300-710

Securing Networks with Cisco Firepower (SNCF)

https://www.2passeasy.com/dumps/300-710/

NEW QUESTION 1
Which two conditions are necessary for high availability to function between two Cisco FTD devices? (Choose two.)

A. The units must be the same version
B. Both devices can be part of a different group that must be in the same domain when configured within the FMC.
C. The units must be different models if they are part of the same series.
D. The units must be configured only for firewall routed mode.
E. The units must be the same model.

Answer: AE

NEW QUESTION 2
Which policy rule is included in the deployment of a local DMZ during the initial deployment of a Cisco NGFW through the Cisco FMC GUI?

A. a default DMZ policy for which only a user can change the IP addresses.
B. deny ip any
C. no policy rule is included
D. permit ip any

Answer: C

NEW QUESTION 3
When creating a report template, how can the results be limited to show only the activity of a specific subnet?

A. Create a custom search in Firepower Management Center and select it in each section of the report.
B. Add an Input Parameter in the Advanced Settings of the report, and set the type to Network/IP.
C. Add a Table View section to the report with the Search field defined as the network in CIDR format.
D. Select IP Address as the X-Axis in each section of the report.

Answer: B

NEW QUESTION 4
What is the disadvantage of setting up a site-to-site VPN in a clustered-units environment?

A. VPN connections can be re-established only if the failed master unit recovers.
B. Smart License is required to maintain VPN connections simultaneously across all cluster units.
C. VPN connections must be re-established when a new master unit is elected.
D. Only established VPN connections are maintained when a new master unit is elected.

Answer: C

NEW QUESTION 5
Which two routing options are valid with Cisco Firepower Threat Defense? (Choose two.)

A. BGPv6
B. ECMP with up to three equal cost paths across multiple interfaces
C. ECMP with up to three equal cost paths across a single interface
D. BGPv4 in transparent firewall mode
E. BGPv4 with nonstop forwarding

Answer: AC

NEW QUESTION 6
Which object type supports object overrides?

A. time range
B. security group tag
C. network object
D. DNS server group

Answer: C

NEW QUESTION 7
What is the result of specifying of QoS rule that has a rate limit that is greater than the maximum throughput of an interface?

A. The rate-limiting rule is disabled.
B. Matching traffic is not rate limited.
C. The system rate-limits all traffic.
D. The system repeatedly generates warnings.

Answer: B

NEW QUESTION 8

Which Firepower feature allows users to configure bridges in routed mode and enables devices to perform Layer 2 switching between interfaces?

A. FlexConfig
B. BDI
C. SGT
D. IRB

Answer: D

NEW QUESTION 9

After deploying a network-monitoring tool to manage and monitor networking devices in your organization, you realize that you need to manually upload an MIB for the Cisco FMC. In which folder should you upload the MIB file?

A. /etc/sf/DCMIB.ALERT
B. /sf/etc/DCEALERT.MIB
C. /etc/sf/DCEALERT.MIB
D. system/etc/DCEALERT.MIB

Answer: C

NEW QUESTION 10

Which action should be taken after editing an object that is used inside an access control policy?

A. Delete the existing object in use.
B. Refresh the Cisco FMC GUI for the access control policy.
C. Redeploy the updated configuration.
D. Create another rule using a different object name.

Answer: C

NEW QUESTION 10

Which CLI command is used to generate firewall debug messages on a Cisco Firepower?

A. system support firewall-engine-debug
B. system support ssl-debug
C. system support platform
D. system support dump-table

Answer: A

NEW QUESTION 15

Which command-line mode is supported from the Cisco Firepower Management Center CLI?

A. privileged
B. user
C. configuration
D. admin

Answer: C

NEW QUESTION 16

Which command must be run to generate troubleshooting files on an FTD?

A. system support view-files
B. sudo sf_troubleshoot.pl
C. system generate-troubleshoot all
D. show tech-support

Answer: B

NEW QUESTION 20

When do you need the file-size command option during troubleshooting with packet capture?

A. when capture packets are less than 16 MB
B. when capture packets are restricted from the secondary memory
C. when capture packets exceed 10 GB
D. when capture packets exceed 32 MB

Answer: D

NEW QUESTION 22

Which two packet captures does the FTD LINA engine support? (Choose two.)

A. Layer 7 network ID
B. source IP

C. application ID
D. dynamic firewall importing
E. protocol

Answer: BE

NEW QUESTION 23
......

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual 300-710 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the 300-710 Product From:

https://www.2passeasy.com/dumps/300-710/

Money Back Guarantee

300-710 Practice Exam Features:

* 300-710 Questions and Answers Updated Frequently

* 300-710 Practice Questions Verified by Expert Senior Certified Staff

* 300-710 Most Realistic Questions that Guarantee you a Pass on Your FirstTry

* 300-710 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year